

GFRP Reinforcement for Concrete Facilities to Protect Against Mudflow

by Valery Hurnovich and Antonio Nanni

A unique complex of mudflow protection facilities was recently constructed to protect the city of Ashgabat, Turkmenistan, using concrete reinforced with glass fiber-reinforced polymer (GFRP) reinforcement. The project's specifications and design provisions followed current Russian standards for fiber-reinforced polymer reinforcement, and the project was completed on time and under budget.

Ashgabat is the capital and largest city of Turkmenistan. The city is situated at the foot of the Kopet Dag mountain range in Central Asia, with the highest nearby peak standing at 2940 m (9646 ft) above sea level. The slopes of the range facing Ashgabat are steep and ravine-scarred. From March to October, periodical convective precipitation events release a total of up to 400 mm (16 in.) of rainfall. After rare but sometimes heavy rains, massive mudflows sweep down the narrow ravines and over the submountain plains.

In 1991, the Turkmenistan government took significant steps toward revitalizing Ashgabat, turning it into a modern city with public buildings, monuments, and parks. The city is famous for its architecture: white marble-clad buildings, mosques with beautiful golden domes, and high monuments. To protect Ashgabat and its people against the risk of mudflows (Fig. 1), the decision was made to construct a complex of mudflow protection facilities. The construction started in March 2020 and was completed in September 2022. The complex of facilities is in the southern part of Ashgabat and receives water from the Kopet Dag (Fig. 2).

The project called for the construction of mudflow storage facilities (Fig. 3) in the streambeds of the main ravines as well as a system of diversion channels and pipelines carrying cleared water to the existing mudflow diversion channel (the so-called Ashgabat Channel).

The primary purpose of the facilities is to receive and intercept mudflow and stormwater from rains falling in the area. After the complete settlement of detrital deposits in the storage facilities, the discharge of the cleared water that was part of the mudflow starts with flood gates being opened and pump stations being activated.



Fig. 1: Streets of Ashgabat, Turkmenistan, after a mud stream inundation (photo credit: <https://centralasia.media/news:1448895/>)



Fig. 2: Location of the mudflow protection facilities

The water diversion facilities are made of reinforced concrete (RC) channels and pipelines that receive and divert the clarified water from the mudflow storage facilities. The water diversion channels receive torrents from the Kopet Dag along their length, thus reducing the amount of rainwater moving to Ashgabat. These massive construction projects included the following:

- Nine mudflow storage facilities;
- Five mudflow channels with a total length of 7 km (4.3 miles);
- Water diversion channels with a total length of 22 km (13.7 miles);



Fig. 3: Mudflow storage facilities



Fig. 4: Sand-coated GFRP reinforcing bars used in the project

- Water diversion conduits with a total length of 9 km (5.6 miles);
- Restoration of an existing mudflow diversion channel with a total length of 19 km (11.8 miles);
- Seven pump stations;
- Two water outlet structures; and
- Restoration of three bridges.

The group of mudflow protection facilities is unique as it can receive mudflow and stormwater for a total volume of 12.4 million m³ (16.2 million yd³) at a time and withstand a magnitude 9.0 earthquake.

To help ensure the maintenance-free service life of the diversion channels for a total of 100 years, GFRP bars were chosen as reinforcement for the concrete in the project. The selected GFRP composite was in the form of sand-coated bars (straight or with bends) (Fig. 4) made of E-glass corrosion-resistant (E-CR) glass fibers embedded in epoxy resin. GFRP bars are currently becoming more popular because of their properties that allow the extension of service life and reduction of construction costs (Table 1). GFRP bars exhibit no corrosion, have high tensile strength and good fatigue strength, are lightweight, and exhibit electromagnetic transparency. While GFRP bars also have low elastic modulus and transverse shear strength, these properties are not significant factors in uniformly loaded slabs-on-ground. In addition, the low weight of GFRP bars minimizes transportation and placement costs.

Material Specifications and Design

The following regulations were used during development of the project for GFRP reinforcement for the channels:

- SP 295.1325800.2017, “Concrete Structures Reinforced with Fibre-Reinforced Polymer Bars. Design Rules”²²; and
- GOST 31938-2012, “Fibre-Reinforced Polymer Bar for Concrete Reinforcement. General Specifications”²³ (Table 2). The main calculation criteria included:
 - Maximum allowable crack opening width of 0.7 mm (0.03 in.);
 - Distance between cracks from 0.5 to 1 m (1.6 to 3.9 ft);
 - Stress in bars under long-term load of not more than 330 MPa (47.8 ksi);

Table 1:

Physical and mechanical properties of GFRP and steel bars used in design

Property	GFRP	Steel bars A500 (GOST R 52544-2006 ¹)
Characteristic tensile resistance, MPa (ksi)	1100 (160)	500 (72.5)
Design tensile resistance, MPa (ksi)	641 (93)	435 (63)
Design resistance to tension under sustained and long-term load, MPa (ksi)	330 (47.9)	435 (63)
Tensile modulus, not less than, MPa (ksi)	50,000 (7250)	200,000 (29,000)
Elongation at failure, ϵ , %	2.2	14.0
Coefficient of linear thermal expansion, 1/°C	$(6.0 \text{ to } 10.0) \times 10^{-6}$	$(11.5 \text{ to } 14.5) \times 10^{-6}$
Conductivity	Nonconductive	Conductive
Magnetic properties	Nonmagnetic	Magnetic
Corrosive and chemical resistance	High	Low

Table 2:
GFRP material specifications

Property	GOST 31938-2012 ³	ASTM D7957/D7957M-17 ⁴
	GFRP/BFRP	GFRP
Fiber mass content, no less than, %	75	70
Nominal ultimate tensile strength, MPa (ksi)	800 (116)	533 to 843 (77.3 to 122.3), depending on bar diameter
Nominal mean tensile modulus of elasticity, no less than, MPa (ksi)	50,000 (7250)	44,800 (6500)
Guaranteed transverse shear strength, no less than, MPa (ksi)	150 (21.7)	131 (19)
Nominal ultimate compression strength, no less than, MPa (ksi)	300 (43.5)	—
Guaranteed bond strength, no less than, MPa (ksi)	12 (1.74)	7.6 (1.1)
Loss in tensile strength after exposure to alkaline conditions, no more than, %	25 (30 days at 60°C [140°F])	20 (90 days at 60°C [140°F])
Guaranteed bond strength after aging in an alkaline environment, no less than, MPa (ksi)	10 (1.45)	—
Mean glass-transition temperature, no less than, °C (°F)	—	100 (212)
Mean degree of cure, %	—	95
Operating temperature limit, no more than, °C (°F)	60 (140)	—
Moisture absorption in 24 hours at 50°C (122°F), no more than, %	—	0.25
Mean moisture absorption to saturation, no more than, %	—	1 (to saturation at 50°C [122°F])

The ACI Detailing Manual

Includes FREE Downloadable CAD Files

The 2020 edition of the *ACI Detailing Manual* includes many new updates and revisions, plus the addition of valuable downloadable CAD files.

Visit concrete.org/store for more information.



American Concrete Institute
Always advancing






Fig. 5: GFRP reinforcement in channel slabs



Fig. 6: Channel slab after concrete casting

- Stress in bars under short-term load of not more than 641 MPa (93 ksi); and
- Concrete B25 with compressive strength of 14.5 MPa (2100 psi).

The design strength of the GFRP bars was calculated with consideration of a material resistance factor of 1.2 and an operation factor of 0.7 (structures operated outdoors or on ground).

The following parameters were chosen for the channels (Fig. 5):

- Slab thickness of 400 mm;
- Bar diameter of 12 mm (0.47 in.);
- Spacing of bars in the slab top mat of 250/250 mm (10/10 in.);
- Spacing of bars in the slab bottom mat of 250/250 mm; and
- Bar lap splice length of 600 mm (24 in.).

Based on the calculations for temperature exposure, the dimensions of channel panels were determined as 30 x 30 m (98.4 x 98.4 ft) (Fig. 6).

GFRP bars with diameters of 10, 12, and 16 mm were used in the project; additionally, 12 mm diameter L-shaped bent bars were employed for splicing. Straight bars were supplied in bundles of a maximum length of 13 m (42.6 ft). The total quantities are given in Table 3.

Economy of GFRP Bar Application

The initial project design called for 12 mm diameter A500 steel bars installed at 250/250 mm in the top and bottom mats of a slab. The total required length of bars was estimated at 7.9 km (4.8 miles), including additions for lap splices. At the time of the construction, the cost for 12 mm diameter steel bars was 0.27 USD/ft, while corresponding GFRP bars cost 0.23 USD/ft.

The project calculations showed that steel bars could be replaced by GFRP bars without changing bar diameter and spacing, leading to a material cost savings of 16% (refer to Table 4).

Costs for the delivery of bars to the construction site

Table 3:

Total number and weight of GFRP bars used in the project

Name	Length, m (ft)	Weight, tonne (ton)
Straight bars		
GFRP 10	151,026 (495,492)	25.97 (28.73)
GFRP 12	7,834,137 (25,702,549)	1997 (2201)
GFRP 16	6955 (22,818)	3.23 (3.56)
Bent bars		
GFRP 12	32,690 (107,250)	8.92 (9.83)
Total	8,024,808 (26,328,111)	2035 (2243)

Table 4:

Direct comparison of material costs for steel and GFRP bars

Material	Bar diameter, mm						Total cost, USD	
	10		12		16		A500	GFRP
	A500	GFRP	A500	GFRP	A500	GFRP		
Length, ft	495,492	495,492	25,809,801	25,809,801	22,818	22,818	—	—
Weight per length, lb/ft	0.415	0.116	0.597	0.171	0.812	0.312		
Total weight, lb	205,431	57,269	15,400,708	4,422,767	18,524	7119		
Cost per length, USD/ft	0.19	0.15	0.27	0.23	0.37	0.36		
Cost, USD	95,134	72,837	7,089,694	5,936,254	8522	8215	7,193,350	6,017,306
Difference, USD							1,176,044	
Savings, %							16	

Note: 1 mm = 0.04 in.; 1 ft = 0.3 m; 1 lb/ft = 1.5 kg/m; 1 lb = 0.45 kg

Table 5:
Comparison of total costs for the project

Reinforcement type	A500	GFRP
Cost for bars, USD	7,193,350	6,017,306
Number of Euro trailers	—	101
Number of railroad cars	110	—
Delivery cost per one Euro trailer, USD	—	4240
Delivery cost per one railroad car, USD	8140	—
Transportation cost, USD	895,400	428,240
Cost including delivery, USD	8,088,750	6,445,546
Difference, USD	1,643,205	
Savings, %	20	

accounted for a significant part of the project's economy. The total weight of steel bars would have been about 7812 tons (7087 tonnes). In contrast, the total weight of the GFRP bars required for the project was about 2243 tons (2035 tonnes).

The total economic efficiency of replacing the steel bars with GFRP bars, including the delivery cost, was 20% (refer to Table 5). While an accurate assessment of costs for unloading, crane operations, and reinforcement cage installation for the project was not carried out, it was also noted that the use of GFRP bars improved construction time and reduced labor costs. The construction of the mudflow protection facilities has been successfully completed, and the owner has decided to apply GFRP bars in new projects.

References

1. GOST R 52544-2006, "Weldable Deformed Reinforcing Rolled Products of A500C and B500C Classes for Reinforcement of Concrete Constructions. Specifications," Federal Agency for Technical Regulation and Metrology, Moscow, Russia, 2006, 23 pp.

2. SP 295.1325800.2017, "Concrete Structures Reinforced with Fibre-Reinforced Polymer Bars. Design Rules," Ministry of Construction, Housing and Utilities, Moscow, Russia, 2017, 55 pp.

3. GOST 31938-2012, "Fibre-Reinforced Polymer Bar for Concrete Reinforcement. General Specifications," Federal Agency for Technical Regulation and Metrology, Moscow, Russia, 2012, 40 pp.

4. ASTM D7957/D7957M-17, "Standard Specification for Solid Round Glass Fiber Reinforced Polymer Bars for Concrete Reinforcement," ASTM International, West Conshohocken, PA, 2017, 5 pp.

Selected for reader interest by the editors.



Valery Hurynovich has over 9 years of experience in the composites industry. He serves as the Chief Operating Officer of Galen Panamerica LLC, a U.S.-based company that provides solutions of composite reinforcement for industrial and civil construction. He received his Executive MBA from TRIUM Global Executive MBA, a partnership of New York

University (NYU) Stern School of Business, New York, NY, USA; HEC Paris School of Management, Paris, France; and The London School of Economics and Political Science (LSE) Department of Management, London, UK.



Antonio Nanni, FACI, is a Professor and Chair of the Department of Civil and Architectural Engineering at the University of Miami, Coral Gables, FL, USA, and ACI President for 2023-2024. He is a member of numerous ACI committees, including ACI Committee 440, Fiber-Reinforced Polymer Reinforcement. He has received several awards, including the 2014 IIFC

Medal from the International Institute for FRP in Construction and the 2012 ASCE Henry L. Michel Award for Industry Advancement of Research.

Stay Up-to-Date with the ACI Concrete Industry Calendar!

Whether you're interested in networking with industry leaders, learning a new technology, or wanting to let others know about your upcoming event, be sure to check out the ACI Events Calendar. With just a few clicks, you can connect with an event near you or post your own event to share with the world!



American Concrete Institute
Always advancing

Search your Events Calendar by...



Certifications and Training



Seminars and Webinars



Events

Search, Click, Connect!

Visit the Events Calendar Page at
www.concrete.org/calendar