
Language Models as Science Tutors

Alexis Chevalier¹ Jiayi Geng¹ Alexander Wettig¹ Howard Chen¹ Sebastian Mizera²
Toni Annala³ Max Jameson Aragon⁴ Arturo Rodríguez Fanlo⁵ Simon Frieder⁶ Simon Machado⁷
Akshara Prabhakar¹ Ellie Thieu⁸⁹ Jiachen T. Wang¹ Zirui Wang¹ Xindi Wu¹ Mengzhou Xia¹
Wenhan Xia¹ Jiatong Yu¹ Jun-Jie Zhu¹⁰¹¹ Zhiyong Jason Ren¹⁰¹¹
Sanjeev Arora¹ Danqi Chen¹

Abstract

NLP has recently made exciting progress toward training language models (LMs) with strong scientific problem-solving skills. However, model development has not focused on real-life use-cases of LMs for science, including applications in education that require processing long scientific documents. To address this, we introduce TUTOREVAL and TUTORCHAT. TUTOREVAL is a diverse question-answering benchmark consisting of questions about long chapters from STEM textbooks, written by experts. TUTOREVAL helps measure real-life usability of LMs as scientific assistants, and it is the first benchmark combining long contexts, free-form generation, and multi-disciplinary scientific knowledge. Moreover, we show that fine-tuning base models with existing dialogue datasets leads to poor performance on TUTOREVAL. Therefore, we create TUTORCHAT, a dataset of 80,000 long synthetic dialogues about textbooks. We use TUTORCHAT to fine-tune Llemma models with 7B and 34B parameters. These LM tutors specialized in math have a 32K-token context window, and they excel at TUTOREVAL while performing strongly on GSM8K and MATH. Our datasets build on open-source materials, and we release our models, data, and evaluations publicly.

Chapter:

[...] One of the key numbers we can extract from mass and momentum is the invariant mass, a number independent of the Lorentz frame: $W^2 c^4 = (\sum_i E_i)^2 - (\sum_i \vec{p}_i)^2 c^2$. This quantity takes its most transparent form in the center-of-mass, where [...].

Question:

How is the first equation in the chapter consistent with Einstein's $E = mc^2$ formula? It looks wrong.

LM Tutor:

The first equation you mentioned, $W^2 c^4 = (\sum_i E_i)^2 - (\sum_i \vec{p}_i)^2 c^2$, is indeed related to the famous $E = mc^2$ formula. [...] So, the first equation is indeed consistent with Einstein's formula.

Key points provided to GPT-4:

- The student is mistaken in saying the first equation is wrong.
- Einstein's $E = mc^2$ is valid only at rest. It can be obtained by setting the momenta $\sum_i \vec{p}_i = 0$, where W is the invariant mass m in $E = mc^2$.
- The second formula is what the student is looking for with $W = m$ and $E_{CM} = E$.

GPT-4 Evaluator:

Presentation: The AI's response is structured in an informative manner [...]. Grade: 1.5/3.

Correctness: The AI's response is correct in stating that the first equation is related to Einstein's $E = mc^2$ formula [...]. However, the AI fails to address the key point that Einstein's formula is valid only when the object is at rest, which is crucial for correctness. [...] Grade: 1.5/3.

Figure 1: Example from TUTOREVAL. Given the chapter, the student asks a question to the LM Tutor. Both the chapter and the question are fed to the LM Tutor to generate the answer. GPT-4 assesses the generation by referencing the human annotated key points (blue: the tutoring task; yellow: evaluation). See detailed examples in §A.

1. Introduction

NLP has recently made exciting progress towards improving LM performance on problem-solving benchmarks such as GSM8K (Cobbe et al., 2021) or MATH (Hendrycks et al.,

¹Princeton Language and Intelligence, Princeton University

²School of Natural Sciences, Institute for Advanced Study

³School of Mathematics, Institute for Advanced Study

⁴Neuroscience Institute, Princeton University

⁵Hebrew University of Jerusalem

⁶Department of Computer Science, Oxford University

⁷FIM - Institute for Mathematical Research, ETH Zürich

⁸Department of Computer Science, University of Wisconsin-Madison

⁹Meta FAIR

¹⁰Department of Civil and Environmental Engineering, Princeton University

¹¹Andlinger Center for Energy and the Environment, Princeton University. Correspondence to: Alexis Chevalier <achevalier@princeton.edu>.




Figure 2: Left: performance breakdown on TUTOREVAL by domains. Right: leaderboard of popular models on TUTOREVAL. Our models, marked in bold, achieve competitive TUTOREVAL performance.

2021b) and on general knowledge benchmarks like MMLU (Hendrycks et al., 2021a). One approach to constructing models for problem-solving consists in fine-tuning base models on math datasets, such as MetaMath (Yu et al., 2023), MAMmoTH (Yue et al., 2023), or WizardMath (Luo et al., 2023). Other approaches train on web-scraped corpora, such as Llemma (Azerbayev et al., 2023) with OpenWebMath (Paster et al., 2023), or on large synthetic datasets, such as Phi-2 (Gunasekar et al., 2023; Li et al., 2023b). This flurry of new LMs raises the question: how can we apply these problem-solving skills to build helpful LM tutors for science? The first challenge for answering this question is the lack of relevant LM evaluations.

Existing science evaluations are lacking in the following ways. First, they do not simulate real-life situations where we use LMs as assistants, such as asking to clarify hard concepts or asking for background information. Second, science evaluations only evaluate the final answer to a problem, not the reasoning process. Third, real-life situations often require LMs to process long scientific materials, which are not tackled by any existing evaluations.

To bridge these gaps, we introduce TUTOREVAL, a long-context question-answering benchmark requiring advanced scientific knowledge, simulating humans seeking to understand textbook materials. TUTOREVAL consists of over 800 questions written by experts in math, physics, computer science, environmental science, and life sciences. TUTOREVAL extends the LM-as-evaluator framework (Li et al., 2023a) by introducing *key points*: we collect sketches of the ground-truth answer from the experts, which an LM evaluator uses to grade the LM tutor’s answers. See Figure 1 for an example. We will show that GPT-4 can be used as a reliable evaluator for TUTOREVAL.

We investigate the importance of fine-tuning for improving TUTOREVAL performance. We find that TUTOREVAL benefits from training on scientific texts and that fine-tuning with existing dialogue datasets delivers poor performance. Therefore, we create TUTORCHAT, the first long-context dialogue dataset for science. TUTORCHAT consists of 80,000 synthetic conversations about textbook chapters generated by GPT-3.5 and GPT-4, covering STEM topics, humanities and social sciences. We use TUTORCHAT to fine-tune long-context models that rival strong closed-source models like Mistral-7B-V2 (Jiang et al., 2023) on TUTOREVAL.

We show that TUTORCHAT is a rich resource for domain-specific fine-tuning. While we find that it is tricky to acquire math skills during fine-tuning, the specificity of TUTORCHAT provides a remedy: combining STEM dialogues with math data yields well-rounded LM tutors with strong math problem-solving skills. With this insight, we construct a new data mixture, MathMix, and we introduce Llemma-7B-32K-MathMix and Llemma-34B-MathMix, two long-context LMs competitive on TUTOREVAL, MATH and GSM8K.

In summary, we introduce TUTOREVAL, the first long-context science benchmark, and TUTORCHAT, the first long-context dialogue dataset for science, and we conduct thorough investigations into the importance of training and fine-tuning with scientific texts. We release competitive long-context models specialized in science and math reasoning, as well as all our data and evaluations at <https://github.com/princeton-nlp/LM-Science-Tutor>.

2. Related Work

LMs for science Minerva (Lewkowycz et al., 2022) and Galactica (Taylor et al., 2022) were two pioneering ef-

Table 1: TUTOREVAL question counts per domain and category. Question categories are described in Section 4.1.

	Math	CS	Physics	Env.	Life	Total
Hard	96	59	54	22	10	241
Misleading	55	21	28	4	5	113
Closed-book	159	100	71	20	20	370
Answer in chapter	128	98	56	20	6	308
Total	362	205	174	53	40	834

forts to train LMs on large corpora of scientific documents to improve problem-solving and scientific knowledge. Llemma (Azerbayev et al., 2023) has replicated Minerva and Galactica’s approach using the open-source OpenWeb-Math dataset (Paster et al., 2023). MMLU (Hendrycks et al., 2021a) and MATH (Hendrycks et al., 2021b) are key benchmarks which have motivated this general research direction. Other problem-solving benchmarks include SciBench (Wang et al., 2023) and SciEval (Sun et al., 2023).

There has been recent interest in developing the applications of LMs to education. EduBot (Li et al., 2023c) applies LMs to English-teaching and MathDial (Macina et al., 2023) studies challenges of using LMs for math education, for which they release a small dataset of human-LM conversations. Various works have studied the expert-level capabilities of LMs and their applicability as teaching or research assistants. Huang et al. (2023) benchmarks GPT-4 on machine learning research tasks. Wu et al. (2023) studies retrieval-augmented capabilities of ChatGPT for education. General studies include Peskoff & Stewart (2023), Frieder et al. (2023), and Collins et al. (2023).

Fine-tuning on model-generated dialogue A popular approach for improving the instruction-following and dialogue capabilities of LMs consists in imitation learning: LMs are trained on the high-quality outputs of larger LMs. Examples include the textbooks of Gunasekar et al. (2023) or Orca (Mukherjee et al., 2023). The success of this distillation approach has led to an accumulation of dialogue datasets. ShareGPT and WildChat (Zhao et al., 2024) are efforts to crowd-source real-life ChatGPT conversations. UltraChat (Ding et al., 2023) and OpenOrca (Lian et al., 2023) are datasets of synthetic text generated by ChatGPT.

LM as an evaluator The research community has recently explored new ways of evaluating LMs. One solution resorts to using strong pre-trained LMs to compare model outputs. AlpacaFarm (Li et al., 2023a) uses LMs to simulate human evaluators by obtaining preference votes between model outputs. Chiang & Lee (2023), Zheng et al. (2023), Chen et al. (2023) analyse GPT-4’s ability to simulate human preferences. LLMBar (Zeng et al., 2023) introduces a systematic evaluation of LLMs as evaluators for instruction-following.

Most works find that GPT-4 is generally reliable, and we build on these findings to introduce TUTOREVAL.

3. TUTOREVAL

In Section 3.1, we show how TUTOREVAL was constructed with the help of experts and how TUTOREVAL can be used for both open-book and closed-book evaluation. In Section 3.2, we explain how we use an LM as an evaluator and we show that GPT-4 correlates well with human judgments. In Section 3.3, we comment on the leaderboard in Figure 2.

3.1. Dataset construction

Question collection We work with 17 annotators, all STEM researchers with teaching experience. Each annotator was provided a set of textbook chapters and was instructed to write questions about chapters which they would be qualified to teach in a class. These chapters come from open-source textbooks collected from libretexts.org, as part of the dataset discussed in Section 4.1. Annotators were given free rein to write questions. They were only instructed to simulate questions that students could plausibly ask about each chapter. See examples in Figure 1 and in Appendix A.

Dataset composition In total, we collect 834 questions spanning math, physics, computer science, life sciences and environmental science. 202 textbook chapters were used, with at least 3 questions per chapter. These chapters contain 1,800 words on average, and up to 6,100 words. We note that TUTOREVAL is biased toward math and computer science, but we hope to extend TUTOREVAL in the future as follow-up work. See Table 1 for statistics.

Data categories TUTOREVAL is a diverse set of questions allowing us to evaluate models in different settings and to track fine-grained behavior. For each question, we report the following information:

1. *Closed-book*: can the *question* be understood without reading the chapter first?
2. *Answer in chapter*: is the *answer* contained in the chapter, or does it require substantial external knowledge?
3. *Misleading*: is the question phrased in a misleading way, such as including false assumptions or an having

overly-confident tone?

4. *Difficulty*: how hard is the question relatively to the chapter’s intended audience?

TUTOREVAL contains 370 closed-book questions, meaning that the question does not refer explicitly to the chapter. This enables evaluation of short-context LMs, and we refer to this evaluation setting as TUTOREVAL-CLOSEDBOOK.

Data validation To ensure the relevance of our data categories, we evaluate GPT-4 on different data categories both in open-book TUTOREVAL and in the closed-book setting (Table 5). First, we see that GPT-4’s results on open-book questions are significantly affected in closed-book evaluation, proving that open-book questions require the chapter. We also see that closed-book questions slightly benefit from open-book evaluation and that splitting questions by *answer in chapter* shows how well GPT-4 is able to utilize long contexts. This demonstrates that TUTOREVAL is a rich benchmark which offers a thorough investigation of long-context understanding in the science domain.

3.2. LM as an Evaluator

Key points as ground-truths We ask human annotators to provide a ground-truth solution to each question by sketching the *key points* that a good teacher should address in answering the student. These key points make it possible to quickly assess the correctness of an answer. Annotators were instructed to draw on their own experience as educators when compiling these key points.

LM-powered evaluation At evaluation time, the LM tutor is prompted to answer each question based on the associated chapter. We let the LM generate up to 800 tokens. To rate the free-form model generations, we prompt an LM evaluator to assign grades to each output. The LM evaluator is instructed to follow the key points as a guide for judging the answer. We use the January 2024 version of GPT-4-Turbo (OpenAI, 2023). GPT-4 is prompted to grade the output’s *presentation* and *correctness*. *Presentation* measures clarity of explanation and general form. *Correctness* tracks factual mistakes and incorrect references to the chapter. Correctness is a more meaningful metric to benchmark LMs, so we usually report only the correctness scores. Nevertheless, presentation scores are informative, and we show that prompting GPT-4 for a presentation score improves human-GPT-4 correlation on correctness.

Human-GPT-4 agreement To show that GPT-4 can be used as a reliable evaluator, we ask each human annotator to grade the outputs of four anonymized models on the 50 questions they created. We report the final scores from humans and GPT-4 in Table 2. We also compute 3 human-GPT-4 correlation metrics: the Pearson, the Spearman, and

the Kendall- τ coefficients (more details in Appendix C). Results show that GPT-4 rankings correlate well with humans rankings on individual questions. Moreover, we find that 14/17 human annotators agree about the overall ranking and that GPT-4 reaches this ranking on 12/17 of the question sets. In Figure 3 we see that the overall scores attributed by each human to each model correlate with the scores obtained from GPT-4 on the same questions.




Figure 3: We show the correlation between the scores from 17 annotators and the GPT-4 scores for four models: Vicuna-13B-16K, Llemma-7B-32K-Ultrachat, Llemma-7B-32K-MathMix, and GPT-4. Each annotator evaluates these models on their own set of 50 questions.

Additional analysis We run ablations to further analyse the effect of our GPT-4-grading strategy on human-GPT-4 correlation. We consider the following modifications:

1. Remove the key points from GPT-4’s prompt
2. Prompt GPT-4 for correctness without presentation
3. Use GPT-3.5-Turbo instead of GPT-4-Turbo

Correlation deteriorates in all cases, indicating the necessity of each component. See Appendix C for details, where we also show in Figure 6 that the key points are particularly useful for GPT-4 to grade its own generations fairly.

We also prompt GPT-4 for preference votes between various models. We find that GPT-4 preferences agree with the rankings obtained from individual grades. Hence our grading approach is at least as reliable as preference voting, while also being much less expensive. See Appendix C.

Future-proofing evaluation Model updates to GPT-4 or using different evaluators will not preserve the TUTOREVAL scores. To facilitate future evaluations, we release the TUTOREVAL outputs of the models ranked in Figure 2, together with all GPT-4 and human grades.

3.3. Evaluating State-of-the-art LMs on TUTOREVAL

Figure 2 shows the leaderboard of TUTOREVAL with state-of-the-art LMs and their domain breakdown. Detailed num-

Table 2: TUTOREVAL scores of 4 models graded by humans and GPT-4. Models are introduced in Section 5. See Appendix B, Table 6 for detailed human evaluation results and Appendix C for data analysis about GPT-4/human agreement.

	Human TUTOREVAL		GPT-4 TUTOREVAL	
	Presentation	Correctness	Presentation	Correctness
Vicuna-13B-V1.5	51.0	49.0	44.5	32.9
LLEMMA-7B-32K-ULTRACHAT	51.4	59.4	46.2	39.4
Llemma-7B-32K-MathMix	67.8	67.9	62.4	50.0
GPT-4	92.3	91.9	89.5	85.2

bers can be found in Table 5 in the appendix. We see in the radar plot that GPT-4 dominates in all domains followed by GPT-3.5 and Mixtral. Among 7B models, Mistral-7B-V2 is the strongest, closely followed by our Llemma-7B-32K-MathMix, which we introduce in Section 5. Table 5 shows that our model is stronger on the subset of math TUTOREVAL questions, owing to Llemma’s specialized training on math data. In Table 3, we compare short-context models on TUTOREVAL-CLOSEDBOOK.

As shown in Table 2, human evaluators give 92% correctness to GPT-4 on TUTOREVAL. This confirms the fact that GPT-4 is already useful in educational settings. Future work will investigate how to build a harder academic benchmark. In the remainder of this paper, we show that TUTOREVAL performance for 7B and 34B models can be greatly improved with dedicated scientific training and fine-tuning.

4. TUTORCHAT

In this section, we build the first dialogue dataset for science. We introduce TUTORCHAT, a dataset of high quality, long-form, synthetic conversations about textbook materials. In Section 5, we will show that TUTORCHAT is highly effective for improving performance on TUTOREVAL, compared to general-purpose dialogue datasets like UltraChat.

4.1. Constructing TUTORCHAT

We construct TUTORCHAT in two steps: first we collect open-source textbooks which we process into a high-quality dataset of long documents, and secondly we generate dialogues about each textbook chapter by simulating teacher-student interactions with GPT-3.5-Turbo and GPT-4-Turbo.

Textbook collection We scrape the domain libretexts.org for textbooks in all academic domains. All textbooks are open-source. We note that libretexts.org is commonly found in web-scraped datasets, such as OpenWebMath. Our dataset, however, is exhaustive, structured, and cleaned.

We collect the HTML from each textbook page and convert it to latex using the OpenWebMath HTML-to-LaTeX pro-

cessor. We apply additional filtering to each page to remove bibliographies and metadata. To structure our dataset further, we concatenate short consecutive textbook chapters, so that each ‘chapter’ in our dataset contains at least 512 words. The resulting dataset consists in 1,685 textbooks, 78,000 chapters, and 160M words, and covers all education domains, including STEM, humanities and social sciences. The dataset is highly structured and documented, each chapter being traceable to its exact position in each textbook. We release this dataset for future research.

Dialogue generation We generate TUTORCHAT from our textbooks using GPT-3.5-Turbo (Brown et al., 2020) and GPT-4-Turbo (OpenAI, 2023). We use two main prompting strategies: we simulate teacher-student conversations using two instances of GPT-3.5 and we use a single instance of GPT-4 to simulate an entire conversation.

For both generation strategies, we simulate *open-book* and *closed-book* conversations using textbook chapters. Open-book dialogues simulate the student asking questions about the chapter to the teacher, and closed-book dialogues simulate the teacher using the chapter to give a lesson to the student about the chapter’s topic. For closed-book dialogues, the teacher is prompted with the entire chapter but not the student, so that the resulting conversation can be understood without access to the textbook chapter.

Using GPT-4, we also generate *textbook exams*: these are exam scripts, with solutions, based on a chapter, without conversational formatting. We find that this helps GPT-4 include harder reasoning tasks than would normally arise in a conversational setting. See Appendix E for more details.

TUTORCHAT consists of 78K dialogues. On average, each dialogue contains 1,800 words over 15 turns. 40% of the dataset is generated with GPT-4, and 60% with GPT-3.5. We create a validation split of 2.5K samples from TUTORCHAT. These textbook chapters were used by TUTOREVAL annotators to write questions.




Figure 4: TUTOREVAL results for fine-tuning LLEMMa-7B-32K with various subsets of TUTORCHAT-STEM. Each subset contains 10K samples. See Table 12 for more results.

4.2. Dataset Inspection

Quality control Empirically, we find that dialogues generated by GPT-4 are more factual and challenging than those written by GPT-3.5. GPT-3.5 dialogues are more error-prone and sometimes wander, but they are more conversational, realistic, and friendly. See Appendix F for examples of dialogues generated by GPT-3.5 and GPT-4.

TUTOREVAL contamination control The train split of TUTORCHAT does not contain any chapters used in TUTOREVAL. We further verify that fine-tuning with TUTORCHAT does not introduce test-set leakage by fine-tuning LLEMMa-7B-32K (see Section 5.3) on TUTORCHAT-STEM where we remove the entire textbooks that were used to construct TUTOREVAL. We find that this ablation performs similarly to the model fine-tuned on the full TUTORCHAT-STEM train set (see Table 4). On TUTOREVAL, the ablation achieves 50.4 compared to 47.8. On TUTOREVAL-CLOSEDBOOK the ablation achieves 47.8 compared to 48.2.

Dataset experiments We run ablations to understand the impact of the TUTORCHAT generation strategy. We sample 10K sequences of the following types:

1. Dialogues generated by GPT-4 versus GPT-3.5
2. Open-book dialogues versus closed-book
3. Dialogues simulating a strong versus a weak student. Strong students are prompted to be confident and knowledgeable, whereas weak students are prompted to be unfocused, error-prone, and
4. A random sample of TUTORCHAT dialogues

We fine-tune LLEMMa-7B-32K (see Section 5.3) on each dataset and we report results in Figure 4 and Table 12 in Appendix G. See also Appendix H for data-processing details. On TUTOREVAL, we find that the GPT-4 data gives better results than GPT-3.5 data. However, this performance gap is mostly due to the 13% of ‘misleading’ questions. Similarly, dialogues simulating weak students mostly help

with misleading questions. This shows that TUTORCHAT helps mitigate sycophancy (Perez et al., 2023).

Open-book dialogues are also more effective than closed-book dialogues, both for TUTOREVAL and for CLOSED-BOOK. We believe that dialogues where an LM and a user discuss a common piece of text occur rarely in existing datasets, making TUTORCHAT a valuable contribution.

Table 3: TUTOREVAL results comparing different pre-trained models and base models. Most pre-trained models are not able to process long contexts so we only evaluate them on TUTOREVAL-CLOSEDBOOK.

	TUTOR-EVAL	CLOSED-BOOK
Math-specialized Models		
MAMmoTH-7B	-	1.5
MAMmoTH-13B	-	24.2
MAMmoTH-70B	-	2.8
WizardMath-7B	-	20.1
WizardMath-13B	-	28.2
WizardMath-70B	-	0.5
Llama-Pro-8B	-	31.6
Generalist Models		
Phi-2	-	28.6
Tulu-2-DPO-7B	-	33.4
Tulu-2-DPO-13B	-	42.6
Tulu-2-DPO-70B	-	59.5
Vicuna-13B-16K	33.2	37.7
Mistral-7B-V1	30.9	36.8
Zephyr-7B	46.3	50.4
Mistral-7B-V2	50.9	53.8
Mixtral-8x7B	66.3	68.2
Llama-3-8B	55.3	59.1
Llama-3-70B	71.3	78.3
GPT-3.5-Turbo-1106	68.3	69.6
GPT-4-Turbo-1106	85.2	86.1
Ablations		
Llama-2-7B-32k-MathMix	30.8	31.7
CodeLlama-32k-MathMix	43.2	37.1
Llemma-7B-MathMix	46.4	46.4
Ours		
Llemma-7B-32K-MathMix	50.5	46.6
Llemma-34B-MathMix	57.2	57.6

Finally, Table 12 shows that the random data sample has the most well-rounded performance across open-book and closed-book evaluations, and misleading and non-misleading questions. This shows that data diversity is key and that the engineering effort put into constructing

TUTORCHAT has produced a useful dataset.

5. Building LM Tutors

In this section, we investigate the main ingredients required for building strong and helpful LM tutors. In the following, we focus on developing LM tutors for math. Therefore, we ask the two following questions:

- (1) How important are training with scientific texts and TUTORCHAT as drivers of performance on TUTOREVAL?
- (2) How can we train an LM tutor that also has strong math problem-solving skills?

In Section 5.1, we begin by introducing our two best models: Llemma-7B-32K-MathMix and Llemma-34B-MathMix, and their training recipes. In Section 5.2, 5.3, 5.4, we answer the two above questions step-by-step, by finding the most suitable base model and the best curated fine-tuning data. As a result, our best models achieve competitive results on TUTOREVAL and math problem-solving tasks.

5.1. Method

We present the two-stage fine-tuning pipeline which we use to obtain the best TUTOREVAL results. We first extend the LM’s context-window to 32K tokens, and then train with TUTORCHAT. See Appendix H for hyperparameters.

Long-context training Llemma-7B has a context window of 4K tokens. This is too short for TUTOREVAL, so we create a 5B-token dataset from OpenWebMath by sampling documents of up to 32K tokens. We fine-tune with an increased RoPE base (Su et al., 2024), following Roziere et al. (2023). We name this model LLEMMA-7B-32K. Because of computational limitations, we are not able to run this context-extension phase on Llemma-34B, but we still increase the RoPE base before fine-tuning on TUTORCHAT.

TUTORCHAT fine-tuning We process teacher/student dialogues as assistant/user dialogues. We fine-tune on open-book dialogues by including the entire textbook chapter, and on closed-book dialogues by removing the textbook chapter. See Appendix H for processing details.

MathMix: a dataset for LM math tutors In Table 3, we compare fine-tuning with TUTORCHAT and TUTORCHAT-STEM, the subset of dialogues about science textbooks. We find that we can further improve TUTOREVAL performance by combining TUTORCHAT-STEM and MetaMath. We process the original MetaMath dataset by randomly concatenating 10 question/answer pairs. The resulting MetaMath dataset contains 40K samples and an average sequence length of 3,000 tokens, similar to TUTORCHAT-STEM. We refer to the mix of TUTORCHAT-STEM and MetaMath as

MathMix. We collect TUTOREVAL results in Tables 3 and 4. See Sections 5.2, 5.3, and 5.4 for analysis.

Table 4: TUTOREVAL results for fine-tuning LLEMMA-7B-32K with different dialogue datasets. We add MetaMath to each dataset because we are also interested in achieving strong performance on MATH and GSM8K, see Figure 5.

Fine-tuning data	TUTOR-EVAL	CLOSED-BOOK
MetaMath	14.5	20.5
UltraChat + MetaMath	39.9 35.0	41.2 45.1
TUTORCHAT + MetaMath	48.4 48.2	50.9 49.7
TUTORCHAT-STEM + MetaMath (=MathMix)	47.8 46.6	48.2 50.5

5.2. Investigating Foundation Models

By comparing Llama-2 based models, CodeLlama and Llemma-7B, we find that TUTOREVAL benefits significantly from training on scientific text.

Baselines We fine-tune Llama-2-7B and CodeLlama-7B with MathMix as in Section 5.1. Recall that Llemma was trained from CodeLlama, which was trained from Llama-2, so this helps isolating the effect of continued-training. To show the impact of long-context training, we also fine-tune a base Llemma model with MATHMIX directly, and refer to this model as LLEMMA-7B-MATHMIX. Finally, we compare these models with MAmmoTH and WizardMath up to 70B parameters, Llama-Pro-8B-Instruct (Wu et al., 2024), and various pre-trained models. The short-context models are only evaluated on TUTOREVAL-CLOSEDBOOK.

Results See Table 3. Llama-2-based models do poorly on TUTOREVAL-CLOSEDBOOK. Only Tulu-2-DPO-70B improves over our best 7B model. The poor scores achieved by the math models confirms that training directly for GSM8K and MATH does not produce usable models. Note also that Llama-Pro-8B-Instruct was trained on the same data as Llemma and was tuned on a dataset including MetaMath. Comparing with LLEMMA-7B-MATHMIX shows the strength of our data.

In our experiments, CODELLAMA-32K-MATHMIX ranks between our Llama-2 and Llemma models. This confirms the usefulness of training on code and on scientific data. Unsurprisingly, Table 5 shows that CodeLlama is strong on computer science questions. Long-context training is found to improve TUTOREVAL performance by 4 points without harming CLOSEDBOOK, verifying that this helps long

context understanding. In summary, comparing Llemma-7B-32K-MathMix with other Llama-2 models shows the strength of training with scientific data and the efficiency of our fine-tuning. Table 5 shows that Llemma-7B-32K-MathMix is stronger than Mistral-7B-V2 on math questions but weaker in other domains. Overall, Mistral performs slightly better than our best 7B Llemma model¹.

5.3. Investigating Fine-tuning Datasets

Having established that LLEMMA-7B-32K is a strong base model, we compare different fine-tuning datasets.

Baselines We fine-tune LLEMMA-7B-32K with the following datasets:

1. UltraChat (80K samples)
2. TUTORCHAT (75K samples)
3. TUTORCHAT-STEM (40K samples)

We also investigate the effect of mixing MetaMath into each of these datasets. Recall that MathMix is TUTORCHAT-STEM + MetaMath and consists of 80K samples total. For exact comparison with MathMix, we only mix 40K UltraChat samples with MetaMath, giving 80K samples total.

Results Table 4 shows that fine-tuning with TUTORCHAT improves TUTOREVAL by 9 points over UltraChat, clearly showing the benefits of TUTORCHAT. MathMix is the strongest model on TUTOREVAL but is weaker than the TUTORCHAT models for closed-book evaluation. However, in Section 5.4, we show that MathMix is much stronger on math problem solving tasks.

5.4. Investigating LM Tutors for Math

Having identified that training with scientific texts and fine-tuning with TUTORCHAT improve TUTOREVAL performance significantly, we investigate how to build a strong LM tutor specialized in math.

In Figure 5, we plot the TUTOREVAL performance of different fine-tuned Llemma-7B-32K models against their average GSM8K and MATH scores (details in Table 13). We see that fine-tuning with TUTORCHAT alone does not improve performance on math tasks. Surprisingly, combining TUTORCHAT with MetaMath does not significantly improve math performance either. However, TUTORCHAT allows us to target science-specific dialogues, and we find that TUTORCHAT-STEM significantly improves math performance when combined with MetaMath to form MathMix.

The resulting model, Llemma-7B-32K-MathMix, outper-

¹Note that Mistral-7B-V2 is an industry-grade closed-source LM and that Llemma-7B-32K-MathMix is obtained from Llama-2 with open-source data.




Figure 5: Combined performance on TUTOREVAL and math oriented datasets (average of GSM8K & MATH). In red are our models trained with MathMix, with 7B and 34B parameters. In purple are 7B-parameter baselines trained from Llemma-7B-32K. We also include the pre-trained Mistral-7B-V2 in green.

forms the strong Mistral-7B-V2 baseline on math tasks, while matching its TUTOREVAL performance. This strong result illustrates the richness and usefulness of the TUTORCHAT dataset. In Tables 14 and 15, we also evaluate our models on code and a suite of general NLP tasks. We find that Llemma-7B-32K-MathMix achieves similar coding performance to CodeLlama-7B.

5.5. Human Evaluation and Empirical Observations

See Table 2 for the human TUTOREVAL scores attributed to LLEMMA-7B-32K-ULTRACHAT and Llemma-7B-32K-MathMix. There is high agreement about these model’s rankings: 16/17 annotators rank MATHMIX above UltraChat for correctness and presentation.

Empirically, we find that Llemma-7B-32K-MathMix tends to give very detailed answers. It often copies GPT-4’s style by using enumerations and choosing similar examples. It also asks lots of follow-up questions.

TUTOREVAL does not evaluate multi-turn conversations. However, we observed that Llemma-7B-32K-MathMix has the ability to hold a conversation about a given chapter over multiple turns without losing coherence. We also noticed that it adjusts the level of its answers depending on how confused the student appears to be, and it often picks up on the student answers by emphasizing how well the student understood the chapter.

We also observed that Llemma-7B-32K-MathMix is quite robust to misleading questions, such as questions implying that the textbook is wrong. In such cases, Llemma-7B-32K-MathMix does not side with the student and politely but firmly clarifies the confusion.

6. Conclusion and Future Work

We have introduced TUTOREVAL and TUTORCHAT with the hope of encouraging the development of LMs as useful scientific assistants. Moreover, the methodology behind TUTOREVAL opens up new avenues for creating ever-more specialised evaluations, relying on LM evaluators to measure behaviors not captured by other NLP metrics.

As follow-up work, we plan to keep building up TUTOREVAL to cover more science disciplines, more levels of difficulty, and more diverse use-cases. We believe that the dataset presented in this paper can be the foundation of a large-scale crowd-sourcing effort for the research community to define how it would like LMs to be applied as a transformative technology.

Impact Statement

This paper presents work whose goal is to advance the field of Machine Learning. There are many potential societal consequences of our work, none of which we feel must be specifically highlighted here.

Acknowledgments

ARF was supported by the Israel Academy of Sciences and Humanities & Council for Higher Education Excellence Fellowship Program for International Postdoctoral Researchers and partially supported by STRANO PID2021-122752NB-I0. SM acknowledges funding provided by the Sivian Fund and the Roger Dashen Member Fund at the Institute for Advanced Study. This material is based upon work supported by the U.S. Department of Energy, Office of Science, Office of High Energy Physics under Award Number DE-SC0009988.

References

Austin, J., Odena, A., Nye, M., Bosma, M., Michalewski, H., Dohan, D., Jiang, E., Cai, C., Terry, M., Le, Q., et al. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732*, 2021.

Azerbayev, Z., Schoelkopf, H., Paster, K., Santos, M. D., McAleer, S., Jiang, A. Q., Deng, J., Biderman, S., and Welleck, S. Llemma: An open language model for mathematics, 2023.

Bisk, Y., Zellers, R., Gao, J., Choi, Y., et al. Pixa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 7432–7439, 2020.

Brown, T. B., Mann, B., Ryder, N., Subbiah, M., Kaplan, J., Dhariwal, P., Neelakantan, A., Shyam, P., Sastry, G., Askell, A., Agarwal, S., Herbert-Voss, A., Krueger, G., Henighan, T., Child, R., Ramesh, A., Ziegler, D. M., Wu, J., Winter, C., Hesse, C., Chen, M., Sigler, E., Litwin, M., Gray, S., Chess, B., Clark, J., Berner, C., McCandlish, S., Radford, A., Sutskever, I., and Amodei, D. Language models are few-shot learners, 2020.

Chen, M., Tworek, J., Jun, H., Yuan, Q., Pinto, H. P. d. O., Kaplan, J., Edwards, H., Burda, Y., Joseph, N., Brockman, G., et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

Chen, Y., Wang, R., Jiang, H., Shi, S., and Xu, R. Exploring the use of large language models for reference-free text quality evaluation: An empirical study, 2023.

Chiang, C.-H. and Lee, H.-y. Can large language models be an alternative to human evaluations? In Rogers, A., Boyd-Graber, J., and Okazaki, N. (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15607–15631, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.870. URL <https://aclanthology.org/2023.acl-long.870>.

Clark, C., Lee, K., Chang, M.-W., Kwiatkowski, T., Collins, M., and Toutanova, K. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In Burstein, J., Doran, C., and Solorio, T. (eds.), *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 2924–2936, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1300. URL <https://aclanthology.org/N19-1300>.

Clark, P., Cowhey, I., Etzioni, O., Khot, T., Sabharwal, A., Schoenick, C., and Tafjord, O. Think you have solved question answering? try arc, the ai2 reasoning challenge. *ArXiv*, abs/1803.05457, 2018. URL <https://api.semanticscholar.org/CorpusID:3922816>.

Cobbe, K., Kosaraju, V., Bavarian, M., Chen, M., Jun, H., Kaiser, L., Plappert, M., Tworek, J., Hilton, J., Nakano, R., Hesse, C., and Schulman, J. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Collins, K. M., Jiang, A. Q., Frieder, S., Wong, L., Zilka, M., Bhatt, U., Lukasiewicz, T., Wu, Y., Tenenbaum, J. B., Hart, W., Gowers, T., Li, W., Weller, A., and Jamnik, M. Evaluating language models for mathematics through interactions, 2023.

Dao, T. FlashAttention-2: Faster attention with better parallelism and work partitioning. 2023.

Dao, T., Fu, D. Y., Ermon, S., Rudra, A., and Ré, C. FlashAttention: Fast and memory-efficient exact attention with IO-awareness. In *Advances in Neural Information Processing Systems*, 2022.

Ding, N., Chen, Y., Xu, B., Qin, Y., Hu, S., Liu, Z., Sun, M., and Zhou, B. Enhancing chat language models by scaling high-quality instructional conversations. In Bouamor, H., Pino, J., and Bali, K. (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 3029–3051, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.183. URL <https://aclanthology.org/2023.emnlp-main.183>.

Frieder, S., Pinchetti, L., Griffiths, R.-R., Salvatori, T., Lukasiewicz, T., Petersen, P. C., Chevalier, A., and Berner, J. Mathematical capabilities of chatgpt. *arXiv preprint arXiv:2301.13867*, 2023.

Gao, L., Tow, J., Abbasi, B., Biderman, S., Black, S., DiPofi, A., Foster, C., Golding, L., Hsu, J., Le Noac'h, A., Li, H., McDonell, K., Muennighoff, N., Ociepa, C., Phang, J., Reynolds, L., Schoelkopf, H., Skowron, A., Sutawika, L., Tang, E., Thite, A., Wang, B., Wang, K., and Zou, A. A framework for few-shot language model evaluation, 12 2023. URL <https://zenodo.org/records/10256836>.

Gunasekar, S., Zhang, Y., Aneja, J., Mendes, C. C. T., Del Giorno, A., Gopi, S., Javaheripi, M., Kauffmann, P., de Rosa, G., Saarikivi, O., et al. Textbooks are all you need. *arXiv preprint arXiv:2306.11644*, 2023.

Hendrycks, D., Burns, C., Basart, S., Zou, A., Mazeika, M., Song, D., and Steinhardt, J. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021a.

Hendrycks, D., Burns, C., Kadavath, S., Arora, A., Basart, S., Tang, E., Song, D., and Steinhardt, J. Measuring mathematical problem solving with the math dataset. In Vanschoren, J. and Yeung, S. (eds.), *Proceedings of the Neural Information Processing Systems Track on Datasets and Benchmarks*, volume 1. Curran, 2021b. URL https://datasets-benchmarks-proceedings.neurips.cc/paper_files/paper/2021/file/be83ab3ecd0db773eb2dc1b0a17836a1-Paper-round2.pdf.

Huang, Q., Vora, J., Liang, P., and Leskovec, J. Benchmarking large language models as ai research agents. *arXiv preprint arXiv:2310.03302*, 2023.

Jiang, A. Q., Sablayrolles, A., Mensch, A., Bamford, C., Chaplot, D. S., Casas, D. d. l., Bressand, F., Lengyel, G., Lample, G., Saulnier, L., et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In Bengio, Y. and LeCun, Y. (eds.), *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL <http://arxiv.org/abs/1412.6980>.

Kwiatkowski, T., Palomaki, J., Redfield, O., Collins, M., Parikh, A., Alberti, C., Epstein, D., Polosukhin, I., Devlin, J., Lee, K., Toutanova, K., Jones, L., Kelcey, M., Chang, M.-W., Dai, A. M., Uszkoreit, J., Le, Q., and Petrov, S. Natural questions: A benchmark for question answering research. *Transactions of the Association for Computational Linguistics*, 7:452–466, 2019. doi: 10.1162/tacl_a_00276. URL <https://aclanthology.org/Q19-1026>.

Lewkowycz, A., Andreassen, A., Dohan, D., Dyer, E., Michalewski, H., Ramasesh, V., Sloane, A., Anil, C., Schlag, I., Gutman-Solo, T., et al. Solving quantitative reasoning problems with language models. *Advances in Neural Information Processing Systems*, 35:3843–3857, 2022.

Li, X., Zhang, T., Dubois, Y., Taori, R., Gulrajani, I., Guestrin, C., Liang, P., and Hashimoto, T. B. Alpacaeval: An automatic evaluator of instruction-following models. https://github.com/tatsu-lab/alpaca_eval, 2023a.

Li, Y., Bubeck, S., Eldan, R., Del Giorno, A., Gunasekar, S., and Lee, Y. T. Textbooks are all you need ii: phi-1.5 technical report. *arXiv preprint arXiv:2309.05463*, 2023b.

Li, Y., Qu, S., Shen, J., Min, S., and Yu, Z. Curriculum-driven edubot: A framework for developing language learning chatbots through synthesizing conversational data, 2023c.

Lian, W., Goodson, B., Pentland, E., Cook, A., Vong, C., and "Teknium". Openorca: An open dataset of gpt augmented flan reasoning traces. <https://huggingface.co/Open-Orca/OpenOrca>, 2023.

Luo, H., Sun, Q., Xu, C., Zhao, P., Lou, J., Tao, C., Geng, X., Lin, Q., Chen, S., and Zhang, D. Wizardmath: Empowering mathematical reasoning for large language models via reinforced evol-instruct. *arXiv preprint arXiv:2308.09583*, 2023.

Macina, J., Daheim, N., Chowdhury, S., Sinha, T., Kapur, M., Gurevych, I., and Sachan, M. MathDial: A dialogue tutoring dataset with rich pedagogical properties grounded in math reasoning problems. In Bouamor, H., Pino, J., and Bali, K. (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 5602–5621, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp.372. URL <https://aclanthology.org/2023.findings-emnlp.372>.

Mukherjee, S., Mitra, A., Jawahar, G., Agarwal, S., Palangi, H., and Awadallah, A. Orca: Progressive learning from complex explanation traces of gpt-4. *arXiv preprint arXiv:2306.02707*, 2023.

OpenAI. Gpt-4 technical report, 2023.

Paperno, D., Kruszewski, G., Lazaridou, A., Pham, N. Q., Bernardi, R., Pezzelle, S., Baroni, M., Boleda, G., and Fernández, R. The LAMBADA dataset: Word prediction requiring a broad discourse context. In Erk, K. and Smith, N. A. (eds.), *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1525–1534, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1144. URL <https://aclanthology.org/P16-1144>.

Paster, K., Santos, M. D., Azerbayev, Z., and Ba, J. Openwebmath: An open dataset of high-quality mathematical web text. *arXiv preprint arXiv:2310.06786*, 2023.

Perez, E., Ringer, S., Lukosiute, K., Nguyen, K., Chen, E., Heiner, S., Pettit, C., Olsson, C., Kundu, S., Kadavath, S., Jones, A., Chen, A., Mann, B., Israel, B., Seethor, B., McKinnon, C., Olah, C., Yan, D., Amodei, D., Amodei, D., Drain, D., Li, D., Tran-Johnson, E., Khundadze, G., Kernion, J., Landis, J., Kerr, J., Mueller, J., Hyun, J., Landau, J., Ndousse, K., Goldberg, L., Lovitt, L., Lucas, M., Sellitto, M., Zhang, M., Kingsland, N., Elhage, N., Joseph, N., Mercado, N., Das-Sarma, N., Rausch, O., Larson, R., McCandlish, S., Johnston, S., Kravec, S., El Showk, S., Lanham, T., Telleen-Lawton, T., Brown, T., Henighan, T., Hume, T., Bai, Y., Hatfield-Dodds, Z., Clark, J., Bowman, S. R., Askell, A., Grosse, R., Hernandez, D., Ganguli, D., Hubinger, E., Schiefer, N., and Kaplan, J. Discovering language model behaviors with model-written evaluations. In Rogers, A., Boyd-Graber, J., and Okazaki, N. (eds.), *Findings of the Association for Computational Linguistics: ACL 2023*, pp. 13387–13434, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-acl.847. URL <https://aclanthology.org/2023.findings-acl.847>.

Peskoff, D. and Stewart, B. Credible without credit: Domain experts assess generative language models. In Rogers, A., Boyd-Graber, J., and Okazaki, N. (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pp. 427–438, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-short.37. URL <https://aclanthology.org/2023.acl-short.37>.

Roziere, B., Gehring, J., Gloeckle, F., Sootla, S., Gat, I., Tan, X. E., Adi, Y., Liu, J., Remez, T., Rapin, J., et al. Code Llama: Open foundation models for code. *arXiv preprint arXiv:2308.12950*, 2023.

Sakaguchi, K., Bras, R. L., Bhagavatula, C., and Choi, Y. Winogrande: an adversarial winograd schema challenge at scale. *Commun. ACM*, 64(9):99–106, aug 2021. ISSN 0001-0782. doi: 10.1145/3474381. URL <https://doi.org/10.1145/3474381>.

Su, J., Ahmed, M., Lu, Y., Pan, S., Bo, W., and Liu, Y. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Sun, L., Han, Y., Zhao, Z., Ma, D., Shen, Z., Chen, B., Chen, L., and Yu, K. Scieval: A multi-level large language model evaluation benchmark for scientific research, 2023.

Taylor, R., Kardas, M., Cucurull, G., Scialom, T., Hartshorn, A., Saravia, E., Poulton, A., Kerkez, V., and Stojnic, R. Galactica: A large language model for science. *arXiv preprint arXiv:2211.09085*, 2022.

Touvron, H., Martin, L., Stone, K., Albert, P., Almahairi, A., Babaei, Y., Bashlykov, N., Batra, S., Bhargava, P., Bhosale, S., Bikel, D., Blecher, L., Ferrer, C. C., Chen, M., Cucurull, G., Esiobu, D., Fernandes, J., Fu, J., Fu, W., Fuller, B., Gao, C., Goswami, V., Goyal, N., Hartshorn, A., Hosseini, S., Hou, R., Inan, H., Kardas, M., Kerkez, V., Khabsa, M., Kloumann, I., Korenev, A., Koura, P. S., Lachaux, M.-A., Lavril, T., Lee, J., Liskovich, D., Lu, Y., Mao, Y., Martinet, X., Mihaylov, T., Mishra, P., Molybog, I., Nie, Y., Poulton, A., Reizenstein, J., Rungta, R., Saladi, K., Schelten, A., Silva, R., Smith, E. M., Subramanian, R., Tan, X. E., Tang, B., Taylor, R., Williams, A., Kuan, J. X., Xu, P., Yan, Z., Zarov, I., Zhang, Y., Fan, A., Kambadur, M., Narang, S., Rodriguez, A., Stojnic, R., Edunov, S., and Scialom, T. Llama 2: Open foundation and fine-tuned chat models, 2023.

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, L., and Polosukhin, I. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Wang, X., Hu, Z., Lu, P., Zhu, Y., Zhang, J., Subramaniam, S., Loomba, A. R., Zhang, S., Sun, Y., and Wang, W. Scibench: Evaluating college-level scientific problem-solving abilities of large language models. *arXiv preprint arXiv:2307.10635*, 2023.

Welbl, J., Liu, N. F., and Gardner, M. Crowdsourcing multiple choice science questions. In Derczynski, L., Xu, W., Ritter, A., and Baldwin, T. (eds.), *Proceedings of the 3rd Workshop on Noisy User-generated Text*, pp. 94–106, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4413. URL <https://aclanthology.org/W17-4413>.

Wu, C., Gan, Y., Ge, Y., Lu, Z., Wang, J., Feng, Y., Luo, P., and Shan, Y. Llama pro: Progressive llama with block expansion, 2024.

Wu, Y., Henriksson, A., Duneld, M., and Nouri, J. Towards improving the reliability and transparency of chatgpt for educational question answering. In Viberg, O., Jivet, I., Muñoz-Merino, P. J., Perifanou, M., and Papathoma, T. (eds.), *Responsive and Sustainable Educational Futures*, pp. 475–488, Cham, 2023. Springer Nature Switzerland. ISBN 978-3-031-42682-7.

Yu, L., Jiang, W., Shi, H., Yu, J., Liu, Z., Zhang, Y., Kwok, J. T., Li, Z., Weller, A., and Liu, W. Metamath: Bootstrap your own mathematical questions for large language models. *arXiv preprint arXiv:2309.12284*, 2023.

Yue, X., Qu, X., Zhang, G., Fu, Y., Huang, W., Sun, H., Su, Y., and Chen, W. Mammoth: Building math generalist models through hybrid instruction tuning. *arXiv preprint arXiv:2309.05653*, 2023.

Zellers, R., Holtzman, A., Bisk, Y., Farhadi, A., and Choi, Y. HellaSwag: Can a machine really finish your sentence? In Korhonen, A., Traum, D., and Márquez, L. (eds.), *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4791–4800, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1472. URL <https://aclanthology.org/P19-1472>.

Zeng, Z., Yu, J., Gao, T., Meng, Y., Goyal, T., and Chen, D. Evaluating large language models at evaluating instruction following. *arXiv preprint arXiv:2310.07641*, 2023.

Zhao, W., Ren, X., Hessel, J., Cardie, C., Choi, Y., and Deng, Y. (inthe)wildchat: 570k chatGPT interaction logs in the wild. In *The Twelfth International Conference on Learning Representations*, 2024. URL <https://openreview.net/forum?id=B18u7ZR1bM>.

Zheng, L., Chiang, W.-L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E. P., Zhang, H., Gonzalez, J., and Stoica, I. Judging llm-as-a-judge with mt-bench and chatbot arena. *ArXiv*, abs/2306.05685, 2023. URL <https://api.semanticscholar.org/CorpusID:259129398>.

A. Examples of TUTOREVAL questions

Below we list some examples of TUTOREVAL questions by domain.

A.1. Mathematics

Chapter url:

https://math.libretexts.org/Bookshelves/Algebra/Advanced_Algebra/09%3A_Sequences_Series_and_the_Binomial_Theorem/9.04%3A_Binomial_Theorem

Question: Can you walk me through the calculations for Exercise 1? I'd like to see another example worked out in the same level of detail as Example 2.

Key points:

- the question asks to calculate 8 choose 5
- the answer is 56, as stated in the chapter
- show the student how to use cancellations in the binomial coefficient formula to avoid carrying out large multiplications

Additional information

- closed-book: no
- answer in chapter: yes
- misleading: no
- difficulty: easy

A.2. Computer science

Chapter url: [https://eng.libretexts.org/Bookshelves/Computer_Science/Applied_Programming/Book%3A_Neural_Networks_and_Deep_Learning_\(Nielsen\)/06%3A_Deep_Learning/6.04%3A_Recent_progress_in_image_recognition](https://eng.libretexts.org/Bookshelves/Computer_Science/Applied_Programming/Book%3A_Neural_Networks_and_Deep_Learning_(Nielsen)/06%3A_Deep_Learning/6.04%3A_Recent_progress_in_image_recognition)

Question: Is the dataset from ILSVRC-2012 a subset of the ImageNet dataset?

Key points:

- the full name of ILSVRC-2012 is ImageNet Large Scale Visual Recognition Challenge 2012
- ILSVRC-2012 contains 1000 categories and 1.2 million images

Additional information:

- closed-book: yes
- answer in chapter: yes
- misleading: no
- difficulty: easy

A.3. Physics

Chapter url:

[https://phys.libretexts.org/Bookshelves/Classical_Mechanics/Classical_Mechanics_\(Dourmashkin\)/13%3A_Energy_Kinetic_Energy_and_Work/13.05%3A_Work_done_by_Non-Constant_Forces](https://phys.libretexts.org/Bookshelves/Classical_Mechanics/Classical_Mechanics_(Dourmashkin)/13%3A_Energy_Kinetic_Energy_and_Work/13.05%3A_Work_done_by_Non-Constant_Forces)

Question: So the work done by a force F between x and y is simply the integral of F along the segment $[x;y]$?

Key points:

- The statement is imprecise.
- It is the integral of the component of F in the $y - x$ direction.

Additional information:

- closed-book: yes
- answer in chapter: yes
- misleading: yes

- difficulty: easy

A.4. Life sciences

Chapter url: [https://med.libretexts.org/Bookshelves/Anatomy_and_Physiology/Anatomy_and_Physiology_1e_\(OpenStax\)/Unit_3%3A_Regulation_Integration_and_Control/17%3A_The_Endocrine_System/17.03%3A_The_Pituitary_Gland_and_Hypothalamus](https://med.libretexts.org/Bookshelves/Anatomy_and_Physiology/Anatomy_and_Physiology_1e_(OpenStax)/Unit_3%3A_Regulation_Integration_and_Control/17%3A_The_Endocrine_System/17.03%3A_The_Pituitary_Gland_and_Hypothalamus)

Question: The section on antidiuretic hormone states that dehydration can result in high blood osmolarity. I don't really understand why that would happen. Will you please explain it to me?

Key points:

Key points:

- The student is confused about the relationship between blood osmolarity and hydration
- State that osmolarity is proportional to the amount of dissolved particles per unit volume
- Mention that the volume of consumed water influences blood volume
- State that lower blood volume given the same number of dissolved particles must result in higher osmolarity

Additional information:

- closed-book: no
- answer in chapter: no
- misleading: no
- difficulty: easy

A.5. Environmental science

Chapter url:

[https://eng.libretexts.org/Bookshelves/Environmental_Engineering_\(Sustainability_and_Conversation\)/Book%3A_Essentials_of_Environmental_Science_\(CK-12\)/13%3A_Untitled_Chapter_13/13.03%3A_New_Page](https://eng.libretexts.org/Bookshelves/Environmental_Engineering_(Sustainability_and_Conversation)/Book%3A_Essentials_of_Environmental_Science_(CK-12)/13%3A_Untitled_Chapter_13/13.03%3A_New_Page)

Question: So eutrophication could lead to hypoxia due to explosive growth of algae that consume oxygen?

Key points:

- This is false.
- The student is confused about the causes of oxygen depletion.
- Need to clarify the logical chain of eutrophication.

Additional information:

- closed-book: no
- answer in chapter: yes
- misleading: no
- difficulty: hard

B. Detailed TUTOREVAL results

Table 5: Detailed TUTOREVAL results for long-context models evaluated in this paper. We show scores by domain, difficulty, on the set of misleading questions, and in closed-book evaluation. Models are grouped as follows (top-down): (1) Strong pre-trained LLMs (2) Medium-sized pre-trained LMs (3) Our best models (4) Ablations of Llemma-7B-32K fine-tuned with different TUTORCHAT-based datasets (4) Ablations of different base models fine-tuned with MathMix (5) Ablations of Llemma models fine-tuned without TUTORCHAT.

Models	Domain					Difficulty		Mis-leading	TUTOR-EVAL	CLOSED-BOOK
	Math	Physics	CS	Life	Env	Easy	Hard			
GPT-4	83.4	84.0	88.9	91.3	86.5	88.6	77.7	75.9	85.5	87.5
Llama-3-70B	63.2	73.2	81.1	84.4	72.0	75.0	62.3	64.0	71.3	78.3
GPT-3.5	63.4	65.9	77.1	79.6	75.8	73.1	58.3	56.6	68.8	70.3
Mixtral-8x7B	61.8	63.1	75.0	72.9	74.2	71.3	55.3	54.4	66.7	68.7
Vicuna-13B-16K	25.6	28.5	47.2	46.3	36.8	38.1	21.3	23.4	33.2	37.7
Mistral-7B-V1	21.6	27.3	45.9	37.9	43.4	34.2	22.8	20.5	30.9	36.8
Zephyr-7B-Beta	36.7	43.9	60.5	53.8	59.1	50.5	35.9	33.5	46.3	50.4
Mistral-7B-V2	43.3	51.1	60.7	53.3	61.6	55.2	40.3	32.9	50.9	53.8
Llama-3-8B	46.5	52.9	68.2	68.1	61.0	59.8	44.1	43.6	55.3	59.8
Llemma-7B-32K-MathMix	45.7	51.1	56.8	55.0	53.1	56.6	35.6	29.4	50.5	46.6
Llemma-34B-MathMix	52.2	58.8	65.2	55.4	56.9	62.0	45.4	40.2	57.2	57.6
Llemma-7B-32K-TutorChat-STEM	43.2	48.6	55.0	49.2	48.4	52.6	36.2	29.0	47.8	48.2
Llemma-7B-32K-TutorChat	45.3	48.6	55.0	46.3	45.0	54.0	34.7	27.8	48.4	50.9
Llemma-7B-32K-TutorChat+MetaMath	43.7	47.0	56.0	49.2	51.6	53.5	35.1	28.5	48.2	49.7
Llama-32K-MathMix	21.0	33.9	40.0	53.8	34.3	33.5	24.2	23.5	30.8	31.7
CodeLlama-32K-MathMix	38.4	38.6	56.3	42.1	41.2	48.4	30.4	30.7	43.2	37.1
Llemma-7B-MathMix	42.9	45.3	55.0	42.5	44.3	51.9	33.1	26.5	46.4	46.4
Llemma-7B-32K-MetaMath	14.4	14.0	17.8	9.2	7.6	16.3	9.9	7.2	14.5	20.5
Llemma-7B-32K-Ultrachat	34.3	37.4	50.8	41.3	43.1	44.6	28.2	22.1	39.9	41.2
Llemma-7B-32K-MetaMath-Ultrachat	29.8	29.9	47.9	32.1	39.6	38.1	25.4	21.2	35.0	45.1

Table 6: Detailed human TUTOREVAL results. The 4 models below are graded blind by all annotators who contributed to TUTOREVAL. Each annotator grades the model on their set of approximately 50 questions and we collect all results to compute the final TUTOREVAL scores.

Models	Domain					Difficulty		Misleading Questions	TUTOR-EVAL
	Math	Physics	CS	Life	Env	Easy	Hard		
GPT-4	88.6	92.2	94.5	95.8	93.8	93.6	85.7	82.7	91.2
Llemma-7B-32K-MathMix	59.6	74.5	77.4	62.1	72.5	71.6	52.3	48.1	66.5
Llemma-7B-32K-Ultrachat	51.6	64.3	69.6	45.4	53.2	62.3	41.7	39.3	56.8
Vicuna-13B-16K	51.4	37.9	67.0	43.8	49.1	53.6	34.0	37.0	48.5

Table 7: We compare the GPT-4 and Llemma-34B-MathMix scores on different subsets of TUTOREVAL questions, evaluated both open-book (TUTOREVAL) and closed-book (CLOSED BOOK). Note that the final CLOSED BOOK score is the score achieved on closed-book questions only (370 questions) but that TUTOREVAL includes all questions (834 questions). These results show that open-book questions cannot be evaluated with CLOSED BOOK. These results also show how well LMs are able to utilize the added context to extract the answer when the question is marked as *answer in chapter*.

	GPT-4		Llemma-34B-MathMix		Number of Questions
	TUTOREVAL	CLOSED BOOK	TUTOREVAL	CLOSED BOOK	
Open-book Questions	83.4	67.2	54.9	42.9	464
Answer <i>not</i> in Chapter	81.4	67.1	50.0	40.5	261
Answer in Chapter	89.6	63.0	60.0	40.1	203
Closed-book Question	88.0	87.5	60.1	57.6	370
Answer <i>not</i> in Chapter	85.1	84.2	56.6	51.9	265
Answer in Chapter	93.9	89.8	68.8	63.4	105
Final score	85.5	87.5	57.2	57.6	834/370

C. TUTOREVAL grading

C.1. Grading template

Below is the template used for prompting the LM-evaluator to assign grades to model outputs on TUTOREVAL.

Your task is to evaluate the teaching abilities of a new AI system which is interacting with a student about a science topic. The student and AI system are working together on a textbook chapter, and I would like you to rate how well the AI system addressed the student's question.

You should give scores from 0 to 3 for PRESENTATION and CORRECTNESS. Half points are allowed. Please refer to the following descriptions:

PRESENTATION: the AI provides an engaging response which will make the student want to learn more. Examples of good presentation skills include: giving the response a clear and helpful structure, picking up on positive aspects of the student's contributions, using examples to clarify complicated ideas, explaining complicated arguments in detail, adding follow-up and broadening remarks, etc.

CORRECTNESS: the AI correctly understands the question and the answer is true and accurate. The answer does not contain any false or misleading statements. The AI does not include any irrelevant information and does not omit any essential reasoning steps. The AI also correctly relates the question to the chapter's content. Pay particular attention to reasoning and calculation mistakes.

Here is the textbook chapter used for this interaction:

```
"""
PASSAGE
"""
```

Here is the student's question:

```
"""
QUESTION
"""
```

To help you in your evaluation, we've compiled some ground-truth key points which a good AI system should cover in its answer. You MUST check that the AI's answer agrees with these key points. These key points have been checked by experts and are 100% correct. These key points are particularly useful for spotting CORRECTNESS errors.

```
"""
Key points to cover:
KEY POINTS
"""
```

Here is the AI's answer:

```
"""
ANSWER
"""
```

Please present your scores as follows:
 PRESENTATION: [explanation]. GRADE: x/3
 CORRECTNESS: [explanation]. GRADE: x/3

C.2. Grading ablations

We collect statistics to help us understand how well TUTOREVAL correlates with human for judging the 4 models evaluated in Table 2. For each of the 834 TUTOREVAL questions, we compute 3 statistics: the Pearson, the Spearman, and the Kendall- τ coefficient between GPT-4 and human grades. The Pearson measures how close GPT-4's grades are to the




Figure 6: For each human annotator, we plot the score attributed to GPT-4 against the score attributed to GPT-4 by itself, with and without the key points. We see that the key points make it possible for GPT-4 to grade its own generations fairly.

human grades, and the Spearman and Kendall- τ measure how similar the rankings are. When computing the Spearman and Kendall- τ , we count it as 0 if either GPT-4 assigns same grades to all models while human grades vary, or if human grades are identical while GPT-4's grades differ.

We average each of these coefficients over the 834 questions. Correlation coefficients for correctness are reported in Table 8 and coefficients for presentation are in Table 9. We compare the final values with the statistics we obtain in three other evaluation configurations:

1. Evaluate without showing GPT-4 the ground-truth key points
2. Evaluate without prompting GPT-4 for a presentation grade
3. Evaluate with GPT-3.5 instead of GPT-4

In all cases, we see that at least one correlation coefficient drops compared to the standard TUTOREVAL configuration. In Figure 6, we see that the key points are particularly useful for GPT-4 to grade its own generations fairly.

Correctness correlation	TUTOREVAL grading	Grading without key-points	Grading without presentation	GPT-3.5 grading
Pearson	60.0	56.7	56.4	47.3
Spearman rank	58.1	55.1	58.0	46.6
Kendall- τ	54.8	52.2	54.9	44.6

Table 8: We report three correlation coefficients between the human and LLM-evaluator correctness scores for each question in TUTOREVAL. The Pearson coefficient measures human/LLM correlation of grades, and the Spearman rank and Kendall- τ coefficients measure correlation of ranking. We run ablations on the standard TUTOREVAL approach by (1) grading with GPT-4 without the key points, (2) grading with GPT-4 without a presentation score and (3) grading with GPT-3.5.

Table 9: Three correlation coefficients for presentation scores between human and LLM-evaluator.

Presentation correlation	TUTOREVAL grading	Grading without key points	GPT-3.5 grading
Pearson	69.2	68.2	37.1
Spearman	67.6	67.2	36.5
Kendall- τ	63.2	62.8	34.2

In order to compare our GPT-4-grading approach to TUTOREVAL with other evaluations using GPT-4 as an evaluator, such as (Li et al., 2023a), we compute GPT-4 preference votes for three pairs of models:

1. Llemma-34B-MathMix and Mistral-7B-V2
2. Mistral-7B-V2 and Llemma-7B-32K-MathMix

3. Llemma-7B-32K-MathMix and Llemma-7B-32K-UltraChat.

For each pair of models A and B, we prompt GPT-4 with the outputs of the two models for each TUTOREVAL question twice, switching the order between the two models. We prompt GPT-4 to decide if Model A or B is more correct, or if there is a tie. When GPT-4 changes does not identify the same model during both rounds, we count this as a tie.

Win and tie rates are collected in Table 10. We find that the ranking that results from preference votes coincides with the ranking of Table 3, even for models which rank relatively closely, like Mistral-7B-V2 and Llemma-7B-32K-MathMix. We conclude that grading is as reliable as preference voting, while being considerably cheaper and faster to run.

win / Tie / win (%)	
Llemma-34B-MathMix	17.1
VS	69.9
Mistral-7B-V2	12.9
Mistral-7B-V2	17.9
VS	68.0
Llemma-7B-32K-MathMix	14.1
Llemma-7B-32K-MathMix	21.4
VS	70.0
Llemma-7B-32K-Ultrachat	8.8

Table 10: Win-rate comparisons of various models on TUTOREVAL questions, judged by GPT-4. The preference-based ranking matches the gradings-based ranking we obtain in Table 3.

D. TUTORCHAT composition

Table 11: Summary statistics for TUTORCHAT dialogues

Domains	Textbooks	Dialogues	Words
Biology	70	6K	9M
Business	77	7K	12M
Chemistry	119	12K	20M
Engineering	134	6K	10M
Geology	39	2K	4M
Human sciences	556	13K	21M
Mathematics	156	7K	12M
Medicine	91	4K	7M
Physics	71	5K	8M
Social sciences	248	12K	20M
Statistics	33	2K	3M
Workforce	91	2K	3M
Total STEM	713	45K	75M
Total	1685	78K	130M

E. TUTORCHAT generation

We generate open-book conversations by simulating a student asking questions about this chapter. We generate closed-book conversations by showing the chapter only to the teacher and prompting the teacher to conduct a class based on the chapter. We diversify our templates by simulating different teacher and student personalities. For example, we sometimes prompt the student to be bright and keen or slow and badly behaved. In total we use 16 different templates.

TUTORCHAT counts 15% of textbook exams, and the rest of TUTORCHAT is evenly split between open-book and closed-book dialogues.

Below is an example of a template used for generating conversations for TUTORCHAT. We initialise the ‘student’ and the ‘teacher’ with system prompts, and we start off the conversation by using a fixed template. We include an entire textbook chapter into this template.

Student system prompt

You are a student who struggles with staying focused and often finds yourself distracted during lessons. In your one-on-one tutoring session, you are dealing with a topic you're not very familiar with. You find yourself drifting off or not fully engaging with the material. Your lack of focus sometimes leads you to ask about things you've already covered or to miss key points in the explanation.

Teacher system prompt

You are a strict and detail-oriented teacher. You insist on precision and thoroughness in all answers. Your teaching style is focused on ensuring students understand the minutiae of every topic. You engage with your students actively but always emphasize the importance of accuracy and detail in their responses. While you are knowledgeable and committed to student learning, your approach is rigid and exacting, leaving no room for ambiguity or imprecise answers.

Template to start conversation

Here is a textbook chapter that you should learn for your upcoming exam. Read it carefully and let me know if you have any questions. This is your main opportunity to clarify any misunderstandings, so make the most of it! Don't be afraid to ask silly questions, I'm here to help!

#####

{text}

#####

Remember I'm your teacher so I'm here to answer all your questions about the textbook! Fire away!

F. TUTORCHAT examples

Below we give two examples of dialogues in TUTORCHAT. First we give a dialogue generated by GPT-4 about a linear algebra textbook chapter, and secondly we give an example of a GPT-3.5-generated dialogue about a biology textbook chapter.

F.1. GPT-4-generated dialogue

The following dialogue was generated using GPT-4. GPT-4 was presented with the following textbook chapter: [Click here](#) and was prompted to write a teacher-student dialogue simulating a class about its content.

<s>

assistant: Today we're going to discuss the concept of diagonalization of matrices. To start, let's consider a simple 2x2 matrix and determine whether it's diagonalizable. Take the matrix $A = \begin{pmatrix} 3 & 1 \\ 0 & 2 \end{pmatrix}$. Can you find the eigenvalues of this matrix?</s>

user: Uh, I'm not sure how to find eigenvalues.</s>

assistant: No problem. To find the eigenvalues, we need to solve the characteristic equation $\det(A - \lambda I) = 0$, where I is the identity matrix and λ represents the eigenvalues. Can you calculate the determinant of $A - \lambda I$?</s>

user: I think so. I subtract λ from the diagonal entries, right? So it becomes $\begin{pmatrix} 3 - \lambda & 1 \\ 0 & 2 - \lambda \end{pmatrix}$.</s>

assistant: That's correct. Now find the determinant of that matrix.</s>

user: I multiply the diagonal entries and then subtract the product of the off-diagonal entries, which gives me $(3 - \lambda)(2 - \lambda) - (0)(1)$, so the determinant is $\lambda^2 - 5\lambda + 6$.</s>

assistant: Almost there, but be careful. The determinant of a 2x2 matrix is the product of the diagonal entries minus the product of the off-diagonal entries. Since the off-diagonal entries in the lower left are zero, you only need to consider the diagonal product. So what's the determinant now?</s>

user: Oh, I see. So the determinant is just $(3 - \lambda)(2 - \lambda)$, which simplifies to $\lambda^2 - 5\lambda + 6$.</s>

assistant: Exactly. Now solve for λ when the determinant equals zero.</s>

user: So I set $\lambda^2 - 5\lambda + 6 = 0$ and solve for λ . I think the solutions are $\lambda = 2$ and $\lambda = 3$.</s>

assistant: That's right, those are the eigenvalues of matrix A. Now, let's find the eigenvectors corresponding to each eigenvalue. Start with $\lambda = 2$.</s>

user: I plug $\lambda = 2$ back into the matrix $A - \lambda I$, right? So I get the matrix $\begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix}$.</s>

assistant: Correct. Now find a vector v such that $(A - 2I)v = 0$.</s>

user: So I'm looking for a vector that makes this matrix equation equal zero... I'm not sure how to do that.</s>

assistant: Think of it as a system of linear equations. What vector can you multiply by that matrix to get the zero vector?</s>

user: Well, if I take $v = \begin{pmatrix} -1 \\ 1 \end{pmatrix}$, then I get the zero vector when I multiply it by $\begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix}$.</s>

assistant: Exactly, so you found an eigenvector for $\lambda = 2$. Now find an eigenvector for $\lambda = 3$.</s>

user: I plug $\lambda = 3$ into $A - \lambda I$ and get $\begin{pmatrix} 0 & 1 \\ 0 & -1 \end{pmatrix}$. So I need a vector that will give me the zero vector when I multiply...</s>

I'm not sure what to pick.</s>

assistant: Look at the system of equations you get from that matrix. It tells you that for any vector v , the first component doesn't matter, but the second component must be the negative of the first to cancel out the 1. Can you find a vector that satisfies this condition?</s>

user: Oh, I think I get it. So if I choose $v = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$, it satisfies the condition.</s>

assistant: Exactly right. Now that we have the eigenvalues and eigenvectors, we can check the criteria for diagonalizability. A matrix is diagonalizable if it has enough linearly independent eigenvectors. Since our matrix is 2x2, we need 2 linearly independent eigenvectors. Do we have that?</s>

user: Yes, the vectors $\begin{pmatrix} -1 \\ 1 \end{pmatrix}$ and $\begin{pmatrix} 1 \\ 0 \end{pmatrix}$ are linearly independent.</s>

F.2. GPT-3.5-generated dialogue

<s>

assistant: Today, we will dive into the intricate world of chromatin, chromosomes, and DNA organization within the eukaryotic cell. We'll explore the distinctions between heterochromatin and euchromatin, the structure of chromosomes, the packing of DNA through supercoiling, the role of telomeres in DNA replication, and the fascinating mechanisms of chromatin loop formation. The goal is to gain a comprehensive understanding of these fundamental concepts in biochemistry.

Does this sound like a good plan for our session today? Can you follow along so far?</s>

user: I understand that you're covering some complex topics today, but I must admit that I'm not very familiar with them. I'll do my best to stay focused, but I may need some extra help to ensure I understand everything properly. Can we maybe start by revisiting the basics before delving into the more intricate details? That might help me grasp the concepts better.</s>

assistant: Absolutely, it's perfectly fine to revisit the basics before delving into the more complex details. Understanding the fundamentals is crucial for building a strong foundation in biochemistry. Let's start by revisiting the basics.

First, let's discuss the distinction between heterochromatin and euchromatin. Heterochromatin and euchromatin are two different structural forms of chromatin, which is a complex of DNA and proteins found in eukaryotic cells. Heterochromatin appears as dark, densely packed regions in the cell nucleus, while euchromatin appears as lighter, less densely packed regions.

Can you explain the differences between heterochromatin and euchromatin based on what we've just discussed?</s>

user: So, from what you've just explained, it seems that heterochromatin is the densely packed form of chromatin, while euchromatin is less densely packed. Heterochromatin appears as dark regions in the cell nucleus, and euchromatin appears as lighter regions. Heterochromatin is typically associated with gene silencing, while euchromatin is associated with active gene expression.

I hope I got that right. It's a bit tricky for me to grasp, but I'm doing my best to follow along.</s>

assistant: You've grasped the basic concepts well! Heterochromatin is indeed densely packed and associated with gene

silencing, while euchromatin is less densely packed and associated with active gene expression. Understanding these distinctions is fundamental to comprehending the organization and regulation of genetic material within eukaryotic cells.

Now, let's move on to the structure of chromosomes and the organization of DNA within them. Can you explain what a chromosome is and how DNA is organized within it based on the information we've covered so far?</s>

user: I remember that chromosomes are structures made of DNA and proteins, and they contain the genetic information of an organism. The DNA within chromosomes is organized through a process called supercoiling, where the DNA strands are tightly coiled around proteins called histones. This coiling allows for the efficient packaging of the long DNA molecules into the compact structure of the chromosome.

I'm trying to connect the dots based on what we've discussed earlier. It's a bit challenging for me, but I'm doing my best to keep up.</s>

assistant: You're absolutely correct! Chromosomes are indeed structures made of DNA and proteins, and they contain the genetic information of an organism. The organization of DNA within chromosomes involves supercoiling, where the DNA strands are tightly coiled around histone proteins, allowing for efficient packaging of the genetic material.

Understanding these fundamental concepts is vital for appreciating the intricacies of DNA organization and its impact on genetic expression. Now, let's delve into the details of supercoiling and its significance in DNA metabolism. Can you explain the concept of supercoiling and its role in DNA packaging and regulation of genetic code based on our discussion?</s>

user: I think supercoiling refers to the coiling of DNA around histone proteins, which allows for the efficient packaging of the DNA into the compact structure of the chromosome. This coiling helps regulate gene expression by controlling the accessibility of the DNA to the cellular machinery that reads and transcribes the genetic code.

I hope I've understood the concept correctly. It's quite challenging for me to grasp these intricate details, but I'm trying my best to follow along.</s>

assistant: You're on the right track! Supercoiling does indeed involve the coiling of DNA around histone proteins to efficiently package the DNA into the compact structure of the chromosome. This packaging plays a crucial role in regulating gene expression by controlling the accessibility of the DNA to the cellular machinery responsible for reading and transcribing the genetic code.

Understanding the impact of supercoiling on gene regulation is essential for comprehending the intricate mechanisms of DNA organization and genetic expression.

Now, let's move on to the next topic: telomeres. Can you explain what telomeres are and their significance in DNA replication and cell division, based on what we've discussed so far?

user: Telomeres are repetitive nucleotide sequences located at the ends of chromosomes. They play a crucial role in DNA replication and cell division by protecting the ends of the chromosomes from deterioration or fusion with neighboring chromosomes. Telomeres also help in preventing the loss of genetic information during DNA replication, as the replication machinery cannot fully replicate the ends of linear DNA molecules.

I'm trying to connect the dots based on our discussion. It's challenging for me to fully engage with the material, but I'm doing my best to grasp the concepts.</s>

assistant: You're absolutely correct! Telomeres are repetitive nucleotide sequences located at the ends of chromosomes, and they serve the crucial role of protecting the chromosome ends from deterioration or fusion with neighboring chromosomes. Additionally, telomeres help prevent the loss of genetic information during DNA replication, as the replication machinery cannot fully replicate the ends of linear DNA molecules.

Understanding the significance of telomeres in DNA replication and chromosome stability is pivotal for comprehending the intricate processes that ensure genetic integrity.

Now, let's move on to the next topic: chromatin structure. Can you explain the concept of chromatin structure and its relevance to gene regulation and DNA organization, based on our discussion so far?</s>

user: I think chromatin structure refers to the organization of DNA and proteins in the nucleus of a cell. It plays a crucial role in gene regulation, as the accessibility of the DNA to the cellular machinery is influenced by the packing and modification of the chromatin structure. Changes in the chromatin structure can impact gene expression by either allowing or preventing

the transcription machinery from accessing specific regions of the DNA.

I'm trying to piece together the information we've discussed. It's quite challenging for me to fully engage with the material, but I'm doing my best to understand the concepts.</s>

assistant: You've captured the essence of chromatin structure very well! Chromatin structure indeed encompasses the organization of DNA and proteins within the nucleus of a cell, and it significantly influences gene regulation. The packing and modification of chromatin structure play a crucial role in determining the accessibility of DNA to the cellular machinery, ultimately impacting gene expression.

Understanding the intricate details of chromatin structure and its impact on gene regulation is fundamental for comprehending the complexities of DNA organization and genetic expression.

Thank you for your diligent effort in grasping these challenging concepts. Your dedication to understanding the material is commendable.

Thank you! That's all for today!

G. TUTORCHAT ablations

Table 12: We control the usefulness of various sub-splits of TUTORCHAT-STEM by fine-tuning LLEMMA-7B-32K and evaluating on TUTOREVAL. All datasets contain 10K samples. The set of misleading questions in TUTOREVAL accounts for most of the performance gaps, suggesting that the model becomes sycophantic when training on certain splits.

	Non-misleading questions	Misleading questions	TUTOREVAL	CLOSED-BOOK
GPT-4 generations	46.7	33.4	45.6	42.6
GPT-3.5 generations	46.8	25.8	43.9	38.4
Open-book dialogues	45.5	27.0	43.3	41.6
Closed-book dialogues	42.2	22.0	39.5	40.1
Strong student	47.2	20.1	43.8	43.3
Weak student	48.0	32.5	46.0	41.6
Random sample	47.9	30.3	45.8	45.9

H. Training details

We fine-tune Llama (Touvron et al., 2023) modes, based on the Transformer architecture (Vaswani et al., 2017). We use FlashAttention (Dao et al., 2022; Dao, 2023) as an efficient implementation of attention.

H.1. Long context training

For long-context training, we fine-tune base models for one epoch on 5B tokens from OpenWebMath with up to 32K tokens per sample. We use a batch-size of 512, a learning rate 2e-5 with a 10% warm-up, and the Adam optimizer (Kingma & Ba, 2015). Following Roziere et al. (2023), we set the RoPE base to 1M to facilitate long-context understanding.

We use 16 H100 GPUs to fine-tune Llemma-7B-32K on this dataset.

H.2. Dialogue fine-tuning

All base models in this paper follow the same hyperparameters for dialogue tuning. We always fine-tune for two epochs, with a batch size of 16 and a learning rate of 1e-5 and a 10% warm-up.

For fine-tuning with TUTORCHAT, we process the GPT-generated dialogues as follows. Teacher/student dialogues are processed as assistant/user dialogues and we remove recurrent text coming from the templates used to generate dialogues. For open-book dialogues we include the chapter before the start-token <s> but we do not train on the text. For closed-book dialogues, we remove the chapter entirely. For textbook-exam generations, we remove the chapter and we randomly re-label

the question/answer sequence as either user/assistant, or assistant/user, or we keep the question/answer labels.

In most cases, we only train the LM on the assistant tokens during loss back-propagation with next-token prediction. For textbook exams and GPT-4-generated dialogues featuring a strong student, we train on the entire conversation. This is to encourage strong question-answering capabilities. In preliminary experiments (not included here), we found that these processing choices improve question TUTOREVAL performance by several points.

To fine-tune with MetaMath, we process the dataset by randomly concatenating 10 question/answer pairs. This forms longer documents and allows us to balance batch sizes when combining MetaMath and TUTORCHAT. We randomly process question/answer pairs as either assistant/user, user/assistant, question/answer, or problem/solution pairs. We fine-tune the LM by backpropagating the loss on the entire sequence.

To fine-tune Llemma-7B-32K, we use one A100 GPU with 80GB memory. To fine-tune Llemma-34B, we use 32 H100 GPUs.

I. Expanded model evaluations

In this section we collect additional evaluation results for some of the models evaluated in this paper. These results give a comprehensive over-view of the strengths and weaknesses of these models. Our goal in this paper is to further the study of LMs that can be used in real-life settings, so we give a holistic over-view of the impact of training with TUTORCHAT.

We evaluate on MBPP (Austin et al., 2021) and HumanEval (Chen et al., 2021) for coding tasks. We use the LM Evaluation Harness (Gao et al., 2023) for all non-coding tasks.

Table 13: Benchmark results for different fine-tuned versions of LLEMMA-7B-32K. † Fine-tuning with MetaMath yields 0% on MATH because the model is unable to output answers which are detected by the official MATH parsing script. The model has over-fit to GSM8K and is unusable for other tasks.

	GSM8K (8)	MATH (4)	Average
LLEMMA-7B	31.9	12.9	22.4
LLEMMA-7B-32K	28.8	13.0	20.9
+ MetaMath	60.0	0 [†]	30.0
+ UltraChat	30.0	13.9	22.0
+ UltraChat + MetaMath	31.1	14.8	23.0
+ TUTORCHAT	28.9	14.8	21.9
+ TUTORCHAT + MetaMath	36.3	16.5	26.4
+ TUTORCHAT-STEM	28.3	14.6	21.5
+ MathMix	55.9	21.7	38.8
Llemma-34B-MathMix	51.1	21.9	36.5
Mistral-7B-V2	38.9	9.0	24.0

Table 14: Coding benchmark results for various fine-tuned versions of LLEMMA-7B-32K and LLEMMA-34B-32K models. We apply greedy decoding for pass@1 scores and temperature 0.8 for pass@10 on HumanEval and MBPP. Following the evaluation in (Roziere et al., 2023), we conducted zero-shot evaluations on HumanEval and 3-shot evaluations on MBPP

	HumanEval		MBPP		
	Pass@1	Pass@10	Pass@1	Pass@10	Average
LLEMMA-7B	28.1	47.6	40.6	61.0	44.3
LLEMMA-7B-32K	28.7	54.3	40.6	59.8	45.8
+ UltraChat	26.2	51.2	31.2	55.6	41.1
+ TUTORCHAT	25	51.2	40.8	61.4	44.8
+MathMix	34.2	56.1	40.8	61.6	48.2
Mistral-7B-V2	38.1	59.1	38.2	57	48.1
CodeLlama 7B	33.5	59.6	41.4	66.7	50.3
Llemma-34B-MathMix	45.1	77.4	52.6	74.0	62.3
CodeLlama 34B	48.8	76.8	55.0	76.2	64.2

Table 15: Evaluation results for various models on non-scientific tasks. We evaluate on ScienceQA (Welbl et al., 2017), PIQA (Bisk et al., 2020), WinoGrande (Sakaguchi et al., 2021), ARC (Clark et al., 2018), HellaSwag (Zellers et al., 2019), BoolQ (Clark et al., 2019), Lambada (Paperno et al., 2016), and Natural Questions (Kwiatkowski et al., 2019). We see that long-context training and fine-tuning with TUTORCHAT and MathMix affects overall performance slightly compared to the base Llemma-7B model. We see also that Mistral is a much more well-rounded model due to its generalist training.

k-shot	SciQ 0	PIQA 0	WinoGrande 0	ARC-E 0	ARC-C 25	HellaSwag 10	LogiQA 0	BoolQ 32	LAMBADA 0	NQ 32	MMLU 5	Average
LLEMMA-7B	94	72	62	71	47	62	30	76	61	12	46	57.6
LLEMMA-7B-32K	93	72	61	71	47	62	31	72	60	11	44	56.7
+ UltraChat	94	72	61	71	48	63	30	75	61	10	44	57.2
+ TUTORCHAT	92	72	62	67	46	61	31	71	60	10	44	56.0
+ MathMix	91	71	59	65	47	60	28	76	56	10	44	55.2
Mistral-7B-V2	95	79	73	82	63	84	33	85	70	26	58	68.0
Llemma-34B-MathMix	94	75	70	72	52	74	34	86	72	20	56	64.1