
# nanoHUB@home Expanding nanoHUB Through Volunteer Computing

Steven Clark, Ben Haley, Martin Hunt, Nathan Denny:HUBzero.org
David Anderson: UC Berkeley


## Signano HUB

- Collaborate
- Simulate
- Explore
- Learn



## PLATFORM FOR SCIENTIFIC COMPUTATION

- 1.5 million users annually
- 175000+ registered users
- 600+ published tools
- Varying resource requirements for tool execution
  - Mostly single core reasonably short duration
  - Several require multinode long walltime cluster access



## PLATFORM FOR SCIENTIFIC COMPUTATION

- GUI development environments
  - o RAPPTURE
  - Jupyter Notebooks
- Source code management GIT/subversion
- Rich Linux based development platform
- Powerful computing resources
  - Purdue community clusters
  - Stampede2 (TACC)
  - Comet (SDSC)
  - Open Science Grid (OSG)



#### On demand

- UI used to declare inputs for simulation
- Command line
- Single simulation or parametric sweep

#### Uncertainty quantification


- Inputs declared as distributions
- Statistical methods used to determine meaningful input combinations
- A simulation is run for each input combination.
- Results include a response surface model which can be used to approximate simulation, sensitivity analysis, and probability distribution function (PDF) for outputs.

#### Exploratory simulation

- Automatically generate simulation input samples covering the space
- Allow for interactive selection of multidimensional input space
- Execute simulation for each sample

- Machine Learning
  - Examine simulation results discern patterns
  - Build approximate simplified models
  - o Requires large quantity of simulation results

## TRADITIONAL COMPUTATION WORKFLOW



#### SIMULATION RESOURCE DEMAND

#### Interactive Users

- 100's active at any given time
- Short lived execution
- Time between runs for analysis


#### UQ

- 10's 100's of simulations requested for single run
- May be staged serially or run in parallel
- Long turn around pushes limits of user patience


#### Exploratory, Machine Learning

 100's - 1000's of simulations requested as part of single study or experiment


## **CLOUD BASED COMPUTATIONAL WORKFLOW**




#### **VOLUNTEER BASED COMPUTATIONAL WORKFLOW**




## SUBMIT ARCHITECTURE - nanoHUB/BOINC









submit host

submit server

inputs

vbox\*


\* iso

boinc app\*

image\*.tar.gz

layer\*.tar.gz app \*.tar.gz

results







## SUBMIT/BOINC - INTEGRATION

#### nanoHUB Application


- o UI
- User supplied data
- Application files

#### submit Server

Common interface between local and all remote resources (HPC + HTC)

#### BOINC Project Server


- Job execution manager for all BOINC submissions submit\_api batch submission
- stage\_docker\_image combines docker save and stage\_file to place tarballs in the download directory. Also creates nanoHUB specific VirtualBox initialization file and boinc\_app startup script.




### SUBMIT/BOINC - INTEGRATION

#### Volunteer Host


- BOINC client download from BOINC website or system package install
- VirtualBox nanoHUB applications run in Linux environment.
   VirtualBox provides access to Linux, Windows and MAC volunteer hosts.
- boinc2docker introduction of docker containers allows simpler change management. Nine docker containers support 316 nanoHUB applications.
- Mounted volumes allow for reduced memory requirement when loading docker container and greater flexibility creating new applications.
- nanoHUB application files sent as tar balls and are not removed at job completion to reduce bandwidth requirement
- User supplied data is also sent as a tarball but is job specific and is removed at job completion



## **Exploratory Simulation - Architecture**




## **Exploratory Simulation**



- Rappture XML schema defines simulation inputs
  - Scalar numeric inputs
  - Fixed lower and upper bounds
  - Automatically generate simulation input samples spanning the range
- Input driver files are uploaded to cache server queue

## **Exploratory Simulation**



- Automated process pulls driver file inputs from cache server queue
- Assemble driver input files into BOINC batches
- Employ submit to execute BOINC batches
- When BOINC batch is complete publish successful results to cache server archive

## Exploratory Simulation - 10,000,000 jobs/yr?


#### Infrastructure Problems

- Number of Processes
- Disk quota
- Memory
- Database transaction processing

#### BOINC Problems

- Large variation in nanoHUB tool requirements executing as a single BOINC application
  - Memory
  - Disk
  - Time

## SPECULATIVE SIMULATION RATE - jobs/month



#### **BOINC COMMUNITY - SIZE**

#### Users

- With credit 530
- With recent credit 210
- Registered in past 24 hours 41

#### Computers

- With credit 1192
- With recent credit 460
- Registered in past 24 hours 10
- Current GigaFLOPS 536.45

