


Encoding an Oscillator into Many Oscillators

Kyungjoo Noh^{1,2,*}, S. M. Girvin^{1,2}, and Liang Jiang^{1,2,3,†}

¹*Departments of Applied Physics and Physics, Yale University, New Haven, Connecticut 06520, USA*

²*Yale Quantum Institute, Yale University, New Haven, Connecticut 06520, USA*

³*Pritzker School of Molecular Engineering, University of Chicago, Chicago, Illinois 60637, USA*

 (Received 22 May 2019; accepted 15 July 2020; published 18 August 2020)

An outstanding challenge for quantum information processing using bosonic systems is Gaussian errors such as excitation loss and added thermal noise errors. Thus, bosonic quantum error correction is essential. Most bosonic quantum error correction schemes encode a finite-dimensional logical qubit or qudit into noisy bosonic oscillator modes. In this case, however, the infinite-dimensional bosonic nature of the physical system is lost at the error-corrected logical level. On the other hand, there are several proposals for encoding an oscillator mode into many noisy oscillator modes. However, these oscillator-into-oscillators encoding schemes are in the class of Gaussian quantum error correction. Therefore, these codes cannot correct practically relevant Gaussian errors due to the established no-go theorems that state that Gaussian errors cannot be corrected by using only Gaussian resources. Here, we circumvent these no-go results and show that it is possible to correct Gaussian errors by using Gottesman-Kitaev-Preskill (GKP) states as non-Gaussian resources. In particular, we propose a non-Gaussian oscillator-into-oscillators code, namely the GKP two-mode squeezing code, and demonstrate that it can quadratically suppress additive Gaussian noise errors in both the position and momentum quadratures except for a small sublogarithmic correction. Furthermore, we demonstrate that our GKP two-mode squeezing code is near optimal in the weak noise limit by proving via quantum information theoretic tools that quadratic noise suppression is optimal when we use two physical oscillator modes. Lastly, we show that our non-Gaussian oscillator encoding scheme can also be used to correct excitation loss and thermal noise errors, which are dominant error sources in many realistic bosonic systems.

DOI: [10.1103/PhysRevLett.125.080503](https://doi.org/10.1103/PhysRevLett.125.080503)

Introduction.—Continuous variable (CV) bosonic quantum systems are ubiquitous in various quantum computing and communication architectures [1,2] and provide unique advantages to, e.g., quantum simulation of bosonic systems such as boson sampling [3–6] and simulation of vibrational quantum dynamics of molecules [7–10]. However, realistic imperfections such as excitation losses and added thermal noise are major challenges for realizing large-scale and fault-tolerant CV quantum information processing.

Quantum error correction (QEC) is essential for scalable and fault-tolerant quantum information processing [11]. Recently, there have been significant advances in using bosonic systems to realize QEC in a more hardware-efficient manner [12]. In many bosonic QEC schemes proposed so far, a finite-dimensional quantum system (e.g., a qubit) is encoded into an oscillator [13–18] or into many oscillators [19–28]. For example, the four-component cat code [15] encodes a logical qubit into an oscillator using cat states with an even number of excitations, i.e., $|0_L\rangle \propto |\alpha\rangle + |-\alpha\rangle$ and $|1_L\rangle \propto |i\alpha\rangle + |-i\alpha\rangle$. Thanks to the inherent hardware efficiency, various qubit-into-an-oscillator bosonic QEC schemes have been realized experimentally [29–37]. However, such schemes are not tailored to CV information processing tasks since the error-corrected

systems are described by discrete variables such as Pauli operators.

On the other hand, an error correction scheme where an infinite-dimensional oscillator mode is encoded into many noisy oscillators can still be tailored to various CV quantum information processing tasks. So far, there have been several proposals for encoding an oscillator into many oscillators [38–45]. For example, in the case of the three-mode Gaussian-repetition code [38,39], an infinite-dimensional oscillator mode is encoded into three oscillators by repeatedly appending the position eigenstates: $|\hat{q}_L = q\rangle \equiv |\hat{q}_1 = q\rangle|\hat{q}_2 = q\rangle|\hat{q}_3 = q\rangle$. Note that in this case, the logical Hilbert space is infinite dimensional because q can be any real number.

However, none of the previously proposed oscillator-into-oscillators codes can correct Gaussian errors. This is because they are *Gaussian quantum error correction* schemes and the established no-go theorems state that Gaussian errors cannot be corrected by using only Gaussian operations [26,46,47]. Since Gaussian errors include excitation losses, thermal noise, and additive Gaussian noise errors that are ubiquitous in many realistic bosonic systems, these no-go results set a hard limit on the practical utility of the proposed Gaussian oscillator encoding schemes.

Moreover, since the quantum capacity [48] of Gaussian channels is finite [49–55], one may be tempted to deduce that useful infinite-dimensional oscillator encoding against Gaussian errors is not possible.

In this Letter, we demonstrate that useful oscillator encoding is nevertheless possible despite the Gaussian no-go results and the finite quantum capacity. That is, we circumvent the established Gaussian no-go results by using the Gottesman-Kitaev-Preskill (GKP) states [14] as a non-Gaussian resource. We also show that nontrivial QEC gain (larger than unity) with oscillator encoding is compatible with the finiteness of Gaussian quantum channel capacity.

GKP states as non-Gaussian resources.—Examples of non-Gaussian resources [56,57] include the single-photon Fock state and photon-number-resolving measurements [3,58], Kerr nonlinearities [59], cubic phase state and gate [14], SNAP gate [60], Schrödinger cat states [13], and GKP states [14,61]. Among these non-Gaussian resources, we focus on the GKP states.

The canonical GKP state (or the grid state) [14,62] is defined as the unique (up to an overall phase) simultaneous eigenstate of the two commuting displacement operators $\hat{S}_q \equiv \exp[i\sqrt{2\pi}\hat{q}]$ and $\hat{S}_p \equiv \exp[-i\sqrt{2\pi}\hat{p}]$ with unit eigenvalues. Explicitly, the canonical GKP state is given by

$$|\text{GKP}\rangle \propto \sum_{n \in \mathbb{Z}} |\hat{q} = \sqrt{2\pi}n\rangle \propto \sum_{n \in \mathbb{Z}} |\hat{p} = \sqrt{2\pi}n\rangle \quad (1)$$

and thus has definite values of *both* the position and the momentum operators modulo $\sqrt{2\pi}$, i.e., $\hat{q} = \hat{p} = 0 \pmod{\sqrt{2\pi}}$. That is, we circumvent the Heisenberg uncertainty principle (i.e., \hat{q} and \hat{p} cannot be measured simultaneously) by measuring the quadrature operators modulo $\sqrt{2\pi}$. Note that the effects of such compromise are negligible if the quantities of interest are much smaller than $\sqrt{2\pi}$, which will be the case below for our purposes [see Eq. (11)].

In Fig. 1(a), we plot the Wigner function of the canonical GKP state with an average photon number $\bar{n} = 5$ [63]. Note that negative peaks in the Wigner function indicate that the




FIG. 1. (a) An approximate GKP state with an average photon number $\bar{n} = 5$. (b) Measurement of the position or momentum operator modulo $\sqrt{2\pi}$. The controlled \oplus and \ominus symbols, respectively, represent the SUM and the inverse-SUM gates where $\text{SUM}_{j \rightarrow k} \equiv \exp[-i\hat{q}_j \hat{p}_k]$. The final measurement in the bottom mode is the homodyne measurement of the position or the momentum quadrature operator.

GKP state is a non-Gaussian state. We also remark that the ability to prepare the canonical GKP state (combined with Gaussian operations) allows us to measure the quadrature operators modulo $\sqrt{2\pi}$ [see Ref. [14] and also Fig. 1(b)], which is needed in our oscillator encoding scheme introduced below [see Fig. 2(b)].

GKP two-mode squeezing code.—Let $|\psi\rangle = \int dq \psi(q) |\hat{q}_1 = q\rangle$ be an arbitrary bosonic state (or data) that we want to encode into two bosonic modes. We define the encoded state of the GKP two-mode squeezing code as follows:

$$|\psi_L\rangle = \text{TS}_{1,2}(G) |\psi\rangle \otimes |\text{GKP}\rangle. \quad (2)$$

Here, $|\text{GKP}\rangle$ is the canonical GKP state in the second mode and $\text{TS}_{1,2}(G) = \exp[g(\hat{a}_1^\dagger \hat{a}_2^\dagger - \hat{a}_1 \hat{a}_2)]$ is the two-mode squeezing operation acting on modes 1 and 2 with a gain $G = \cosh^2(g) \geq 1$ [hence the name of the code; see Fig. 2(a)]. We refer to the first mode as the data mode and the second mode as the ancilla mode. In the Heisenberg picture, the two-mode squeezing operation $\text{TS}_{1,2}(G)$ transforms the quadrature operator $\hat{x} = (\hat{q}_1, \hat{p}_1, \hat{q}_2, \hat{p}_2)^T$ into $\hat{x}' = (\hat{q}'_1, \hat{p}'_1, \hat{q}'_2, \hat{p}'_2)^T = \mathbf{S}_{\text{TS}}(G) \hat{x}$, where the 4×4 symplectic matrix $\mathbf{S}_{\text{TS}}(G)$ associated with $\text{TS}_{1,2}(G)$ is given by (see, e.g., Ref. [2])

$$\mathbf{S}_{\text{TS}}(G) = \begin{bmatrix} \sqrt{G} \mathbf{I} & \sqrt{G-1} \mathbf{Z} \\ \sqrt{G-1} \mathbf{Z} & \sqrt{G} \mathbf{I} \end{bmatrix}. \quad (3)$$

Here, $\mathbf{I} = \text{diag}(1, 1)$ and $\mathbf{Z} = \text{diag}(1, -1)$. Note that the gain G can be chosen at will to optimize the performance of the error correction scheme.

For the noise model, we consider the independent and identically distributed additive Gaussian noise errors, i.e., $\mathcal{N}^{(1)}[\sigma] \otimes \mathcal{N}^{(2)}[\sigma]$, mainly due to their experimental relevance (see also [69]). In the Heisenberg picture, $\mathcal{N}^{(k)}[\sigma]$ adds Gaussian random noise $\xi_q^{(k)}$ and $\xi_p^{(k)}$ to the quadrature operators of the k th mode. Thus, the quadrature operator \hat{x}' is further transformed via the additive Gaussian noise error into $\hat{x}'' = \hat{x}' + \boldsymbol{\xi}$, where $\boldsymbol{\xi} = [\xi_q^{(1)}, \xi_p^{(1)}, \xi_q^{(2)}, \xi_p^{(2)}]^T$ is the quadrature noise vector following $\boldsymbol{\xi} \sim_{\text{iid}} \mathcal{N}(0, \sigma^2)$ [see Fig. 2(a)].

The decoding procedure [shown in Fig. 2(b)] starts with an application of the inverse of the encoding circuit $[\text{TS}_{1,2}(G)]^\dagger$. Then, the quadrature operator is transformed into $\hat{x}''' = [\mathbf{S}_{\text{TS}}(G)]^{-1} \hat{x}'' = \hat{x} + \mathbf{z}$, where $\mathbf{z} \equiv [\mathbf{S}_{\text{TS}}(G)]^{-1} \boldsymbol{\xi}$ is the reshaped quadrature noise vector, which is given by

$$\mathbf{z} = \begin{bmatrix} \sqrt{G} \xi_q^{(1)} - \sqrt{G-1} \xi_q^{(2)} \\ \sqrt{G} \xi_p^{(1)} + \sqrt{G-1} \xi_p^{(2)} \\ \sqrt{G} \xi_q^{(2)} - \sqrt{G-1} \xi_q^{(1)} \\ \sqrt{G} \xi_p^{(2)} + \sqrt{G-1} \xi_p^{(1)} \end{bmatrix} \equiv \begin{bmatrix} z_q^{(1)} \\ z_p^{(1)} \\ z_q^{(2)} \\ z_p^{(2)} \end{bmatrix}. \quad (4)$$




FIG. 2. (a) Encoding circuit of the GKP two-mode squeezing code subject to independent and identically distributed additive Gaussian noise errors. (b) Decoding circuit of the GKP two-mode squeezing code. Note that the circuits for the measurements of the position and the momentum operators modulo $\sqrt{2\pi}$ (at the end of the decoding) are defined in Fig. 1(b).

The role of the two-mode squeezing operations in the encoding and the decoding circuits is clear by now: they transform uncorrelated additive noise ξ into *correlated* additive noise z . This means that after noise reshaping, we can extract useful information about the data noise $z_q^{(1)}$ and $z_p^{(1)}$ by measuring only the ancilla noise $z_q^{(2)}$ and $z_p^{(2)}$. Importantly, the encoded logical information in the data mode is not revealed through this process because the data mode need not be measured. Note also that we need to measure *both* the position and momentum noise in the ancilla mode. This is precisely the reason why the simultaneous quadrature measurement (modulo $\sqrt{2\pi}$) in Fig. 1(b) is needed at the end of the decoding circuit [71].

Based on the outcomes of the simultaneous measurement of the ancilla quadrature noise modulo $\sqrt{2\pi}$, we estimate that $z_q^{(2)}$ and $z_p^{(2)}$ are given by the smallest displacements that are compatible with the modular measurement outcomes, i.e.,

$$\bar{z}_q^{(2)} = R_{\sqrt{2\pi}}[z_q^{(2)}] \quad \text{and} \quad \bar{z}_p^{(2)} = R_{\sqrt{2\pi}}[z_p^{(2)}], \quad (5)$$

where $R_s(z) \equiv z - n^*(z)s$ and $n^*(z) \equiv \text{argmin}_{n \in \mathbb{Z}} |z - ns|$ [72]. We then further estimate that the data quadrature noise $z_q^{(1)}$ and $z_p^{(1)}$ are

$$\begin{aligned} \bar{z}_q^{(1)} &= -\frac{2\sqrt{G(G-1)}}{2G-1} \bar{z}_q^{(2)} \quad \text{and} \\ \bar{z}_p^{(1)} &= \frac{2\sqrt{G(G-1)}}{2G-1} \bar{z}_p^{(2)}, \end{aligned} \quad (6)$$

which are obtained by taking into account the correlation in the reshaped noise z and using a maximum likelihood estimation method as detailed in the Supplemental Material [64].

The decoding operation is simply to remove the estimated noise in the data mode by applying the counterdisplacement operations $\exp[i\hat{p}_1 \bar{z}_q^{(1)}]$ and $\exp[-i\hat{q}_1 \bar{z}_p^{(1)}]$ to the data mode [see Fig. 2(b)]. As a result, we are left with the following logical position and momentum quadrature noise:

$$\xi_q^{(\text{out})} \equiv z_q^{(1)} - \bar{z}_q^{(1)} \quad \text{and} \quad \xi_p^{(\text{out})} \equiv z_p^{(1)} - \bar{z}_p^{(1)}, \quad (7)$$

whose variances $(\sigma_q)^2 = (\sigma_p)^2 = (\sigma_L)^2$ are given by

$$(\sigma_L)^2 = \frac{\sigma^2}{2G-1} + \sum_{n \in \mathbb{Z}} \frac{4G(G-1)}{(2G-1)^2} 2\pi n^2 \times q_n(\sigma). \quad (8)$$

Here, $q_n(\sigma) \equiv \int_{(n-1/2)\sqrt{2\pi}}^{(n+1/2)\sqrt{2\pi}} dz p[\sqrt{2G-1}\sigma](z)$, where $p[\sigma](z) \equiv (1/\sqrt{2\pi\sigma^2}) \exp[-(z^2/2\sigma^2)]$ is the probability density function of the Gaussian normal distribution $\mathcal{N}(0, \sigma^2)$. See the Supplemental Material [64] for the derivation of Eq. (8).




FIG. 3. (a) The minimum standard deviations of the output logical quadrature noise $\sigma_q = \sigma_p = \sigma_L^*$ as a function of the input standard deviation σ for the GKP two-mode squeezing code and (b) the optimal two-mode squeezing gain G^* that achieves σ_L^* , translated to the required single-mode squeezing in the unit of decibel $20 \log_{10} \lambda^*$, where $\lambda^* \equiv \sqrt{G^* + \sqrt{G^* - 1}}$. The black dotted line, the green dashed line, and the grey dotted line in (a) represent the breakeven point $\sigma_L = \sigma$, the asymptotic expression $\sigma_L^* = (2\sigma^2/\sqrt{\pi})\sqrt{\log_e[\pi^3/2\sigma^4]}$, and the lower bound on σ_L in Eq. (12), respectively. Also, the yellow dashed line in (b) represents $G^* = (\pi/8\sigma^2)(\log_e[\pi^3/2\sigma^4])^{-1} + \frac{1}{2}$.

Recall that we can freely choose the gain G to optimize the performance of the GKP two-mode squeezing code. Here, we choose G such that the standard deviation of the output logical quadrature noise σ_L is minimized. In Fig. 3, we plot the minimum standard deviation of the output logical quadrature noise σ_L^* and the optimal gain G^* that achieves σ_L^* as a function of the input noise standard deviation σ . These optimal values are obtained via a brute-force numerical optimization.

From the numerical optimization, we find that for $\sigma \geq \sigma_c \equiv 0.558$, the optimal gain G^* is trivially given by $G^* = 1$ and thus the GKP two-mode squeezing code cannot reduce the noise standard deviation: $\sigma_L^* = \sigma$. On the other hand, if the input noise is small enough, i.e., $\sigma < \sigma_c = 0.558$, the optimal gain G^* is strictly larger than 1, and the minimum standard deviation of the output quadrature noise σ_L can be made smaller than the input noise standard deviation σ : $\sigma_L^* < \sigma$. Moreover in the $\sigma \ll 1$ regime, we analytically find that the optimal gain G^* is asymptotically given by

$$G^* \xrightarrow{\sigma \ll 1} \frac{\pi}{8\sigma^2} \left(\log_e \left[\frac{\pi^3/2}{2\sigma^4} \right] \right)^{-1} + \frac{1}{2}, \quad (9)$$

and the optimal output standard deviation σ_L^* is given by

$$\sigma_L^* \xrightarrow{\sigma \ll 1} \frac{2\sigma^2}{\sqrt{\pi}} \sqrt{\log_e \left[\frac{\pi^3/2}{2\sigma^4} \right]}. \quad (10)$$

See the Supplemental Material [64] for a detailed derivation. As shown in Fig. 3, these asymptotic expressions agree well with the exact numerical results in the small σ regime. Note that the standard deviations (STDs) of the ancilla noise are given by

$$\text{STD}[z_q^{(2)}] = \text{STD}[z_q^{(2)}] = \sqrt{(2G-1)\sigma} = o(1) \quad (11)$$

and thus are much smaller than the spacing of the GKP state $\sqrt{2\pi}$ at the optimal gain G^* . Moreover, Eq. (10) implies that the output standard deviation σ_L^* decreases quadratically in σ (i.e., $\sigma_L^* \propto \sigma^2$) except for a small sublogarithmic correction. We remark that the quadratic suppression is the best one can hope for when using two physical oscillator modes. That is, σ_L is fundamentally lower bounded by

$$\sigma_L \geq \frac{\sigma^2}{\sqrt{e(1-\sigma^2)}} > \frac{\sigma^2}{\sqrt{e}} \quad (12)$$

due to the finite quantum capacity of $\mathcal{N}[\sigma]$ (see the Supplemental Material [64] for the proof). Thus, our GKP two-mode squeezing code is asymptotically near optimal in the weak noise limit up to an overall constant factor [see Fig. 3(a) for an illustration].

Excitation loss and thermal noise errors.—Excitation loss errors with external thermal noise are described by Gaussian thermal-loss channels that can be converted via a quantum-limited amplification to an additive Gaussian noise channel [12,54]. For instance, the bosonic pure-loss channel with loss probability $\gamma \in [0, 1]$ can be converted to an additive Gaussian noise channel $\mathcal{N}[\sigma]$ with $\sigma = \sqrt{\gamma}$. Hence, the GKP two-mode squeezing code can also handle the excitation loss errors because we can simply convert the loss errors into the additive noise errors and then apply the same decoding scheme presented above [73].

Assuming the amplification decoding, the critical value of the standard deviation $\sigma_c = 0.558$ corresponds to the critical loss probability $\gamma_c = (\sigma_c)^2 = 0.311$ in the case of pure excitation loss. Thus, the GKP two-mode squeezing code helps when the loss probability is below 31.1%. For example, for 1% loss probability (i.e., $\gamma = 0.01$ and

$\sigma = \sqrt{\gamma} = 0.1$), the optimal two-mode squeezing gain is given by $G^* = 4.806$, which requires $20 \log_{10} \lambda^* = 12.35$ dB single-mode squeezing operations. In this case, the output noise standard deviation is given by $\sigma_L^* = 0.036$, equivalent to the loss probability 0.13%. This corresponds to a QEC “gain” for the protocol of $1/0.13 \simeq 7.7$ in terms of the loss probability and $0.1/0.036 \simeq 2.8$ in terms of displacement noise.

Experimental realizations and potential applications.—Our oscillator encoding scheme requires Gaussian operations and GKP states. While Gaussian resources are readily available in many realistic bosonic systems, preparing a canonical GKP state is not strictly possible because it would require infinite squeezing. Recently, however, there have been many proposals for preparing an approximate GKP state in various experimental platforms [14,74–86]. Notably, approximate GKP states have been realized in both trapped ion [33–35] and circuit QED [37] systems. Thus, our GKP two-mode squeezing code can in principle be realized in the state-of-the-art quantum computing platforms.

Imperfections in realistic GKP states such as finite squeezing will add additional quadrature noise to the system. Indeed, we show in the Supplemental Material [64] that a nontrivial QEC gain $\sigma^2/(\sigma_L^*)^2 > 1$ can be achieved only when the supplied GKP states have a squeezing larger than the critical value 11.0 dB. On the other hand, the squeezing of the experimentally realized GKP states ranges from 5.5 to 9.5 dB [34,37]. In this regard, we stress that our oscillator encoding scheme is compatible with *nondeterministic* GKP state preparation schemes since the GKP states can be prepared off-line and then supplied to the error correction circuit in the middle of the decoding procedure (in a similar fashion to the standard magic state injection protocol [87]). Thus, in near-term experiments, it will be more advantageous to use post-selection to achieve sufficiently high GKP squeezing at the expense of success probability [88].

Our work paves the way toward robust CV quantum information processing via oscillator encoding schemes that can correct experimentally relevant Gaussian errors. As an example, we discuss in the longer version of the paper [89] how to perform logical beam splitter operations, which are needed, e.g., for error-corrected boson sampling. Also, a recent follow-up work [90] has theoretically demonstrated that the GKP two-mode squeezing code proposed in this Letter can be used to enhance the robustness of CV distributed sensing protocols. Moreover, we also expect that our oscillator encoding scheme can be useful for overcoming loss errors in transduction protocols [91,92].

We acknowledge support from the ARL-CDQI (W911NF-15-2-0067), ARO (W911NF-18-1-0020, W911NF-18-1-0212), ARO MURI (W911NF-16-1-0349), AFOSR MURI (FA9550-15-1-0015, FA9550-19-1-0399),

DOE (DE-SC0019406), NSF (EFMA-1640959, OMA-1936118), and the Packard Foundation (2013-39273). K.N. acknowledges support from the Korea Foundation for Advanced Studies.

*Corresponding author.

noh827@gmail.com

†Corresponding author.

liang.jiang@uchicago.edu

- [1] S. L. Braunstein and P. van Loock, Quantum information with continuous variables, *Rev. Mod. Phys.* **77**, 513 (2005).
- [2] C. Weedbrook, S. Pirandola, R. García-Patrón, N. J. Cerf, T. C. Ralph, J. H. Shapiro, and S. Lloyd, Gaussian quantum information, *Rev. Mod. Phys.* **84**, 621 (2012).
- [3] S. Aaronson and A. Arkhipov, The computational complexity of linear optics, in *Proceedings of the Forty-third Annual ACM Symposium on Theory of Computing, STOC '11* (ACM, New York, NY, USA, 2011), pp. 333–342.
- [4] C. S. Hamilton, R. Kruse, L. Sansoni, S. Barkhofen, C. Silberhorn, and I. Jex, Gaussian Boson Sampling, *Phys. Rev. Lett.* **119**, 170501 (2017).
- [5] R. García-Patrón, J. J. Renema, and V. Shchesnovich, Simulating boson sampling in lossy architectures, *Quantum* **3**, 169 (2019).
- [6] H. Wang, J. Qin, X. Ding, M.-C. Chen, S. Chen, X. You, Y.-M. He, X. Jiang, L. You, Z. Wang, C. Schneider, J. J. Renema, S. Höfling, C.-Y. Lu, and J.-W. Pan, Boson Sampling with 20 Input Photons and a 60-Mode Interferometer in a 10^{14} -Dimensional Hilbert Space, *Phys. Rev. Lett.* **123**, 250503 (2019).
- [7] J. Huh, G. G. Guerreschi, B. Peropadre, J. R. McClean, and A. Aspuru-Guzik, Boson sampling for molecular vibronic spectra, *Nat. Photonics* **9**, 615 (2015).
- [8] C. Sparrow, E. Martín-López, N. Maraviglia, A. Neville, C. Harrold, J. Carolan, Y. N. Joglekar, T. Hashimoto, N. Matsuda, J. L. O’Brien, D. P. Tew, and A. Laing, Simulating the vibrational quantum dynamics of molecules using photonics, *Nature (London)* **557**, 660 (2018).
- [9] W. R. Clements, J. J. Renema, A. Eckstein, A. A. Valido, A. Lita, T. Gerrits, S. W. Nam, W. S. Kolthammer, J. Huh, and I. A. Walmsley, Approximating vibronic spectroscopy with imperfect quantum optics, *J. Phys. B* **51**, 245503 (2018).
- [10] C. S. Wang, J. C. Curtis, B. J. Lester, Y. Zhang, Y. Y. Gao, J. Freeze, V. S. Batista, P. H. Vaccaro, I. L. Chuang, L. Frunzio, L. Jiang, S. M. Girvin, and R. J. Schoelkopf, Efficient Multiphoton Sampling of Molecular Vibronic Spectra on a Superconducting Bosonic Processor, *Phys. Rev. X* **10**, 021060 (2020).
- [11] D. Gottesman, An introduction to quantum error correction and fault-tolerant quantum computation, [arXiv:0904.2557](https://arxiv.org/abs/0904.2557).
- [12] V. V. Albert, K. Noh, K. Duivenvoorden, D. J. Young, R. T. Brierley, P. Reinhold, C. Vuillot, L. Li, C. Shen, S. M. Girvin, B. M. Terhal, and L. Jiang, Performance and structure of single-mode bosonic codes, *Phys. Rev. A* **97**, 032346 (2018).
- [13] P. T. Cochrane, G. J. Milburn, and W. J. Munro, Macroscopically distinct quantum-superposition states as a

- bosonic code for amplitude damping, *Phys. Rev. A* **59**, 2631 (1999).
- [14] D. Gottesman, A. Kitaev, and J. Preskill, Encoding a qubit in an oscillator, *Phys. Rev. A* **64**, 012310 (2001).
- [15] Z. Leghtas, G. Kirchmair, B. Vlastakis, R. J. Schoelkopf, M. H. Devoret, and M. Mirrahimi, Hardware-Efficient Autonomous Quantum Memory Protection, *Phys. Rev. Lett.* **111**, 120501 (2013).
- [16] M. Mirrahimi, Z. Leghtas, V. V. Albert, S. Touzard, R. J. Schoelkopf, L. Jiang, and M. H. Devoret, Dynamically protected cat-qubits: A new paradigm for universal quantum computation, *New J. Phys.* **16**, 045014 (2014).
- [17] M. H. Michael, M. Silveri, R. T. Brierley, V. V. Albert, J. Salmilehto, L. Jiang, and S. M. Girvin, New Class of Quantum Error-Correcting Codes for a Bosonic Mode, *Phys. Rev. X* **6**, 031006 (2016).
- [18] L. Li, C.-L. Zou, V. V. Albert, S. Muralidharan, S. M. Girvin, and L. Jiang, Cat Codes with Optimal Decoherence Suppression for a Lossy Bosonic Channel, *Phys. Rev. Lett.* **119**, 030502 (2017).
- [19] I. L. Chuang, D. W. Leung, and Y. Yamamoto, Bosonic quantum codes for amplitude damping, *Phys. Rev. A* **56**, 1114 (1997).
- [20] J. Harrington and J. Preskill, Achievable rates for the Gaussian quantum channel, *Phys. Rev. A* **64**, 062301 (2001).
- [21] M. Bergmann and P. van Loock, Quantum error correction against photon loss using NOON states, *Phys. Rev. A* **94**, 012311 (2016).
- [22] K. Fukui, A. Tomita, and A. Okamoto, Analog Quantum Error Correction with Encoding a Qubit into an Oscillator, *Phys. Rev. Lett.* **119**, 180507 (2017).
- [23] M. Y. Niu, I. L. Chuang, and J. H. Shapiro, Hardware-efficient bosonic quantum error-correcting codes based on symmetry operators, *Phys. Rev. A* **97**, 032323 (2018).
- [24] K. Fukui, A. Tomita, A. Okamoto, and K. Fujii, High-Threshold Fault-Tolerant Quantum Computation with Analog Quantum Error Correction, *Phys. Rev. X* **8**, 021054 (2018).
- [25] K. Fukui, A. Tomita, and A. Okamoto, Tracking quantum error correction, *Phys. Rev. A* **98**, 022326 (2018).
- [26] C. Vuillot, H. Asasi, Y. Wang, L. P. Pryadko, and B. M. Terhal, Quantum error correction with the toric Gottesman-Kitaev-Preskill code, *Phys. Rev. A* **99**, 032344 (2019).
- [27] K. Fukui, High-threshold fault-tolerant quantum computation with the GKP qubit and realistically noisy devices, [arXiv:1906.09767](https://arxiv.org/abs/1906.09767).
- [28] K. Noh and C. Chamberland, Fault-tolerant bosonic quantum error correction with the surface-Gottesman-Kitaev-Preskill code, *Phys. Rev. A* **101**, 012316 (2020).
- [29] Z. Leghtas, S. Touzard, I. M. Pop, A. Kou, B. Vlastakis, A. Petrenko, K. M. Sliwa, A. Narla, S. Shankar, M. J. Hatridge, M. Reagor, L. Frunzio, R. J. Schoelkopf, M. Mirrahimi, and M. H. Devoret, Confining the state of light to a quantum manifold by engineered two-photon loss, *Science* **347**, 853 (2015).
- [30] N. Ofek, A. Petrenko, R. Heeres, P. Reinhold, Z. Leghtas, B. Vlastakis, Y. Liu, L. Frunzio, S. M. Girvin, L. Jiang, M. Mirrahimi, M. H. Devoret, and R. J. Schoelkopf, Extending the lifetime of a quantum bit with error correction in superconducting circuits, *Nature (London)* **536**, 441 (2016).
- [31] S. Touzard, A. Grimm, Z. Leghtas, S. O. Mundhada, P. Reinhold, C. Axline, M. Reagor, K. Chou, J. Blumoff, K. M. Sliwa, S. Shankar, L. Frunzio, R. J. Schoelkopf, M. Mirrahimi, and M. H. Devoret, Coherent Oscillations Inside a Quantum Manifold Stabilized by Dissipation, *Phys. Rev. X* **8**, 021005 (2018).
- [32] L. Hu, Y. Ma, W. Cai, X. Mu, Y. Xu, W. Wang, Y. Wu, H. Wang, Y. P. Song, C.-L. Zou, S. M. Girvin, L.-M. Duan, and L. Sun, Quantum error correction and universal gate set operation on a binomial bosonic logical qubit, *Nat. Phys.* **15**, 503 (2019).
- [33] C. Flühmann, V. Negnevitsky, M. Marinelli, and J. P. Home, Sequential Modular Position and Momentum Measurements of a Trapped Ion Mechanical Oscillator, *Phys. Rev. X* **8**, 021001 (2018).
- [34] C. Flühmann, T. L. Nguyen, M. Marinelli, V. Negnevitsky, K. Mehta, and J. P. Home, Encoding a qubit in a trapped-ion mechanical oscillator, *Nature (London)* **566**, 513 (2019).
- [35] C. Flühmann and J. P. Home, Direct Characteristic-Function Tomography of Quantum States of the Trapped-Ion Motional Oscillator, *Phys. Rev. Lett.* **125**, 043602 (2020).
- [36] A. Grimm, N. E. Frattini, S. Puri, S. O. Mundhada, S. Touzard, M. Mirrahimi, S. M. Girvin, S. Shankar, and M. H. Devoret, The Kerr-Cat Qubit: Stabilization, Readout, and Gates, [arXiv:1907.12131](https://arxiv.org/abs/1907.12131).
- [37] P. Campagne-Ibarcq, A. Eickbusch, S. Touzard, E. Zalys-Geller, N. E. Frattini, V. V. Sivak, P. Reinhold, S. Puri, S. Shankar, R. J. Schoelkopf, L. Frunzio, M. Mirrahimi, and M. H. Devoret, A stabilized logical quantum bit encoded in grid states of a superconducting cavity, [arXiv:1907.12487](https://arxiv.org/abs/1907.12487).
- [38] S. Lloyd and J.-J. E. Slotine, Analog Quantum Error Correction, *Phys. Rev. Lett.* **80**, 4088 (1998).
- [39] S. L. Braunstein, Error Correction for Continuous Quantum Variables, *Phys. Rev. Lett.* **80**, 4084 (1998).
- [40] Samuel L. Braunstein, Quantum error correction for communication with linear optics, *Nature (London)* **394**, 47 (1998).
- [41] T. Aoki, G. Takahashi, T. Kajiya, J. Yoshikawa, S. L. Braunstein, P. van Loock, and A. Furusawa, Quantum error correction beyond qubits, *Nat. Phys.* **5**, 541 (2009).
- [42] P. Hayden, S. Nezami, G. Salton, and B. C. Sanders, Spacetime replication of continuous variable quantum information, *New J. Phys.* **18**, 083043 (2016).
- [43] P. Hayden, S. Nezami, S. Popescu, and G. Salton, Error correction of quantum reference frame information, [arXiv:1709.04471](https://arxiv.org/abs/1709.04471).
- [44] P. Faist, S. Nezami, V. V. Albert, G. Salton, F. Pastawski, P. Hayden, and J. Preskill, Continuous symmetries and approximate quantum error correction, [arXiv:1902.07714](https://arxiv.org/abs/1902.07714).
- [45] M. P. Woods and Á. M. Alhambra, Continuous groups of transversal gates for quantum error correcting codes from finite clock reference frames, *Quantum* **4**, 245 (2020).
- [46] J. Eisert, S. Scheel, and M. B. Plenio, Distilling Gaussian States with Gaussian Operations is Impossible, *Phys. Rev. Lett.* **89**, 137903 (2002).

- [47] J. Niset, J. Fiurášek, and N. J. Cerf, No-Go Theorem for Gaussian Quantum Error Correction, *Phys. Rev. Lett.* **102**, 120501 (2009).
- [48] Quantum capacity of a quantum channel is a fundamental information-theoretic quantity that determines the maximum quantum state transmission rate of the channel achievable with an optimal QEC scheme.
- [49] A. S. Holevo and R. F. Werner, Evaluating capacities of bosonic Gaussian channels, *Phys. Rev. A* **63**, 032312 (2001).
- [50] M. M. Wolf, D. Pérez-García, and G. Giedke, Quantum Capacities of Bosonic Channels, *Phys. Rev. Lett.* **98**, 130501 (2007).
- [51] M. M. Wilde, P. Hayden, and S. Guha, Quantum trade-off coding for bosonic communication, *Phys. Rev. A* **86**, 062306 (2012).
- [52] M. Rosati, A. Mari, and V. Giovannetti, Narrow bounds for the quantum capacity of thermal attenuators, *Nat. Commun.* **9**, 4339 (2018).
- [53] K. Sharma, M. M. Wilde, S. Adhikari, and M. Takeoka, Bounding the energy-constrained quantum and private capacities of phase-insensitive bosonic gaussian channels, *New J. Phys.* **20**, 063025 (2018).
- [54] K. Noh, V. V. Albert, and L. Jiang, Quantum capacity bounds of Gaussian thermal loss channels and achievable rates with Gottesman-Kitaev-Preskill codes, *IEEE Trans. Inf. Theory* **65**, 2563 (2019).
- [55] K. Noh, S. Pirandola, and L. Jiang, Enhanced energy-constrained quantum communication over bosonic gaussian channels, *Nat. Commun.* **11**, 457 (2020).
- [56] Q. Zhuang, P. W. Shor, and J. H. Shapiro, Resource theory of non-gaussian operations, *Phys. Rev. A* **97**, 052317 (2018).
- [57] R. Takagi and Q. Zhuang, Convex resource theory of non-gaussianity, *Phys. Rev. A* **97**, 062337 (2018).
- [58] E. Knill, R. Laflamme, and G. J. Milburn, A scheme for efficient quantum computation with linear optics, *Nature (London)* **409**, 46 (2001).
- [59] S. Lloyd and S. L. Braunstein, Quantum Computation over Continuous Variables, *Phys. Rev. Lett.* **82**, 1784 (1999).
- [60] S. Krastanov, V. V. Albert, C. Shen, C.-L. Zou, R. W. Heeres, B. Vlastakis, R. J. Schoelkopf, and L. Jiang, Universal control of an oscillator with dispersive coupling to a qubit, *Phys. Rev. A* **92**, 040303(R) (2015).
- [61] B. Q. Baragiola, G. Pantaleoni, R. N. Alexander, A. Karanjai, and N. C. Menicucci, All-Gaussian Universality and Fault Tolerance with the Gottesman-Kitaev-Preskill Code, *Phys. Rev. Lett.* **123**, 200502 (2019).
- [62] K. Duivenvoorden, B. M. Terhal, and D. Weigand, Single-mode displacement sensor, *Phys. Rev. A* **95**, 012305 (2017).
- [63] The canonical GKP state has an infinite average photon number (hence is unphysical) because it is superpositions of infinitely many ($\sum_{n \in \mathbb{Z}}$) infinitely squeezed states ($|\hat{q} = \sqrt{2\pi}n\rangle$ or $|\hat{p} = \sqrt{2\pi}n\rangle$). However, one can define an approximate GKP state with a finite average photon number (or finite squeezing) by applying a nonunitary operator $\exp[-\Delta^2 \hat{n}]$ to the canonical GKP state and then normalizing the output state: $|\text{GKP}_\Delta\rangle \propto \exp[-\Delta^2 \hat{n}]|\text{GKP}\rangle$ [14]. See Supplemental Material [64] for a more detailed discussion of approximate GKP states.
- [64] See Supplemental Material at <http://link.aps.org/supplemental/10.1103/PhysRevLett.125.080503>, which includes Refs. [65–68] and contains detailed discussions of approximate GKP states and maximum likelihood estimation method for deriving Eq. (6). It also includes derivations of Eqs (8), (10), (12) and analysis of our GKP two-mode squeezing code with noisy ancilla GKP states.
- [65] B. Schumacher and M. A. Nielsen, Quantum data processing and error correction, *Phys. Rev. A* **54**, 2629 (1996).
- [66] S. Lloyd, Capacity of the noisy quantum channel, *Phys. Rev. A* **55**, 1613 (1997).
- [67] I. Devetak, The private classical capacity and quantum capacity of a quantum channel, *IEEE Trans. Inf. Theory* **51**, 44 (2005).
- [68] M. M. Wolf, G. Giedke, and J. I. Cirac, Extremality of Gaussian Quantum States, *Phys. Rev. Lett.* **96**, 080502 (2006).
- [69] Correlated additive noise models can always be converted into an uncorrelated one via Gaussian operations using Williamson’s decomposition [70]. The resulting uncorrelated noise may have different variances across different modes. Although the analysis will get somewhat more complex, our scheme still works in the presence of noise imbalance. A simple suboptimal strategy would be to make the less noisy quadrature more noisy by manually adding more noise to the less noisy quadrature. One can also apply a similar maximum likelihood estimation method, detailed in the Supplemental Material [64], to tailor our scheme to the independent noise models with noise imbalance.
- [70] J. Williamson, On the algebraic problem concerning the normal forms of linear dynamical systems, *Am. J. Math.* **58**, 141 (1936).
- [71] Note that $\hat{q}_2 = \hat{p}_2 = 0$ modulo $\sqrt{2\pi}$ holds because the ancilla mode is initialized to the canonical GKP state. Thus, measuring the output quadrature operators $\hat{q}_2'' = \hat{q}_2 + z_q^{(2)}$ and $\hat{p}_2'' = \hat{p}_2 + z_p^{(2)}$ modulo $\sqrt{2\pi}$ is equivalent to measuring just the ancilla quadrature noise $z_q^{(2)}$ and $z_p^{(2)}$ modulo $\sqrt{2\pi}$.
- [72] More explicitly, $R_s(z)$ is a periodic function with period s and is given by $R_s(z) = z$ if $z \in [-s/2, s/2]$.
- [73] Note, however, that the amplification decoding may not be the optimal decoding strategy. See Refs. [12,54] for more discussions on the optimal decoding.
- [74] B. C. Travaglione and G. J. Milburn, Preparing encoded states in an oscillator, *Phys. Rev. A* **66**, 052322 (2002).
- [75] S. Pirandola, S. Mancini, D. Vitali, and P. Tombesi, Constructing finite-dimensional codes with optical continuous variables, *Europhys. Lett.* **68**, 323 (2004).
- [76] S. Pirandola, S. Mancini, D. Vitali, and P. Tombesi, Generating continuous variable quantum codewords in the near-field atomic lithography, *J. Phys. B* **39**, 997 (2006).
- [77] H. M. Vasconcelos, L. Sanz, and S. Glancy, All-optical generation of states for encoding a qubit in an oscillator, *Opt. Lett.* **35**, 3261 (2010).
- [78] B. M. Terhal and D. Weigand, Encoding a qubit into a cavity mode in circuit QED using phase estimation, *Phys. Rev. A* **93**, 012315 (2016).
- [79] K. R. Motes, B. Q. Baragiola, A. Gilchrist, and N. C. Menicucci, Encoding qubits into oscillators with atomic

- ensembles and squeezed light, *Phys. Rev. A* **95**, 053819 (2017).
- [80] D. J. Weigand and B. M. Terhal, Generating grid states from Schrödinger-cat states without postselection, *Phys. Rev. A* **97**, 022341 (2018).
- [81] J. M. Arrazola, T. R. Bromley, J. Izaac, C. R. Myers, K. Brádler, and N. Killoran, Machine learning method for state preparation and gate synthesis on photonic quantum computers, *Quantum Sci. Technol.* **4**, 024004 (2019).
- [82] D. Su, C. R. Myers, and K. K. Sabapathy, Conversion of gaussian states to non-gaussian states using photon-number-resolving detectors, *Phys. Rev. A* **100**, 052301 (2019).
- [83] M. Eaton, R. Nehra, and O. Pfister, Non-Gaussian and Gottesman–Kitaev–Preskill state preparation by photon catalysis, *New J. Phys.* **21**, 113034 (2019).
- [84] Y. Shi, C. Chamberland, and A. Cross, Fault-tolerant preparation of approximate GKP states, *New J. Phys.* **21**, 093007 (2019).
- [85] D. J. Weigand and B. M. Terhal, Realizing modular quadrature measurements via a tunable photon-pressure coupling in circuit qed, *Phys. Rev. A* **101**, 053840 (2020).
- [86] J. Hastrup, K. Park, J. B. Brask, R. Filip, and U. L. Andersen, Measurement-free preparation of grid states, [arXiv:1912.12645](https://arxiv.org/abs/1912.12645).
- [87] S. Bravyi and A. Kitaev, Universal quantum computation with ideal clifford gates and noisy ancillas, *Phys. Rev. A* **71**, 022316 (2005).
- [88] We also remark that the fault-tolerant GKP state preparation scheme in Ref. [84] will be useful for achieving the required critical squeezing level (11.0 dB), going beyond the experimentally realized squeezing level (9.5 dB) achieved via nonfault-tolerant methods [37].
- [89] K. Noh, S. M. Girvin, and L. Jiang, Encoding an oscillator into many oscillators, [arXiv:1903.12615](https://arxiv.org/abs/1903.12615).
- [90] Q. Zhuang, J. Preskill, and L. Jiang, Distributed quantum sensing enhanced by continuous-variable error correction, *New J. Phys.* **22**, 022001 (2020).
- [91] M. Zhang, C.-L. Zou, and L. Jiang, Quantum Transduction with Adaptive Control, *Phys. Rev. Lett.* **120**, 020502 (2018).
- [92] H.-K. Lau and A. A. Clerk, High-fidelity bosonic quantum state transfer using imperfect transducers and interference, *npj Quantum Inf.* **5**, 31 (2019).