

Re-evaluating the Evidence for a Hadean-Eoarchean Dynamo

Short title: The Hadean-Eoarchean Dynamo

Cauê S. Borlina^{1*}, Benjamin P. Weiss¹, Eduardo A. Lima¹, Fengzai Tang², Richard J. M. Taylor², Joshua F. Einsle^{2,3}, Richard J. Harrison², Roger R. Fu⁴, Elizabeth A. Bells⁵, Ellen W. Alexanders⁵, Heather M. Kirkpatrick⁵, Matthew M. Wielicki⁶, T. Mark Harrison⁵, Jahan Ramezani¹, Adam C. Maloof⁷

¹Department of Earth, Atmospheric and Planetary Sciences, Massachusetts Institute of Technology (MIT), Cambridge, MA, USA

²Department of Earth Sciences, University of Cambridge, Cambridge, UK

³Department of Materials Science and Metallurgy, University of Cambridge, Cambridge, UK

⁴Department of Earth and Planetary Sciences, Harvard University, Cambridge, MA, USA

⁵Institute of Geophysics and Planetary Physics and Department of Earth and Space Sciences, University of California, Los Angeles, USA

⁶Department of Geological Sciences, University of Alabama, Tuscaloosa, AL, USA

⁷Department of Geosciences, Princeton University, Princeton, New Jersey, USA

*correspondence: caue@mit.edu

Abstract

The time of origin of the geodynamo has important implications for the thermal evolution of the planetary interior and the habitability of early Earth. It has been proposed that detrital zircon grains from Jack Hills, Western Australia provide evidence for an active geodynamo as early as 4.2 billion years ago (Ga). However, our combined paleomagnetic, geochemical and mineralogical studies on Jack Hills zircons indicate that the majority have poor magnetic recording properties and secondary magnetization carriers that post-date the formation of the zircons. Therefore, the existence of the geodynamo prior to 3.5 Ga remains unknown.

MAIN TEXT

Introduction

Determining the history of the geodynamo prior to 3.5 Ga is limited by the lack of a well-preserved Archean-Hadean rock record. However, the discovery of Hadean detrital zircon grains in metasediments of the Jack Hills, Western Australia, (1) opens up the possibility of studying the magnetic history of the Earth during its first billion years. In particular, primary ferromagnetic inclusions (e.g., magnetite) in the zircons may contain a thermoremanent magnetization (TRM) that records the paleointensity of the ancient field during primary cooling (2–5).

To preserve such a record, magnetite-bearing zircon crystals must have avoided being heated above magnetite's 580°C Curie temperature over their subsequent histories (3, 6). Furthermore, obtaining accurate paleointensity studies with well-determined ages for bulk zircon grains requires that the zircons' natural remanent magnetization (NRM) be dominated by a TRM rather than a secondary crystallization remanent magnetization (CRM) carried by ferromagnetic inclusions formed or altered during aqueous alteration events after zircon crystallization (3, 6).

A recent study (7) using single crystal paleointensity analyses of Jack Hills zircon grains suggested that a geodynamo existed as early as 4.2 Ga with a surface field ~0.1–1 times that of present-day Earth. However, that study (7) had three limitations: (1) the ages of the NRMs in the grains analyzed are unknown (3, 8); (2) the grains were not shown to contain a TRM rather than a secondary CRM (6, 9, 10); (3) the study's grain selection criteria, which targeted grains with NRM intensities >10⁻¹² Am², might inadvertently exclude zircons that would have recorded the absence of a dynamo (i.e., that carry no magnetization). Additionally, there have been no independent studies corroborating their findings. The latter issue is particularly important because Jack Hills zircons have some of the weakest magnetic NRMs measured in the history of paleomagnetism and therefore require exceptionally sensitive magnetometry techniques and stringent contamination controls. To further evaluate the evidence of an early dynamo and address these limitations, we conducted coupled paleomagnetic, geochemical and mineralogical analyses on Jack Hills detrital zircon grains.

We extracted the zircon crystals from pebble conglomerates acquired at the Hadean zircon discovery locality at Erawandoo Hill using nonmagnetic techniques (see Materials and Methods). From these samples, 3,754 zircons were washed with HCl acid and mounted in nonmagnetic epoxy, polished to approximately their midplanes, and dated using U–Pb chronometry. Grains found to be older than 3.5 Ga (a total of 250) then were analyzed using backscattered scanning electron microscopy (BSE), cathodoluminescence (CL) imaging, and Li-ion imaging. BSE and CL images were used to assess the likelihood of secondary CRM by identifying zircon overgrowths, recrystallization zones, metamictization, cracks, and secondary deposits of minerals in void spaces (11). The goal of Li-ion imaging was to constrain the possibility of secondary TRM by providing estimates of the peak metamorphic temperatures experienced by zircons (10).

We defined a set of selection criteria that enables the identification of detrital zircon grains minimally affected by secondary TRM and CRM overprints (Fig. 1): (1) U–Pb age discordance <10% (see Materials and Methods); (2) lack of visible cracks, metamictization and secondary deposits in BSE images and the presence of zonation in CL images interpreted as a primary igneous

texture; and (3) presence of detectable primary Li zoning with thickness of $<20\ \mu\text{m}$ as observed by Li-ion imaging (10). Criterion (3) indicates the absence of TRM overprints acquired during ≥ 1 My, $\geq 550^\circ\text{C}$ metamorphic events under the assumption that natural Li diffusivity is similar to experimentally-determined values (12). Note that these three criteria are based on measurements that only probe the polished surface of the grain (i.e., do not survey the full grain volume) and that are unable to resolve the $<1\ \mu\text{m}$ diameter single-domain magnetite grains that would carry stable primary magnetization. Thus, these criteria likely are necessary but not sufficient requirements for identifying a zircon with primary NRM.

Out of a total of 250 zircon grains, only 3 grains passed all of the above selection criteria. We selected these 3 grains, along with 53 grains that failed one or more criteria (including 13 subsamples from 6 grains; see Materials and Methods), for subsequent paleomagnetic studies. We also selected an additional 21 nonmagnetically-extracted grains in their natural unpolished form from the same host rocks, only 4 of which were acid-washed, as a control to confirm that our polishing and ion and electron microprobe measurements do not fundamentally alter the zircons' NRMs. In total, we conducted paleomagnetic analyses on a total of 77 grains.

Given the weak NRMs of the zircons (ranging between 6.05×10^{-15} and 4.15×10^{-12} Am² prior to demagnetization), their magnetic moments were analyzed using superconducting quantum interference device (SQUID) microscopy (13) (see Materials and Methods). Following methods previously developed for Bishop Tuff zircons (2), we obtained paleointensity estimates for the 77 grains using the in-field zero-field zero-field in-field (IZZI) double-heating protocol (14) with partial TRM (pTRM) alteration checks at every second heating step starting at 300°C .

Our paleomagnetic quality criteria are permissive compared to those of typical paleointensity studies of younger rocks (see SM). This is because the overall goal of this study was to establish the presence or absence of a > 3.5 Ga geodynamo, which only requires paleointensities with order-of-magnitude uncertainties. Therefore, paleointensity estimates were considered acceptable when (a) the NRM component had a difference ratio sum (DRATS) $\leq 25\%$ (15) and (b) the sample gained a moment in the direction of the laboratory field during in-field steps with a maximum angular deviation (MAD) $\leq 15^\circ$ over the same temperature range as the NRM component (16). Criterion (a) indicates that minimal thermochemical alteration occurred during the paleointensity experiments, while criterion (b) provides evidence that the sample can record an ancient field's direction and intensity (while not requiring the presence or absence of such a field when the zircon acquired its magnetic record). In summary, samples that pass our initial selection criteria and paleomagnetic criteria are candidates for providing a robust constraint on the dynamo at the time of their crystallization. Conversely, unstable NRM in a sample would either indicate the absence of a dynamo (if the sample passes the selection and paleomagnetic criteria), or that the sample is unsuitable for paleointensity experiments (either due to poor magnetic recording properties and/or sample alteration during laboratory heating).

Following the paleointensity experiments we obtained images of select grains with quantum diamond magnetometry (QDM) (17) coupled with transmission electron microscopy (TEM) to elucidate the origin of the magnetic sources within the grain.

Results

Out of the 77 zircon grains analyzed for paleointensity estimations, only a total of 6 grains passed the two paleomagnetic criteria. We found that 63 out of the 77 samples failed paleomagnetic criterion (a), indicating alteration during our experiments. Additionally, we found that 54 samples have poor magnetic recording properties as indicated by their failure of paleomagnetic criterion (b). Among the 6 grains that passed both paleomagnetic criteria, only 2 passed all five combined selection and paleomagnetic criteria (Fig. 2). Even if we were to exclude Li zonation as one of the selection criteria, there would be no additional grains that would pass the other selection and paleomagnetic criteria (12). Additionally, our analyses of the unpolished control grains confirm

that polishing the grains did not increase the incidence of alteration during experiments or the magnetic recording quality (see SM).

The two grains that passed the five combined criteria were sample 071320, with a U–Pb age of 3.973 ± 0.001 Ga, and sample 080211, with a U–Pb age of 3.979 ± 0.007 Ga. Figure 2 summarizes the selection process starting from the initial 3,754 grains and ending at these 2 grains. Figures 3 and 4 show BSE, CL, Li, and paleomagnetic data for these two grains. The two grains each have at least two NRM components. Sample 071320 (Fig. 3) has a possible low temperature component between room temperature and 200°C, a possible medium temperature component between 200°C and 300°C, and a high temperature between 300°C and 580°C. Sample 080211 (Fig. 4) has a low temperature component between room temperature and 510°C and a high temperature component between 510°C and 580°C. The 580°C peak demagnetization temperature of the NRMs for both samples indicates that the high temperature components are carried by nearly pure magnetite. Figure 5 shows an example of a grain that passes all of the selection criteria but fails all of the paleomagnetic criteria. The majority of our grains present NRM demagnetization similar to the one in Figure 5: unstable demagnetization, alteration and no in-field acquisition of remanence.

Subsequent to the paleointensity studies, grains 071320 and 080211 were analyzed in more detail to elucidate the nature and origin of their ferromagnetic inclusions. First, the isothermal remanent magnetization (IRM) of the samples was imaged with QDM (17), with a resolution of 1.17 $\mu\text{m}/\text{pixel}$, to determine the location of the magnetic sources (Fig. 6). Following this procedure, we used TEM to investigate internal regions with the strongest magnetization. We found no evidence of primary ferromagnetic inclusions. Instead, we observed magnetite crystals [identified using Moiré diffraction interferometry; (9)] growing inside voids fed by iron that diffused along the regions of intersecting dislocations. We also identified magnetite crystals with high aspect ratios, crystallographically-aligned with the host zircon and growing along dislocation cores [Fig. 6; see also ref. (9)]. The alignment, aspect ratios, and locations of the magnetite grains within regions of recovery from accumulated radiation damage demonstrate that the grains are secondary in origin (18–20). The presence of secondary magnetite is not linked to alteration during laboratory heating steps as demonstrated by the fact these two grains passed paleomagnetic criterion (a) and that they contain voids with a diversity of shapes and sizes that commonly are empty or filled with phases other than magnetite, most commonly baddeleyite and ilmenite (21). The magnetite apparently formed as result of natural fluid alteration at an unknown time during the last 3.9 billion years (9), meaning that their bulk host zircons would have acquired a secondary CRM.

Discussion

The data presented here suggest that the vast majority of Jack Hills zircon are not suitable for paleointensity studies of the Hadean-Eoarchean magnetic field. In particular, only 2 out of 77 grains passed our five selection and paleomagnetic criteria. These two grains yielded results similar to the those previously reported for Jack Hills zircons (7) that were interpreted to be a record of Hadean-Eoarchean dynamo: initial NRM intensities of $\sim 1 \times 10^{-12}$ Am², no signs of alteration, and stable NRM demagnetization exhibiting multiple components. However, close examination of both of grains shows that their magnetic carriers are most likely secondary in origin. Therefore, the ages of their NRMs are unknown and certainly younger than their U–Pb ages. Their multi-component NRMs are consistent with a CRM overprinted by partial TRM due to heating events in the Jack Hills outcrop or by younger CRMs. The presence of a CRM means that the thermal paleointensity experiments, which implicitly assume that the NRM is a TRM, will yield unreliable paleointensity values. We also note that unlike the previous study (7), we found that the majority of grains analyzed paleomagnetically have poor demagnetization and remagnetization behavior.

We suggest that the difference in results between our study and that of ref. (7) may be due to our different measurement protocol, in which we acid-washed the grains to remove considerable amounts of secondary magnetic deposits, used high sensitivity magnetic microscopy that enabled

measurements of samples with up to 1,000 times weaker NRM, and employed QDM and TEM to constrain whether the magnetic carriers are primary in origin. Elucidating the early evolution of the geodynamo may require as yet-unidentified detrital minerals that are less prone to radiation damage.

Materials and Methods

Source location of the samples

Field work was conducted in the Jack Hills in 2002 and 2012. We separated zircons from five rock samples (named D175C, D175H, D175L and Cong14c) collected at the Hadean zircon discovery site, location W74 (22), in the Jack Hills, Western Australia, Australia (1) during these field trips. Table S1 shows the sampling information about the bulk samples and the source material for the grains.

Zircon separation from host rocks

The five rock samples were manually sledged to gravel size fragments in the Massachusetts Institute of Technology (MIT) Isotope Laboratory. These fragments then were pulverized in a Shatterbox® using an all-ceramic grinding vessel and sieved to <500 µm grain size. The material then was mixed in water in a 4 L beaker and the suspended material (<~5 µm) was decanted; this wash process was repeated 15 times. The remaining sand- and silt-size fraction then was dried under a heat lamp (max temperature of 45 °C). The heavy-mineral aliquot was separated by immersion in a high-density liquid (methylene iodide, Sp. Gr. = 3.32), followed by rinsing in acetone and air drying. Zircon grains then were hand-picked under a binocular microscope using nonmagnetic tweezers. Note that our separation procedures did not involve the standard use of a Frantz Isodynamic Separator for removing paramagnetic and ferromagnetic minerals, as the high magnetic field of the Frantz would otherwise alter any original natural remanent magnetization (NRM) that might have been present in the grains.

Ion and electron microprobe measurements

U and Pb isotopes, backscattered electron microscopy (BSE), cathodoluminescence (CL), and Li-ion measurements were carried out in the UCLA Secondary Ion Mass Spectrometry (SIMS) Laboratory at the University of California, Los Angeles (UCLA). The samples were transported between MIT and UCLA in magnetically shielded cans. Approximately 400 grains were placed in 10 separate 2.5-cm diameter Epoxy EPO-TEK 301 mounts and polished to approximately their midplanes. Information about bulk rock source for the zircon grains and their respective mount number are compiled in Table S1. U and Pb isotopes were measured on a CAMECA *ims1270* SIMS, using an $^{16}\text{O}^-$ primary beam, with beam currents of 12–15 nA. A beam diameter of ~20–30 µm was used. Isotopes measured were $^{94}\text{Zr}_2\text{O}$, ^{204}Pb , ^{206}Pb , ^{207}Pb , ^{208}Pb , ^{232}Th , ^{238}U , and $^{238}\text{U}_{16}\text{O}$. The mass-resolving power was ≥ 5500 . We used oxygen flooding for improved U and UO ionization (23). For the common Pb correction, we used a ^{204}Pb correction assuming laboratory contamination with environmental Pb from southern California, specifically the San Diego sewage (24), with common $^{206}\text{Pb}/^{204}\text{Pb} = 18.86$, common $^{207}\text{Pb}/^{204}\text{Pb} = 15.62$, and common $^{208}\text{Pb}/^{204}\text{Pb} = 38.34$. An initial $^{206}\text{Pb}/^{207}\text{Pb}$ ratio survey on 3,754 grains was used to identify grains older than 3.5 Ga for all mounts except UCLA 1, 2 and 3; the latter were instead surveyed for grains older than 3.8 Ga. U-Pb measurements, and BSE, CL and Li images were then acquired from grains that passed this criterion. We calculated the $^{207}\text{Pb}/^{206}\text{Pb}$ and $^{206}\text{Pb}/^{238}\text{U}$ dates and inferred the $^{207}\text{Pb}/^{235}\text{U}$ using the known U isotope ratio ($^{238}\text{U}/^{235}\text{U} = 137.88$). We assigned ages using $^{207}\text{Pb}/^{206}\text{Pb}$ ratios. $^{207}\text{Pb}/^{206}\text{Pb}$ and $^{206}\text{Pb}/^{238}\text{U}$ were used to compute the discordance (25, 26):

$$\left| \frac{\left(\frac{^{207}\text{Pb}}{^{206}\text{Pb}} \right)_{\text{age}}}{\left(\frac{^{206}\text{Pb}}{^{238}\text{U}} \right)_{\text{age}}} - 1 \right| \times 100\%. \quad (1)$$

Table S2 compiles U-Pb measurements for the grains that passed the initial $^{206}\text{Pb}/^{207}\text{Pb}$ survey. Table S3 contains age and uncertainties for the 77 grains selected for the paleomagnetic experiments.

BSE and CL images were acquired with a Tescan Vega 3 scanning electron microscope equipped with a Tescan 3-channel color cathodoluminescence detector and Tescan retractable BSE detector (27).

Li-ion images were acquired using a CAMECA *ims1290* SIMS at the UCLA SIMS Laboratory. We used the Hyperion II RF plasma primary ion source (28) with a 250-300 pA ^{16}O -beam focused to a $<1\ \mu\text{m}$ spot size. We rastered the beam over a $50 \times 50\ \mu\text{m}$ area and recorded 10 frames of ion images of ^7Li and ^{30}Si . We used the program WinImage to accumulate the 10 frames each of ^7Li and ^{30}Si (image intensity was integrated over all 10 frames), and computed the ratio of the two to get an image of $^7\text{Li}/^{30}\text{Si}$ intensity. We ratioed ^7Li to ^{30}Si to account for charging (where ionization rate may be heterogeneous due to accumulation of charge in the sample as it is continually bombarded with negative secondary ions). The spatial resolution of the images is equivalent to the spot size, so any feature $>1\ \mu\text{m}$ is not an artifact. Because boundaries on zones are resolved to $\leq 1\ \mu\text{m}$, blurring of zones by more than this value means they are actually physically smooth over that length scale. A detectable Li zoning with thickness of $<20\ \mu\text{m}$ provides evidence that the sample has not been heated $>550^\circ\text{C}$ for more than 1 million years (10). However, this method might provide an underestimation of the peak temperature experienced by the grains in some cases (12). As presented in the main text, whether or not the Li band criterion is used to filter our samples does not change the overall outcome of this study.

In the supplementary material we provide evidence that the ion and electron microprobe work measurements did not remagnetize the samples. We also provide the complete data set of images taken from all measured grains.

Acid-washing

We previously showed that most Jack Hills zircon grains, when untreated with concentrated (6M) hydrochloric acid (HCl) acid, have magnetization likely dominated by secondary minerals coating the zircons (6). Therefore, prior to paleomagnetic measurements, all grains analyzed here (with the exception of 4 whole grains; see section 5 of the SM) were washed with 6M HCl solution for 12 minutes at room temperature followed by rinsing in Milli-Q® water and air drying. Zircon crystals from samples D175C and D175H were washed with HCl prior to U-Pb measurements, while grains from D175L and CONG14C were washed with HCl after U-Pb measurements. All grains selected for paleomagnetic measurements were extracted from the epoxy mounts using nonmagnetic tools (SEMPREX probe needle, lot 18, demagnetized with a bulk tape eraser) and washed in 70% sulfuric acid (H_2SO_4) for 3 hours to remove any residual epoxy deposits prior to magnetic measurements. During extraction 4 samples (180812, 181518, 180408, 010109 and 180212) fragmented into two pieces and 1 sample (181113) into three pieces. All acid-washing steps were performed in the MIT Isotope Laboratory cleanroom facilities.

Paleomagnetism

Following HCl and H_2SO_4 acid washing, grains were mounted in pits drilled into Corning Eagle XG glass slides, following similar procedures previously developed for analyzing zircons from the Bishop Tuff (2). Figure S3 shows the overall measuring setup. Optical and magnetic field images of the four glass holders with the grains mounted in the pits prior to demagnetization are shown in the Figure S4. The absolute orientation of the grains was not maintained between mounting in the

epoxy for the electron microscopy and ion probe measurements and in the glass mount for paleomagnetic measurements. However, the orientation of the grains and the glass mount was kept fixed throughout the paleomagnetic measurements.

Heating steps were conducted with an ASC Scientific TD48-SC thermal demagnetizer, which provides temperature control with accuracy of better than $\pm 5^\circ\text{C}$. An in-field, zero-field, zero-field, in-field (IZZI) protocol was used in this experiment (14). The in-field step used a 50 μT laboratory magnetic field.

Due to the overall weak magnetic moments of the samples (between 6.05×10^{-15} and $4.15 \times 10^{-12} \text{ Am}^2$), NRM measurements were conducted with the superconducting quantum interference device (SQUID) microscope (13) in the MIT Paleomagnetism Laboratory. The configuration used in these experiments, including the sample holder and the mount with the zircon crystals, yields an approximate distance from the SQUID sensor to the midplane of the sample of $\sim 360 \mu\text{m}$ (Figure S3). This distance includes the sensor to the window separation ($\sim 200 \mu\text{m}$), the thickness of the Corning Eagle XG glass left at the bottom of the wells ($\sim 60 \mu\text{m}$), and half of the size of the grain ($\sim 100 \mu\text{m}$).

Using SQUID microscopy, we mapped the out-of-the-plane component of the magnetic field of individual zircons at a fixed distance above the sample (Figure S2). Maps were $3 \text{ mm} \times 3 \text{ mm}$ in size with spatial sampling of $25 \mu\text{m}$. Magnetic field maps were subsequently inverted for the magnetic moment using previously-validated techniques (2, 29). At each demagnetization/remagnetization step, zircon grains with weak moments ($< 1 \times 10^{-13} \text{ Am}^2$) were measured 4 times and the inverted moments averaged to obtain accurate estimates of their net moments, while stronger magnetic samples were measured only once. When magnetic sources were not observed in our measurements, we assumed a maximum magnetic moment of $\sim 6 \times 10^{-15} \text{ Am}^2$, which is the noise floor of the MIT SQUID microscope at this sensor-sample distance.

All magnetic measurements, including magnetic maps and processed data, are located in the dataset (see SM) and will be uploaded to the Magnetism Information Consortium (MagIC) database.

Quantum diamond microscopy (QDM)

After paleomagnetic measurements, select grains were extracted from the glass mount, placed in epoxy EPO-TEK 301 and polished again. We used the QDM (17) in the Harvard Paleomagnetism Laboratory to constrain the location of the magnetization carriers within the grains. Samples were measured in contact with the sensing diamond after a 0.4 T IRM was applied in the out-of-plane direction using an ASC Model IM-10-3 impulse magnetizer. We measured the magnetic field intensity along the [111] direction of the diamond crystal lattice using projective magnetic microscopy [PMM; (17)]. We isolate the magnetic field signal of ferromagnetic grains by measuring the sample successively under two mutually anti-parallel 0.9 mT bias fields and compute the out-of-plane magnetic field using a spectral algorithm (29). Figure 6 shows the QDM measurements. The absolute orientation of the grain was not kept constant between the SQUID microscopy measurements and these QDM measurements.

Transmission electron microscopy (TEM)

TEM was conducted in the Wolfson Electron Microscopy Suite at the University of Cambridge. Our TEM analysis targeted locations based on the QDM maps previously measured. The transmission electron microscopy foil was prepared using a dual-beam focused ion beam (FIB) microscope FEI Helios NanoLab (Hillsboro, Oregon, USA) with an area of $\sim 60 \mu\text{m}^2$ and a depth of $\sim 7 \mu\text{m}$. An in-situ lift-out technique was employed to site-specifically extract the foil from the place with magnetic signals mapped with the QDM and a clean-up procedure with low acceleration voltage was used to reduce surface damage of the foil. The TEM sample was examined using a FEI Tecnai Osiris TEM with an extreme Schottky field-emission gun. The instrument was equipped with four large area energy dispersive X-ray spectrometer (EDS) detectors, providing a fast

chemical compositional measurement. The analysis was carried out at scanning TEM (STEM) mode at 200 kV, where both bright field (BF) and high angle annular-dark field (HAADF) images were acquired.

H2: Supplementary Materials

Materials and Methods

Fig. S1: Test for remagnetization of Jack Hills zircon mounts from BSE and CL measurements.

Fig. S2: Test for remagnetization of Jack Hills zircon mounts from ion microprobe measurements.

Fig. S3: Setup for magnetic measurements using SQUID microscopy.

Fig. S4: Maps of the NRM of Jack Hills zircons as mounted in quartz mounts.

Fig. S5: Compilation of IRM demagnetization of markers used in this study.

Fig. S6: Paleomagnetic data for zircon grain 080201 (3.117 ± 0.006 Ga).

Table S1: Information about source blocks for analyzed zircon grains from Jack Hills, Western Australia.

Table S2: Compilation of U-Pb ages for grains that passed initial $^{207}\text{Pb}/^{206}\text{Pb}$ survey.

Table S3: General information about the 77 grain samples paleomagnetically analyzed in this study.

Table S4: Summary of the paleomagnetic data for the 77 samples paleomagnetically analyzed in this study.

Table S5: Comparison of paleomagnetic data between polished and unpolished grains.

Table S6: Summary of principal component analysis and maximum angular deviation (MAD) of the 77 samples analyzed here.

Table S7: Summary of maximum angular deviation (MAD) values of the in-field component acquired during paleointensity measurements by the 77 samples.

Database S1: BSE, CL, and Li data

Database S2: Paleomagnetic data

References and Notes

1. W. Compston, R. T. Pidgeon, Jack Hills, evidence of more very old detrital zircons in Western Australia. *Nature*. **321**, 766–769 (1986).
2. R. R. Fu, B. P. Weiss, E. A. Lima, P. Kehayias, J. F. D. F. Araujo, D. R. Glenn, J. Gelb, J. F. Einsle, A. M. Bauer, R. J. Harrison, G. A. H. Ali, R. L. Walsworth, Evaluating the paleomagnetic potential of single zircon crystals using the Bishop Tuff. *Earth Planet. Sci. Lett.* **458**, 1–13 (2017).
3. B. P. Weiss, A. C. Maloof, N. Tailby, J. Ramezani, R. R. Fu, V. Hanus, D. Trail, E. Bruce Watson, T. M. Harrison, S. A. Bowring, J. L. Kirschvink, N. L. Swanson-Hysell, R. S. Coe, Pervasive remagnetization of detrital zircon host rocks in the Jack Hills, Western Australia and implications for records of the early geodynamo. *Earth Planet. Sci. Lett.* **430**, 115–128 (2015).
4. J. A. Tarduno, E. G. Blackman, E. E. Mamajek, Detecting the oldest geodynamo and attendant shielding from the solar wind: Implications for habitability. *Phys. Earth Planet. Inter.* **233**, 68–87 (2014).
5. M. Sato, S. Yamamoto, Y. Yamamoto, Y. Okada, M. Ohno, H. Tsunakawa, S. Maruyama, Rock-magnetic properties of single zircon crystals sampled from the Tanzawa tonalitic pluton, central Japan. *Earth, Planets Space* **67**, 150 (2015).
6. B. P. Weiss, R. R. Fu, J. F. Einsle, D. R. Glenn, P. Kehayias, E. A. Bell, J. Gelb, J. F. D. F. Araujo, E. A. Lima, C. S. Borlina, P. Boehnke, D. N. Johnstone, T. M. Harrison, R. J. Harrison, R. L. Walsworth, Secondary magnetic inclusions in detrital zircons from the Jack Hills, Western Australia, and implications for the origin of the geodynamo. *Geology*. **46**, 427–430 (2018).

7. J. A. Tarduno, R. D. Cottrell, W. J. Davis, F. Nimmo, R. K. Bono, A Hadean to
Paleoarchean geodynamo recorded by single zircon crystals. *Science*. **349**, 521–524 (2015).
8. B. P. Weiss, A. C. Maloof, T. M. Harrison, N. L. Swanson-Hysell, R. R. Fu, J. Kirschvink,
E. Bruce Watson, R. S. L. Coe, S. M. Tikoo, Reply to Comment on “Pervasive
remagnetization of detrital zircon host rocks in the Jack Hills, Western Australia and
implications for records of the early dynamo.” *Earth Planet. Sci. Lett.* **450**, 409–412
(2016).
9. F. Tang, R. J. M. Taylor, J. F. Einsle, C. S. Borlina, R. R. Fu, H. Weiss, Benjamin P
Williams, W. Williams, L. Nagy, P. A. Midgley, E. A. Lima, R. J. Bell, Elizabeth A.
Harrison, T. Mark Alexander, Ellen Harrison, Secondary magnetite in ancient zircon
precludes analysis of a Hadean geodynamo. *Proc. Natl. Acad. Sci.* **116**, 407–412 (2018).
10. D. Trail, D. J. Cherniak, E. B. Watson, T. M. Harrison, B. P. Weiss, I. Szumila, Li zoning
in zircon as a potential geospeedometer and peak temperature indicator. *Contrib. Mineral.
Petro.* **171**, 1–15 (2016).
11. F. Corfu, J. M. Hanchar, P. W. O. Hoskin, P. Kinny, Atlas of zircon textures. *Rev. Mineral.
Geochemistry*. **53**, 469–500 (2003).
12. M. Tang, R. L. Rudnick, W. F. McDonough, M. Bose, Y. Goreva, Multi-mode Li diffusion
in natural zircons: Evidence for diffusion in the presence of step-function concentration
boundaries. *Earth Planet. Sci. Lett.* **474**, 110–119 (2017).
13. B. P. Weiss, E. A. Lima, L. E. Fong, F. J. Baudenbacher, Paleomagnetic analysis using
SQUID microscopy. *J. Geophys. Res.* **112**, 1–20 (2007).
14. Y. Yu, L. Tauxe, A. Genevey, Toward an optimal geomagnetic field intensity
determination technique. *Geochem., Geophys. Geosyst.* **5** (2004),
doi:10.1029/2003GC000630.
15. L. Tauxe, H. Staudigel, Strength of the geomagnetic field in the cretaceous normal
superchron: New data from submarine basaltic glass of the troodos ophiolite. *Geochem.
Geophys. Geosyst.* **5** (2004), doi:10.1029/2003GC000635.
16. J. L. Kirschvink, The least-squares line and plane and the analysis of paleomagnetic data.
Geophys. J. R. Astron. Soc. **62**, 699–718 (1980).
17. D. R. Glenn, R. R. Fu, P. Kehayias, D. Le Sage, E. A. Lima, B. P. Weiss, R. L. Walsworth,
Micrometer-scale magnetic imaging of geological samples using a quantum diamond
microscope. *Geochem. Geophys. Geosyst.* **18**, 3254–3267 (2017).
18. L. F. White, J. R. Darling, D. E. Moser, D. A. Reinhard, T. J. Prosa, D. Bullen, D. Olson,
D. J. Larson, D. Lawrence, I. Martin, Atomic-scale age resolution of planetary events. *Nat.
Commun.* **8**, 15597 (2017).
19. N. E. Timms, S. M. Reddy, J. D. Fitz Gerald, L. Green, J. R. Muhling, Inclusion-localised
crystal-plasticity, dynamic porosity, and fast-diffusion pathway generation in zircon. *J.
Struct. Geol.* **35**, 78–89 (2012).
20. S. Piazzolo, A. La Fontaine, P. Trimby, S. Harley, L. Yang, R. Armstrong, J. M. Cairney,
Deformation-induced trace element redistribution in zircon revealed using atom probe
tomography. *Nat. Commun.* **7**, 10490 (2016).
21. T. Geisler, U. Schaltegger, F. Tomaschek, Re-equilibration of zircon in aqueous fluids and
melts. *Elements* **3**, 43–50 (2007).
22. A. J. Cavosie, S. A. Wilde, D. Liu, P. W. Weiblen, J. W. Valley, Internal zoning and U-Th-
Pb chemistry of Jack Hills detrital zircons: A mineral record of early Archean to
Mesoproterozoic (4348–1576 Ma) magmatism. *Precambrian Res.* **135**, 251–279 (2004).
23. X. Quidelleur, M. Grove, O. M. Lovera, T. M. Harrison, A. Yin, F. J. Ryerson, Thermal
evolution and slip history of the Renbu Zedong Thrust, southeastern Tibet. *J. Geophys.
Res.* **102**, 2659–2679 (1997).
24. C. Patterson, D. Settle, B. Glover, Analysis of lead in polluted coastal seawater. *Mar.*

Chem. **4**, 305–319 (1976).

25. C. J. Spencer, C. L. Kirkland, R. J. M. Taylor, Strategies towards statistically robust interpretations of in situ U-Pb zircon geochronology. *Geosci. Front.* **7**, 581–589 (2016).
26. Q. Wang, S. A. Wilde, New constraints on the Hadean to Proterozoic history of the Jack Hills belt, Western Australia. *Gondwana Res.* **55**, 74–91 (2018).
27. E. A. Bell, P. Boehnke, M. D. Hopkins-Wielicki, T. M. Harrison, Distinguishing primary and secondary inclusion assemblages in Jack Hills zircons. *Lithos.* **234–235**, 15–26 (2015).
28. M. C. Liu, K. D. McKeegan, T. M. Harrison, G. Jarzebinski, L. Vltava, The Hyperion-II radio-frequency oxygen ion source on the UCLA ims1290 ion microprobe: Beam characterization and applications in geochemistry and cosmochemistry. *Int. J. Mass Spectrom.* **424**, 1–9 (2018).
29. E. A. Lima, B. P. Weiss, Ultra-high sensitivity moment magnetometry of geological samples using magnetic microscopy. *Geochem. Geophys. Geosyst.* **17**, 3754–3774 (2016).
30. E. A. Bell, T. M. Harrison, M. T. McCulloch, E. D. Young, Early Archean crustal evolution of the Jack Hills Zircon source terrane inferred from Lu-Hf, 207Pb/206Pb, and $\delta^{18}\text{O}$ systematics of Jack Hills zircons. *Geochim. Cosmochim. Acta.* **75**, 4816–4829 (2011).
31. G. A. Paterson, L. Tauxe, A. J. Biggin, R. Shaar, L. C. Jonestrask, On improving the selection of Thellier-type paleointensity data. *Geochem. Geophys. Geosyst.* **15**, 1180–1192 (2014).
32. T. Berndt, A. R. Muxworthy, K. Fabian, Does size matter? Statistical limits of paleomagnetic field reconstruction from small rock specimens. *J. Geophys. Res.* **121**, 15–26 (2016).
33. P. W. Reiners, R. W. Carlson, P. R. Renne, K. M. Cooper, D. E. Granger, N. M. McLean, B. Schoene, *Geochronology and thermochronology*. (Wiley, New York, 2017).

Acknowledgments

We acknowledge Ronald L. Walsworth for developing the quantum diamond magnetometer, the National Science Foundation (grants EAR 1647504 and DMS 1521765) and Thomas F. Peterson, Jr. for support. The UCLA ion microprobe facility is partly supported by a grant from the Instrumentation and Facilities Program, Division of Earth Sciences, National Science Foundation (1339051).

473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493

Figures and Tables




Figure 1. Examples of grains that pass and fail the selection criteria. (A-C) Example of a zircon grain (071320; 3.973 ± 0.001 Ga) that passes all selection criteria: U-Pb age discordance < 10%, (A) presence of zonation in CL, (B) no signs of secondary deposits on the exposed surface from BSE, and (C) ~20 μ m Li zonation banding (black arrow) indicating that the sample may not have been fully thermally remagnetized since crystallization; (D-F) Example of a zircon grain (120208; 3.666 ± 0.004 Ga) that passes some of the selection criteria: U-Pb age discordance < 10%, (D) presence of zonation in CL, (E) no signs of secondary deposits on the exposed surface from BSE, (F) and no observed Li zonation. (G-I) Example of a zircon grain (151808; 3.527 ± 0.007 Ga) that fails most of the selection criteria: U-Pb age discordance < 10%, (G) absence of igneous zonation, (H) presence of secondary minerals filling cracks at lower right side of grain (white arrow), and (I) no observed Li zonation.

494
495
496
497
498
499
500
501
502
503




Figure 2. Summary of zircon selection from the initial 3,754 dated grains. Each circle shows the amount of zircon grains during each selection step. Histogram on the top right shows the measured age distribution of the 3,754 grains measured. From the 250 grains that were older than 3.5 Ga, we selected all grains that passed all the selection criteria (3 grains) plus an additional set of 53 grains. The histograms on the bottom left show the amount of grains that satisfy different selection criteria [(1) U–Pb age discordance <10%; (2) lack of visible cracks, metamictization and secondary deposits; and (3) detectable primary Li zoning with thickness of <20 μm] and paleomagnetic criteria [(a) the NRM component had a difference ratio sum (DRATS) ≤25 and (b) the sample gained a moment in the direction of the laboratory field during in-field steps with a maximum angular deviation (MAD) ≤15° over the same temperature range as the NRM component] for the 56 grains selected for paleomagnetic analysis. Only two grains pass the selection and the paleomagnetic criteria. In addition to the 56 polished grains shown here, 21 whole grains were also analyzed paleomagnetically as a control. No grain showed evidence for a Hadean-Eoarchean dynamo.

504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520




Figure 3. Paleomagnetic data for zircon grain 071320 ($3.973 \pm 0.001 \text{ Ga}$) that passes all selection and paleomagnetic criteria. (A) Orthographic projection of NRM vector endpoints during thermal demagnetization. Closed symbols show the X_1-Y_1 projection of the magnetization; opened symbols show Z_1-Y_1 projection of the magnetization. (B-D) Magnetic field (B_z) maps measured at a height of $\sim 360 \mu\text{m}$ above the grains obtained with the SQUID microscope for NRM, 500°C and 575°C steps. We use a “1” subscript on X_1 , Y_1 and Z_1 to denote the fact that the grain orientation during the thermal demagnetization and paleointensity experiments is different from the grain orientation during the BSE, CL and Li measurements, and the QDM measurements (Figure 6). (E) NRM lost versus pTRM gained during progressive laboratory heating, blue triangles show pTRM checks. Red line shows the measurements used to compute paleointensity values (550-580°C). (F-H) show CL, BSE, Li images of the grains.




Figure 4. Paleomagnetic data for zircon grain 080211 (3.979 ± 0.007 Ga) that passes all selection and paleomagnetic criteria. (A) Orthographic projection of NRM vector endpoints during thermal demagnetization. Closed symbols show X-Y projection of the magnetization; opened symbols show Z-Y projection of the magnetization. (B-D) Magnetic field (B_z) maps measured at a height of ~ 360 μm above the grains obtained with the SQUID microscope for NRM, 500°C and 575°C steps. We use a “1” subscript on X_1 , Y_1 and Z_1 to denote the fact that the grain orientation during the thermal demagnetization and paleointensity experiments is different from that during the BSE, CL and Li measurements, and the QDM measurements (Figure 6). (E) NRM lost versus pTRM gained during progressive laboratory heating, blue triangles show pTRM checks. Red line shows the measurements used to compute paleointensity values (550-580°C). (F-H) CL, BSE, Li images of the grains.




Figure 5. Paleomagnetic data for zircon grain 150107 ($4.094 \pm 0.005 \text{ Ga}$) that passes the selection criteria but fails the paleomagnetic criteria. (A) Zijderveld diagram showing paleomagnetic direction. Closed symbols show X-Y projection of the magnetization; opened symbols show Z-Y projection of the magnetization. (B-D) Magnetic field (B_z) maps at a height of $\sim 360 \mu\text{m}$ above the grains obtained with the SQUID microscope for NRM, 500°C and 580°C steps. We use a “1” subscript on X_1 , Y_1 and Z_1 to denote the fact that the grain orientation during the thermal demagnetization and paleointensity experiments is different from the grain orientation during the BSE, CL and Li measurements. (E) NRM lost versus pTRM gained during progressive laboratory heating, blue triangles show pTRM checks. Red line shows the measurements used to compute paleointensity values (550-580°C). (F-H) show CL, BSE, Li images of the grains.

549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568




Figure 6. Magnetite grains located in dislocations and filling parts of voids postdating igneous formation of the zircon host. Shown are zircon grains 071320 (A-C) and 080211 (D-F). (A and D) QDM maps of the magnetic field (B_z) of an isothermal remanent magnetization applied to the grain, used to locate magnetic sources for grains 071320 and 080211. We use X_2 , Y_2 and Z_2 to denote that the grains orientation for these measurements are not the same as that during the paleointensity experiments (Figs. 3-5). (B and E) BSE image of the grains. Grains were repolished after paleomagnetic experiments and prior to these BSE images. Note the difference when compared to the earlier BSE images of the same grains in Figs. 3-4; the images here expose several cracks that were not previously visible. (C and F) TEM analysis conducted in the vicinity of the strongest magnetic region of the grain by extracting rectangular focused ion beam sections (from rectangular regions visible in the BSE images). Magnetite (“mag”) grains are seen to be forming inside voids that intersect dislocations (“disloc”) and growing along dislocation cores that formed during recovery. Magnetite commonly is associated with baddeleyite (“badd”), a secondary product formed after recovery from radiation damage (21), pointing to the fact that the magnetite crystals were not present in the zircon structure when the zircon crystal formed.

569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585

588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637

Supplementary Materials for

Re-evaluating the Evidence for a Hadean-Eoarchean Dynamo

Cauê S. Borlina*, Benjamin P. Weiss, Eduardo A. Lima, Fengzai Tang, Richard J.M. Taylor,
Joshua F. Einsle, Richard J. Harrison, Roger R. Fu, Elizabeth A. Bell, Ellen W. Alexander,
Heather M. Kirkpatrick, Matthew M. Wielicki, T. Mark Harrison, Jahan Ramezani, Adam C.
Maloof

*corresponding author. Email: caue@mit.edu

1. Introduction

In these supplementary materials, we present more details about our methodology and further discuss their implications. This includes our ion and electron microprobe measurements (Section 2), paleomagnetic measurements (Section 3), paleomagnetic data analysis (Section 4), and the effects of sample polishing (Section 5). We also present data tables containing source blocks and sampling locations for the zircons (Table S1), U-Pb measurements (Table S2), and paleomagnetic data analysis results (Tables S3-S7).

Throughout this manuscript we have used “ X_n ”, “ Y_n ” and “ Z_n ”, where $n = 1, 2, 3$, to represent three different coordinate systems. That is to show that the orientation used to obtain the SQUID microscopy measurements ($n = 1$; Figs. 3-5 and Fig. S6), is different than the orientation used during the QDM measurements ($n = 2$; Fig. 6), which is also different than the orientation used during the BSE, CL, Li measurements ($n = 3$; Fig. S2). During each session of experiments, however, the orientation of the grains was kept constant.

2. Ion and electron microprobe measurements do not remagnetize samples

Prior to conducting the U-Pb, BSE, CL and Li measurements, we verified that these measurements do not detectably overprint the natural remanent magnetization (NRM) in the grains. In particular, four zircon crystals from the Mud Tank carbonatite outcrop (30), Northern Territory, Australia, were imparted with an anhysteretic remanent magnetization (ARM) using an alternating field of 200 mT and a 0.4 mT bias field in the Massachusetts Institute of Technology (MIT) Paleomagnetism Laboratory. Samples were progressively alternating-field (AF) demagnetized to a peak field of 80 mT and their magnetic moments measured using a 2G Enterprises Superconducting Rock Magnetometer model 755 at MIT to infer their ARM coercivity spectrum. They were then again imparted with the same ARM as before, sent to UCLA to be imaged with BSE and CL, and shipped back to MIT. Samples were kept in magnetic shielding cans during transport. At MIT, the samples were again AF demagnetized. BSE and CL imaging of grains 1 and 2 was conducted at a height of 40 and 90 mm, respectively; while grains 3 and 4 were measured at a height of 20 and 60 mm, respectively, gold coated (Figure S1). No magnetic overprint was observed to have been acquired at UCLA (only a slight decay of the magnetization was observed and is likely due to viscous decay of the ARM in the shielded can and shielded room)

We also conducted a second test to assess the effects on the sample’s magnetization of U-Pb measurements and Li imaging using the UCLA ion probe. The out of the page component (B_z) of the NRM of holders UCLA 3 and 7 were measured with the MIT superconducting quantum interference device (SQUID) microscope (13) before and after measurements with the ion probe at UCLA (Figure S2). Samples were kept in magnetic shielding cans during transport as before. No variation in the overall NRM of the samples was observed. These experiments collectively demonstrate that our U-Pb, Li, BSE, and CL measurements do not detectably overprint the NRM of the samples. Section 5 provides further evidence for this.




Figure S1. Test for remagnetization of Jack Hills zircon mounts from BSE and CL measurements. Four zircons from the Mud Tank carbonatite outcrop, Northern Territory, Australia, demagnetization curves, and their respective equal area plots. Samples were initially imparted an anhysteretic remanent magnetization (ARM) using an alternating field of 200 mT and a 0.4 mT bias field, then progressively alternating-field (AF) demagnetized to a peak field of 800 mT and measured using a 2G Enterprises Superconducting Rock Magnetometer 755 in the MIT Paleomagnetism Laboratory. They were then again imparted with the same ARM as before, sent to UCLA for BSE and CL imaging, and shipped back to MIT. At MIT, the samples were again AF demagnetized. The demagnetization curves present no difference in magnetic behavior before and after the measurements.

723
724
725
726




Figure S2. Test for remagnetization of Jack Hills zircon mounts from ion microprobe measurements. (A, B) BSE image of epoxy holders UCLA 3 and UCLA 7, containing 325 and 400 Jack Hills zircon grains, respectively. (C, D) Upward magnetic field component (B_z) of the NRM of two zircon-bearing quartz holders obtained with the SQUID microscope measured at a height of $\sim 200\ \mu\text{m}$ above the grains. We use X_3 , Y_3 and Z_3 to show that the grain orientations in the epoxy mount is not the same as that during the thermal demagnetization and paleointensity experiments (Figures 3-5). (E, F) Upward field component of the NRM of two holders obtained with the SQUID microscope after U-Pb, BSE, CL and Li measurements obtained at UCLA. We did not observe any difference in the magnetization before and after imaging the grains.

727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742




Figure S3. Setup for magnetic measurements using SQUID microscopy. (A) Photograph of one of the quartz holders. (B) Cross-sectional view of the measurement setup referenced to the coordinate system presented in (A).

3. Paleomagnetism

In this section, we discuss general aspects of the grain orientation during the paleointensity experiment, the inversion of non-dipolar magnetic sources and how the data will be organized and available for this paper. Figure S3 shows the setup for the holders and the samples with respect to the SQUID microscope.

Figure S4 shows the 4 samples holders used in this experiment with mounted zircons on top of their respective SQUID microscope magnetic maps (B_z). Each dark circle represents a hole used to mount one of the 77 zircon grains. The white circles identify non-acid washed zircon grains that were given an isothermal remanent magnetization (IRM) in a field of 0.4 T with an ASC Scientific IM-10 Pulse Magnetizer. Because of their high magnetic moment, these grains were used as reference for the location and orientation of the zircon grains during the experiments: since the grains with IRM are mutually oriented with the grains selected for paleomagnetic analysis, we can use the first to locate the latter.

Figure S5 shows the demagnetization of the IRM of the markers along with Curie temperature indicators for goethite (“goeth”), pyrrhotite (“pyrr”), magnetite (“mag”) and hematite (“hem”). We observe goethite (grains “B” and “L”), pyrrhotite (grains “C”, “H”, “I”, “J”, “K”), magnetite (“C”, “D”) and hematite (grains “A”, “E”, “F”, “G”, “I”) as the major magnetic carriers among the markers. A similar assemblage of ferromagnetic minerals was previously observed in an IRM study of Jack Hills zircons (6) as well as in the pebble conglomerate that hosts the zircons (3). Alteration, characterized by increase of remanence during demagnetization, can also be observed in grains “B”, “H” and “L”. These interpretations are based on the characteristic thermal unblocking temperature of the remanence.

Some of the grains’ magnetic fields were modestly non-dipolar and these data were ignored [181518_h04 (pTRM check at 555 °C), 182014_h20 (pTRM check at 555 °C), 180212_h22 (560 °C Z step, 560 °C I step), 111202_h24 (560 °C Z step, 565 °C Z step), 150315_h14 (535 °C I step)]. The exception was sample WGNW3, for which the majority of measurements were non-dipolar. We fit for dipolar source for this sample to provide an order-of-magnitude estimate of the magnetic moment variation of the grain.

Included with the supplementary material of this article is a compiled dataset that includes BSE, CL, Li images, calibrated SQUID microscopy maps in .mat format (to be read using Matlab), plotted paleomagnetic data, compiled paleomagnetic data [analyzable with Paleomag X, with files named with the tag “paleox”; or with Magnetic Information Consortium (MagIC) standard, with files named with the tag “MagIC”; there are also text files with all the compiled data as well as data

in the “.mat” format for Matlab], and compiled statistics [“stats” and “statsPICRIT”, the latter follows the standard of ref. (30); see section 7 for analysis description]. These data are also available through the Magnetism Information Consortium (MagIC) database.




Figure S4. Maps of the NRM of Jack Hills zircons as mounted in quartz mounts. Out-of-the-page field component (B_z) of the NRM of four samples holders used in this study [(A) holder C2, (B) E1, (C) F1 and (D) T1]. Measurements were obtained with the SQUID microscope at a height of $\sim 360 \mu\text{m}$ above the top of the grains (Fig. S3). The grain orientation, shown by the compass in the center of the figure, is the same as the one shown in Figures 3-5 and S6. Black circles show where zircon grains were mounted; white circles show where marker zircons were mounted to constrain the location and orientation of each grain analyzed paleomagnetically. The white circles are non-acid washed zircon grains that were applied an isothermal remanent magnetization (IRM) of 0.4 T with an ASC Scientific IM-10 Pulse Demagnetizer and used as reference for the location and orientation of the zircon grains during the experiments.




Figure S5. Compilation of IRM demagnetization of markers used in this study. Starting from the left, the grey lines denote the Curie temperatures for goethite (“goeth”), pyrrhotite (“pyrr”), magnetite (“mag”) and hematite (“hem”). We observe goethite (grains “B” and “L”), pyrrhotite (grains “C”, “H”, “I”, “J”, “K”), magnetite (“C”, “D”) and hematite (grains “A”, “E”, “F”, “G”, “I”) as the major magnetic carriers among the markers. Alteration, characterized by increase of remanence during demagnetization, can also be observed in grains “B”, “H” and “L”. Red line shows the detection limit of our instrument.

4. Paleomagnetic data analysis

Jack Hills detrital zircon grains are among of the weakest-moment samples ever measured in paleomagnetism. Grains with NRMs below $\sim 10^{-14}$ Am² exhibit noisy demagnetization due to statistics of small numbers of ferromagnetic grains and measurement noise (29, 32). Because we are mainly interested in an order-of-magnitude paleointensity estimate to establish the presence or absence of a dynamo, standard paleomagnetic quality criteria will provide an overly conservative selection of the dataset. For example, none of the samples analyzed here have all $\delta pTRM_{ij} \leq 25\%$, where $\delta pTRM_{ij}$ is the difference between the pTRM check in the i th temperature step after heating to the j th temperature step and pTRM gained in the i th temperature step. The exception is sample 080201 (which fails our selection criteria due to the presence of cracks; Figure S6). Most of the samples have demagnetization similar to what we show in main text Fig. 5 (see Database S1). Thus, we considered a sample to be a reliable paleomagnetic recorder if it did not alter during lab experiments and if it gained magnetic moment in the direction of the bias field during in-field steps of the IZZI protocol. To determine in-lab heating alteration we used the difference ratio sum (DRATS) parameter (15, 31), defined as:

$$DRATS = \frac{\left| \sum_{i=1}^{end} \delta pTRM_{i,j} \right|}{x_{end}} \times 100, \quad (2)$$

where x_{end} is the last pTRM gained step. This parameter is an aggregate measure of the success of pTRM checks instead of analyzing them individually. This is useful during low temperature steps when little pTRM may be gained and, as a result, some samples might yield a large discrepancy between the pTRM check step and the pTRM gained at the same temperature step, inappropriately failing a pTRM check. We used a threshold value of $DRATS \leq 25\%$ to identify samples that did not alter during the experiments. Values for all samples are compiled in Table S4.

We used principal component analysis (PCA) (16) to determine whether the in-field components acquired by the grains were trending towards North, as expected from the in-field application during heating steps (which pointed North in the reference frame that the paleomagnetic data are presented). This would indicate that the samples acquired magnetic field, suggesting that they may be robust paleomagnetic recorders. Zero-field and in-field PCA analysis of the components are presented in tables S5 and S6. We considered a maximum angular deviation (MAD) $< 25^\circ$ (16) as indication that the field was adequately recorded. For reference, we also computed the modified PICRIT03 parameters (31), a set of paleomagnetic statistics, for all samples analyzed.

In the study that previously reported paleomagnetism of Jack Hills detrital zircon grains (7), only grains with $NRM > 1 \times 10^{-12}$ Am² were subjected to their Thellier-Thellier protocol. We did not use the magnitude of the NRM as a selection criterion for three reasons: (i) ref. (2) obtained reliable paleomagnetic records from the Bishop Tuff zircon crystals with NRM moments as low as 1.8×10^{-13} Am² and 40% of our samples have NRM moments above this threshold; (ii) such weak moments are at least 30 times stronger than the sensitivity of our magnetometer (2); (iii) such data selection would be biased against a no-dynamo scenario.




Figure S6. Paleomagnetic data for zircon grain 080201 (3.117 ± 0.006 Ga). (A) Zijderveld diagram showing paleomagnetic direction. Closed symbols show X-Y projection of the magnetization; opened symbols show Z-Y projection of the magnetization. (B-D) Magnetic field (B_z) maps at a height of ~360 μm above the grains obtained with the SQUID microscope for NRM, 500°C and 575°C steps. We use X_1 , Y_1 and Z_1 to denote the fact that the grain orientation during the thermal demagnetization and paleointensity experiments is different from the grain orientation during the BSE, CL and Li measurements. (E) NRM lost versus pTRM gained during progressive laboratory heating, blue triangles show pTRM checks. Red line shows the measurements used to compute paleointensity values (550-580°C). (F-H) show CL, BSE, Li images of the grains.

844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861

5. Effects of polishing samples

A factor that might enhance thermochemical alteration during our double-heating paleointensity experiments is the polishing of the grains required for the imaging and dating procedures that occurred prior to beginning the magnetic measurements. Such polishing may have exposed magnetic minerals in the original interior of the zircons to alteration in air, which otherwise would be encapsulated in whole grains. We tested for this effect by conducting double-heating paleointensity experiments on 21 whole grains zircons (of which 4 were non-acid-washed and the remaining acid-washed) following the same heating and measurement schedule as that used for polished grains. These whole grains were randomly selected from separates from rock sample cong14c without the use of any selection criteria (see Table S1). We observed that 19 grains altered during experiments (by failing the DRATS requirement described in Section 4), 12 were poor magnetic field recorders (did not gain moment in the direction of the reference field during in-field steps by failing the MAD requirement as in Section 4), and no grain passed the paleomagnetic criteria.

Table S5 provides a comparison of results from non-polished and polished grains. As used before, grains that had DRATS values $\leq 25\%$ were considered to not have altered, while grains that had MAD values $\leq 15\%$ for the in-field magnetic component were considered robust paleomagnetic recorders. We thus conclude that there is no systematic difference between the suitability of polished grains and non-polished grains for paleointensity analyses since about 0% of unpolished and 11% of polished grains pass the paleomagnetic criteria.

We can also compare the PCA of the NRM component of polished and non-polished grains (16). While Section 2 provides evidence that the U-Pb, BSE, CL and Li measurements do not overprint the NRM of our polished samples, we can use the unpolished grain paleomagnetic dataset (which did not undergo U-Pb, BSE, CL and Li measurements) to further test that conclusion. In particular, we could identify NRM overprints using the magnetic measurements if we observed well-constrained components that are origin-trending with MAD values $\leq 15\%$, obtained from PCA (16). Grains that had a single NRM component with MAD values $\leq 15\%$ totaled 12 (20%) out of 56 for polished grains, versus 2 (10%) out of 21 for non-polished. No distinct overprint was observed in the polished grains when compared to the non-polished ones. PCA analysis of all grain are compiled in Tables S6 (zero-field steps) and S7 (in-field steps).

Table S1. Information about source blocks for analyzed zircon grains from Jack Hills, Western Australia. Table includes block sample names, mass, mount name given a source rock, sampling location (Australian Map Grid 1984 datum) and sampling date.

Block Name	Mass (kg)	Mounts	Sample Location		Sampling Date (MM/DD/YYYY)
			Latitude (°)	Longitude (°)	
D175C	2.6	UCLA 1, 2, 3	-26.16664	116.99148	7/31/2012
D175H	8.6	UCLA 6, 7, 8	-26.16664	116.99148	8/3/2012
D175L	2.0	UCLA 11, 12	-26.16664	116.99148	8/3/2012
Cong14c	2.8	UCLA 15, 18	-26.16674	116.99134	7/31/2012

1-8-6	2912	74.9	-	-	-	-	99.67	-	-	-	-	0.21080	0.009750	0.993
1-8-7	3448	2.7	3716	237.0	3544	82.5	99.97	0.7797	0.06540	31.800	2.6600	0.29580	0.000520	1.000
1-9-11	3426	30.0	-	-	-	-	99.64	-	-	-	-	0.29150	0.005620	0.993
AS3 standard	1008	18.3	1365	203.0	1233	118.0	99.92	0.2358	0.03890	2.367	0.3900	0.07278	0.000655	0.999
AS3 standard	1108	10.5	988	110.0	1026	77.7	99.97	0.1656	0.02000	1.746	0.2100	0.07650	0.000404	0.999
AS3 standard	1074	11.9	1066	157.0	1068	106.0	99.99	0.1797	0.02880	1.864	0.2990	0.07521	0.000446	0.999
AS3 standard	1103	10.6	1018	112.0	1045	78.1	99.91	0.1710	0.02040	1.799	0.2150	0.07629	0.000405	0.999
AS3 standard	1089	11.7	1170	115.0	1142	74.1	99.93	0.1991	0.02150	2.080	0.2250	0.07576	0.000442	0.999
AS3 standard	1116	13.2	1054	104.0	1075	71.3	99.94	0.1777	0.01900	1.881	0.2020	0.07679	0.000509	0.998
AS3 standard	1140	19.1	1018	106.0	1058	74.2	99.93	0.1711	0.01920	1.835	0.2070	0.07775	0.000747	0.996
AS3 standard	1428	153.0	766	112.0	958	110.0	100.00	0.1262	0.01950	1.569	0.2790	0.09014	0.007230	0.893
AS3 standard	944	37.4	1487	343.0	1279	188.0	99.85	0.2594	0.06700	2.522	0.6520	0.07053	0.001290	0.998
AS3 standard	1298	15.4	1141	163.0	1196	110.0	99.95	0.1936	0.03020	2.248	0.3510	0.08424	0.000668	0.999
AS3 standard	1252	17.7	1203	247.0	1221	160.0	99.96	0.2051	0.04610	2.327	0.5250	0.08228	0.000743	0.999
AS3 standard	1090	12.7	1141	130.0	1123	84.9	99.94	0.1936	0.02410	2.024	0.2530	0.07583	0.000483	0.999
AS3 standard	1090	14.8	990	113.0	1021	79.5	99.98	0.1659	0.02050	1.734	0.2140	0.07580	0.000558	0.998
AS3 standard	1077	17.0	1131	101.0	1113	66.1	99.98	0.1919	0.01860	1.992	0.1950	0.07531	0.000639	0.996
AS3 standard	1146	6.0	1210	123.0	1187	78.0	99.99	0.2064	0.02300	2.218	0.2470	0.07796	0.000235	1.000
AS3 standard	1100	6.0	1020	113.0	1046	77.9	99.99	0.1714	0.02050	1.801	0.2150	0.07620	0.000229	1.000
AS3 standard	1109	13.2	988	103.0	1026	73.0	99.97	0.1657	0.01870	1.748	0.1980	0.07652	0.000507	0.998
AS3 standard	1102	5.5	1047	117.0	1065	79.7	100.00	0.1763	0.02130	1.854	0.2240	0.07628	0.000208	1.000
2-1-6	4010	50.4	-	-	-	-	99.37	-	-	-	-	0.42780	0.014400	0.994
2-1-7	3660	7.2	1756	301.0	2793	186.0	99.96	0.3132	0.06120	14.650	2.8700	0.33930	0.001590	1.000
2-10-5	4164	3.6	3548	339.0	3952	123.0	99.97	0.7339	0.09110	48.020	5.9600	0.47450	0.001160	1.000
2-12-19	3803	22.0	-	-	-	-	99.92	-	-	-	-	0.37280	0.005420	0.998
2-2-1	4251	3.4	2521	222.0	3587	105.0	99.94	0.4786	0.05100	33.220	3.5400	0.50350	0.001150	1.000
2-2-4	3893	28.4	-	-	-	-	99.74	-	-	-	-	0.39580	0.007470	0.988
2-9-19	3738	9.7	3076	389.0	3491	157.0	99.74	0.6116	0.09730	30.120	4.8000	0.35720	0.002280	0.999
AS3 standard	1089	5.3	1184	129.0	1151	82.0	99.99	0.2020	0.02400	2.110	0.2510	0.07578	0.000202	1.000
AS3 standard	1087	9.4	953	135.0	995	96.4	99.98	0.1590	0.02420	1.660	0.2530	0.07571	0.000356	1.000

AS3 standard	1133	15.5	923	131.0	987	96.1	99.96	0.1540	0.02340	1.640	0.2500	0.07744	0.000603	0.999
AS3 standard	1072	25.8	2677	2890.0	1874	1130.0	99.87	0.5150	0.68000	5.330	7.0500	0.07514	0.000963	1.000
AS3 standard	1139	12.7	955	195.0	1013	141.0	99.95	0.1600	0.03510	1.710	0.3760	0.07768	0.000495	1.000
AS3 standard	1087	16.6	1028	257.0	1047	177.0	99.95	0.1730	0.04680	1.800	0.4880	0.07569	0.000628	1.000
AS3 standard	1093	12.2	1006	124.0	1034	86.3	99.92	0.1690	0.02250	1.770	0.2350	0.07591	0.000461	0.999
AS3 standard	1061	10.1	1210	163.0	1157	102.0	99.96	0.2060	0.03050	2.130	0.3140	0.07471	0.000373	0.999
3-1-10	5389	539.0	10400	8140.0	6525	1550.0	-452.00	4.0160	6.33000	616.800	942.0000	1.11400	0.430000	0.970
3-13-14	4171	5.0	4700	386.0	4336	116.0	99.93	1.0730	0.12400	70.560	8.1600	0.47680	0.001600	1.000
3-14-18	3968	22.8	-	-	-	-	99.64	-	-	-	-	0.41590	0.006330	0.992
3-20-14	4050	7.3	4392	403.0	4160	126.0	99.91	0.9766	0.12400	59.190	7.5000	0.43960	0.002160	0.999
3-3-2	4061	14.4	4490	476.0	4198	147.0	99.86	1.0070	0.14800	61.460	9.0600	0.44280	0.004270	0.998
3-5-16	3749	4.0	3994	357.0	3832	119.0	99.92	0.8582	0.10300	42.560	5.1200	0.35970	0.000955	1.000
s3-8-14	3959	98.2	-	-	-	-	99.87	-	-	-	-	0.41350	0.027100	0.952
AS3 standard	1118	45.1	1056	119.0	1076	81.5	99.53	0.1780	0.02170	1.887	0.2320	0.07687	0.001740	0.983
AS3 standard	1264	60.8	1164	155.0	1200	104.0	99.44	0.1979	0.02890	2.259	0.3350	0.08276	0.002570	0.978
AS3 standard	918	111.0	1002	152.0	976	104.0	99.68	0.1681	0.02750	1.615	0.2690	0.06966	0.003750	0.947
AS3 standard	974	102.0	943	93.5	952	70.5	99.66	0.1575	0.01680	1.554	0.1770	0.07157	0.003600	0.899
AS3 standard	947	202.0	1061	154.0	1024	121.0	98.42	0.1788	0.02810	1.742	0.3270	0.07065	0.006970	0.851
6-13-2	3571	8.9	1513	96.2	2579	66.5	98.90	0.2646	0.01890	11.680	0.8310	0.32020	0.001850	0.997
6-15-17	3737	4.6	3158	227.0	3523	89.1	99.90	0.6320	0.05740	31.110	2.8200	0.35700	0.001070	1.000
6-2-12	1897	17.8	5395	70.2	3136	19.7	96.90	1.3090	0.02510	20.950	0.4260	0.11610	0.001150	0.876
6-2-20	3942	7.1	3574	247.0	3813	89.3	99.90	0.7408	0.06680	41.760	3.7600	0.40880	0.001930	0.999
6-20-10	1779	47.6	445	26.9	740	34.7	93.10	0.0715	0.00448	1.072	0.0708	0.10880	0.002840	0.919
6-20-12	3693	9.2	2887	194.0	3384	81.2	99.80	0.5650	0.04720	27.020	2.2400	0.34690	0.002100	0.997
6-20-16	4035	6.6	4128	295.0	4065	96.3	100.00	0.8972	0.08670	53.800	5.2000	0.43490	0.001920	0.999
6-5-19	3785	17.8	3677	260.0	3747	92.1	99.70	0.7690	0.07150	39.070	3.6300	0.36850	0.004320	0.992
6-7-11	3899	14.2	1099	60.5	2451	56.3	97.00	0.1859	0.01110	10.180	0.6200	0.39730	0.003760	0.988
6-7-7	3275	6.8	1020	63.7	2013	59.8	98.30	0.1715	0.01160	6.258	0.4270	0.26470	0.001140	0.998
6-8-10	1435	35.0	987	75.5	1137	57.8	95.70	0.1655	0.01360	2.064	0.1750	0.09045	0.001660	0.976

AS3 standard	1073	39.1	1057	96.6	1062	64.8	99.70	0.1781	0.01760	1.846	0.1820	0.07517	0.001460	0.981
AS3 standard	1046	18.7	1027	87.6	1033	59.9	99.90	0.1727	0.01590	1.766	0.1630	0.07418	0.000689	0.995
AS3 standard	1041	41.8	952	91.2	979	68.3	99.50	0.1591	0.01640	1.623	0.1760	0.07399	0.001530	0.982
AS3 standard	1088	16.1	1086	95.2	1087	63.5	99.90	0.1836	0.01750	1.917	0.1830	0.07575	0.000609	0.996
AS3 standard	1099	30.8	1077	92.9	1084	63.3	99.90	0.1818	0.01700	1.909	0.1810	0.07614	0.001170	0.987
AS3 standard	1077	15.4	1085	93.8	1083	62.6	99.90	0.1834	0.01720	1.904	0.1790	0.07533	0.000577	0.997
7-10-1	4162	2.4	3418	118.0	3903	44.8	99.94	0.6993	0.03120	45.700	2.0600	0.47400	0.000754	0.999
7-10-15	3387	4.0	3325	461.0	3364	174.0	100.00	0.6749	0.12000	26.460	4.7000	0.28440	0.000731	1.000
7-10-17	2824	26.5	541	84.5	1246	117.0	99.96	0.0876	0.01430	2.413	0.3940	0.19980	0.003240	0.995
7-10-18	3543	11.2	3399	113.0	3490	40.0	99.74	0.6944	0.02960	30.110	1.2300	0.31450	0.002290	0.986
7-10-20	3487	10.3	2922	71.5	3267	29.8	99.67	0.5735	0.01750	23.980	0.7330	0.30320	0.002020	0.976
7-11-12	3633	5.3	3384	129.0	3543	47.9	99.87	0.6904	0.03370	31.750	1.5500	0.33360	0.001160	0.997
7-12-3	3420	10.5	2915	134.0	3223	56.3	99.53	0.5718	0.03260	22.900	1.3300	0.29050	0.001960	0.993
7-13-10	3463	11.7	2550	148.0	3090	68.2	98.87	0.4852	0.03410	19.980	1.4100	0.29860	0.002260	0.994
7-13-20	3973	1.0	3899	121.0	3948	41.1	99.95	0.8309	0.03440	47.820	1.9800	0.41740	0.000289	1.000
7-13-4	4180	5.4	3717	144.0	4023	51.0	99.95	0.7799	0.03970	51.580	2.6400	0.47970	0.001730	0.998
7-14-10	1873	46.0	1424	233.0	1615	150.0	99.96	0.2472	0.04510	3.905	0.7230	0.11460	0.002920	0.991
7-14-12	3560	7.1	2011	54.9	2880	30.8	96.22	0.3662	0.01160	16.050	0.5170	0.31800	0.001470	0.990
7-14-17	4115	5.2	2343	85.9	3410	43.4	99.71	0.4383	0.01920	27.750	1.2300	0.45910	0.001600	0.997
7-15-16	4091	2.1	3949	127.0	4043	43.0	99.89	0.8451	0.03640	52.630	2.2700	0.45170	0.000651	0.999
7-15-4	3677	14.4	2973	107.0	3410	45.5	99.21	0.5860	0.02640	27.730	1.2900	0.34320	0.003240	0.979
7-15-6	4276	2.7	4183	205.0	4246	66.7	99.96	0.9134	0.06100	64.460	4.3000	0.51180	0.000924	1.000
7-15-7	4197	4.2	3596	113.0	3992	41.3	99.90	0.7468	0.03070	49.960	2.0700	0.48520	0.001360	0.998
7-16-18	3841	1.3	3153	88.0	3588	34.8	99.94	0.6308	0.02230	33.240	1.1700	0.38220	0.000339	1.000
7-17-16	3809	3.9	1107	29.5	2404	27.5	99.92	0.1873	0.00543	9.669	0.2890	0.37440	0.000958	0.997
7-17-18	4216	2.2	2414	56.6	3512	27.7	99.95	0.4542	0.01280	30.770	0.8680	0.49140	0.000742	0.999
7-17-8	4227	4.1	3236	106.0	3877	41.6	99.91	0.6521	0.02720	44.530	1.8600	0.49530	0.001390	0.998
7-18-15	4003	4.4	4050	149.0	4019	48.9	99.83	0.8742	0.04340	51.340	2.5200	0.42590	0.001240	0.998
7-19-1	4100	4.2	3603	118.0	3930	42.1	99.92	0.7489	0.03190	46.940	1.9900	0.45460	0.001280	0.998
7-19-20	3500	4.5	3629	490.0	3547	174.0	99.99	0.7559	0.13300	31.880	5.6300	0.30590	0.000898	1.000

7-19-3	3470	10.0	3823	482.0	3595	165.0	99.88	0.8096	0.13500	33.490	5.6000	0.30000	0.001940	0.999
7-19-7	3836	1.5	3719	136.0	3795	48.0	99.95	0.7804	0.03760	41.010	1.9900	0.38110	0.000372	1.000
7-2-13	3575	6.3	3558	481.0	3569	173.0	99.97	0.7367	0.12900	32.610	5.7300	0.32110	0.001310	1.000
7-2-20	3597	3.9	3547	103.0	3579	36.9	99.94	0.7336	0.02770	32.950	1.2300	0.32580	0.000822	0.998
7-2-4	3746	7.0	3515	501.0	3664	183.0	99.98	0.7251	0.13400	35.900	6.6400	0.35910	0.001650	1.000
7-2-9	4088	3.8	3450	135.0	3865	50.1	99.87	0.7078	0.03590	44.000	2.2200	0.45090	0.001150	0.999
7-20-6	2183	22.1	1286	46.1	1665	34.5	98.97	0.2208	0.00873	4.156	0.1750	0.13650	0.001740	0.954
7-3-10	4219	3.0	3803	125.0	4080	43.2	99.90	0.8039	0.03500	54.610	2.3600	0.49260	0.000994	0.999
7-3-12	3975	2.2	2187	49.1	3238	25.7	99.97	0.4039	0.01070	23.270	0.6140	0.41780	0.000600	0.999
7-3-14	2102	17.1	821	133.0	1254	124.0	99.98	0.1358	0.02350	2.439	0.4200	0.13030	0.001270	0.998
7-3-15	3534	7.2	3427	117.0	3495	43.3	99.69	0.7017	0.03100	30.250	1.3300	0.31260	0.001450	0.995
7-3-20	3543	6.8	3454	491.0	3510	181.0	99.98	0.7087	0.13000	30.730	5.6500	0.31450	0.001380	1.000
7-3-4	4231	3.6	4119	165.0	4195	54.4	99.89	0.8945	0.04860	61.250	3.3400	0.49670	0.001210	0.999
7-3-8	4153	2.7	2763	85.8	3632	37.4	99.95	0.5352	0.02040	34.750	1.3200	0.47100	0.000849	0.999
7-4-12	3524	6.6	3460	120.0	3501	43.0	99.81	0.7104	0.03180	30.430	1.3300	0.31070	0.001320	0.996
7-4-13	3400	3.1	3306	470.0	3365	178.0	99.99	0.6700	0.12200	26.480	4.8200	0.28670	0.000573	1.000
7-4-18	3325	8.4	3009	429.0	3202	173.0	99.93	0.5948	0.10600	22.420	4.0000	0.27330	0.001470	1.000
7-4-5	4011	4.0	3345	109.0	3774	41.4	99.78	0.6802	0.02830	40.150	1.6800	0.42820	0.001160	0.998
7-5-12	2690	33.9	1231	55.5	1875	31.6	98.92	0.2104	0.01040	5.339	0.1970	0.18410	0.003780	0.928
7-5-17	3937	4.8	1961	56.3	3091	31.7	99.95	0.3556	0.01180	19.990	0.6550	0.40760	0.001290	0.996
7-5-3	4083	2.9	3078	86.0	3718	35.1	99.95	0.6120	0.02150	37.910	1.3400	0.44920	0.000877	0.999
7-6-14	4012	1.8	1998	49.6	3160	27.8	99.96	0.3634	0.01050	21.480	0.6160	0.42860	0.000510	0.999
7-6-19	3597	9.9	1847	58.8	2809	35.0	99.95	0.3318	0.01220	14.900	0.5480	0.32570	0.002090	0.985
7-7-1	4078	2.5	3682	132.0	3943	46.3	99.89	0.7702	0.03620	47.570	2.2200	0.44790	0.000755	0.999
7-7-10	2903	6.5	1291	207.0	2034	155.0	99.99	0.2218	0.03920	6.412	1.1300	0.20970	0.000836	1.000
7-7-13	3631	4.9	2424	83.7	3137	40.4	99.55	0.4564	0.01890	20.960	0.8740	0.33310	0.001070	0.997
7-7-19	3419	8.2	2474	76.0	3028	35.9	99.47	0.4679	0.01730	18.720	0.6970	0.29020	0.001540	0.990
7-7-20	4123	2.3	3881	121.0	4042	41.4	99.89	0.8260	0.03430	52.580	2.1800	0.46170	0.000713	0.999
7-7-6	1688	96.4	434	21.2	701	38.3	86.15	0.0697	0.00352	0.995	0.0752	0.10350	0.005410	0.724
7-8-1	3575	6.2	3476	468.0	3539	171.0	99.98	0.7145	0.12400	31.630	5.5100	0.32110	0.001300	1.000
7-8-16	4198	2.1	4063	125.0	4154	41.5	99.94	0.8783	0.03650	58.790	2.4400	0.48550	0.000700	0.999

7-8-17	4227	9.6	4011	137.0	4156	45.8	99.69	0.8631	0.03970	58.940	2.7100	0.49520	0.003240	0.990
7-8-19	4194	4.2	4018	163.0	4136	53.7	99.73	0.8649	0.04700	57.760	3.1100	0.48430	0.001360	0.999
7-8-3	3683	5.5	3229	439.0	3516	170.0	100.00	0.6503	0.11200	30.890	5.3400	0.34450	0.001230	1.000
7-8-9	3760	11.1	3490	548.0	3663	201.0	99.96	0.7183	0.14600	35.880	7.2900	0.36230	0.002640	0.999
7-9-17	4149	6.7	2070	247.0	3289	136.0	99.99	0.3786	0.05280	24.520	3.4200	0.46970	0.002110	1.000
7-9-19	3968	4.9	3821	117.0	3918	40.5	99.87	0.8089	0.03290	46.410	1.8900	0.41610	0.001350	0.997
7-9-8	4047	1.5	2259	78.0	3323	39.8	99.98	0.4197	0.01720	25.380	1.0300	0.43860	0.000438	1.000
AS3 standard	1085	12.6	1018	329.0	1040	227.0	100.00	0.1711	0.05970	1.784	0.6220	0.07563	0.000476	1.000
AS3 standard	1111	30.0	973	202.0	1016	144.0	99.92	0.1629	0.03650	1.721	0.3860	0.07662	0.001150	0.998
AS3 standard	3581	25.9	1502	285.0	2577	200.0	99.95	0.2624	0.05570	11.660	2.5000	0.32230	0.005430	0.997
AS3 standard	1093	9.2	1022	170.0	1044	117.0	100.00	0.1717	0.03080	1.797	0.3230	0.07591	0.000348	1.000
AS3 standard	1090	14.0	1029	184.0	1049	126.0	99.99	0.1731	0.03340	1.809	0.3500	0.07580	0.000529	0.999
AS3 standard	1132	21.5	985	182.0	1031	129.0	99.99	0.1650	0.03280	1.762	0.3510	0.07741	0.000838	0.999
AS3 standard	1107	17.4	1000	186.0	1034	130.0	99.98	0.1677	0.03360	1.768	0.3550	0.07644	0.000665	0.999
AS3 standard	1085	18.5	1321	234.0	1234	140.0	99.95	0.2274	0.04450	2.370	0.4650	0.07560	0.000698	0.999
AS3 standard	1040	16.5	1209	215.0	1150	134.0	99.95	0.2063	0.04020	2.103	0.4100	0.07394	0.000603	0.999
AS3 standard	1366	23.0	1149	542.0	1227	367.0	99.96	0.1952	0.10000	2.347	1.2100	0.08723	0.001040	1.000
AS3 standard	1136	49.6	1050	388.0	1078	266.0	99.68	0.1768	0.07080	1.891	0.7570	0.07757	0.001930	0.998
AS3 standard	1091	21.0	1057	425.0	1068	288.0	99.91	0.1782	0.07770	1.864	0.8130	0.07586	0.000793	1.000
AS3 standard	1100	17.6	1262	447.0	1203	275.0	99.94	0.2163	0.08430	2.271	0.8860	0.07617	0.000669	1.000
AS3 standard	1066	28.7	1149	435.0	1120	280.0	99.87	0.1950	0.08060	2.015	0.8330	0.07492	0.001070	0.999
AS3 standard	1101	27.9	1014	193.0	1042	135.0	99.97	0.1703	0.03510	1.790	0.3700	0.07624	0.001060	0.998
AS3 standard	1075	24.7	986	197.0	1014	139.0	99.98	0.1653	0.03570	1.714	0.3700	0.07523	0.000927	0.998
AS3 standard	1100	16.4	996	199.0	1029	140.0	99.99	0.1671	0.03610	1.755	0.3790	0.07618	0.000626	0.999
AS3 standard	1132	26.8	932	241.0	993	176.0	99.98	0.1555	0.04330	1.660	0.4620	0.07742	0.001040	0.999
AS3 standard	1101	19.8	1017	228.0	1044	158.0	99.98	0.1709	0.04150	1.796	0.4360	0.07622	0.000756	0.999
AS3 standard	1113	11.7	999	219.0	1035	154.0	99.98	0.1676	0.03970	1.772	0.4200	0.07668	0.000449	1.000
AS3 standard	1266	7.4	1088	55.9	1149	38.9	99.98	0.1839	0.01030	2.100	0.1190	0.08285	0.000314	0.998
AS3 standard	1245	8.1	1088	39.9	1142	27.3	99.92	0.1839	0.00733	2.079	0.0829	0.08199	0.000337	0.995
AS3 standard	1303	14.5	1178	63.5	1223	42.8	99.88	0.2005	0.01180	2.334	0.1400	0.08445	0.000629	0.992
AS3 standard	1256	4.9	1132	47.4	1175	32.1	99.97	0.1919	0.00877	2.182	0.1010	0.08243	0.000206	0.999

AS3 standard	1253	3.9	1065	43.9	1128	30.5	99.98	0.1796	0.00804	2.038	0.0913	0.08231	0.000163	0.999
AS3 standard	1291	7.9	1098	47.8	1165	32.6	99.92	0.1857	0.00880	2.150	0.1010	0.08394	0.000343	0.996
AS3 standard	1274	6.6	1058	38.2	1131	26.5	99.94	0.1784	0.00698	2.046	0.0795	0.08321	0.000281	0.996
AS3 standard	1270	6.3	1071	40.5	1139	27.8	99.95	0.1808	0.00742	2.070	0.0840	0.08304	0.000267	0.997
AS3 standard	1256	10.3	1120	44.2	1168	31.1	99.90	0.1898	0.00816	2.158	0.0967	0.08245	0.000435	0.994
AS3 standard	1262	10.2	1142	47.2	1184	31.4	99.83	0.1938	0.00873	2.209	0.0994	0.08271	0.000433	0.993
AS3 standard	1254	8.5	1092	43.7	1148	30.2	99.91	0.1847	0.00803	2.096	0.0921	0.08234	0.000356	0.995
AS3 standard	1238	11.5	1189	57.1	1207	36.7	99.96	0.2026	0.01070	2.282	0.1190	0.08168	0.000479	0.994
AS3 standard	1270	13.5	1152	47.4	1194	32.2	99.91	0.174	0.00880	2.241	0.1030	0.08304	0.000573	0.989
AS3 standard	1109	30.0	1085	39.2	1093	29.5	99.89	0.1834	0.00719	1.935	0.0851	0.07654	0.001150	0.941
AS3 standard	1008	11.7	1147	40.1	1100	26.0	99.61	0.1947	0.00744	1.955	0.0756	0.07280	0.000420	0.989
AS3 standard	1109	34.9	1087	35.3	1095	26.2	99.62	0.1838	0.00647	1.939	0.0758	0.07653	0.001340	0.895
AS3 standard	1114	24.1	1083	42.0	1094	28.5	99.91	0.1830	0.00770	1.936	0.0824	0.07672	0.000928	0.959
AS3 standard	1132	68.1	1095	37.8	1107	35.6	99.65	0.1851	0.00695	1.975	0.1040	0.07741	0.002650	0.763
AS3 standard	1109	306.0	1134	43.1	1126	113.0	68.11	0.1924	0.00798	2.030	0.3370	0.07654	0.011700	0.423
AS3 standard	1107	28.5	1109	39.0	1108	27.5	99.96	0.1877	0.00719	1.978	0.0807	0.07646	0.001090	0.937
AS3 standard	1068	30.1	1142	51.7	1117	36.3	99.85	0.1937	0.00957	2.003	0.1070	0.07499	0.001120	0.961
AS3 standard	1065	26.6	1029	38.6	1041	27.8	99.80	0.1731	0.00702	1.787	0.0763	0.07487	0.000989	0.951
AS3 standard	1019	22.9	1067	37.2	1051	25.4	99.73	0.1800	0.00680	1.816	0.0704	0.07320	0.000827	0.957
8-10-15	1916	227.0	9025	186.0	3981	145.0	59.30	3.0550	0.11700	49.410	7.2200	0.11730	0.014900	0.605
8-10-16	4004	5.3	4002	288.0	4003	96.1	99.90	0.8604	0.08310	50.550	4.8800	0.42610	0.001510	0.999
8-10-19	3993	5.3	3021	249.0	3635	103.0	99.80	0.5978	0.06170	34.870	3.6200	0.42310	0.001490	0.999
8-10-2	4056	6.4	1689	107.0	3001	68.9	98.70	0.2995	0.02150	18.220	1.3000	0.44120	0.001910	0.998
8-11-6	2343	16.6	1616	115.0	1959	71.0	98.40	0.2849	0.02300	5.883	0.4810	0.14980	0.001460	0.993
8-11-8	3515	4.1	2094	127.0	2897	68.1	99.00	0.3837	0.02730	16.340	1.1600	0.30890	0.000812	0.999
8-12-10	3514	3.5	3443	267.0	3488	98.3	99.90	0.7059	0.07070	30.030	3.0000	0.30860	0.000704	1.000
8-12-16	3723	5.7	1836	136.0	2881	81.4	99.20	0.3295	0.02800	16.070	1.3700	0.35360	0.001330	0.999
8-12-4	3625	11.0	2365	179.0	3104	87.0	99.50	0.4432	0.04020	20.260	1.8200	0.33160	0.002370	0.997
8-13-12	3534	4.4	3665	306.0	3580	108.0	99.90	0.7656	0.08380	32.990	3.6200	0.31260	0.000886	1.000
8-13-18	3761	6.2	899	51.7	2170	55.6	97.50	0.1496	0.00921	7.479	0.4640	0.36260	0.001470	0.998

8-16-12	3727	5.5	840	49.5	2086	56.0	97.90	0.1391	0.00874	6.801	0.4300	0.35460	0.001280	0.998
8-16-14	4051	6.7	4314	359.0	4136	114.0	99.90	0.9526	0.10900	57.760	6.5900	0.43970	0.001970	0.999
8-16-3	4127	5.1	4180	291.0	4144	94.1	99.80	0.9126	0.08630	58.240	5.4900	0.46280	0.001600	0.999
8-18-14	3536	19.0	-	-	-	-	99.90	-	-	-	-	0.31310	0.003860	1.000
8-19-11	3855	4.8	4036	311.0	3916	103.0	100.00	0.8704	0.09040	46.320	4.8100	0.38600	0.001230	1.000
8-19-15	3469	8.2	3440	248.0	3459	90.8	100.00	0.7052	0.06560	29.150	2.7000	0.29980	0.001590	0.998
8-19-2	3521	4.8	2202	139.0	2957	71.5	99.60	0.4071	0.03030	17.400	1.3000	0.31000	0.000968	0.999
8-2-1	3117	6.3	2962	213.0	3055	87.0	99.70	0.5833	0.05240	19.270	1.7400	0.23950	0.000941	0.999
8-2-11	3979	6.6	3990	297.0	3983	99.7	99.90	0.8568	0.08540	49.520	4.9600	0.41910	0.001840	0.999
8-2-12	3534	5.7	3444	248.0	3501	91.6	99.90	0.7061	0.06570	30.440	2.8400	0.31260	0.001160	0.999
8-3-10	3331	37.8	359	33.5	1170	70.9	92.60	0.0573	0.00550	2.167	0.2210	0.27430	0.006630	0.972
8-3-8	3603	10.4	3047	229.0	3393	92.9	99.60	0.6043	0.05700	27.250	2.5800	0.32710	0.002210	0.998
8-5-9	3137	39.9	430	61.4	1214	112.0	95.10	0.0690	0.01020	2.306	0.3650	0.24250	0.006090	0.989
8-6-11	3478	6.8	3295	240.0	3410	91.3	99.90	0.6672	0.06210	27.740	2.5800	0.30150	0.001330	0.999
8-6-15	2870	13.8	1210	81.7	1954	65.1	97.90	0.2064	0.01530	5.849	0.4390	0.20550	0.001750	0.994
8-6-16	1459	39.0	279	18.5	451	26.1	88.60	0.0443	0.00300	0.559	0.0401	0.09161	0.001880	0.958
8-6-8	3756	8.4	1846	128.0	2907	76.2	98.90	0.3315	0.02640	16.520	1.3200	0.36130	0.002000	0.998
8-7-9	2852	28.9	1310	82.5	2020	63.1	93.30	0.2253	0.01570	6.309	0.4550	0.20310	0.003610	0.969
8-8-20	3954	5.1	4094	333.0	4000	109.0	99.80	0.8871	0.09750	50.410	5.5400	0.41220	0.001400	1.000
8-8-3	3500	3.3	3151	226.0	3368	88.9	99.90	0.6303	0.05730	26.570	2.4100	0.30580	0.000643	1.000
8-8-5	3217	7.2	346	20.8	1095	41.5	91.50	0.0552	0.00341	1.941	0.1200	0.25510	0.001170	0.997
8-9-12	3323	14.0	2415	195.0	2940	95.9	99.60	0.4545	0.04390	17.100	1.7100	0.27290	0.002450	0.996
8-9-3	3783	5.7	3635	264.0	3731	94.7	99.90	0.7576	0.07200	38.440	3.6800	0.36810	0.001390	0.999
8-9-6	3906	4.4	2304	150.0	3254	75.0	99.00	0.4296	0.03320	23.650	1.8200	0.39920	0.001170	0.999
8-9-7	4569	542.0	2463	768.0	3774	94.3	98.60	0.4653	0.17500	40.140	3.8200	0.62570	0.234000	0.143
AS3 standard	1096	16.2	947	91.0	993	65.5	99.90	0.1582	0.01640	1.659	0.1710	0.07605	0.000616	0.997
AS3 standard	1074	13.0	1049	92.2	1057	62.5	99.90	0.1768	0.01680	1.833	0.1740	0.07520	0.000485	0.998
AS3 standard	1080	13.1	1044	91.1	1056	62.0	99.90	0.1758	0.01660	1.828	0.1730	0.07542	0.000491	0.998
AS3 standard	1084	9.2	1137	111.0	1119	72.1	100.00	0.1929	0.02050	2.009	0.2140	0.07556	0.000347	0.999
AS3 standard	269	544.0	913	62.3	745	139.0	83.20	0.1521	0.01110	1.082	0.2840	0.05162	0.012300	0.470
AS3 standard	1102	4.5	1206	113.0	1169	71.3	100.00	0.2057	0.02110	2.163	0.2220	0.07626	0.000172	1.000

AS3 standard	1093	6.6	1189	114.0	1156	72.1	100.00	0.2026	0.02120	2.121	0.2220	0.07594	0.000248	1.000
AS3 standard	1008	19.0	991	130.0	996	90.3	99.20	0.1661	0.02360	1.667	0.2370	0.07278	0.000681	0.998
AS3 standard	1119	25.8	1104	94.5	1109	63.8	99.90	0.1869	0.01740	1.982	0.1870	0.07693	0.000994	0.991
AS3 standard	1100	15.6	1102	94.6	1102	62.6	100.00	0.1865	0.01740	1.959	0.1820	0.07619	0.000593	0.997
AS3 standard	1087	11.4	1122	97.7	1110	63.9	100.00	0.1901	0.01800	1.984	0.1880	0.07569	0.000431	0.998
9-10-3	229	3950.0	1703	1920.0	1154	1530.0	80.00	0.3023	0.38700	2.116	4.6900	0.05075	0.086800	0.639
9-11-2	3493	23.3	2755	374.0	3200	163.0	98.90	0.5331	0.08890	22.380	3.7400	0.30450	0.004590	0.996
9-12-6	4165	6.1	3930	254.0	4087	85.8	99.70	0.8398	0.07240	55.000	4.7300	0.47500	0.001960	0.999
9-13-12	1807	52.2	1153	252.0	1403	184.0	98.70	0.1958	0.04670	2.984	0.7210	0.11050	0.003180	0.993
9-13-15	3216	19.1	825	68.4	1785	78.8	98.40	0.1365	0.01210	4.799	0.4500	0.25500	0.003090	0.993
9-14-16	3467	7.4	2589	162.0	3111	74.2	99.70	0.4943	0.03760	20.410	1.5700	0.29950	0.001430	0.998
9-14-3	4292	597.0	-	-	-	-	63.10	-	-	-	-	0.51760	0.210000	0.937
9-14-9	3124	28.7	2511	151.0	2865	71.4	99.20	0.4762	0.03460	15.800	1.1800	0.24060	0.004340	0.971
9-15-12	3630	7.8	1514	81.2	2616	56.1	98.60	0.2648	0.01590	12.150	0.7260	0.33290	0.001700	0.996
9-18-12	1084	28.3	1068	84.8	1073	56.7	100.00	0.1802	0.01550	1.877	0.1610	0.07556	0.001070	0.987
9-18-8	5353	343.0	1443	6160.0	3709	4670.0	-55.90	0.2509	1.20000	37.570	177.0000	1.08600	0.266000	0.999
9-2-13	3493	22.3	2618	255.0	3140	110.0	99.40	0.5009	0.05930	21.030	2.3800	0.30450	0.004390	0.993
9-2-16	3214	10.3	1564	101.0	2401	67.0	99.20	0.2746	0.01990	9.643	0.7020	0.25470	0.001660	0.996
9-20-1	3487	10.6	813	57.4	1919	65.4	96.00	0.1344	0.01010	5.620	0.4270	0.30330	0.002070	0.996
9-20-11	3763	25.9	313	18.1	1268	47.3	91.10	0.0497	0.00295	2.487	0.1630	0.36320	0.006190	0.967
9-3-11	3340	69.4	888	173.0	1919	183.0	94.10	0.1477	0.03080	5.621	1.1900	0.27600	0.012200	0.978
9-3-19	5773	652.0	585	824.0	3055	1170.0	-31.80	0.0951	0.14000	19.270	23.3000	1.47000	0.696000	0.957
9-3-6	3943	12.6	2642	421.0	3439	193.0	99.40	0.5066	0.09840	28.570	5.6400	0.40910	0.003430	0.999
9-4-3	4941	200.0	1483	835.0	3451	611.0	-928.00	0.2586	0.16300	28.920	18.0000	0.81100	0.114000	0.975
9-5-18	4324	907.0	895	812.0	2511	936.0	-136.00	0.1489	0.14500	10.860	10.9000	0.52880	0.327000	0.805
9-7-6	3470	16.5	1489	150.0	2502	105.0	98.70	0.2599	0.02940	10.750	1.2200	0.30000	0.003200	0.996
9-9-9	3268	26.0	2087	362.0	2742	193.0	98.40	0.3822	0.07760	13.890	2.8300	0.26360	0.004350	0.997
AS3 standard	1085	8.6	1144	90.9	1124	58.8	100.00	0.1943	0.01680	2.025	0.1750	0.07561	0.000324	0.999
AS3 standard	1119	40.7	1080	66.7	1093	48.0	99.70	0.1825	0.01220	1.935	0.1390	0.07690	0.001570	0.959
AS3 standard	1069	17.9	1094	66.9	1085	44.1	99.90	0.1849	0.01230	1.912	0.1270	0.07500	0.000670	0.991

AS3 standard	1085	14.7	1142	76.4	1123	50.2	99.90	0.1939	0.01420	2.022	0.1500	0.07563	0.000555	0.995
AS3 standard	1094	21.5	1092	68.0	1093	44.8	99.90	0.1847	0.01250	1.934	0.1290	0.07596	0.000815	0.987
AS3 standard	1104	94.9	1064	65.9	1077	55.1	98.00	0.1795	0.01210	1.889	0.1570	0.07635	0.003620	0.820
AS3 standard	1051	101.0	1113	77.8	1092	63.9	98.00	0.1884	0.01440	1.932	0.1840	0.07436	0.003740	0.852
AS3 standard	1077	29.1	1075	85.5	1075	56.9	99.80	0.1814	0.01570	1.884	0.1610	0.07532	0.001090	0.986
AS3 standard	1097	39.7	1018	93.1	1043	65.2	99.20	0.1710	0.01690	1.794	0.1790	0.07609	0.001510	0.980
AS3 standard	990	77.1	818	87.8	866	70.6	98.20	0.1353	0.01550	1.346	0.1630	0.07213	0.002730	0.950
AS3 standard	1070	10.0	1062	88.5	1064	59.5	99.90	0.1791	0.01620	1.853	0.1670	0.07504	0.000374	0.999
AS3 standard	1080	17.6	1007	73.2	1030	51.5	99.90	0.1691	0.01330	1.758	0.1400	0.07542	0.000661	0.994
AS3 standard	1118	20.2	1034	73.2	1061	51.3	99.90	0.1739	0.01330	1.843	0.1440	0.07688	0.000780	0.992
AS3 standard	1056	49.6	1048	73.7	1051	52.9	98.90	0.1765	0.01350	1.814	0.1470	0.07455	0.001840	0.953
AS3 standard	1032	29.8	1093	75.8	1073	50.9	99.60	0.1848	0.01390	1.876	0.1440	0.07364	0.001080	0.982
11-10-16	3424	5.1	1025	63.4	2101	59.9	99.86	0.1724	0.01150	6.922	0.4670	0.29110	0.000959	0.999
11-10-19	4132	9.7	4074	161.0	4113	53.5	99.92	0.8814	0.04710	56.460	3.0300	0.46460	0.003030	0.993
11-10-3	3343	35.0	961	55.5	1994	57.1	98.06	0.1607	0.01000	6.124	0.4000	0.27640	0.006180	0.940
11-12-2	3493	13.6	3569	199.0	3521	73.3	99.90	0.7396	0.05370	31.060	2.3100	0.30450	0.002680	0.993
11-13-6	3599	6.2	732	42.4	1886	52.9	99.93	0.1203	0.00737	5.409	0.3340	0.32620	0.001310	0.998
11-14-10	3498	10.6	2455	109.0	3068	51.4	99.89	0.4635	0.02470	19.520	1.0400	0.30550	0.002100	0.992
11-16-15	5265	1430.0	-	-	-	-	9.99	-	-	-	-	-	-	0.981
11-16-2	3161	19.6	201	12.3	740	31.9	95.71	0.0316	0.00197	1.073	0.0651	0.24620	0.003040	0.980
11-20-10	6004	6340.0	531	4570.0	3120	4620.0	5.42	0.0859	0.77000	20.600	98.3000	1.73900	8.070000	0.955
11-4-4	2546	38.5	777	48.4	1403	48.7	99.97	0.1281	0.00846	2.982	0.1910	0.16890	0.003880	0.938
11-5-1	3525	8.0	2342	120.0	3030	58.0	99.88	0.4381	0.02670	18.770	1.1300	0.31080	0.001600	0.997
11-8-12	3693	4.0	3634	191.0	3672	68.0	99.99	0.7573	0.05210	36.220	2.4900	0.34690	0.000904	0.999
11-8-13	3502	4.4	3339	175.0	3442	65.8	99.98	0.6787	0.04550	28.660	1.9200	0.30620	0.000876	0.999
AS3 standard	1051	17.3	1124	68.5	1100	44.9	99.66	0.1906	0.01270	1.953	0.1310	0.07435	0.000639	0.992
AS3 standard	1092	38.5	1043	73.7	1059	51.7	99.70	0.1756	0.01340	1.838	0.1450	0.07588	0.001460	0.970
AS3 standard	1365	22.3	1020	51.7	1136	39.3	99.96	0.1714	0.00940	2.060	0.1190	0.08718	0.001010	0.980
AS3 standard	1098	8.6	1100	67.5	1099	45.0	99.98	0.1861	0.01240	1.953	0.1310	0.07611	0.000328	0.998
AS3 standard	1101	8.6	1067	92.1	1079	62.3	99.95	0.1801	0.01690	1.893	0.1770	0.07624	0.000327	0.999

12-1-15	3249	3.7	1792	43.4	2565	26.5	99.17	0.3205	0.00889	11.500	0.3260	0.26030	0.000608	0.997
12-10-15	2797	510.0	7838	754.0	4243	377.0	63.02	2.3730	0.39500	64.300	24.3000	0.19650	0.061200	0.582
12-10-6	3274	4.3	1692	51.0	2519	31.8	99.11	0.3002	0.01030	10.950	0.3740	0.26460	0.000730	0.997
12-14-12	3989	4.8	4021	129.0	3999	42.1	99.86	0.8659	0.03730	50.360	2.1300	0.42180	0.001350	0.997
12-14-17	2812	17.9	5998	28.0	3818	14.8	98.49	1.5360	0.01100	41.970	0.6260	0.19820	0.002170	0.721
12-14-5	3966	3.5	4053	123.0	3995	40.3	99.84	0.8751	0.03590	50.120	2.0300	0.41540	0.000960	0.999
12-15-3	3746	5.1	979	21.7	2244	22.5	98.18	0.1640	0.00391	8.119	0.2020	0.35900	0.001200	0.992
12-17-6	4019	2.8	2346	55.9	3349	27.7	99.60	0.4390	0.01250	26.060	0.7380	0.43050	0.000816	0.998
12-17-9	3822	2.6	2930	71.1	3486	29.8	99.64	0.5755	0.01740	29.960	0.9080	0.37760	0.000644	0.998
12-2-8	3655	4.2	3698	103.0	3670	36.4	99.93	0.7747	0.02830	36.130	1.3300	0.33830	0.000921	0.997
12-20-11	3768	8.3	2747	76.2	3372	32.3	99.64	0.5313	0.01810	26.690	0.8800	0.36430	0.001990	0.987
12-20-12	3773	10.7	2757	56.2	3380	26.1	99.82	0.5338	0.01340	26.900	0.7180	0.36550	0.002590	0.965
12-20-5	3918	6.5	3703	106.0	3843	37.7	99.79	0.7760	0.02930	43.040	1.6300	0.40230	0.001750	0.993
12-3-11	3775	7.8	1769	56.0	2873	34.4	99.13	0.3159	0.01140	15.940	0.5730	0.36600	0.001890	0.990
12-3-3	3978	4.8	1602	37.9	2894	26.2	98.86	0.2822	0.00754	16.300	0.4470	0.41890	0.001330	0.994
12-6-13	3827	1810.0	-	-	-	-	22.21	-	-	-	-	0.37880	0.454000	0.891
12-8-2	2788	12.0	1145	34.8	1859	29.5	97.17	0.1944	0.00645	5.238	0.1810	0.19540	0.001430	0.978
12-9-3	3383	4.1	1781	39.2	2639	23.5	99.31	0.3183	0.00801	12.450	0.3120	0.28370	0.000751	0.995
AS3 standard	1083	11.7	1143	39.3	1122	26.0	99.95	0.1939	0.00728	2.020	0.0774	0.07553	0.000439	0.989
AS3 standard	1098	16.9	1059	30.2	1072	20.9	99.96	0.1786	0.00552	1.875	0.0593	0.07612	0.000644	0.964
AS3 standard	1102	15.9	1098	37.2	1099	25.3	99.92	0.1856	0.00684	1.952	0.0734	0.07626	0.000607	0.977
AS3 standard	1094	7.4	1080	30.6	1084	20.7	99.99	0.1823	0.00561	1.910	0.0592	0.07597	0.000282	0.993
AS3 standard	1085	23.0	1050	31.7	1062	22.0	99.96	0.1770	0.00579	1.845	0.0617	0.07563	0.000867	0.940
AS3 standard	1101	8.7	1144	39.2	1129	25.7	99.94	0.1942	0.00727	2.042	0.0770	0.07623	0.000333	0.993
AS3 standard	1112	17.4	1125	37.3	1121	25.7	99.91	0.1907	0.00689	2.015	0.0764	0.07663	0.000668	0.973
AS3 standard	1100	15.9	1092	38.1	1095	26.0	99.95	0.1846	0.00700	1.939	0.0752	0.07620	0.000604	0.979
AS3 standard	1094	9.3	1049	35.4	1064	24.2	99.92	0.1767	0.00646	1.851	0.0680	0.07596	0.000352	0.992
AS3 standard	1046	22.9	1049	55.0	1048	38.0	99.83	0.1766	0.01000	1.807	0.1050	0.07418	0.000842	0.981
AS3 standard	1067	23.7	1090	36.0	1083	26.4	99.53	0.1842	0.00662	1.904	0.0756	0.07496	0.000884	0.956
AS3 standard	1102	18.3	1076	40.7	1085	28.0	99.83	0.1817	0.00747	1.910	0.0803	0.07625	0.000696	0.976

AS3 standard	1089	25.3	1150	44.6	1129	29.8	99.83	0.1954	0.00828	2.041	0.0894	0.07577	0.000958	0.958
AS3 standard	1089	25.3	1150	44.6	1129	29.8	99.83	0.1954	0.00828	2.041	0.0894	0.07577	0.000958	0.958
AS3 standard	1115	15.7	1104	34.6	1108	23.4	99.96	0.1868	0.00636	1.977	0.0686	0.07677	0.000603	0.974
AS3 standard	1096	9.0	1090	34.1	1092	22.9	99.94	0.1842	0.00626	1.931	0.0660	0.07604	0.000343	0.991
AS3 standard	1122	29.5	1080	38.0	1094	28.5	99.66	0.1823	0.00697	1.936	0.0825	0.07701	0.001140	0.939
AS3 standard	1122	29.5	1080	38.0	1094	28.5	99.66	0.1823	0.00697	1.936	0.0825	0.07701	0.001140	0.939
15-1-1	4219	4.7	3853	209.0	4097	73.0	99.70	0.8178	0.05900	55.540	4.0700	0.49260	0.001560	0.999
15-1-11	3980	9.1	836	32.5	2231	37.6	94.70	0.1384	0.00573	8.004	0.3340	0.41930	0.002550	0.989
15-1-12	3510	7.1	3044	177.0	3332	71.3	99.70	0.6034	0.04390	25.610	1.8700	0.30780	0.001420	0.998
15-1-14	3147	14.3	548	22.3	1404	32.8	89.80	0.0887	0.00377	2.985	0.1290	0.24410	0.002200	0.978
15-1-15	4065	8.8	888	39.9	2341	46.1	95.60	0.1476	0.00710	9.033	0.4550	0.44380	0.002610	0.994
15-1-5	3347	5.3	3192	194.0	3288	74.8	99.70	0.6408	0.04930	24.490	1.8800	0.27720	0.000941	0.999
15-1-7	4094	4.9	4072	213.0	4087	70.5	99.90	0.8808	0.06210	54.960	3.8900	0.45260	0.001500	0.999
15-1-9	3662	60.7	278	15.6	1137	55.8	86.20	0.0440	0.00253	2.063	0.1680	0.33990	0.013500	0.893
15-10-13	3448	18.5	900	65.7	1991	70.1	98.40	0.1497	0.01170	6.106	0.4910	0.29580	0.003540	0.989
15-10-18	2147	69.1	89	3.1	231	11.7	60.30	0.0138	0.00049	0.255	0.0145	0.13370	0.005290	0.728
15-10-20	3540	8.5	495	17.7	1517	29.4	84.40	0.0798	0.00296	3.454	0.1290	0.31380	0.001730	0.989
15-10-9	3122	11.4	125	4.6	508	15.0	75.60	0.0196	0.00072	0.649	0.0243	0.24030	0.001730	0.982
15-11-10	4038	3.7	633	25.6	2005	36.9	97.10	0.1032	0.00439	6.202	0.2620	0.43590	0.001080	0.998
15-11-11	3532	3.6	3362	177.0	3469	66.4	99.90	0.6846	0.04630	29.460	1.9900	0.31220	0.000718	0.999
15-11-14	2643	20.4	359	18.6	895	29.7	91.70	0.0573	0.00305	1.413	0.0706	0.17890	0.002200	0.974
15-11-19	3925	27.9	3703	189.0	3849	69.7	99.80	0.7761	0.05200	43.270	3.0400	0.40440	0.007510	0.964
15-11-20	3991	4.6	4214	259.0	4064	83.0	99.90	0.9227	0.07720	53.730	4.4800	0.42230	0.001310	0.999
15-11-8	3391	4.5	1191	61.6	2228	51.1	95.50	0.2028	0.01150	7.974	0.4520	0.28510	0.000825	0.999
15-12-11	3877	243.0	-	-	-	-	100.00	-	-	-	-	0.39160	0.063200	1.000
15-12-12	2515	2550.0	139	55.5	411	636.0	52.30	0.0218	0.00879	0.498	0.9380	0.16580	0.252000	0.919
15-12-15	3293	9.6	711	21.2	1694	26.9	95.70	0.1166	0.00367	4.304	0.1400	0.26770	0.001640	0.982
15-12-19	3289	8.2	947	41.8	1951	42.4	96.70	0.1583	0.00750	5.828	0.2850	0.26700	0.001400	0.995
15-13-11	3250	9.3	819	27.7	1797	30.5	86.20	0.1355	0.00487	4.868	0.1760	0.26050	0.001540	0.987
15-13-12	3328	17.1	267	8.9	970	21.9	92.20	0.0424	0.00143	1.599	0.0560	0.27380	0.002990	0.950

15-13-13	3329	20.6	1632	88.0	2513	56.7	97.60	0.2881	0.01760	10.890	0.6640	0.27410	0.003600	0.977
15-13-14	3141	36.6	407	19.6	1177	38.8	89.00	0.0652	0.00325	2.186	0.1220	0.24320	0.005600	0.911
15-13-18	3343	20.9	3072	171.0	3238	70.0	98.40	0.6106	0.04260	23.270	1.6700	0.27640	0.003690	0.983
15-13-3	3278	5.8	512	18.6	1413	28.6	88.70	0.0826	0.00312	3.021	0.1130	0.26530	0.000979	0.995
15-13-5	3872	6.6	699	31.6	1999	41.6	95.90	0.1145	0.00545	6.164	0.2930	0.39030	0.001700	0.996
15-13-8	2981	11.2	414	14.9	1119	25.8	85.10	0.0663	0.00246	2.010	0.0764	0.22010	0.001530	0.983
15-14-10	3585	6.0	3704	213.0	3627	74.4	99.90	0.7765	0.05860	34.590	2.6100	0.32310	0.001270	0.999
15-14-14	3520	8.4	3285	211.0	3433	79.4	99.80	0.6647	0.05440	28.400	2.3000	0.30980	0.001690	0.998
15-14-19	2921	17.0	630	26.3	1408	34.0	91.30	0.1027	0.00450	3.002	0.1340	0.21200	0.002220	0.972
15-14-6	3268	21.4	540	18.0	1450	29.6	89.60	0.0873	0.00303	3.172	0.1210	0.26350	0.003590	0.935
15-15-10	3687	4.1	3265	172.0	3532	65.7	99.70	0.6594	0.04440	31.420	2.1000	0.34550	0.000920	0.999
15-15-12	3430	12.4	435	14.0	1359	27.1	94.00	0.0698	0.00232	2.814	0.1020	0.29230	0.002340	0.977
15-15-15	4057	5.4	3543	199.0	3879	72.3	99.80	0.7325	0.05360	44.600	3.2500	0.44160	0.001610	0.999
15-15-16	3518	3.3	3354	190.0	3458	71.7	99.80	0.6826	0.04970	29.130	2.1300	0.30950	0.000655	1.000
15-15-2	3047	14.1	638	22.2	1478	29.7	86.80	0.1040	0.00380	3.288	0.1260	0.22930	0.002020	0.973
15-15-5	3645	3.8	3685	211.0	3659	73.9	99.80	0.7710	0.05780	35.720	2.6700	0.33600	0.000838	0.999
15-15-7	3528	3.7	3088	165.0	3361	65.2	99.70	0.6146	0.04120	26.400	1.7600	0.31150	0.000743	0.999
15-16-1	3751	4.4	788	29.5	2040	35.2	95.90	0.1301	0.00517	6.460	0.2580	0.36020	0.001050	0.997
15-16-12	3450	56.3	1082	133.0	2168	129.0	95.50	0.1827	0.02440	7.457	1.0700	0.29600	0.010700	0.969
15-16-16	3533	4.0	3392	188.0	3481	70.2	99.90	0.6924	0.04940	29.820	2.1300	0.31240	0.000813	0.999
15-16-17	3447	5.4	2494	129.0	3054	59.5	99.30	0.4724	0.02940	19.250	1.1900	0.29550	0.001040	0.998
15-16-18	3444	5.7	1600	68.9	2561	45.2	98.70	0.2817	0.01370	11.460	0.5540	0.29500	0.001090	0.997
15-16-19	3703	7.8	919	31.8	2158	33.7	95.00	0.1532	0.00569	7.375	0.2780	0.34920	0.001790	0.991
15-16-6	3434	3.4	3181	156.0	3338	60.9	99.80	0.6380	0.03970	25.770	1.6000	0.29300	0.000642	0.999
15-16-8	3492	4.3	1232	49.8	2321	40.1	98.70	0.2105	0.00936	8.832	0.3890	0.30420	0.000842	0.998
15-17-12	3513	17.4	1775	142.0	2714	86.8	98.80	0.3171	0.02900	13.490	1.2400	0.30850	0.003470	0.993
15-17-14	3583	8.5	792	35.0	1949	40.2	97.00	0.1307	0.00613	5.817	0.2700	0.32280	0.001780	0.993
15-17-17	2502	29.2	236	8.7	621	19.5	73.70	0.0372	0.00141	0.844	0.0354	0.16440	0.002850	0.911
15-17-18	3110	27.5	415	16.0	1176	31.9	81.10	0.0664	0.00264	2.184	0.1000	0.23860	0.004120	0.928
15-17-3	3383	7.7	652	20.9	1666	27.9	96.50	0.1064	0.00359	4.158	0.1420	0.28350	0.001390	0.990
15-17-5	3651	4.5	2629	134.0	3245	60.3	99.60	0.5036	0.03130	23.430	1.4500	0.33740	0.000999	0.999

15-17-6	3036	21.2	329	9.9	987	21.6	83.80	0.0524	0.00161	1.643	0.0561	0.22770	0.003010	0.922
15-17-8	3489	6.0	1410	60.0	2457	43.9	98.20	0.2446	0.01160	10.240	0.4860	0.30360	0.001180	0.997
15-18-10	3449	5.3	1178	48.5	2251	40.9	97.70	0.2006	0.00903	8.182	0.3700	0.29590	0.001000	0.997
15-18-13	3937	10.1	211	7.2	1070	23.7	81.10	0.0332	0.00115	1.868	0.0671	0.40760	0.002750	0.982
15-18-15	2257	50.6	238	7.6	562	20.5	60.30	0.0376	0.00122	0.739	0.0351	0.14250	0.004180	0.795
15-18-3	2882	10.5	570	21.4	1311	29.5	86.00	0.0924	0.00363	2.636	0.1060	0.20690	0.001340	0.987
15-18-4	3875	4.2	1352	41.6	2649	31.9	95.20	0.2333	0.00797	12.580	0.4270	0.39100	0.001080	0.997
15-18-6	2997	14.1	302	9.9	919	21.4	87.50	0.0480	0.00161	1.472	0.0521	0.22230	0.001950	0.969
15-18-8	3527	6.9	3436	194.0	3494	71.8	99.80	0.7040	0.05120	30.220	2.2100	0.31130	0.001390	0.998
15-18-9	3481	224.0	485	58.2	1471	141.0	100.00	0.0782	0.00974	3.256	0.5930	0.30200	0.043600	0.613
15-19-14	3443	4.7	3211	101.0	3356	38.5	99.93	0.6457	0.02580	26.240	1.0300	0.29470	0.000890	0.997
15-19-17	3464	5.3	1494	31.2	2502	21.7	96.43	0.2608	0.00610	10.750	0.2510	0.29880	0.001020	0.989
15-19-2	3385	7.6	3076	117.0	3266	47.0	99.82	0.6115	0.02930	23.940	1.1500	0.28390	0.001390	0.995
15-19-5	3256	8.1	856	20.3	1839	22.2	93.11	0.1419	0.00359	5.118	0.1340	0.26150	0.001350	0.980
15-2-10	4007	23.6	2943	357.0	3612	152.0	99.60	0.5787	0.08740	34.070	5.2300	0.42690	0.006750	0.995
15-2-16	3463	2.4	2976	157.0	3274	64.4	99.90	0.5866	0.03870	24.140	1.5900	0.29850	0.000469	1.000
15-2-2	3537	6.2	2768	148.0	3234	64.1	99.70	0.5362	0.03530	23.160	1.5300	0.31320	0.001260	0.998
15-2-3	3624	12.6	3552	216.0	3598	75.8	99.40	0.7351	0.05820	33.600	2.5800	0.33150	0.002730	0.995
15-2-5	3736	9.7	3567	186.0	3676	66.4	99.70	0.7390	0.05020	36.340	2.4400	0.35670	0.002290	0.996
15-2-7	3905	7.4	3941	222.0	3917	75.6	99.80	0.8430	0.06350	46.360	3.5300	0.39890	0.001960	0.998
15-20-6	3902	7.6	853	23.8	2204	26.6	97.94	0.1414	0.00422	7.764	0.2300	0.39810	0.002020	0.986
15-20-8	4082	3.8	3385	102.0	3837	38.2	99.76	0.6906	0.02660	42.750	1.6500	0.44900	0.001140	0.998
15-3-15	3535	5.5	3634	224.0	3571	79.3	99.90	0.7572	0.06120	32.670	2.6300	0.31290	0.001120	0.999
15-3-5	3417	9.1	2939	174.0	3230	73.5	99.60	0.5777	0.04250	23.080	1.7400	0.28980	0.001690	0.997
15-3-6	3368	13.2	3300	188.0	3342	72.0	99.60	0.6686	0.04870	25.890	1.9100	0.28080	0.002380	0.993
15-3-7	3229	10.8	1192	46.4	2136	39.3	90.20	0.2031	0.00866	7.197	0.3170	0.25710	0.001760	0.988
15-4-1	3515	5.9	2989	151.0	3312	61.8	99.60	0.5898	0.03730	25.110	1.5900	0.30870	0.001180	0.998
15-4-11	4140	14.2	3941	1030.0	4074	347.0	99.50	0.8428	0.29400	54.270	18.9000	0.46700	0.004470	1.000
15-4-12	3538	6.6	3040	193.0	3348	77.5	99.80	0.6026	0.04790	26.040	2.0600	0.31340	0.001340	0.999
15-4-13	3544	4.9	2349	120.0	3045	58.7	99.00	0.4396	0.02680	19.070	1.1600	0.31460	0.001000	0.999
15-4-19	3570	3.3	2681	139.0	3217	62.0	99.40	0.5158	0.03270	22.760	1.4500	0.32000	0.000686	0.999

15-4-20	3456	4.2	3043	188.0	3297	75.8	99.60	0.6032	0.04670	24.720	1.9200	0.29720	0.000810	0.999
15-4-6	3491	5.9	3392	168.0	3454	62.6	99.90	0.6924	0.04420	29.030	1.8500	0.30410	0.001160	0.998
15-4-7	3514	3.2	3324	169.0	3443	64.1	99.80	0.6746	0.04400	28.700	1.8800	0.30850	0.000645	1.000
15-4-8	3852	5.5	3780	202.0	3827	69.1	99.80	0.7975	0.05630	42.350	2.9500	0.38520	0.001410	0.999
15-5-12	3138	12.7	302	14.9	973	31.1	89.70	0.0480	0.00243	1.607	0.0799	0.24280	0.001930	0.988
15-5-14	2960	16.3	430	17.4	1137	29.4	89.20	0.0689	0.00288	2.065	0.0887	0.21720	0.002190	0.972
15-5-4	3339	8.4	1688	69.4	2555	43.4	98.40	0.2994	0.01400	11.380	0.5290	0.27580	0.001470	0.993
15-5-5	4120	8.5	1752	75.9	3083	47.8	98.10	0.3122	0.01550	19.830	0.9800	0.46080	0.002640	0.993
15-5-9	3142	9.9	451	15.4	1252	25.9	81.80	0.0724	0.00256	2.430	0.0875	0.24340	0.001520	0.985
15-6-10	3397	40.4	3150	801.0	3303	306.0	99.10	0.6301	0.20300	24.860	7.8000	0.28610	0.007420	0.997
15-6-12	2658	291.0	203	12.6	594	98.2	54.50	0.0319	0.00202	0.795	0.1740	0.18060	0.031700	0.758
15-6-20	2580	31.4	272	10.6	715	23.0	86.50	0.0430	0.00172	1.022	0.0458	0.17230	0.003240	0.908
15-6-3	1756	536.0	-	-	-	-	61.90	-	-	-	-	0.10740	0.031500	0.656
15-6-4	3174	21.4	728	72.2	1653	81.8	95.20	0.1195	0.01250	4.092	0.4100	0.24830	0.003360	0.992
15-6-8	3597	14.5	557	19.6	1644	32.5	91.40	0.0902	0.00332	4.050	0.1620	0.32560	0.003080	0.973
15-7-10	3403	15.0	628	21.3	1645	30.9	87.70	0.1024	0.00364	4.056	0.1540	0.28730	0.002770	0.968
15-7-11	2696	19.5	282	9.6	771	20.4	73.90	0.0447	0.00156	1.138	0.0429	0.18480	0.002180	0.950
15-7-14	2512	44.7	248	6.8	650	20.0	63.10	0.0393	0.00110	0.896	0.0374	0.16550	0.004400	0.777
15-7-18	3100	6.9	576	22.7	1421	31.3	94.80	0.0935	0.00384	3.053	0.1250	0.23700	0.001030	0.994
15-8-5	4051	4.2	3763	218.0	3953	76.0	99.80	0.7927	0.06050	48.060	3.6700	0.43970	0.001250	0.999
15-9-4	3224	6.8	724	25.0	1674	30.0	96.80	0.1188	0.00435	4.198	0.1540	0.25630	0.001100	0.993
15-9-5	3298	15.8	2281	115.0	2860	59.8	99.20	0.4245	0.02550	15.720	0.9850	0.26860	0.002700	0.988
15-9-8	3924	4.0	956	37.6	2328	38.7	95.00	0.1598	0.00676	8.901	0.3770	0.40400	0.001070	0.998
AS3 standard	1078	19.6	1162	86.7	1133	56.0	99.90	0.1975	0.01610	2.051	0.1680	0.07535	0.000738	0.993
AS3 standard	1056	17.6	1108	77.1	1090	50.6	99.90	0.1875	0.01420	1.927	0.1460	0.07453	0.000650	0.993
AS3 standard	1104	16.1	1038	71.5	1060	49.3	100.00	0.1748	0.01300	1.839	0.1380	0.07634	0.000617	0.994
AS3 standard	1058	24.1	1166	91.4	1129	58.5	99.80	0.1983	0.01700	2.040	0.1750	0.07461	0.000895	0.990
AS3 standard	1081	13.6	1175	86.0	1142	54.8	99.90	0.1999	0.01600	2.080	0.1660	0.07546	0.000513	0.996
AS3 standard	1066	22.0	1178	91.8	1139	58.1	99.90	0.2004	0.01710	2.070	0.1760	0.07490	0.000821	0.992
AS3 standard	1093	11.9	1201	90.2	1163	57.3	100.00	0.2047	0.01690	2.143	0.1770	0.07593	0.000451	0.997
AS3 standard	1092	28.0	1166	84.2	1140	55.6	99.90	0.1982	0.01570	2.074	0.1680	0.07590	0.001060	0.985

AS3 standard	1081	11.3	1191	91.5	1152	57.6	100.00	0.2029	0.01710	2.111	0.1770	0.07547	0.000424	0.998
AS3 standard	1099	25.3	1231	93.6	1184	58.0	99.90	0.2105	0.01760	2.210	0.1830	0.07617	0.000962	0.989
AS3 standard	1089	16.7	1016	72.1	1039	50.1	99.90	0.1707	0.01310	1.783	0.1370	0.07575	0.000631	0.994
AS3 standard	1063	38.6	1188	86.6	1144	54.4	99.70	0.2023	0.01610	2.086	0.1650	0.07479	0.001440	0.971
AS3 standard	1102	28.7	1042	78.8	1062	55.0	99.90	0.1755	0.01440	1.845	0.1540	0.07626	0.001090	0.985
AS3 standard	1083	5.3	1065	65.6	1071	44.4	100.00	0.1797	0.01200	1.871	0.1250	0.07554	0.000199	0.999
AS3 standard	1065	12.6	1078	66.9	1074	44.8	99.90	0.1820	0.01230	1.879	0.1270	0.07489	0.000471	0.996
AS3 standard	1084	23.7	1116	72.3	1105	49.1	99.80	0.1890	0.01330	1.969	0.1430	0.07557	0.000892	0.987
AS3 standard	1095	11.2	1135	85.8	1121	55.8	100.00	0.1926	0.01590	2.017	0.1660	0.07598	0.000426	0.998
AS3 standard	1080	20.3	1130	74.9	1113	48.8	99.90	0.1916	0.01380	1.993	0.1440	0.07543	0.000764	0.990
AS3 standard	1103	19.2	1079	73.8	1087	49.4	99.80	0.1822	0.01350	1.916	0.1420	0.07629	0.000732	0.992
AS3 standard	1116	26.0	938	68.6	992	49.4	99.90	0.1565	0.01230	1.657	0.1290	0.07679	0.000999	0.986
AS3 standard	1065	27.0	1073	68.9	1070	46.9	99.80	0.1812	0.01260	1.870	0.1320	0.07485	0.001000	0.982
AS3 standard	1062	15.1	1036	65.7	1044	45.8	99.90	0.1744	0.01200	1.797	0.1260	0.07475	0.000562	0.994
AS3 standard	1091	29.4	1073	67.7	1079	47.0	99.90	0.1812	0.01240	1.894	0.1340	0.07583	0.001110	0.978
AS3 standard	1095	18.4	1113	86.7	1107	57.2	99.90	0.1884	0.01600	1.975	0.1680	0.07601	0.000698	0.994
AS3 standard	1124	17.8	1061	64.3	1082	43.6	99.60	0.1788	0.01180	1.902	0.1250	0.07713	0.000689	0.991
AS3 standard	1052	23.1	1082	76.9	1072	51.6	99.70	0.1827	0.01410	1.874	0.1460	0.07438	0.000854	0.989
AS3 standard	1035	13.4	1117	72.6	1089	47.3	99.90	0.1891	0.01340	1.923	0.1360	0.07375	0.000491	0.996
AS3 standard	1102	11.2	1189	85.3	1158	54.0	99.90	0.2025	0.01590	2.129	0.1660	0.07626	0.000427	0.998
AS3 standard	1086	7.8	1111	73.0	1102	48.1	100.00	0.1881	0.01340	1.962	0.1400	0.07565	0.000294	0.999
AS3 standard	1075	8.8	977	58.1	1008	41.0	99.90	0.1637	0.01050	1.698	0.1090	0.07526	0.000330	0.998
AS3 standard	1091	10.1	1079	59.5	1083	40.0	100.00	0.1822	0.01090	1.906	0.1150	0.07585	0.000382	0.997
AS3 standard	1084	14.5	1066	66.5	1072	45.4	99.90	0.1798	0.01220	1.874	0.1280	0.07559	0.000548	0.994
AS3 standard	1066	13.8	1046	70.6	1053	48.2	99.90	0.1763	0.01290	1.821	0.1340	0.07491	0.000512	0.996
AS3 standard	1046	22.9	1049	55.0	1048	38.0	99.83	0.1766	0.01000	1.807	0.1050	0.07418	0.000842	0.981
AS3 standard	1067	23.7	1090	36.0	1083	26.4	99.53	0.1842	0.00662	1.904	0.0756	0.07496	0.000884	0.956
AS3 standard	1102	18.3	1076	40.7	1085	28.0	99.83	0.1817	0.00747	1.910	0.0803	0.07625	0.000696	0.976
AS3 standard	1089	25.3	1150	44.6	1129	29.8	99.83	0.1954	0.00828	2.041	0.0894	0.07577	0.000958	0.958
18-1-16	3392	8.1	3149	114.0	3299	44.5	99.87	0.6298	0.02890	24.770	1.1300	0.28530	0.001480	0.994

18-1-17	3212	13.2	488	31.9	1344	45.2	99.97	0.0786	0.00534	2.757	0.1670	0.25440	0.002130	0.998
18-1-18	3536	5.3	2676	84.1	3193	37.3	99.94	0.5145	0.01980	22.200	0.8530	0.31300	0.001070	0.996
18-1-2	3466	4.2	3366	107.0	3429	40.1	99.96	0.6856	0.02810	28.280	1.1600	0.29910	0.000818	0.998
18-10-11	4186	5.0	4188	139.0	4187	45.0	99.94	0.9148	0.04140	60.760	2.7400	0.48170	0.001620	0.997
18-10-20	3547	5.8	2903	87.3	3297	37.0	99.97	0.5688	0.02120	24.720	0.9380	0.31520	0.001180	0.995
18-10-7	3498	7.9	3642	148.0	3549	52.3	99.87	0.7593	0.04040	31.970	1.7000	0.30540	0.001550	0.995
18-10-8	3476	6.6	3407	145.0	3451	54.0	99.85	0.6964	0.03820	28.910	1.5900	0.30110	0.001280	0.997
18-11-11	3539	7.6	3576	115.0	3552	41.2	99.86	0.7416	0.03100	32.060	1.3400	0.31360	0.001540	0.993
18-11-13	4138	7.5	3191	91.5	3800	36.5	99.98	0.6406	0.02330	41.190	1.5200	0.46640	0.002360	0.991
18-11-18	3634	4.8	3213	102.0	3477	39.8	99.90	0.6460	0.02610	29.720	1.2000	0.33360	0.001050	0.997
18-11-19	3453	5.7	3135	98.0	3332	38.5	99.94	0.6262	0.02470	25.610	1.0100	0.29660	0.001080	0.996
18-11-20	3611	7.1	2860	86.5	3320	36.7	99.97	0.5585	0.02090	25.310	0.9520	0.32870	0.001520	0.992
18-11-4	3892	4.5	1109	26.2	2456	23.3	99.93	0.1877	0.00483	10.240	0.2580	0.39550	0.001180	0.993
18-11-6	3837	7.9	551	13.6	1766	21.9	99.91	0.0892	0.00231	4.691	0.1230	0.38130	0.002000	0.980
18-12-11	3869	10.6	3762	129.0	3833	44.5	99.97	0.7925	0.03580	42.570	1.9100	0.38960	0.002750	0.988
18-12-17	3513	5.5	1954	53.6	2819	30.1	99.96	0.3542	0.01130	15.060	0.4770	0.30840	0.001090	0.994
18-12-6	4108	9.7	3377	151.0	3851	54.3	99.89	0.6886	0.03950	43.380	2.3800	0.45690	0.002990	0.994
18-12-7	3747	6.5	964	33.8	2230	32.7	99.95	0.1614	0.00609	7.994	0.2900	0.35930	0.001530	0.994
18-12-8	4104	7.6	4284	159.0	4162	50.1	99.91	0.9436	0.04790	59.290	2.9800	0.45570	0.002340	0.995
18-13-14	3647	5.8	3603	119.0	3631	42.5	99.93	0.7489	0.03220	34.740	1.5000	0.33640	0.001280	0.996
18-13-15	3537	4.5	2023	82.8	2872	46.3	99.96	0.3686	0.01760	15.920	0.7710	0.31330	0.000910	0.998
18-13-19	3652	5.4	3662	127.0	3655	45.3	99.96	0.7649	0.03490	35.600	1.6300	0.33750	0.001190	0.997
18-13-20	4011	5.0	4027	121.0	4016	40.5	99.90	0.8676	0.03520	51.220	2.0800	0.42820	0.001420	0.997
18-13-5	3548	5.4	3462	108.0	3517	39.5	99.96	0.7110	0.02860	30.930	1.2400	0.31550	0.001100	0.996
18-13-7	4136	8.2	1536	49.2	2950	35.2	99.80	0.2691	0.00968	17.270	0.6340	0.46560	0.002590	0.989
18-14-12	3804	4.7	1046	28.8	2344	27.3	99.95	0.1761	0.00525	9.057	0.2700	0.37310	0.001150	0.995
18-14-16	4103	9.4	3984	124.0	4063	43.1	99.89	0.8552	0.03570	53.700	2.3200	0.45540	0.002880	0.990
18-14-2	4072	3.1	3319	92.1	3805	35.2	99.97	0.6735	0.02390	41.410	1.4700	0.44600	0.000928	0.998
18-14-6	3592	7.3	3521	111.0	3566	40.7	99.91	0.7267	0.02980	32.520	1.3500	0.32460	0.001540	0.993
18-15-13	3560	10.9	1265	47.1	2387	38.7	99.93	0.2167	0.00889	9.499	0.4010	0.31790	0.002250	0.986
18-15-15	3576	4.6	499	16.1	1542	26.2	99.95	0.0805	0.00269	3.565	0.1180	0.32140	0.000957	0.996

18-15-16	3518	6.8	2305	72.3	3007	36.1	99.95	0.4298	0.01600	18.330	0.6880	0.30940	0.001360	0.993
18-15-17	3669	4.6	684	18.9	1863	23.4	99.89	0.1119	0.00326	5.267	0.1440	0.34130	0.001020	0.996
18-15-18	4176	7.1	4203	135.0	4185	44.3	99.88	0.9194	0.04020	60.640	2.6900	0.47840	0.002300	0.994
18-15-20	3523	11.7	3560	114.0	3537	41.2	99.95	0.7372	0.03080	31.560	1.3200	0.31050	0.002350	0.984
18-15-5	3829	6.8	2123	54.8	3111	28.7	99.96	0.3900	0.01180	20.400	0.6050	0.37940	0.001710	0.989
18-15-6	3864	8.6	472	13.7	1647	25.0	99.80	0.0759	0.00228	4.063	0.1250	0.38830	0.002210	0.983
18-15-9	3479	10.1	1171	35.2	2263	29.8	99.88	0.1993	0.00654	8.287	0.2730	0.30160	0.001970	0.980
18-16-14	3504	12.3	1098	44.8	2215	40.0	99.92	0.1858	0.00825	7.856	0.3480	0.30670	0.002440	0.984
18-16-16	3482	9.8	3398	108.0	3451	40.3	99.92	0.6940	0.02840	28.920	1.1900	0.30220	0.001910	0.988
18-17-1	3499	11.8	1286	40.9	2368	31.8	99.98	0.2207	0.00775	9.304	0.3220	0.30570	0.002330	0.976
18-17-10	3531	6.8	3524	136.0	3528	48.8	99.88	0.7276	0.03640	31.290	1.5500	0.31190	0.001370	0.996
18-17-11	4050	47.8	-	-	-	-	99.93	-	-	-	-	0.43940	0.014100	0.997
18-17-12	3676	6.1	2327	62.4	3118	30.4	99.95	0.4347	0.01390	20.550	0.6460	0.34290	0.001360	0.992
18-17-14	3862	3.1	2236	72.8	3191	37.8	99.96	0.4146	0.01600	22.160	0.8620	0.38760	0.000805	0.999
18-17-3	3358	10.6	709	26.8	1727	29.7	99.95	0.1163	0.00463	4.476	0.1600	0.27910	0.001900	0.990
18-17-9	3531	6.8	3524	136.0	3528	48.8	99.88	0.7276	0.03640	31.290	1.5500	0.31190	0.001370	0.996
18-18-11	3508	9.4	1054	32.3	2176	30.5	99.97	0.1776	0.00590	7.526	0.2560	0.30740	0.001870	0.984
18-18-13	3523	3.7	3183	96.3	3395	37.5	99.95	0.6385	0.02450	27.330	1.0500	0.31040	0.000738	0.998
18-18-20	4184	4.7	3743	117.0	4035	42.0	99.95	0.7872	0.03250	52.190	2.2000	0.48080	0.001540	0.997
18-18-5	3796	4.0	2817	92.3	3421	39.3	99.89	0.5481	0.02220	28.050	1.1200	0.37110	0.000967	0.998
18-19-1	3583	23.0	518	14.9	1577	27.7	99.94	0.0837	0.00250	3.726	0.1290	0.32280	0.004830	0.903
18-19-14	3494	4.4	3511	114.0	3500	41.6	99.95	0.7240	0.03050	30.410	1.2900	0.30470	0.000859	0.998
18-19-16	3866	4.8	701	22.8	1998	29.3	99.79	0.1149	0.00394	6.156	0.2070	0.38870	0.001250	0.996
18-19-19	4053	5.5	4022	127.0	4043	41.5	99.96	0.8663	0.03670	52.590	2.1900	0.44030	0.001610	0.996
18-19-5	3380	6.1	2190	67.1	2864	35.0	99.96	0.4046	0.01460	15.790	0.5800	0.28310	0.001110	0.994
18-19-6	3446	19.9	2389	71.6	3004	33.7	99.98	0.4486	0.01610	18.270	0.6390	0.29540	0.003790	0.935
18-19-8	3868	12.1	3865	157.0	3867	52.1	99.82	0.8213	0.04420	44.070	2.3100	0.38910	0.003120	0.989
18-19-9	3596	5.9	921	22.7	2097	23.4	99.86	0.1535	0.00405	6.890	0.1820	0.32550	0.001240	0.990
18-2-1	3324	7.2	3121	108.0	3246	42.9	99.91	0.6228	0.02720	23.460	1.0300	0.27320	0.001250	0.995
18-2-12	3949	43.8	2901	106.0	3556	43.8	99.56	0.5684	0.02580	32.190	1.4300	0.41070	0.012000	0.789
18-2-20	3986	9.6	2377	43.9	3342	23.7	99.94	0.4460	0.00985	25.890	0.6270	0.42110	0.002710	0.966

18-2-3	3268	10.5	2482	67.6	2938	32.0	99.87	0.4697	0.01540	17.060	0.5700	0.26350	0.001770	0.980
18-2-6	4056	13.6	513	13.2	1825	22.3	99.87	0.0828	0.00222	5.034	0.1330	0.44120	0.004010	0.942
18-20-11	3427	7.9	1387	40.3	2402	31.8	99.91	0.2400	0.00776	9.654	0.3330	0.29180	0.001490	0.991
18-20-12	3410	8.7	2574	73.9	3069	32.9	99.93	0.4908	0.01710	19.530	0.6660	0.28860	0.001620	0.987
18-20-14	3965	4.6	3651	113.0	3857	40.7	99.96	0.7617	0.03080	43.620	1.7900	0.41530	0.001260	0.997
18-20-2	3712	4.5	1787	60.6	2845	37.4	99.94	0.3195	0.01240	15.470	0.6060	0.35110	0.001030	0.997
18-20-6	3505	7.3	3507	106.0	3506	38.6	99.95	0.7230	0.02820	30.590	1.2000	0.30690	0.001450	0.993
18-20-7	3366	6.3	1779	67.5	2627	39.9	99.93	0.3177	0.01380	12.290	0.5220	0.28050	0.001140	0.996
18-3-1	4062	6.8	4097	135.0	4073	45.4	99.87	0.8880	0.03960	54.240	2.4700	0.44300	0.002030	0.995
18-3-10	3449	6.1	3375	130.0	3422	49.0	99.96	0.6881	0.03410	28.080	1.4000	0.29600	0.001160	0.997
18-3-3	3531	7.2	3404	110.0	3485	41.0	99.94	0.6957	0.02900	29.940	1.2500	0.31210	0.001460	0.994
18-3-4	3963	6.6	2645	98.1	3454	44.8	99.94	0.5072	0.02290	29.000	1.3200	0.41470	0.001810	0.995
18-3-5	4087	5.0	1015	35.6	2488	34.8	99.88	0.1706	0.00647	10.590	0.3970	0.45040	0.001520	0.996
18-3-8	3640	4.7	3684	134.0	3656	47.0	99.93	0.7710	0.03680	35.620	1.7000	0.33500	0.001020	0.998
18-4-11	3734	6.6	3617	129.0	3693	46.9	99.93	0.7526	0.03520	36.980	1.7500	0.35640	0.001540	0.996
18-4-18	3752	5.2	2801	82.9	3385	35.7	99.94	0.5441	0.01990	27.040	0.9860	0.36050	0.001220	0.996
18-4-8	4099	8.9	4068	167.0	4088	55.2	99.86	0.8794	0.04870	55.060	3.0500	0.45410	0.002710	0.994
18-5-12	3390	11.7	3354	122.0	3377	46.0	99.94	0.6826	0.03180	26.820	1.2600	0.28500	0.002130	0.987
18-5-8	3505	4.7	3513	153.0	3508	55.3	99.94	0.7245	0.04090	30.640	1.7200	0.30670	0.000932	0.999
18-5-9	3467	6.0	1383	48.3	2424	35.2	99.93	0.2393	0.00928	9.880	0.3770	0.29940	0.001150	0.995
18-6-10	3402	7.2	2245	72.7	2906	37.1	99.72	0.4167	0.01600	16.490	0.6390	0.28710	0.001320	0.993
18-6-12	3559	4.5	721	25.7	1850	31.3	99.84	0.1184	0.00446	5.187	0.1910	0.31780	0.000932	0.997
18-6-14	3497	6.0	427	13.4	1378	24.5	99.93	0.0685	0.00222	2.884	0.0937	0.30530	0.001190	0.993
18-6-3	3539	5.1	2475	77.8	3103	36.6	99.93	0.4679	0.01770	20.240	0.7660	0.31380	0.001030	0.996
18-6-6	3783	9.0	722	25.4	1977	32.1	99.87	0.1184	0.00441	6.010	0.2220	0.36800	0.002180	0.987
18-7-10	4018	9.2	4017	141.0	4017	47.0	99.73	0.8648	0.04070	51.280	2.4200	0.43010	0.002660	0.991
18-7-15	3647	5.1	3145	118.0	3459	46.1	99.94	0.6288	0.02980	29.170	1.3700	0.33650	0.001130	0.998
18-7-17	3484	16.6	3455	125.0	3474	47.8	99.73	0.7091	0.03300	29.600	1.4400	0.30280	0.003240	0.976
18-7-2	3634	3.4	1138	31.3	2326	27.7	99.89	0.1930	0.00578	8.881	0.2690	0.33370	0.000740	0.997
18-7-8	3551	5.8	3624	143.0	3577	50.3	99.95	0.7544	0.03880	32.890	1.6800	0.31620	0.001190	0.997
18-8-11	3498	10.8	1422	81.8	2470	57.3	99.82	0.2468	0.01580	10.390	0.6430	0.30540	0.002130	0.995

18-8-12	4122	3.1	2891	76.5	3666	32.4	99.96	0.5659	0.01860	35.990	1.1800	0.46130	0.000965	0.998
18-9-12	4139	13.2	3936	145.0	4072	51.8	99.76	0.8415	0.04140	54.150	2.8100	0.46670	0.004170	0.986
18-9-8	3533	5.8	2549	101.0	3134	46.3	99.89	0.4850	0.02330	20.890	0.9990	0.31240	0.001170	0.997
AS3 standard	1111	29.7	1061	51.6	1077	35.4	99.92	0.1788	0.00944	1.889	0.1010	0.07660	0.001140	0.961
AS3 standard	1117	36.6	1081	45.9	1093	35.6	99.97	0.1826	0.00841	1.934	0.1030	0.07683	0.001410	0.942
AS3 standard	1094	9.4	1096	50.6	1096	33.4	99.99	0.1854	0.00930	1.942	0.0967	0.07596	0.000357	0.996
AS3 standard	1099	10.0	1123	51.6	1115	34.1	99.99	0.1903	0.00953	1.999	0.1010	0.07616	0.000380	0.995
AS3 standard	1137	16.0	1052	43.6	1080	30.5	99.98	0.1772	0.00797	1.896	0.0869	0.07762	0.000625	0.985
AS3 standard	1150	25.6	1100	44.9	1117	30.9	99.89	0.1860	0.00826	2.003	0.0915	0.07811	0.001010	0.960
AS3 standard	1082	34.7	1074	48.0	1076	32.6	99.68	0.1812	0.00879	1.886	0.0927	0.07549	0.001310	0.937
AS3 standard	1153	22.0	1181	64.6	1171	41.9	99.85	0.2011	0.01200	2.169	0.1310	0.07824	0.000869	0.983
AS3 standard	1243	35.5	1153	47.5	1185	33.7	99.83	0.1959	0.00882	2.213	0.1070	0.08191	0.001480	0.927
AS3 standard	1134	23.7	1078	58.3	1097	40.0	99.95	0.1821	0.01070	1.946	0.1160	0.07751	0.000922	0.980
AS3 standard	1093	22.3	1131	56.6	1118	36.9	99.97	0.1918	0.01050	2.009	0.1090	0.07594	0.000847	0.979
AS3 standard	1081	38.5	1054	41.6	1063	29.1	99.67	0.1777	0.00761	1.849	0.0818	0.07547	0.001450	0.903
AS3 standard	1099	11.9	1091	42.6	1093	28.3	99.98	0.1843	0.00784	1.935	0.0819	0.07614	0.000455	0.990
AS3 standard	1097	19.4	1121	45.1	1113	30.4	99.85	0.1899	0.00832	1.992	0.0897	0.07607	0.000738	0.977
AS3 standard	1097	24.7	1078	41.9	1084	29.3	99.90	0.1820	0.00768	1.909	0.0838	0.07608	0.000940	0.960
AS3 standard	1099	22.6	1102	41.5	1101	29.4	99.95	0.1864	0.00763	1.957	0.0856	0.07616	0.000861	0.967
AS3 standard	1095	24.2	1106	39.8	1102	25.9	99.93	0.1872	0.00734	1.961	0.0756	0.07598	0.000918	0.952
AS3 standard	1118	29.4	1061	41.7	1080	28.6	99.90	0.1789	0.00763	1.897	0.0816	0.07689	0.001130	0.941
AS3 standard	1128	9.3	1042	39.8	1070	27.3	99.98	0.1755	0.00726	1.870	0.0771	0.07727	0.000361	0.994
AS3 standard	1127	34.3	1233	43.8	1195	28.6	99.92	0.2108	0.00822	2.245	0.0914	0.07722	0.001330	0.908
AS3 standard	1103	10.4	1093	42.0	1096	28.1	99.99	0.1847	0.00771	1.943	0.0814	0.07630	0.000397	0.992
AS3 standard	1127	13.5	1108	40.6	1114	26.6	99.97	0.1875	0.00747	1.996	0.0784	0.07724	0.000522	0.986
AS3 standard	1103	10.9	1071	41.3	1081	27.9	99.98	0.1807	0.00756	1.901	0.0798	0.07630	0.000416	0.992
AS3 standard	1083	24.2	1095	42.8	1091	29.0	99.88	0.1851	0.00788	1.927	0.0836	0.07553	0.000910	0.961
AS3 standard	1108	12.9	1106	44.8	1107	29.8	99.99	0.1871	0.00824	1.974	0.0872	0.07648	0.000492	0.989
AS3 standard	1126	26.0	1104	46.8	1111	30.0	99.86	0.1867	0.00861	1.987	0.0884	0.07717	0.001010	0.959
AS3 standard	1109	22.3	1066	41.9	1080	29.2	99.96	0.1798	0.00766	1.897	0.0834	0.07653	0.000856	0.967
AS3 standard	1114	13.5	1097	43.8	1103	29.4	99.98	0.1855	0.00806	1.962	0.0858	0.07674	0.000520	0.988

AS3 standard	1188	28.7	1060	47.4	1103	32.8	99.82	0.1788	0.00866	1.963	0.0958	0.07962	0.001160	0.955
AS3 standard	1106	7.6	1189	67.0	1160	42.7	99.95	0.2025	0.01250	2.133	0.1320	0.07640	0.000289	0.998

959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986

987 **Table S3. General information about the 77 grain samples paleomagnetically analyzed in this study.** The table lists grain name (grains that
 988 fragmented have hole number “hxx” next to the name to different the fragments), source rock, age of the grain in million years (My) calculated
 989 from $^{207}\text{Pb}/^{206}\text{Pb}$, standard error (1 sigma) in My, age of the grain in My calculated from $^{206}\text{Pb}/^{238}\text{U}$, discordance calculated between $^{207}\text{Pb}/^{206}\text{Pb}$
 990 and $^{206}\text{Pb}/^{238}\text{U}$ according to equation (1), selection criteria 1 and 2 (“PASS” if sample passes the criterion; “FAILS” if sample fails the criterion;
 991 “?” if we do not have data for the criterion), NRM, maximum pTRM check, maximum pTRM check above 500°C, 530°C and 550°C, DRATS
 992 calculated according to equation (2), MAD calculated from in-field steps, paleomagnetic criteria “a” and “b”, and overall paleomagnetic and
 993 selection criteria. Dashed values (“-”) represent no measurements were obtained.
 994

Sample name	Source rock	Age ($^{207}\text{Pb}/^{206}\text{Pb}$) (My)	Age unc. (My)	Age ($^{206}\text{Pb}/^{238}\text{U}$) (My)	Discordance (%)	BSEM and CL no cracks?	Li band?	Acid wash?	Pass selection criteria?	Pass selection criteria? (no Li)	NRM (Am ²)	Max. pTRM check (%)	Max. pTRM check (%) >500°C	Max. pTRM check (%) >530°C	Max. pTRM check (%) >550°C	DRATS (%)	MAD in-field (°C)	Pass paleomagnetic criteria?	Pass selection and paleomagnetic criteria?	Pass selection and paleomagnetic criteria? (no Li)
K1	D175C	3275	8	3071	7	FAIL	?	PASS	FAIL	FAIL	8.95E-13	63.0	63.0	63.0	17.3	47.9	22.7	FAIL	FAIL	FAIL
K2	D175C	3123	10	2836	10	FAIL	?	PASS	FAIL	FAIL	2.84E-12	31.8	31.8	22.5	16.6	26.4	16.3	FAIL	FAIL	FAIL
020919	D175C	3738	10	3076	22	FAIL	PASS	PASS	FAIL	FAIL	1.96E-14	19355.1	19355.1	19355.1	19355.1	173.1	19.7	FAIL	FAIL	FAIL
021005	D175C	4164	4	3548	17	PASS	PASS	PASS	FAIL	FAIL	3.80E-14	668405.9	668405.9	170.7	16.3	16863.9	8.5	FAIL	FAIL	FAIL
031314	D175C	4171	5	4700	11	FAIL	PASS	PASS	FAIL	FAIL	1.38E-13	1114036.6	1114036.6	1114036.6	99.1	12833.0	15.5	FAIL	FAIL	FAIL
011306	D175C	3402	3	3049	12	FAIL	PASS	PASS	FAIL	FAIL	6.62E-15	367.8	367.8	56.5	48.2	21.1	33.9	FAIL	FAIL	FAIL
011011	D175C	3564	4	4174	15	PASS	PASS	PASS	FAIL	FAIL	1.09E-14	466.5	466.5	466.5	99.6	8232.0	10.6	FAIL	FAIL	FAIL
180203	CONG14C	3268	11	2482	32	FAIL	FAIL	PASS	FAIL	FAIL	1.73E-13	1065.2	1065.2	61.8	30.0	3.3	11.7	PASS	FAIL	FAIL
180301	CONG14C	4062	7	4097	1	FAIL	PASS	PASS	FAIL	FAIL	2.87E-14	7933.8	7933.8	100.0	100.0	1507359.5	7.2	FAIL	FAIL	FAIL
180308	CONG14C	3640	5	3684	1	FAIL	PASS	PASS	FAIL	FAIL	6.42E-15	99.9	99.9	99.9	99.9	31236.8	38.4	FAIL	FAIL	FAIL
180715	CONG14C	3647	5	3145	16	FAIL	PASS	PASS	FAIL	FAIL	3.37E-13	874.8	874.8	64.6	19.2	69.6	47.8	FAIL	FAIL	FAIL
180812 (h03)	CONG14C	4122	3	2891	43	FAIL	PASS	PASS	FAIL	FAIL	6.65E-15	5553.8	5553.8	199.4	174.6	1817.8	36.6	FAIL	FAIL	FAIL
180812 (h11)	CONG14C	4122	3	2891	43	FAIL	PASS	PASS	FAIL	FAIL	6.64E-15	7681.3	7681.3	93.7	93.7	137657.8	20.1	FAIL	FAIL	FAIL
181008	CONG14C	3476	7	3407	2	FAIL	PASS	PASS	FAIL	FAIL	2.07E-13	130.9	130.9	48.4	48.4	34.6	24.3	FAIL	FAIL	FAIL
181113 (h05)	CONG14C	4138	8	3191	30	FAIL	FAIL	PASS	FAIL	FAIL	6.80E-15	95.7	95.7	95.7	95.7	1446.4	30	FAIL	FAIL	FAIL
181113 (h12)	CONG14C	4138	8	3191	30	FAIL	FAIL	PASS	FAIL	FAIL	2.22E-13	258.9	258.9	258.9	99.8	20166.2	26.1	FAIL	FAIL	FAIL
181113 (h19)	CONG14C	4138	8	3191	30	FAIL	FAIL	PASS	FAIL	FAIL	1.88E-14	11511.9	11511.9	99.6	99.6	1271.6	40.4	FAIL	FAIL	FAIL
181118	CONG14C	3634	5	3213	13	FAIL	PASS	PASS	FAIL	FAIL	2.76E-14	8961.1	8961.1	8961.1	8961.1	8828.5	13.1	FAIL	FAIL	FAIL
181402	CONG14C	4072	3	3319	23	FAIL	PASS	PASS	FAIL	FAIL	6.51E-15	9070.7	9070.7	103.6	99.5	74487.0	30.8	FAIL	FAIL	FAIL
181518 (h04)	CONG14C	4176	7	4203	1	FAIL	PASS	PASS	FAIL	FAIL	1.28E-14	1253.3	1253.3	103.5	81.7	50.8	43.9	FAIL	FAIL	FAIL
181518 (h06)	CONG14C	4176	7	4203	1	FAIL	PASS	PASS	FAIL	FAIL	1.86E-13	238.8	238.8	71.8	71.8	41.2	38.3	FAIL	FAIL	FAIL

182006	CONG14C	3505	7	3507	0	FAIL	PASS	PASS	FAIL	FAIL	4.61E-14	25877.8	25877.8	99.9	99.9	295006.3	37.3	FAIL	FAIL	FAIL
182014	CONG14C	3965	5	3651	9	FAIL	PASS	PASS	FAIL	FAIL	4.44E-14	99.3	99.3	99.3	99.3	135107.2	31.6	FAIL	FAIL	FAIL
180408 (h29)	CONG14C	4099	9	4068	1	FAIL	FAIL	PASS	FAIL	FAIL	3.53E-14	171.7	171.7	171.7	97.6	5727.2	24.5	FAIL	FAIL	FAIL
180408 (h30)	CONG14C	4099	9	4068	1	FAIL	FAIL	PASS	FAIL	FAIL	5.43E-14	3174.3	3174.3	3174.3	99.0	5888.0	26.3	FAIL	FAIL	FAIL
022003	D175C	4215	6	-	-	FAIL	?	PASS	FAIL	FAIL	9.86E-14	247.4	129.5	129.5	99.0	24301.8	33.9	FAIL	FAIL	FAIL
030311	D175C	4061	14	-	-	FAIL	FAIL	PASS	FAIL	FAIL	6.37E-15	69576.4	69576.4	69576.4	116.6	6073.2	14.4	FAIL	FAIL	FAIL
010109 (h31)	D175C	3256	9	-	-	FAIL	?	PASS	FAIL	FAIL	8.94E-14	100.0	100.0	100.0	100.0	148016.0	21.3	FAIL	FAIL	FAIL
010109 (h32)	D175C	3256	9	-	-	FAIL	?	PASS	FAIL	FAIL	1.00E-13	393.0	393.0	128.1	100.0	38759.5	27.2	FAIL	FAIL	FAIL
181119	CONG14C	3453	6	3135	10	FAIL	FAIL	PASS	FAIL	FAIL	1.53E-13	104263.7	99.9	99.9	99.9	36337.2	37.1	FAIL	FAIL	FAIL
181011	CONG14C	4186	5	4188	0	FAIL	FAIL	PASS	FAIL	FAIL	6.68E-15	9909.1	9909.1	99.8	99.8	268258.8	18.8	FAIL	FAIL	FAIL
180212 (h21)	CONG14C	3949	44	2901	36	PASS	FAIL	PASS	FAIL	FAIL	8.94E-14	148.2	148.2	148.2	118.6	252.4	28.8	FAIL	FAIL	FAIL
180212 (h22)	CONG14C	3949	44	2901	36	PASS	FAIL	PASS	FAIL	FAIL	8.50E-14	324.8	324.8	324.8	62.2	46.9	23.6	FAIL	FAIL	FAIL
181211	CONG14C	3869	11	3762	3	FAIL	FAIL	PASS	FAIL	FAIL	2.82E-13	1536.4	1536.4	1536.4	92.9	209.5	9.5	FAIL	FAIL	FAIL
011318	D175C	3361	7	-	-	FAIL	?	PASS	FAIL	FAIL	4.15E-12	138.2	138.2	35.0	17.9	45.6	44.3	FAIL	FAIL	FAIL
011715	D175C	3771	18	3452	9	FAIL	FAIL	PASS	FAIL	FAIL	6.64E-15	7179.7	132.9	100.0	100.0	36868.6	17.4	FAIL	FAIL	FAIL
062016	D175H	4035	7	4128	2	FAIL	PASS	PASS	FAIL	FAIL	9.66E-13	411.5	70.3	32.6	27.2	17.5	38.3	FAIL	FAIL	FAIL
071320	D175H	3873	1	3899	1	PASS	PASS	PASS	PASS	PASS	1.14E-12	40.5	40.5	40.5	40.5	17.4	12.3	PASS	PASS	PASS
070816	D175H	4198	2	4063	3	FAIL	PASS	PASS	FAIL	FAIL	2.13E-13	97.6	51.8	51.6	51.6	469.8	9.9	FAIL	FAIL	FAIL
080211	D175H	3979	7	3990	0	PASS	PASS	PASS	PASS	PASS	1.46E-12	40.7	10.5	10.5	10.5	13.4	14.8	PASS	PASS	PASS
080201	D175H	3117	6	2962	5	FAIL	PASS	PASS	FAIL	FAIL	1.02E-12	21.9	21.9	21.9	5.7	2.4	19.2	FAIL	FAIL	FAIL
110812 (QDM)	D175L	3693	4	3634	2	FAIL	PASS	PASS	FAIL	FAIL	3.53E-13	183.1	183.1	21.2	10.6	14.8	26.1	FAIL	FAIL	FAIL
110813 (QDM)	D175L	3502	4	3339	5	FAIL	PASS	PASS	FAIL	FAIL	5.10E-13	26.6	25.7	25.7	10.9	3.1	20.8	FAIL	FAIL	FAIL
111019 (QDM)	D175L	4132	10	4074	1	FAIL	FAIL	PASS	FAIL	FAIL	3.84E-14	255.4	255.4	100.0	100.0	195.6	30.1	FAIL	FAIL	FAIL
110910 (QDM)	D175L	4245	6	-	-	FAIL	PASS	PASS	FAIL	FAIL	3.10E-14	134.7	134.7	53.3	53.3	24.2	46.8	FAIL	FAIL	FAIL
111202 (QDM)	D175L	3493	14	3569	2	FAIL	PASS	PASS	FAIL	FAIL	1.26E-12	67.4	67.4	23.8	12.3	22.2	8.5	PASS	FAIL	FAIL
121412	D175L	3989	5	4021	1	PASS	FAIL	PASS	FAIL	PASS	1.61E-13	13122.7	13122.7	13122.7	13122.7	70.2	32.5	FAIL	FAIL	FAIL
120208	D175L	3666	4	3698	1	PASS	FAIL	PASS	FAIL	PASS	3.54E-13	240.5	240.5	240.5	240.5	25.8	17.5	FAIL	FAIL	FAIL
121405	D175L	3966	4	4053	2	PASS	FAIL	PASS	FAIL	PASS	4.09E-14	6910.3	6910.3	6910.3	3499.8	169.3	33.3	FAIL	FAIL	FAIL
150107	CONG14C	4094	5	4072	1	PASS	PASS	PASS	PASS	PASS	3.22E-14	298.8	298.8	298.8	21.3	672.7	26.6	FAIL	FAIL	FAIL
150315	CONG14C	3535	6	3634	3	PASS	FAIL	PASS	FAIL	PASS	3.77E-14	730.0	99.9	99.9	99.9	66.3	34.1	FAIL	FAIL	FAIL
150407	CONG14C	3514	3	3324	6	PASS	FAIL	PASS	FAIL	PASS	1.98E-14	519.9	519.9	519.9	144.5	148.0	26.9	FAIL	FAIL	FAIL

995
996
997
998
999
1000

151119	CONG14C	3925	28	3703	6	FAIL	FAIL	PASS	FAIL	FAIL	5.09E-13	83.9	83.9	83.9	58.7	56.9	40.1	FAIL	FAIL	FAIL
150203	CONG14C	3624	13	3552	2	FAIL	FAIL	PASS	FAIL	FAIL	1.05E-13	233.2	233.2	28.3	28.3	0.2	7.3	PASS	FAIL	FAIL
151120	CONG14C	3991	5	4214	5	FAIL	PASS	PASS	FAIL	FAIL	1.69E-12	177.7	177.7	177.7	30.3	34.7	12.2	FAIL	FAIL	FAIL
151808	CONG14C	3527	7	3436	3	FAIL	FAIL	PASS	FAIL	FAIL	6.82E-14	200674.4	200674.4	200674.4	145.5	4.1	6.9	PASS	FAIL	FAIL
WGAW1	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	3.50E-13	675.5	675.5	28.1	28.1	2.1	15.4	FAIL	FAIL	FAIL
WGAW2	CONG14E	3664	12	837	338	?	?	PASS	FAIL	FAIL	2.23E-12	5800.9	5800.9	21.5	6.7	63.2	7.2	FAIL	FAIL	FAIL
WGAW3	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	2.12E-13	295.5	295.5	35.6	35.6	4.3	40.6	FAIL	FAIL	FAIL
WGAW4	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	2.13E-13	89.8	89.8	89.8	89.8	50.7	25	FAIL	FAIL	FAIL
WGAW5	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	1.44E-12	63.0	63.0	17.9	10.9	83.0	45.2	FAIL	FAIL	FAIL
WGAW6	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	3.76E-14	1296.3	1296.3	172.0	172.0	107.5	22.4	FAIL	FAIL	FAIL
WGAW7	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	3.11E-13	2015.9	2015.9	2015.9	31.3	868.0	23.3	FAIL	FAIL	FAIL
WGAW8	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	3.79E-13	75.7	67.1	50.4	50.4	259.4	28.2	FAIL	FAIL	FAIL
WGAW9	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	1.08E-12	47345.2	47345.2	47345.2	47345.2	53.6	33.6	FAIL	FAIL	FAIL
WGAW10	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	1.19E-13	5842.5	5842.5	78.5	78.5	120.1	-	FAIL	FAIL	FAIL
WGAW11	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	5.96E-14	87.6	87.6	87.6	87.6	611.6	7.1	FAIL	FAIL	FAIL
WGAW12	CONG14E	2345	74	260	802	?	?	PASS	FAIL	FAIL	5.65E-14	19909.0	19909.0	76.2	20.9	65.5	6.4	FAIL	FAIL	FAIL
WGAW13	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	1.64E-13	73.6	73.6	54.3	54.3	157.0	-	FAIL	FAIL	FAIL
WGAW14	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	1.79E-13	858.7	858.7	858.7	101.0	51.7	8.9	FAIL	FAIL	FAIL
WGAW15	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	6.00E-14	99.8	99.8	99.8	99.8	125747.9	44.6	FAIL	FAIL	FAIL
WGAW16	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	3.01E-14	5059.6	5059.6	78.6	78.6	251.9	35.3	FAIL	FAIL	FAIL
WGAW17	CONG14E	?	-	-	-	?	?	PASS	FAIL	FAIL	9.48E-14	476.9	476.9	476.9	476.9	94.3	39.2	FAIL	FAIL	FAIL
WGNW1	CONG14E	?	-	-	-	?	?	FAIL	FAIL	FAIL	1.06E-12	310.3	310.3	310.3	310.3	70.5	13.8	FAIL	FAIL	FAIL
WGNW2	CONG14E	?	-	-	-	?	?	FAIL	FAIL	FAIL	7.55E-13	855.1	855.1	855.1	855.1	1448.7	37.4	FAIL	FAIL	FAIL
WGNW3	CONG14E	?	-	-	-	?	?	FAIL	FAIL	FAIL	1.54E-12	215.4	215.4	215.4	215.4	5610.0	2.9	FAIL	FAIL	FAIL
WGNW4	CONG14E	?	-	-	-	?	?	FAIL	FAIL	FAIL	2.22E-13	1317.5	1317.5	1317.5	33.0	52.4	3.3	FAIL	FAIL	FAIL

1001 **Table S4. Summary of the paleomagnetic data for the 77 samples paleomagnetically analyzed in this study.** Listed are grain name (grains
1002 that fragmented have hole number “hxx” next to the name to different the fragments), the paleointensity fit range, calculated paleointensity, standard
1003 error of the paleointensity, and paleointensity paraments (f , β , q , maximum DRAT and CDRAT). Dashed values (“-”) represent no measurements
1004 were obtained or no magnetic signal from the grain.
1005

Sample name	Fit range (oC)	Paleointensity (μT)	Std. error (μT)	f	β	q	Max. DRAT	CDRAT
K1	550-565	36.1	17.7	0.264	0.491	0.2	86	119.06
K2	550-565	65.9	16.6	0.233	0.251	0.6	42.2	59.5
020919	550-565	-82.6	25.6	9.801	0.31	11.5	154	136.17
021005	550-565	-95.9	36.1	0.101	0.377	-0.1	15649.6	4809.23
031314	550-565	-33.9	17.6	6.886	0.52	5	122.4	91.5
011306	550-565	19	10.5	0.604	0.555	0.2	68.8	22.69
011011	550-565	-298	273.3	0.077	0.917	0	1877.4	1765.43
180203	550-580	-14.6	7.9	12.35	0.544	5	20.5	4.23
180301	550-580	-5.7	2	12.291	0.355	3.2	144.7	126.08
180308	550-580	-19.1	6.8	6.032	0.358	6.2	228.9	274.14
180715	550-580	38	18.7	0.563	0.493	0.2	52.1	82.81
180812 (h03)	550-580	-22.9	4.1	1.385	0.179	1.7	183	69.29
180812 (h11)	550-580	-66.3	25.2	6.306	0.381	6.2	112.1	189.22
181008	550-580	20.1	11.5	0.179	0.572	-0.2	90.6	77.43
181113 (h05)	550-580	-36.7	4.7	5.007	0.128	16.7	315.4	28.27
181113 (h12)	550-580	-38.9	4.8	12.714	0.122	23.1	152.8	88.87
181113 (h19)	550-580	-12.8	6.9	0.853	0.542	-0.2	161.1	21.19
181118	-	-	-	-	-	-	-	-
181402	550-580	-37.6	12.3	5.897	0.326	-9.6	156.2	98.38
181518 (h04)	550-580	95.3	33.3	0.549	0.349	-1.4	58.7	37.74
181518 (h06)	550-580	-26.4	8.7	8.759	0.331	-4.5	123.9	97.8
182006	550-580	-39.2	4.8	79.203	0.123	38.6	132.6	170.61
182014	550-580	-34.9	7.1	9.685	0.205	21.7	84.9	150.52
180408 (h29)	550-580	-71.3	8.9	13.117	0.125	47.2	19.8	32.06

180408 (h30)	550-580	-45.9	10.9	100.774	0.238	-532	103.1	24.61
022003	550-580	-13.3	6	17.943	0.453	9.6	272.5	179.05
030311	-	-	-	-	-	-	-	-
010109 (h31)	550-580	-15.3	1.9	55.465	0.125	-12	109.8	71.21
010109 (h32)	550-580	-22	6	22.573	0.271	43.7	88.3	43.98
181119	550-580	-42.2	4.9	19.854	0.115	-30.3	122.9	70.55
181011	550-580	-12.4	2.2	15.639	0.177	-21.4	105.6	88
180212 (h21)	550-580	68.8	24.1	0.768	0.35	-0.5	197.7	107.65
180212 (h22)	550-580	85.3	51.1	0.791	0.599	-0.5	108.9	41.82
181211	550-580	55.7	3.8	0.914	0.068	-11.2	943.2	123.71
011318	550-580	22.2	7.2	0.446	0.325	-1.9	211.1	183.33
011715	550-580	-11.5	1.7	15.07	0.152	-46	178.9	156.16
062016	550-580	61.7	24.1	0.585	0.391	1.1	16.7	14.07
071320	550-580	23.3	5	0.402	0.213	1.2	61.7	44.86
070816	550-580	-12	4.9	2.523	0.405	1.3	1667.1	1456.53
080211	550-580	41.9	15.2	0.278	0.363	0.6	20.7	37.66
080201	550-580	48.8	3.2	0.392	0.065	4.9	17	4.29
110812 (QDM)	550-580	14.4	8.6	0.272	0.596	-0.5	100.8	34.61
110813 (QDM)	550-580	-22.4	9.3	0.406	0.413	-0.4	100.5	17.96
111019 (QDM)	550-580	-20.1	12.4	1.955	0.617	-4.1	731.1	651.5
110910 (QDM)	550-580	-41	20.1	5.136	0.49	-12.9	143.6	41.91
111202 (QDM)	550-580	6.7	3.8	0.609	0.566	0.5	17.3	37.61
121412	550-580	-6	3.3	2.355	0.55	-4.6	73.2	80.89
120208	550-580	-4.2	2.3	0.531	0.545	0.5	16	8.55
121405	550-580	-54.3	18.5	4.288	0.341	4.2	164.8	131.18
150107	550-580	-50.2	29.5	18.078	0.587	-10.3	216.3	358.11
150315	550-580	-10	5.8	6.88	0.581	4.5	251.1	133.84
150407	550-580	16.9	8.3	0.368	0.492	-0.3	377	269.34
151119	550-580	-37.1	10.7	6.924	0.289	1.8	176.5	82.28
150203	550-580	-5.4	2	2.408	0.38	3.9	7.5	0.19
151120	550-580	23.4	14.2	0.302	0.605	-0.7	105.4	62.09

151808	550-580	-2.5	0.6	1.486	0.246	2.1	6.6	4.27
WGAW1	550-580	-33.1	18.8	0.803	0.567	0.6	49.5	5.77
WGAW2	550-580	-4.8	2.4	0.312	0.503	0.4	165	253.28
WGAW3	550-580	-106.1	39	0.993	0.367	-0.8	512.3	12.44
WGAW4	550-580	-21.1	10.7	4.405	0.505	-2.1	113.7	121.88
WGAW5	550-580	-35.7	18.9	0.096	0.528	0	67.3	121.24
WGAW6	550-580	6.1	3.5	1.083	0.571	0.2	737.6	188.23
WGAW7	550-580	-32.7	8.2	25.699	0.251	18.8	1352.6	1116.1
WGAW8	550-580	-30.1	10.5	12.794	0.348	-39.4	161.2	340.63
WGAW9	550-580	-56.7	22.3	4.732	0.393	-0.8	77.7	44.72
WGAW10	-	-	-	-	-	-	-	-
WGAW11	550-580	4.6	2.7	1.108	0.586	-0.6	2208.2	1969.05
WGAW12	550-580	-3.9	1.8	6.699	0.463	6.9	40.8	132.23
WGAW13	-	-	-	-	-	-	-	-
WGAW14	550-580	-3.7	1.5	4.821	0.399	5.1	45	66.86
WGAW15	550-580	-0.2	0.1	0.079	0.501	-0.1	100	350.92
WGAW16	550-580	-60.9	25.3	3.653	0.416	-6.1	715.3	400.55
WGAW17	550-580	-45	28.2	5.414	0.626	-4.9	185.6	85.74
WGNAW1	550-580	-0.8	0.4	1.044	0.512	0.6	93.6	87.29
WGNAW2	550-580	-26.7	9.8	2.806	0.366	2.3	1670.2	1627.28
WGNAW3	550-580	0	0	1.554	0.618	-1.7	96.7	113.21
WGNAW4	550-580	1.6	1	0.393	0.626	0.2	33.4	85.31

1006
1007
1008
1009
1010
1011

Table S5. Comparison of paleomagnetic data between polished and unpolished grains. Table compares polished (56 grains) and unpolished grains (21 grains). We show values for NRM range, number of grains that fail paleomagnetic criterion “a” (DRATS ≤ 25) showing that they altered, number of grains that fail paleomagnetic criterion “b” (sample gained a moment in the direction of the laboratory field during in-field steps with a maximum angular deviation (MAD) $\leq 15^\circ$ over the same temperature range as the NRM component) showing that they are bad recorders, and the grains that pass both criteria. These results ignore the selection criteria and only consider the paleomagnetic data. We do not observe any significant difference in the resulting data between non-polished and polished grains.

	Unpolished	Polished
NRM range (Am ₂)	3.01x10 ⁻¹⁴ to 2.23x10 ⁻¹²	6.05x10 ⁻¹⁵ to 4.15x10 ⁻¹²
Alteration (fails paleomagnetic criterion “a”)	19 (90%)	44 (79%)
Poor magnetic recorders (fails paleomagnetic criterion “b”)	12 (57%)	42 (75%)
No signs of alteration (passes paleomagnetic criterion “a”) and robust recorder (passes paleomagnetic criterion “b”)	0 (0%)	6 (11%)
Total	21 (100%)	56 (100%)

Table S6. Summary of principal component analysis and maximum angular deviation (MAD) of the 77 samples analyzed here. We show grain name (grains that fragmented have hole number “hxx” next to the name to different the fragments), component (“LT” for low temperature component, “MT” medium temperature component, “HT” high temperature component), range of the component, MAD value and if the component was forced through the origin.

Sample name	Component	Range (°C)	MAD (°)	Origin forced?
K1	LT	025-400	12.1	
	MT	400-510	4.8	
	HT	510-565	7.4	Y
K2	HT	025-565	3.8	Y
020919	LT	025-400	35.3	
	HT	400-565	23.3	Y
021005	HT	025-565	22.6	Y
031314	HT	025-565	10.3	Y
011306	HT	025-565	23.5	Y
011011	HT	025-565	33.3	Y
180203	HT	025-680	28.8	Y
180301	HT	025-565	26.7	Y
180308	HT	025-565	33.8	Y
180715	LT	025-510	9.2	
	HT	510-680	30.7	Y
180812 (h03)	HT	025-565	30.4	Y
180812 (h11)	HT	025-565	27.2	Y
181008	HT	025-680	18.3	Y
181113 (h05)	HT	025-565	43.6	Y
181113 (h12)	LT	0-200	32.3	
	MT	300-500	37.1	
	HT	500-565	39.6	Y
181113 (h19)	HT	025-565	30.1	Y
181118	-	-	-	-
181402	HT	510-565	29.7	Y
181518 (h04)	LT	0-565	27.5	
	HT	565-680	26.3	Y
181518 (h06)	HT	025-680	48.0	Y
182006	LT	025-535	40.3	
	HT	535-565	14.6	Y

182014	HT	025-565	42.1	Y
180408 (h29)	HT	025-565	23.8	Y
180408 (h30)	HT	025-565	43.3	Y
022003	HT	025-560	32.2	Y
030311	-	-	-	-
010109 (h31)	HT	025-565	34.9	Y
010109 (h32)	HT	025-565	35.4	Y
181119	HT	025-565	44.1	Y
181011	HT	025-565	39.3	Y
180212 (h21)	HT	025-630	13.5	Y
180212 (h22)	HT	025-630	10.7	Y
181211	HT	025-660	6.8	Y
011318	LT	025-500	4.5	
	HT	500-660	36.6	Y
011715	HT	25-565	29.1	Y
062016	HT	025-580	11.6	Y
	LT	025-200	12.4	
071320	MT	200-300 (?)	0.1	
	HT	300-680	10.6	Y
070816	HT	025-680	39.1	Y
080211	LT	025-510	13.3	
	HT	510-680	11.8	Y
080201	LT	025-300	19.0	
	HT	300-680	10.0	Y
110812 (QDM)	HT	025-680	32.9	Y
110813 (QDM)	LT	025-400	11.1	
	HT	400-680	45.3	Y
111019 (QDM)	HT	025-580	34.9	Y
110910 (QDM)	HT	025-600	37.8	Y
111202 (QDM)	HT	025-680	26.7	Y
121412	HT	025-680	23.6	Y
	LT	025-500	23.5	
120208	MT	500-580	45.0	
	HT	580-680	46.6	Y
121405	HT	025-680	31.4	Y
150107	HT	025-680	19.0	Y
150315	HT	025-680	40.6	Y
150407	HT	025-680	24.8	Y
151119	HT	025-680	41.6	Y

150203	HT	025-680	27.8	Y
151120	HT	025-680	38.0	Y
151808	HT	025-680	30.0	Y
WGAW1	HT	025-680	38.6	Y
WGAW2	HT	025-680	39.0	Y
WGAW3	HT	025-680	46.0	Y
WGAW4	HT	025-680	40.8	Y
WGAW5	HT	025-680	8.5	Y
WGAW6	HT	025-680	40.5	Y
WGAW7	HT	025-680	32.6	Y
WGAW8	HT	025-680	42.4	Y
WGAW9	HT	025-680	15.8	Y
WGAW10	-	-	-	-
WGAW11	HT	025-680	35.7	Y
WGAW12	HT	025-680	44.9	Y
WGAW13	-	-	-	-
WGAW14	HT	025-680	40.5	Y
WGAW15	HT	025-680	29.6	Y
WGAW16	HT	025-680	42.5	Y
WGAW17	HT	025-680	34.9	Y
WGNAW1	HT	025-680	37.9	Y
WGNAW2	HT	025-680	42.7	Y
WGNAW3	HT	025-680	30.0	Y
WGNAW4	HT	025-680	43.9	Y

1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073

1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084

Table S7. Summary of maximum angular deviation (MAD) values of the in-field component acquired during paleointensity measurements by the 77 samples. All in-field data points were used to calculate the MADs anchored to the origin. Listed are grain name and the in-field MAD value.

Sample name	MAD (°)
K1	22.7
K2	16.3
020919	19.7
021005	8.5
031314	15.5
011306	33.9
011011	10.6
180203	11.7
180301	7.2
180308	38.4
180715	47.8
180812 (h03)	36.6
180812 (h11)	20.1
181008	24.3
181113 (h05)	30
181113 (h12)	26.1
181113 (h19)	40.4
181118	13.1
181402	30.8
181518 (h04)	43.9
181518 (h06)	38.3
182006	37.3
182014	31.6
180408 (h29)	24.5
180408 (h30)	26.3
022003	33.9
030311	14.4
010109 (h31)	21.3
010109 (h32)	27.2
181119	37.1
181011	18.8
180212 (h21)	28.8
180212 (h22)	23.6
181211	9.5
011318	44.3

011715	17.4
062016	38.3
071320	12.3
070816	9.9
080211	14.8
080201	19.2
110812 (QDM)	26.1
110813 (QDM)	20.8
111019 (QDM)	30.1
110910 (QDM)	46.8
111202 (QDM)	8.5
121412	32.5
120208	17.5
121405	33.3
150107	26.6
150315	34.1
150407	26.9
151119	40.1
150203	7.3
151120	12.2
151808	6.9
WGAW1	15.4
WGAW2	7.2
WGAW3	40.6
WGAW4	25
WGAW5	45.2
WGAW6	22.4
WGAW7	23.3
WGAW8	28.2
WGAW9	33.6
WGAW10	-
WGAW11	7.1
WGAW12	6.4
WGAW13	-
WGAW14	8.9
WGAW15	44.6
WGAW16	35.3
WGAW17	39.2
WGNAW1	13.8
WGNAW2	37.4
WGNAW3	2.9
WGNAW4	3.3

1086
1087
1088
1089
1090
1091
1092