

See discussions, stats, and author profiles for this publication at: <https://www.researchgate.net/publication/333666861>

Minimum image quality for reliable optical characterizations of soil particle shapes

Article in *Computers and Geotechnics* · June 2019

DOI: 10.1016/j.compgeo.2019.103110

CITATIONS

3

READS

222

4 authors, including:



Quan Sun

Clemson University

19 PUBLICATIONS 77 CITATIONS

[SEE PROFILE](#)



Junxing Zheng

Iowa State University

71 PUBLICATIONS 606 CITATIONS

[SEE PROFILE](#)



Fatin Altuhafi

University College London

17 PUBLICATIONS 492 CITATIONS

[SEE PROFILE](#)


Some of the authors of this publication are also working on these related projects:



Accelerated Simulations of Realistic Granular Soils Using PhysX Engine [View project](#)



Effectiveness of Geotextile/Geogrids in Roadway Construction; Determine a Granular Equivalent (G.E.) Factor [View project](#)



Technical Communication

Minimum image quality for reliable optical characterizations of soil particle shapes

Quan Sun^a, Junxing Zheng^{b,*}, Matthew R. Coop^c, Fatin N. Altuhafi^d^a Department of Civil, Construction and Environmental Engineering, Iowa State University, 403 Town Engineering Building, Ames, IA 50011, USA^b Department of Civil, Construction and Environmental Engineering, Iowa State University, 354 Town Engineering Building, Ames, IA 50011, USA^c Department of Civil, Environmental and Geomatic Engineering, UCL, Chadwick Building, Gower Street, London WC1E 6BT, United Kingdom^d Institute for Risk and Disaster Reduction, UCL, Kathleen Lonsdale Building, London WC1E 6BS, United Kingdom

ARTICLE INFO

Keywords:

Optical shape characterization
Granular soils
Image quality

ABSTRACT

Remarkable advances have been seen in image-based methods for automating soil particle shape characterizations in the last decade. However, the accuracy and reliability of image-based methods has rarely been questioned. This study shows that image quality affects the computational results of particle shape descriptors, including aspect ratio, sphericity, convexity, circularity, and roundness. These descriptors display a hierarchy of resistance to the effects of low image quality. The particle length, perimeter, and area are used as controlling parameters for quantifying the influence of image quality. The minimum requirements for ensuring reliable image-based shape characterization of these parameters are established.

1. Introduction

Particle shape is a fundamental property of granular soils. Angular and elongated particles create stronger inter-particle locking and larger coordination numbers. Therefore, they do not roll and slide as the more rounded and spherical particles. Experimental and numerical studies have shown that angular and elongated soils exhibit larger index void ratios, a larger angle of internal friction, larger dilatancy, a larger constant volume friction angle, larger compressibility, and a larger small-strain modulus than rounded and spherical soils [1,3,5,7,9,14,15,20,23,28,31,41,38,39].

Traditionally, the particle shape is measured through either manual measurement or visual comparison to reference charts [16,17,25]. The manual method is tedious and the chart method is subjective. Both methods are difficult to implement on a large number of particles [12].

Significant advances have been seen in image-based methods for automating particle shape measurements in the last two decades. A variety of imaging techniques have been developed and applied to particle shape analysis by geotechnical engineers ([6,8,10,19,18,21,22,24,29,30,35,42,36,37,40]; and many others), and a review of these techniques was provided by Hryciw et al. [11]. Commercial image-based particle shape analyzers, such as products from Malvern, the Sympatec QicPic, and the Camsizer, have also been used in geotechnical research [4,3,2].

Image-based methods significantly improve accuracy and efficiency

of particle shape characterizations compared to manual and visual methods. However, the reliability of image-based methods has rarely been questioned by geotechnical engineers. Whenever erroneous results are encountered by geotechnical engineers, they would rather attribute these results to the complexity and uncertainty of soil particles, not the computer. In fact, image-based methods are not always reliable and precise as they are affected by many factors.

The image quality is the most important factor and is also the most questioned factor. For example, a particle is captured under eight different resolutions with the particle lengths (L) in a range of 3350 pixels to 25 pixels in Fig. 1(a)–(h). The low quality image produces an aliasing effect at particle boundaries and the smaller and sharper corners are not delineated accurately. The computational geometry technique [37] has been used to determine Wadell's roundness, R [34]. The parameter R measures the sharpness of corners on the particle as illustrated in Table 1. The lower quality images, especially when L is smaller than 130 pixels, significantly change the particle boundaries and therefore overestimate R . When soil's R changes by 0.1 (the R ranges from 0 to 1), the predicted critical state friction angle will vary by as much as 1.7 degrees [9], and the peak friction angle could vary by 2.4 degrees [5]. Such large differences in soil strength parameters would profoundly affect geotechnical design and analysis, which demonstrates the importance of reliable particle shape characterizations.

As geotechnical engineers rely increasingly on image based soil particle shape characterization, the minimum accepted image quality

* Corresponding author.

E-mail addresses: quansun@iastate.edu (Q. Sun), junxing@iastate.edu (J. Zheng), m.coop@ucl.ac.uk (M.R. Coop), f.altuhafi@ucl.ac.uk (F.N. Altuhafi).




Fig. 1. Effects of image quality on particle shape analysis.

Table 1
Commonly used particle shape descriptors.

Descriptors	Formula	Note	Reference
Aspect ratio (Width-to-length ratio sphericity, elongation)	$AR = \frac{W}{L}$	The ratio of the width of the particle (W) to the length of particle (L).	Krumbein and Sloss [17]
Circle ratio sphericity	$S_C = \frac{D_{ins}}{D_{cir}}$	The ratio of the diameter of the largest inscribed circle of the particle (D_{ins}) to the smallest circumscribing circle of the particle (D_{cir}).	Santamarina and Cho [27]
Diameter sphericity	$S_D = \frac{D_e}{D_{cir}}$	The ratio of the diameter of a circle having the same area as the original particle (D_e) to the diameter of the minimum circumscribing circle (D_{cir}).	Wadell [34]
Area sphericity	$S_A = \frac{A}{A_{cir}}$	The ratio of the area of the particle (A) to the area of the smallest circumscribing circle (A_{cir}).	Riley [26]
Perimeter sphericity	$S_P = \frac{P_e}{P}$	The ratio of the perimeter of the circle having the same area as the particle (P_e) to the real perimeter of the particle (P).	Kuo and Freeman [18]
Circularity	$C = \frac{4\pi A}{P^2}$	The ratio of the area of the particle (A) to the area of the circle having the same perimeter as the particle ($P^2/4\pi$).	ISO [13]
Convexity(solidity)	$C_x = \frac{A}{A_c}$	The ratio of the area of the particle (A) to the area of the minimum convex boundary circumscribing the particle (A_c).	Mora and Kwan [22]
Roundness(angularity)	$R = \frac{\sum_{i=1}^N r_i / N}{r_{ins}}$	The ratio of the average radius of corner circles of the particles (r_i is the radius of i -th corner and N is the number of corners) to the radius of the maximum inscribed circle (r_{ins}).	Wadell [32-34]




Fig. 2. The reference particles (lengths of particles are 3350 pixels).

must be considered. However, existing studies using image based particle characterization rarely addressed this issue. Therefore, this study investigates the effects of image quality on computational results of commonly used particle shape descriptors in geotechnical engineering. Based on the results, minimum criteria for image quality that ensure

accuracy and reliability of particle shape analyses are established. This research is important and original as these minimum criteria can be used as a guideline for use and development of image-based soil particle characterization techniques by geotechnical engineers. In addition, numerous correlations between particle shape descriptors and the




Fig. 3. Effects of image qualities on the roundness computations.

macro-mechanical behavior of soils have been developed in the literature [1,3,5,7,9,20,28,41,38,39]. These minimum criteria will allow geotechnical engineers to obtain reliable particle shape characterizations, which are a prerequisite to use these correlations.

2. Commonly used particle shape descriptors and reference particles for analysis

A variety of parameters have been proposed for quantifying particle shapes from two-dimensional particle projections. Eight commonly used shape descriptors in geotechnical engineering are summarized in

Table 1. The numerical range of all these parameters is from 0 to 1. Some descriptors in **Table 1** may have different terminologies, while describing the same particle property, while in other cases the same descriptor may be defined in different ways. For example, the convexity is also called as solidity and sphericity has different definitions. Computations of the shape descriptors in **Table 1** involve the particle's area, perimeter, convex boundary, inscribed and circumscribing circles, width, and length. These parameters can each be determined by the computational geometry technique developed by Zheng and Hryciw [37]. In particular, the computational geometry technique can automatically identify corners on the particle perimeter and fit appropriate




Fig. 4. The relationships between particle shape characterizations and particle lengths.

circles to corners to determine roundness.

It is challenging to establish a minimum criterion of image quality for particle shape characterizations due to the complexity of soil

particles. The particle shape in an image may vary from very angular to well-rounded. Angular particles having complex surface structures require high resolution images to quantify, but rounded particles do not.

Table 2

The minimum criteria for ensuring reliable particle shape characterizations (units are pixels).

Shape descriptors		L_{\min}	P_{\min}	$\text{Sqrt}(A)_{\min}$	Hierarchy
Aspect ratio (AR)		25	100	25	Coarse descriptors
Circle ratio sphericity (S_C)					Evaluating principal dimensions of particles
Diameter sphericity (S_D)		100	350	75	Medium coarse descriptor
Area sphericity (S_A)					Related to areas of particles
Perimeter sphericity (S_P)		130	400	100	Fine descriptor
Circularity					Related to perimeter of particles
Convexity		250	900	200	Very fine descriptors
Roundness (R)	Very angular to angular ($0 < R < 0.17$)				Evaluating perimeters of particles
	Angular to rounded ($0.17 < R < 0.70$)	130	550	100	
	Rounded to well-rounded ($0.70 < R < 1.0$)	75	350	70	

The particle size in an image may vary over a wide range, and as a result, the same image resolution may be sufficient to delineate larger particles' shapes, but not smaller particles. Therefore, the minimum criteria must consider both particle size and shape.

To consider the effects of different particle shapes, this paper utilized twelve reference particles from the Powers' chart [25] as shown in Fig. 2. These particles include very angular to well-rounded and elongated to spherical shapes, which represent the typical particle shapes encountered in natural, crushed, and manufactured granular soils.

To consider the effects of particle sizes, the image quality is quantified using particle's length (L), perimeter (P), and area (A) in pixels, and not correlated to the physical dimensions of the particles. As such, the pixel-based minimum image quality criteria will be maintained regardless of the physical particle sizes. For example, if the minimum required particle length is 250 pixels for reliably characterizing roundnesses of angular particles, this criterion can be applied to all the particles with any sizes. If the actual particle size is 0.005 mm, a microscope may be required to capture this particle with a particle length of 250 pixels to meet the minimum image quality criterion. If the actual particle size is 50 mm, a cellphone camera may be adequate to capture this particle with a particle length of 250 pixels to meet the minimum image quality criterion.

3. Influence of image qualities on particle shape characterizations

The twelve particle projections in Fig. 2 have the same L of 3350 pixels, which represents high quality images. These particle projections are downscaled to generate new particle projections having L values of 1150, 800, 500, 250, 130, 100, 75, 50, 25, 15, and 8 pixels, which represent lower quality images. The computational geometry technique [37] was then used to compute the eight shape descriptors for each particle at different image qualities. The roundness computational results are shown in Fig. 3 (the results for $L = 1150$ pixels are not shown as they are identical to $L = 3350$ pixels). The R values are overestimated when image quality decreases because sharp and small corners of particles are missed.

The minimum L (L_{\min}) has been defined to ensure that the cumulative increases of particle shape descriptors are smaller than 2% relative to the overall measured range of that parameter for all of the particles. The typical measured range of R values of granular soils is from 0.1 to 1.0, so the L_{\min} is computed as 0.018, which is rounded to 0.20 as R values are usually reported in two decimals. The L_{\min} values are delineated as thick lines in Fig. 3. As shown, when the particles' L values are larger than L_{\min} , the image quality has a negligible impact on the R values. However, once the particles' L values are lower than L_{\min} , significant increases of the R values occur due to the changing of geometries of corners, so the image quality significantly affects the R computations. The L_{\min} establishes the minimum required particle length for particle roundness characterizations. As expected, angular

particles need larger L_{\min} values than rounded particles in Fig. 3. The results of Fig. 3 are summarized in Fig. 4(h).

The same computations were repeated for the remaining seven descriptors and all the results are shown in Fig. 4. When L decreases, the shape descriptors tend to increase (the convexity slightly decreases and then shows an inconsistent pattern of change below L_{\min}). Therefore, the shape descriptors will be overestimated at a lower resolution. The typical measured range of aspect ratio, sphericity descriptors and circularity of granular soils is around 0.5, and therefore the L_{\min} for these descriptors is $2\% \times 0.5 = 0.01$. The typical measured range of convexity of granular soils is around 0.1 and therefore the L_{\min} for convexity is $2\% \times 0.1 = 0.002$. These L_{\min} values are also plotted in Fig. 4. The L_{\min} values for elongated and spherical particles of most of the descriptors are very close, so they are not differentiated, as they have been for roundness.

Only relying on particle length may not be sufficient to define the minimum image quality because of the irregularity and complexity of soil particles. Therefore, we combine the particle's length, perimeter, and area together to establish the minimum image quality criterion. The relationships between eight shape descriptors and particle perimeter (P) and the square root of particle area ($\text{sqrt}(A)$) are plotted in Fig. 4. The P_{\min} and $\text{sqrt}(A)_{\min}$ are also defined similarly to the definition of L_{\min} and these values are superimposed on the figures. They again define cumulative increases of particle shape descriptors to be smaller than 2% of the overall measured range. Table 2 summarizes the minimum criteria (i.e., L_{\min} , P_{\min} , and $\text{sqrt}(A)_{\min}$) for image quality for different shape descriptors.

4. Hierarchy of shape descriptors for resistance to the effects of low image quality

Low image qualities significantly affect the curvilinearities of perimeters (or boundaries) of particles because severe aliasing effects occur, as shown in Fig. 1. Therefore, the very fine descriptors, R and convexity, that are directly evaluating curvilinearities of particle perimeters have poor resistance to the low image quality and require the largest L_{\min} , P_{\min} and $\text{sqrt}(A)_{\min}$ values among the investigated descriptors. The fine descriptors, S_P and circularity, are related to perimeters of particles, but not directly analyzing them. Therefore, these two descriptors require relatively less strict criteria of image quality.

Low image qualities have limited influences on the areas of particles. Therefore, the medium coarse descriptors, S_D and S_A , which are related to areas of particles, require loose criteria. Low image qualities have minor influences on the principal dimensions (length and width) of particles. Therefore, the coarse descriptors, AR and S_C , which evaluate principal dimensions, require the loosest criteria of image quality.

5. Conclusion

An analysis of common shape descriptors applied to standard particle images from Powers [25] has shown that the low image resolution relative to the particle size can have a severe influence on the values of the various parameters. The particle shape descriptors will generally tend to be overestimated for low resolution images, but different shape descriptors show different resistances to low image quality, allowing a hierarchy of descriptor to be defined. The particle length, perimeter, and area are used as controlling parameters for establishing the minimum image quality for ensuring reliable optical characterizations of particle shapes, ranging from aspect ratio at the coarsest level, through various sphericities in the intermediate range to convexity and roundness at the finest. While the values of minimum required resolution do not vary much between angular and rounded particles for most descriptors, for roundness there is a clear need for better resolution as the particles become more angular.

Acknowledgments

This material is based upon work supported by the U.S. National Science Foundation under Grant No. CMMI 1917332. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the authors and do not necessarily reflect the views of the National Science Foundation.

References

- [1] Alshibli KA, Cil MB. Influence of particle morphology on the friction and dilatancy of sand. *J Geotech Geoenviron Eng* 2018;144(3):04017118.
- [2] Altuhafi FN, Coop MR. Changes to particle characteristics associated with the compression of sands. *Géotechnique* 2011;61(6):459–71. Thomas Telford Ltd.
- [3] Altuhafi FN, Coop MR, Georgiannou VN. Effect of particle shape on the mechanical properties of natural sands. *J Geotech Geoenviron Eng* 2016;142(12):1–15.
- [4] Altuhafi F, O'Sullivan C, Cavarretta I. Analysis of an image-based method to quantify the size and shape of sand particles. *J Geotech Geoenviron Eng* 2013;139(8):1290–307. American Society of Civil Engineers (ASCE).
- [5] Bareither CA, Edil TB, Benson CH, Mickelson DM. Geological and physical factors affecting the friction angle of compacted sands. *J Geotech Geoenviron Eng* 2008;134(10):1476–89. American Society of Civil Engineers (ASCE).
- [6] Bowman ET, Soga K, Drummond W. Particle shape characterisation using Fourier descriptor analysis. *Géotechnique* 2001;51(6):545–54. Thomas Telford Ltd.
- [7] Cavarretta I, Coop M, O'Sullivan C. The influence of particle characteristics on the behaviour of coarse grained soils. *Géotechnique* 2010;60(6):413–23. Thomas Telford Ltd.
- [8] Chandan C, Sivakumar K, Masad E, Fletcher T. Application of imaging techniques to geometry analysis of aggregate particles. *J Comput Civil Eng* 2004;18(1):75–82. American Society of Civil Engineers (ASCE).
- [9] Cho G-C, Dodds J, Santamarina JC. Particle shape effects on packing density, stiffness, and strength: natural and crushed sands. *J Geotech Geoenviron Eng* 2006;132(5):591–602. American Society of Civil Engineers (ASCE).
- [10] Gélinas V, Vidal D. Determination of particle shape distribution of clay using an automated AFM image analysis method. *Powder Technol* 2010;203(2):254–64. Elsevier B.V.
- [11] Hryciw RD, Zheng J, Ohm H-S, Li J. Innovations in optical geotechnical characterization. *Geo-Congress 2014 Keynote Lectures*. American Society of Civil Engineers (ASCE); 2014.
- [12] Hryciw RD, Zheng J, Shetler K. Comparison of particle roundness and sphericity by traditional chart and computer methods. *J Geotech Geoenviron Eng* 2016;142(9):04016038.
- [13] ISO. ISO 9276-6: 2008: Representation of results of particle size analysis – Part 6: descriptive and quantitative representation of particle shape and morphology.
- [14] Jerves AX, Kawamoto RY, Andrade JE. Effects of grain morphology on critical state: a computational analysis. *Acta Geotech* 2016;11(3):493–503.
- [15] Kandasami R, Murthy T. Effect of particle shape on the mechanical response of a granular ensemble. *Geomechanics from Micro to Macro*. Informa UK Limited; 2014. p. 1093–8.
- [16] Krumbein WC. Measurement and geological significance of shape and roundness of sedimentary particles. *SEPM J Sediment Res Soc Sediment Geol* 1941;11.
- [17] Krumbein WC, Sloss LL. *Stratigraphy and sedimentation*. San Francisco: W.H. Freeman and Company; 1951.
- [18] Kuo C-Y, Freeman R. Imaging indices for quantification of shape, angularity, and surface texture of aggregates. *Transp Res Record: J Transp Res Board* 2000;1721:57–65.
- [19] Kuo C-Y, Frost J, Lai J, Wang L. Three-dimensional image analysis of aggregate particles from orthogonal projections. *Transp Res Record: J Transp Res Board* 1996;1526:98–103.
- [20] Liu X, Yang J. Shear wave velocity in sand: effect of grain shape. *Géotechnique* 2018;68(8):742–8. Thomas Telford Ltd.
- [21] Matsushima T, Katagiri J, Uesugi K, Tsuchiyama A, Nakano T. 3D shape characterization and image-based DEM simulation of the lunar soil simulant FJS-1. *J Aerosp Eng* 2009;22(1):15–23. American Society of Civil Engineers (ASCE).
- [22] Mora CF, Kwan AKH. Sphericity, shape factor, and convexity measurement of coarse aggregate for concrete using digital image processing. *Cem Concr Res* 2000;30(3):351–8.
- [23] Nouguier-Lehon C, Cambou B, Vincens E. Influence of particle shape and angularity on the behaviour of granular materials: a numerical analysis. *Int J Numer Anal Meth Geomech* 2003;27(14):1207–26.
- [24] Ohm H-S, Hryciw RD. Translucency segregation table test for sand and gravel particle size distribution. *Geotech Test J* 2013;36(4):20120221. ASTM International.
- [25] Powers MC. A new roundness scale for sedimentary particles. *SEPM J Sediment Res Soc Sediment Geol* 1953;23.
- [26] Riley NA. Projection sphericity. *SEPM J Sediment Res Soc Sediment Geol* 1941;11.
- [27] Santamarina JC, Cho GC. Soil behaviour: the role of particle shape. *Advances in Geotechnical Engineering: The Skempton Conference*. London: Thomas Telford, London; 2004. p. 604–17.
- [28] Shin H, Santamarina JC. Role of particle angularity on the mechanical behavior of granular mixtures. *J Geotech Geoenviron Eng* 2013;139(2):353–5. American Society of Civil Engineers (ASCE).
- [29] Sukumaran B, Ashmawy AK. Quantitative characterisation of the geometry of discrete particles. *Géotechnique* 2001;51(7):619–27.
- [30] Tafesse S, Fernlund JMR, Bergholm F. Digital sieving-Matlab based 3-D image analysis. *Eng Geol* 2012;137–138(2012):74–84.
- [31] Vangla P, Roy N, Gali ML. Image based shape characterization of granular materials and its effect on kinematics of particle motion. *Granular Matter* 2017;20(1). Springer Nature.
- [32] Wadell H. Volume, shape, and roundness of rock particles. *J Geol* 1932;40(5):443–51. University of Chicago Press.
- [33] Wadell H. Sphericity and roundness of rock particles. *J Geol* 1933;41(3):310–31. University of Chicago Press.
- [34] Wadell H. Volume, shape, and roundness of quartz particles. *J Geol* 1935;43(3):250–80. University of Chicago Press.
- [35] Wettimunay R, Penumadu D. Application of Fourier analysis to digital imaging for particle shape analysis. *J Comput Civ Eng* 2004;18(1):2–9. American Society of Civil Engineers (ASCE).
- [36] Zheng J, Hryciw RD. Soil particle size characterization by stereophotography. *Geotechnical Special Publication*; 2014.
- [37] Zheng J, Hryciw RD. Traditional soil particle sphericity, roundness and surface roughness by computational geometry. *Géotechnique* 2015;65(6):494–506.
- [38] Zheng J, Hryciw RD. Index void ratios of sands from their intrinsic properties. *J Geotech Geoenviron Eng* 2016;142(12):06016019.
- [39] Zheng J, Hryciw RD. Particulate material fabric characterization by rotational haar wavelet transform. *Comput Geotech* 2017;88:46–60.
- [40] Zheng J, Hryciw RD. Identification and Characterization of Particle Shapes from Images of Sand Assemblies Using Pattern Recognition. *J Comput Civil Eng* 2018;32(3).
- [41] Zheng J, Hryciw RD, Ventola A. Compressibility of sands of various geologic origins at pre-crushing stress levels. *Geol Geotech Eng* 2017;35(5):2037–51.
- [42] Zheng J, Hryciw R, Ohm H-S. Three-dimensional translucent segregation table (3D-TST) test for soil particle size and shape distribution. *Geomechanics from Micro to Macro*. Informa UK Limited; 2014.