
20. Artificial intelligence and behavioral geography

Paul M. Torrens

I pointed out that his copy of *Binary File Transfer Monthly* was possibly the most boring document I had ever seen in my life. (Coupland 1995: 167)

20.1. INTRODUCTION

Artificial intelligence (AI) and behavioral geography have long enjoyed a symbiotic relationship. While AI was initially viewed as a tool that geographers could use to automate their work, that vista is shifting. Indeed, many authors—among them, Thrift and French (2002), Graham (2005), and Stephenson (1993)—have suggested that AI has become an autonomous producer, of a sort, of *geography*. This new view, of AI creating and shaping geography, is profound, in its suggestion that we have somehow ceded geography-making to machines and software. In this chapter, I will make the argument that the geography-smithing capabilities of AI are perhaps set to have the most significant impact in behavioral geography. In this chapter, I will review the growing fusion between AI and behavioral geography, beginning in the 1980s, when it was hoped that AI would help geographers *do* geography with greater efficiency, speed, and accuracy, and when there was significant enthusiasm for the technology ahead of something of a retreat from the community's good graces in the 1990s and 2000s. From there, I will pivot the discussion to the early 21st century, when the development of AI took off against a backcloth of ubiquitous computing and matured consumer AI products that made use of spatial data and geographical context to ascribe intelligence to devices and software. I will also discuss a range of potential applications in which AI and behavioral geography are closely intertwined, in the milieu of machine and computer vision, virtual worlds, agent-based models, human-computer interaction, and cyber-physical systems. The motivation, in highlighting these applications of behavioral geography and AI over other uses, relates partially to my own vantage on the topic, as well as to near-future developments for AI and behavioral geography. This latter topic serves as the focus for concluding remarks.

20.2. BACKGROUND

The development of AI can be traced back to the very beginnings of the age of digital computers. Alan Turing was among the first to sketch the tableau for AI while outlining his ideas for intelligent machines. After years working on the problem of whether machines could be fashioned to compute, Turing (1936, 1938) posited the simple and provocative question of whether machines could think (Turing 1950). This set into motion decades of deliberation about what might be considered as intelligent in a machine, and how machine AI may compare with or contrast to human intelligence.

A first criterion for intelligence in AI generally wavers around a central idea that the machines involved should display human-like intelligence, or at least that they should do things that a human would regard as being intelligent (Simon 1977: 1059). (Indeed, the premise that the machine should convince a human interpreter of its intelligence was at the heart of the imitation game that Turing (1950) used as an allegory in his seminal paper.) A second, popular notion is that machine intelligence might be a moving benchmark (Kurzweil 1990: 12). Under this conceptualization, machines are envisaged with the capacity to grow more and more intelligent, advancing toward some future level of sophistication (usually referred to as a technological singularity; Ulam 1958) in which machines become self-aware, conscious, as intelligent as humans, more intelligent than humans, or some combination of these conditions that propels us into a post-human era (Vinge 1993). A third, perhaps interim, criterion between Turing's computers and civilization-running artificial minds (Banks 1996) is that AI should endow machines with the ability to do things that humans do (Simon 1977), albeit with tireless capacity and precision that human effort might lack. Under this consideration, AI assumes some of the attributes of intelligent automata (von Neumann 1951) or perhaps robots (Asimov 1941), with independence and automation factoring as important defining criteria.

20.3. ARTIFICIAL INTELLIGENCE AND 20TH CENTURY GEOGRAPHY

The potential for AI as a medium for automating human analytical tasks seems to have been the initial avenue through which geographers began to use AI. Initially, it was hoped that AI would energize geography by assuming the day-to-day tasks of geographical analysis that were amenable to automation: aspects of the geographer's job that took a long time, required duplication of effort, or were grand in their analytical burden. This view is well articulated in Dobson's (1983) paper on *automated geography*, in which he outlined scenarios in which computer cartography, geographic information systems (GIS), remote sensing, and visualization (which were then still relatively novel) could supplement manual techniques in geographic problem solving to bolster the scale and speed of analysis. (Interestingly, in the same paper, Dobson cautioned that a predominant focus on measurement and objects that were easily accessible to automation might sway geographers from "other important phenomena, such as the behavioral aspects of many problems"; Dobson 1983: 139.)

Smith's (1984) paper on the pertinence of AI for geographical problem solving introduced the important distinction between what he termed an engineering approach and a cognitive approach to using AI in geography. Indeed, in AI research (Brooks 1991), a similar distinction is often made between AI for computers and AI for thought. The engineering view of AI in geography considers machine intelligence in its most obvious form, as a set of *machine* procedures (usually algorithms and heuristics) that work to perform tasks. Image processing to unveil spatial patterns in data is a typical example of the engineering approach (Bernstein 1976). An alternative view, the cognitive approach, pitches AI in geography as a mimetic medium for representing *human* processes of intelligent tasks. Symbolic reasoning on spatial relationships or objects is perhaps best

representative of the cognitive approach to AI in geography as it was considered in the 1980s (Kuipers 1982).

Smith's characterization of the engineering approach to AI in geographical analysis echoes Dobson's assertions that AI might be productively used to automate many of the *things that geographers do*, such as interpretation, monitoring, planning, and translation (Smith 1984: 149). Referenced, in Smith's depiction, is the idea of AI as an expert system (Feigenbaum et al. 1971) that contains a corpus of domain knowledge as well as the functions to apply it to a given task, resembling perhaps how humans use their knowledge to inform their actions. Openshaw's "Geographical Analysis Machine" (Openshaw et al. 1987), for example, is an early example of the engineering approach to AI in geography, used to automate a battery of spatial analysis tasks by brute-force heuristic computing. Fisher et al. (1988) saw the potential use of AI, particularly expert systems and computer vision, in automating the interpretive tasks of geography relative to physical landscapes and phenomena. Estes et al. (1986) also discussed the idea of using AI as expert systems to automate exhaustive data searches over remotely sensed data, using heuristics relative to a knowledge base (a classification scheme, for example). Armstrong made a similar and salient point in arguing that computational science (which would include applied AI in most definitions) comes into particular usefulness when brought to bear on "problems that heretofore were either intractable, or, in some cases, unimagined" (Armstrong 2000: 146). Again, here, we see the argument that AI might leverage human talents for analysis, but that it would do so at scale, with the implication that new questions might be posed or that new insight might be gained beyond the reach of human operators.

Smith's discussion of AI in geography also invoked what Simon distinguished as *artificial thinking* (as distinct from AI), with the addendum that the machines involved would exhibit "similarity of process as well as similarity of product" (Simon 1977: 159). This argument bridges some of the gap between the engineering and cognitive approaches of AI. It is in the invocation of artificial thinking that we see the seeds of *AI and behavioral geography*, in which machines assume some of the analysis *abilities* of geographers, alongside their analysis tasks. In other words, there is an argument to be made that the types of problem solving (Newell and Simon 1972) that geographers engage in (and that machines could take on, or take over) might invoke behaviors that *are geographical*. Smith (1984) lists several examples—acquiring knowledge, organizing it, and reasoning relative to decisions—that we might regard as adjuring special geographic activities (Freudenschuh and Egenhofer 1997). For example, the ways in which we go about acquiring geographic information may be distinct relative to schemes for gathering other information types (Golledge 1978; Gould 1975). Similarly, geographic knowledge may be stored in the brain in physical structures that are special, such as dedicated place cells (Brun et al. 2002; O'Keefe et al. 1998), or in memory as cognitive and perceptual structures such as mental maps (Gould and White 1974; Vishton and Cutting 1995). Spatial decisions may be structured via criteria, such as spatial hierarchies, that diverge from other decisions (Clark 1993; Kuipers 2000). By extension, if machines could be programmed to mimic, replicate, or improve these human processes, then those machines might come to be regarded as intelligent geographical machines, in part by assuming spatial abilities to accomplish tasks.

In hindsight, the use of AI in geography took off quite successfully after the late 1980s, in large part owing to its usefulness in supporting GIS. Initially, at least, the introduction

of AI into geography met with some skepticism along a few significant lines of critique. Some in geography seemed to grapple with what AI could introduce to the field. At the time, the concept of AI might have seemed quite far afield from the topical pursuits of many geographers. For example, in a commentary on Smith's (1984) paper introducing AI to geography, Nystuen (1984: 359) remarked that, "AI programs take a great deal of expert intellectual effort and financial (computer) support. Few geographical problems command such attention . . . Smith should reflect on the resource realities of a small social science discipline like geography." Couclelis (1986: 2) at the time phrased, very well, another popular apprehension, rooted in "resistance to the underlying 'human computer' metaphor" that AI presented. Her argument, which is well taken, speaks to the perhaps lofty claims for AI in the 1970s and 1980s (Handler 2008; Lighthill 1972), which went as far as to suggest that AI might model the mind, mimic human thought, or teach machines to learn.

In the last 30–40 years, of course, computers and computing have become much more essential to the work that geographers do, particularly in facets of the discipline for which machines can automate routine tasks and in areas that allow geographers to do their work with greater reach, with more precision, and in less time than they would otherwise be able to accomplish (Dobson 1983). Along the same lines, as AI has been woven into the backcloth of our everyday lives and experiences (Dodge and Kitchin 2005) and into the things that we do to accomplish our research, our growing exposure to AI technology (and in some cases our inability to understand its artificiality) has diluted at least some of the skepticism and naysaying around its potential use. However, the automation of geography has never dodged controversy (Thrift and French 2002), and legitimate concerns still persist around differential access to computing, to the knowledge that it produces, and to the data that it invariably casts as a by-product of analysis trained on geographic behavior.

20.4. BEHAVIORAL GEOGRAPHY AND NEW WAVE AI

Many people now rely on AI to *do geography*, whether to accentuate their geographical thinking or to enhance (or to supplant) their spatial abilities with machines and software that are quicker, more thorough, safer, or often simply more usable than other media that they might use. As a result, AI has had ample opportunity to analyze and train upon humans' spatial behavior and its geographic context. The interactivity between AI and behavioral geography is upfront in some cases, as in use of in-dash navigation systems and software. In other arenas, the connection between AI and behavioral geography is much more subtle. For example, when one swipes a customer loyalty card at a point of purchase and is rewarded with a set of coupons, various types of AI are released to wash over the data that the behavior reveals or implies (space–time shopping rhythms, response to place-based marketing, location-based sensitivity to price, etc.) to merchants, marketers, and finance providers.

Still further threads, from behavioral geography to AI (and vice-versa), continue to unfurl as much of our personal, social, and commercial activity continues to be mediated by the Web. For example, as GIS and geocomputation moved to the Web, and as user behavior moved to browsers and then to Web-based social platforms, elements of the

geography that we had built for a world of desktop computing followed. On the Web, that geography took on new relevance to a range of AI-based classifiers, big data processing schemes, and ontology that was shaping the semantic web (Berners-Lee et al. 2001). In the early phases of the development of the Internet and the Web, geography had consistently lagged behind most innovations by a gap of 5–10 years, adopting these technologies and adding a “spatial spin” to them after a significant lag. That gap soon closed, however, and geography led the development of many of the innovations that characterized “Web 2.0” (the social and mobile Web), where a long tradition of spatial reasoning on symbols and knowledge domains that was well developed in behavioral geography and formalized in GIS could easily be ported to the new platforms (Couclelis and Golledge 1983).

Geography has almost concurrently turned out to be one of the most robust frameworks for adding structure to the massive streams and silos of unstructured data that many businesses and fields of study now manage. Much early work in geographic information science grappled with the problem of unifying spatial data across varying conceptualizations of geography, object types, scales of analysis, levels of uncertainty, tolerance for precision, and so forth. The work that geographers invested in uniting spatial data, a large portion of which was centered on human factors of data collection and use as well as behavioral factors (Dykes et al. 2005), produced very robust schemes for data-mining and knowledge discovery. A number of these schemes have taken on new relevance relative to big data, as reliable “glue” for binding disparate data fragments.

More recently, efforts to develop AI components of human-centered computing have begun to take on attributes of behavioral geography. Computers have shrunk in size and form factors, to the point that they are now routinely placed into the artifacts and substrate of our daily lives. The initial phase of this embedding centered on ubiquitous computing (Weiser 1991, 1993), in which computers became part of the fabric of *non-computational things*. Recently, however, ubiquitous computing has begun to spread to *us*, to people, with the result that computing is developed for both sides of interactions between the person and the things that we manipulate, use, value, pass by, and so on. These developments bring people’s use of computing into sharper focus around the medium in which the computing presents. For example, for wearable computers, there is now a need to understand locomotion and interactions between people and things, often relative to small spaces such as tabletops and the body itself (Zhang 2012). For mobile computing, there is renewed interest in motifs of human movement at urban and intra-urban scales, such as trips, paths, areas and points of interest, spaces of access and accessibility, and so on (Mishra et al. 2015; Sun et al. 2012). For urban computing, there is a strong connection to aspects of behavioral geography that relate to environmental cognition and the affordances that built spaces provide for activity and interaction (Zheng et al. 2014).

Increasingly, behavioral geography is also used to generate efficiencies in the actual informatics of AI. This is a very interesting turn, as it places behavioral geography in the center of efforts to enhance AI in computation, reversing the original vision of AI as a way to speed up routine human labor for geographical tasks. The most noticeable instantiation of behavioral geography’s influence in AI for informatics has been its use for crawling the huge troves of behaviorally indexed spatial data that are now cast by our interactions with each other, things, and events (Torrens 2010). In information search, behavioral geography is invoked by heuristics that leverage geographic-like behavior and strategies for browsing, crawling, indexing, relating, spanning, traversing, classifying, choosing,

structuring, deciding, and so on (Hjaltason and Samet 2003). In these ways, behavioral geography and AI are beginning to connect as cyberinfrastructure, as algorithms and heuristics for thinking and reasoning about information as it presents in computational spaces, network spaces, information spaces, and tangible spaces.

20.5. EXAMPLES OF BEHAVIORAL GEOGRAPHY AI

In this section, I will turn to discussion of how behavioral geography and AI have developed synergies in several key areas to a point in which they are largely coupled. In particular, developments in machine and computer vision, robotics, virtual worlds and virtual geographic environments, computer–human interaction, and cyber–physical systems are noteworthy examples that explain the significant synergy between AI and behavioral geography.

20.5.1. Machine and Computer Vision

The popular use of computer vision (Szeliski 2010) in devices and software has been particularly influential in allying behavioral geography and AI. Machine vision, i.e. the use of hardware imaging to provide visual “awareness” to devices, is going through many of the advantageous changes that catalyzed the proliferation of Geographic Positioning Systems (GPS) (Abler 1993). For example, high-resolution cameras are now relatively cheap to make and are small-sized, with the result that they may be embedded quite easily in a range of devices. The data that such cameras generate, which are often rapid in their supply and high resolution in their detail, are usually easily integrated with processors and software across diverse platforms, with the result that AI can be brought to bear quickly and efficiently on data as they are produced. For example, cameras on phones initially had little to do with the main use-scenario for the phone (voice telephony). However, when paired to the *platform* that the phone as a device affords (mobility, social networking, shopping, tagging encountered objects), cameras became a main feature, in part because the vistas they afforded could be allied to users’ general behavior on the device. Much of this behavior is geographical: using the camera to scan barcodes in particular places and time, tagging images with activities and place names, building overlapping vantages of points of interest as images are uploaded to photo-sharing silos, and so on. Mobile phones are often carried everywhere, piggy-backing on the user’s activity space, and so on-board positioning sensors can provide a relatively tireless and high-resolution location signal to dock that behavior across a variety of tangible spaces and cyberspaces. This docking is significant because it provides a pathway between real space and cyberspace, easing the potential formation of data shadows cast from behavior in one space to behavior in another space, or to many other spaces. When this docking takes place across millions of phones around the clock, individual behavioral geographies may be allied to broader profiles of behavior and behavioral geography, developed from aggregates of the data cast by the technology, with aggregation mediated by AI. For example, algorithms such as *Structure from Motion* (Koenderink and van Doorn 1991; Snavely et al. 2008) and *Scale-Invariant Feature Transform* (Lowe 2004) can use behavioral geography to build structure in (and across) image and positional data, often with minimal localization. There is also a

broad range of work in computer vision that analyzes the behavioral geography of people as they appear in images and video. These schemes are often based on recognition schemes that use behavioral geography alongside AI techniques such as hidden Markov models (Nguyen, Phung, Venkatesh, and Bui 2005) to quickly and exhaustively benchmark signals and patterns in images to a knowledge base that can tag those data to classes of behavior (tagged as states with associated confidence in a hidden Markov model, for example).

20.5.2. Robots

Turing's (1950) initial vision for intelligent machines kick-started decades of developing robotic machines (Matarić 2007). Much effort in robotics has focused on providing machines with behavioral geography, via AI. Behavioral geography is important for robots because they are required to sense the geography of their surroundings, to proactively plan for the geography that they encounter or might encounter, to move through space and time relative to often-complex ambient conditions and complicated instructional goals, and to engage in tasks that require human-like activities and abilities. Behavioral geography is particularly important in robot-motion planning (Latombe 1991), which requires that robots measure space and time relative to goals (Ferguson and Stentz 2007; Fujimura 1996), that they move (Latombe 1999), detect collisions (Mezouar and Chaumette 2002), avoid collisions (Badler et al. 1994), and coordinate their locomotion (Reynolds 1993).

Associations between robotics and behavioral geography are likely to grow closer. The access that AI-driven autonomous machines have to spatial data is now unprecedented, and in many arenas of their development, robotic machines can make use of big data, knowledge domains, semantics, data-mining, and computer vision advances to "be geographical" in incredibly sophisticated and life-like ways. For example, recently, there has been considerable work to develop mental mapping abilities in robotics, i.e. to develop robot understanding of encountered events and things in space and time, and to build knowledge bases from that understanding, either for a task at hand or for longer-term skill acquisition. These developments have been realized, popularly, in robotic products that make use of robot-generated maps to actuate and impel machines in the real world. Consider that we are now about to share our days with semi-autonomous cars that self-drive while also sensing and avoiding pedestrians (Thrun et al. 2006), and that we already have cause to dodge robotic vacuums that can map and navigate dirty floors (Jones 2006).

20.5.3. Virtual Worlds and Virtual Geographic Environments

Many geographies now present beyond the realm of the tangible, as information spaces (Mitchell 1995) and cyberspaces (Dodge and Kitchin 2000). In some cases, the virtual geography (Batty 1997) those digital spaces represent is mapped to real-world spaces, such that the virtual space manifests as an analog of a physical space (Shiode 2001). We might refer to these as virtual *worlds* because we can inhabit them, vicariously, as avatars (Bainbridge 2007; Rheingold 1993; The Economist 2006); or we might more specifically refer to them as virtual geographic environments (Lin et al. 2013, 2015). In the case of virtual geographic environments, there is often a deliberate emphasis on *faithfully* representing reality in digital, virtual form, so that the virtual environment is fashioned from real data that correspond to real places and spaces.

The question of how behavioral geography remains the same or differs when one moves from the tangible world to virtual geography looms large in research on virtual worlds (Spiers and Maguire 2006; Zyda 2005). Much work has been done to explore how people move (Crooks et al. 2009), judge distances (Thompson et al. 2004), mediate personal space (Bailenson et al. 2001), plan paths (Salomon et al. 2003), wayfind (Golledge et al. 1996), navigate (Richardson et al. 1999), interact (Lamarche and Donikian 2004), and build (Hudson-Smith 2002; Shiode and Torrens 2008) in virtual geographic settings. Because the spaces and geographies in virtual worlds are *digital*, it can often be relatively straightforward to extract plentiful and meaningful data directly from the world (El-Nasr et al. 2013); as models of things that have been constructed (Hudson-Smith 2002); as sequences of events, actions, reactions, and interactions (Thawonmas and Iizuka 2008; Wallner and Krigstein 2015); as movement paths (Kang et al. 2013); as mental maps (Torrens 2015a), and so on. Indeed, many benchmarks for massively multiplayer online worlds, role-playing games, and multiplayer online battle arenas rely on the behavioral geography of players and teams within the virtual setting (Pedersen et al. 2010). Similarly, many “serious games” are played out in virtual worlds as proxies for tangible forms of behavioral geography or as what-if experiments (Barnes et al. 2009; von Ahn 2006).

When real humans interact with each other in virtual worlds, we can make use of the digital manifestation of their behavioral geography to build a knowledge base, which can then be used to fashion AI representations of that behavior (Torrens 2007). This can be done through trial. In computer games, for example, game developers go through deliberative testing phases to build worlds and gameplay that entertain, that advance a story, that present challenges, and so on. In testing, the game designers often evaluate the behavioral geography that a particular virtual world or story or challenge produces, and they use analytics to code aspects of this geography into what is often termed “game engine AI,” i.e. the mechanics of the game behavior and phenomena that it supports (Baillie-deByl 2004; Champandard 2003; Millington 2006; Nareyek 2004). The use of AI from behavioral geography in gaming, in particular, is perhaps best reflected in recurring data structures for computer games. Examples include navigation graphs that map players to particular geographies of activity, interaction, and events in the game (Nieuwenhuisen et al. 2007; Sud et al. 2008), and around non-player characters (NPCs) that are often required to move, run away, give chase, and collaborate with realistic behavioral geography (Laird and van Lent 2001). Indeed, the fidelity of NPC behavioral geography is often a selling point of many commercial games (Cass 2002). In some cases, movement in gameplay is built directly from real-world data of human movement (Lee and Lee 2006). Indeed, machine learning of movement for virtual characters is increasingly sourced in real-world data from behavior in physical and social geographies (Lee et al. 2007; Torrens and Griffin 2013; Torrens et al. 2011, 2012). And locomotion data for avatar representations of human users and for NPCs in virtual worlds and games are increasingly built atop motion-capture data recorded from real people (Arikan and Forsyth 2002; Torrens 2014, 2015b).

20.5.4. Computer–Human Interaction

Behavioral geography and AI have recently become very closely intertwined in the realm of information geography, particularly in *information search* in and across databases. Spatial data access on databases has long mimicked aspects of behavioral geography

that pertain to how humans collect and collate data, particularly the human behaviors of abstraction, clustering, and hierarchy in sorting data, in organizing data for efficient access and recall, and in classifying data into knowledge bases (Samet et al. 2014). This functionality is commonly encountered on the Web, for example. Various pieces of your online behavior (queries with particular toponyms in them, searches with persistent address indices, goods purchased for delivery to home locations, and so on) may be referenced and composited by AI while you use the Web, to generate a likely location for you as a user (Fu et al. 2014; Lieberman et al. 2010; Samet et al. 2014). This location can be used to tailor content such as language (Lieberman and Samet 2012; Zhang and Gelernter 2014), maps (Samet et al. 2014), marketing (Rand and Rust 2011), and so on. For instances in which the information is being accessed via mobile devices, the AI may have direct access to the GPS hardware on a user's phone so that the location can be read rapidly and directly. As more and more AI-driven schemes for analyzing human interaction with databases develop, a growing corpus of semantic knowledge is developing around search and data technology. Indeed, there is a convincing argument to be made that a secondary, location-aware and location-enabled, instance of the web (and the "internet of things") is being formed around these technologies (Crampton et al. 2013; Zhang and Tsou 2009). Egenhofer (2002), for example, has suggested that a geosemantic web may have emerged, in which AI and behavioral geography have enabled the development of large and useful knowledge bases atop the substrate of web-based internet and communications technologies. Egenhofer's (2002) thesis regarding the geosemantic web echoes earlier arguments that he and Mark (Egenhofer and Mark 1995) made regarding the potential for GIS to build computer-based naïve geographies, as formal models of everyday geographic knowledge.

20.5.5. Cyber–physical Systems

It is worth noting that behavioral geography, AI, and machines are becoming coupled in new and innovative ways as cyber–physical systems. Cyber–physical systems are physical systems that rely in some large part on computing to determine their behavior. The term "cyber," in this context, relates to the thinking capabilities of the systems, which we usually delegate to AI. We might also consider people and things as elements of cyber–physical systems, with the inference that those systems may have opportunities (or cause, or leeway, or authority) to support our behavior, to supplement our behavior, or to supplant our behavior (Nechyba and Xu 1997).

In many instances, cyber–physical systems hold sway over our everyday lives, and mediate (perhaps even dictate) our behavioral geography across a wide range of activities. The emergence and proliferation of smart highways (Collier and Weiland 1994) and related intelligent transportation systems is a relatively recent and prominent development of cyber–physical systems that impacts behavioral geography. For example, some smart highways are designed to produce traffic-calming effects on travel, by linking data output from embedded sensors that monitor traffic volume and speed to behavioral models of expected driver reaction and knock-on effects that scale from individual road segments up to entire transportation networks (Cetin et al. 2002; Raney et al. 2003). Consider e-commerce platforms for ordering household goods as another example. Warehouses and store rooms are now almost overwhelmingly built and operated as cyber–physical

systems in which human users order goods by interfacing either directly or through some intermediary system with the storage facility's inventory databases (see Castells' (2001) detailed treatment of the global flow of information and material that makes this happen in the fashion industry, for example). Data access schemes are commonly used to match user demand (and estimated demand) to provider locations around the world, by modeling expected availability of components and products, relative to the rhythms and motifs of user buying habits and tastes in particular places and times (Chan et al. 2004). The logistics of how to assemble goods and components efficiently and cheaply can be determined using AI that models pricing behavior of merchants and suppliers, where economic geography often factors strongly in the determinative mechanisms, particularly when speed ("just in time") is a major pricing factor (Mair et al. 1988). Even within stores and warehouses, AI-driven robots are often deployed to search the geography of shelves and aisles to grab and ship items for delivery and packaging (Guizzo 2008). Once shipped, AI routines monitor traffic and fleet operations to determine delivery schedules and routes (Ran et al. 2012), relying on positioning systems (Liao 2003) as well as activity-based models of likely traffic patterns and reactions to traffic events (Crainic et al. 2009). For delivery drivers, in-car navigation systems provide trip directions, while also providing customers with updates regarding the goods' arrival timing and location of delivery on a given property (Skog and Händel 2009).

20.6. CONCLUSIONS

In this chapter, I have presented an overview of the origins of strong ties between AI and behavioral geography, as originally conjured in the 1980s, when computing was relatively novel to the geographical sciences. Since that period, computers have become much more closely intertwined with everything that we do, and as we have relied upon AI to accentuate our behavior, we have perhaps become more reliant on AI to do that for us, thereby begetting more dependence on and credence in AI. Nevertheless, the potential pitfalls of growing connectivity between behavioral geography and AI have not been masked from geographic inquiry.

Many of the technologies produced at the intersection of AI and behavioral geography have the potential to enrich our lives, by making things easier, cheaper, broadly accessible, and more usable. Many location-based services that assist us in our everyday tasks fall into this category. Others, such as predictive AI atop location-aware technologies in evolving smart homes (Marco et al. 2008), could help us in profound ways, by monitoring and mediating our behavioral geography as we age in place, for example. Yet the downside to continued and strengthening synergy between behavioral geography and AI is perhaps equally profound. As we offload important aspects of our behavioral geography to hardware, systems, and software, we risk sidelining important components of human expertise (see Chapters 7 and 11). Many in the geography community have also decried the loss of locational and activity privacy that has emerged as AI has grown more finely attuned to behavioral geography (Dobson and Fisher 2003). Others see the potential (and actual) pitfalls in ceding real access and real space to algorithms and heuristics that tag, like, price, and validate our lives (Curry 1997), while openly pondering why so many of us voluntarily "feed" AI big spoonfuls of our private data (Graham and Shelton 2013).

REFERENCES

Abler, R.F. (1993), Everything in its place: GPS, GIS, and geography in the 1990s, *The Professional Geographer*, **45** (2), 131–139.

Arikan, O. and D.A. Forsyth (2002), Interactive motion generation from examples, *ACM Transactions on Graphics*, **21** (3), 483–490.

Armstrong, M.P. (2000), Geography and computational science, *Annals of the Association of American Geographers*, **90** (1), 146–156.

Asimov, I. (1941), Liar!, *Astounding Science Fiction*, **XXVII** (May), 43–56.

Badler, N.I., R. Bindiganavale, J.P. Granieri, S. Wei and Z. Zhao (1994), Posture interpolation with collision avoidance, in *Proceedings of Computer Animation '94*, Geneva, May 25–28, IEEE, pp.13–20.

Bailenson, J., J. Blascovich, A. Beall and J. Loomis (2001), Equilibrium theory revisited: Mutual gaze and personal space in virtual environments, *Presence*, **10** (6), 583–598.

Baillie-deByl, P. (2004), *Programming Believable Characters for Computer Games*, Charles Hingham, MA: River Media.

Bainbridge, W.S. (2007), The scientific research potential of virtual worlds, *Science*, **317** (5837), 472–476.

Banks, I.M. (1996), *Excession*, London: Orbit.

Barnes, T., L.M. Encarnaçao and C.D. Shaw (2009), Serious games, *Computer Graphics and Applications*, **29** (2), 18–19.

Batty, M. (1997), Virtual geography, *Futures*, **29** (4), 337–352.

Berners-Lee, T., J. Hendler and O. Lassila (2001), The semantic Web, *Scientific American* **284** (5), 34–44.

Bernstein, R. (1976), Digital image processing of earth observation sensor data, *IBM Journal of Research and Development*, **20** (1), 40–57.

Brooks, R.A. (1991), Intelligence without representation, *Artificial Intelligence*, **47** (1–3), 139–159.

Brun, V.H., M.K. Otnass, S. Molden, H.-A. Steffenach, M.P. Witter, M.-B. Moser and E.I. Moser (2002), Place cells and place recognition maintained by direct entorhinal-hippocampal circuitry, *Science*, **296** (5576), 2243–2246.

Cass, S. (2002), Mind games: To beat the competition, video games are getting smarter, *IEEE Spectrum*, **39** (12), 40–44.

Castells, M. (2001), *The Internet Galaxy: Reflections on the Internet, Business, and Society*, New York: Oxford University Press.

Cetin, N., K. Nagel, B. Raney and A. Voellmy (2002), Large-scale multi-agent transportation simulations, *Computer Physics Communications*, **147** (1–2), 559–564.

Champandard, A. (2003), *AI Game Development: Synthetic Creatures with Learning and Reactive Behaviors*, Indianapolis, IN: New Riders.

Chan, L.M.A., Z.J.M. Shen, D. Simchi-Levi and J.L. Swann. (2004), Coordination of pricing and inventory decisions: A survey and classification, in D. Simchi-Levi, S.D. Wu and Z.-J. Shen (eds), *Handbook of Quantitative Supply Chain Analysis: Modeling in the E-Business Era*, Boston, MA: Springer, pp.335–392.

Clark, W.A.V. (1993), Search and choice in urban housing markets, in T. Gärling and R.G. Golledge (eds), *Behavior and Environment: Psychological and Geographical Approaches*, Amsterdam: Elsevier/North Holland, pp.298–316.

Collier, C.W. and R.J. Weiland (1994), Smart cars, smart highways, *IEEE Spectrum*, **31**, 27–33.

Couclelis, H. (1986), Artificial intelligence in geography: Conjectures on the shape of things to come, *The Professional Geographer*, **38** (1), 1–11.

Couclelis, H. and R.G. Golledge (1983), Analytic research, positivism, and behavioral geography, *Annals of the Association of American Geographers*, **73** (3), 331–339.

Coupland, D. (1995), *Microserfs*, New York: Reagan Books.

Crainic, T.G., N. Ricciardi and G. Storchi (2009), Models for evaluating and planning city logistics systems, *Transportation Science*, **43** (4), 432–454.

Crampton, J.W., M. Graham, A. Poorthuis, T. Shelton, M. Stephens, M.W. Wilson and M. Zook (2013), Beyond the geotag: Situating “big data” and leveraging the potential of the geoweb, *Cartography and Geographic Information Science*, **40** (2), 130–139.

Crooks, A., A. Hudson-Smith and J. Dearden (2009), Agent Street: An environment for exploring agent-based models in Second Life, *Journal of Artificial Societies and Social Simulation*, **12** (4), 10.

Curry, M. (1997), The digital individual and the private realm, *Annals of the Association of American Geographers*, **87** (4), 681–699.

Dobson, J.E. (1983), Automated geography, *The Professional Geographer*, **35** (2), 135–143.

Dobson, J.E. and P. Fisher (2003), Geoslavery, *IEEE Technology and Society Magazine*, **22** (1), 47–52.

Dodge, M. and R.M. Kitchin (2000), *Mapping Cyberspace*, Routledge, London.

Dodge, M. and R.M. Kitchin (2005), Code and the transduction of space, *Annals of the Association of American Geographers*, **95** (1), 162–180.

Dykes, J., A.M. MacEachran and M.-J. Kraak (2005), *Exploring Geovisualization*, London: Elsevier.

Egenhofer, M.J. (2002), Toward the semantic geospatial web, in K. Makki and N. Pissinou (eds), *The Tenth ACM International Symposium on Advances in Geographic Information Systems*, McLean, VA: ACM, pp. 1–4.

Egenhofer, M.J. and D.M. Mark (1995), Naive geography, in A.U. Frank and W. Kuhn (eds), *Spatial Information Theory: A Theoretical Basis for GIS*, International Conference COSIT '95 Semmering, Austria, September 21–23, 1995, Lecture Notes in Computer Science, Vol. 988, Berlin: Springer, pp. 1–15.

El-Nasr, M.S., A. Drachen and A. Canossa (2013), *Game Analytics: Maximizing the Value of Player Data*, New York: Springer Science & Business Media.

Estes, J.E., C. Sailer and L.R. Tinney (1986), Applications of artificial intelligence techniques to remote sensing, *The Professional Geographer*, **38** (2), 133–141.

Feigenbaum, E.A., B.G. Buchanan and J. Lederberg (1971), On generality and problem solving: A case study using the DENDRAL program, in B. Meltzer and D. Michie (eds), *Machine Intelligence 6*, Edinburgh: Edinburgh University Press, pp. 151–165.

Ferguson, D. and A. Stentz (2007), Field D*: An interpolation-based path planner and replanner, in S. Thrun, R. Brooks and H. Durrant-Whyte (eds), *Robotics Research*, Springer Tracts in Advanced Robotics, Vol. 28, Berlin: Springer, pp. 239–253.

Fisher, P.F., W. Mackaness, G. Peacegood and G. Wilkinson (1988), Artificial intelligence and expert systems in geodata processing, *Progress in Physical Geography*, **12** (3), 371–388.

Freudschuh, S.M. and M.J. Egenhofer (1997), Human conceptions of spaces: Implications for GIS, *Transactions in GIS*, **2** (4), 361–375.

Fu, C., H. Samet and J. Sankaranarayanan, J. (2014), WeiboStand: Capturing Chinese breaking news using Weibo tweets, in A. Pozdnoukhov and S. Xu (eds), *Proceedings of the 7th ACM SIGSPATIAL International Workshop on Location-Based Social Networks*, November 4, 2014, Berkeley, CA: ACM, pp. 41–48.

Fujimura, K. (1996), Path planning with multiple objectives, *IEEE Robotics & Automation Magazine*, **3** (1), 33–38.

Golledge, R.G. (1978), Representing, interpreting and using cognized environments, *Proceedings of the Regional Science Association*, **41** (1), 168–204.

Golledge, R.G., R. Klatzky and J. Loomis (1996), Cognitive mapping and wayfinding by adults without vision, in J. Portugali (ed.), *The Construction of Cognitive Maps*, Dordrecht: Kluwer Academic, pp. 215–246.

Gould, P. (1975), Acquiring spatial information, *Economic Geography*, **51** (2), 87–99.

Gould, P. and R. White (1974), *Mental Maps*, New York: Routledge.

Graham, M. and T. Shelton (2013), Geography and the future of big data, big data and the future of geography, *Dialogues in Human Geography*, **3** (3), 255–261.

Graham, S.N. (2005), Software-sorted geographies, *Progress in Human Geography*, **29** (5), 562–580.

Guizzo, E. (2008), Three engineers, hundreds of robots, one warehouse, *IEEE Spectrum*, **45** (7), 26–34.

Hendler, J. (2008), A letter from the editor: Avoiding another AI winter, *IEEE Intelligent Systems*, **23** (2), 2–4.

Hjaltason, G.R. and H. Samet (2003), Index-driven similarity search in metric spaces, *ACM Transactions on Database Systems*, **28** (4), 517–580.

Hudson-Smith, A. (2002), 30 days in active worlds, in R. Schroeder (ed.), *The Social Life of Avatars: Presence and Interaction in Shared Virtual Environments*, London: Springer, pp. 77–89.

Jones, J.L. (2006), Robots at the tipping point: The road to iRobot Roomba, *IEEE Robotics & Automation Magazine*, **13** (1), 76–78.

Kang, S.-J., Y.B. Kim, T. Park and C.-H. Kim (2013), Automatic player behavior analysis system using trajectory data in a massive multiplayer online game, *Multimedia Tools and Applications*, **66** (3), 383–404.

Koenderink, J.J. and A.J. van Doorn (1991), Affine structure from motion, *Journal of the Optical Society of America*, **8** (2), 377–385.

Kuipers, B. (1982), The “map in the head” metaphor, *Environment and Behavior*, **14** (2), 202–220.

Kuipers, B. (2000), The spatial semantic hierarchy, *Artificial Intelligence*, **119** (1–2), 191–233.

Kurzweil, R. (1990), *The Age of Intelligent Machines*, Cambridge, MA: MIT Press.

Laird, J.E. and M. van Lent (2001), Human-level AI's killer application: Interactive computer games, *AI Magazine*, **22** (2), 15.

Lamarche, F. and Donikian, S. (2004), Crowd of virtual humans: A new approach for real time navigation in complex and structured environments, *Computer Graphics Forum*, **23** (3), 509–518.

Latombe, J.-C. (1991), *Robot Motion Planning*, Norwell, MA: Kluwer Academic.

Latombe, J.-C. (1999), Motion planning: A journey of robots, molecules, digital actors, and other artifacts, *International Journal of Robotics Research*, **18** (11), 1119–1128.

Lee, J. and K.H. Lee (2006), Precomputing avatar behavior from human motion data, *Graphical Models*, **68** (2), 158–174.

Lee, K.H., M.G. Choi, Q. Hong and J. Lee (2007), Group behavior from video: A data-driven approach to crowd simulation, in M. Gleicher and D. Thalmann (eds), *ACM SIGGRAPH/Eurographics Symposium on Computer Animation*, San Diego, CA: Eurographics Association, pp. 109–118.

Liao, Z. (2003), Real-time taxi dispatching using global positioning systems, *Communications of the ACM*, **46** (5), 81–83.

Lieberman, M.D. and H. Samet (2012), Adaptive context features for toponym resolution in streaming news, in J. Callan, Y. Maarek and M. Sanderson (eds), *Proceedings of the 35th International ACM SIGIR Conference on Research and Development in Information Retrieval*, New York: ACM, pp. 731–740.

Lieberman, M.D., H. Samet and J. Sankaranayanan (2010), Geotagging: Using proximity, sibling, and prominence clues to understand comma groups, in R. Purves, C.B. Jones and P. Clough (eds), *Proceedings of the 6th Workshop on Geographic Information Retrieval*, New York: ACM, pp. 1–8.

Lighthill, J. (1972), Artificial Intelligence: A general survey, in J. Lighthill, N.S. Sutherland, R.M. Needham, H.C. Longuet-Higgins and D. Michie (eds), *Artificial Intelligence: A Paper Symposium*, London: Science Research Council of Great Britain, pp. 3–35.

Lin, H., M. Chen and G. Lu (2013), Virtual geographic environment: A workspace for computer-aided geographic experiments, *Annals of the Association of American Geographers*, **103** (3), 465–482.

Lin, H., M. Batty, S.E. Jørgensen, B. Fu, M. Konecny, A. Voinov, . . . M. Chen (2015), Virtual environments begin to embrace process-based geographic analysis, *Transactions in GIS*, **19** (4), 1–5.

Lowe, D. (2004), Distinctive image features from scale-invariant keypoints, *International Journal of Computer Vision*, **60** (2), 91–110.

Mair, A., R. Florida and M. Kenney (1988), The new geography of automobile production: Japanese transplants in North America, *Economic Geography*, **64** (4), 352–373.

Marco, A., R. Casas, J. Falco, H. Gracia, J.I. Artigas and A. Roy (2008), Location-based services for elderly and disabled people, *Computer Communications*, **31** (6), 1055–1066.

Matarić, M.J. (2007), *The Robotics Primer*, Cambridge, MA: MIT Press.

Mezouar, Y. and F. Chaumette (2002), Avoiding self-occlusions and preserving visibility by path planning in the image, *Robotics and Autonomous Systems*, **41** (2), 77–87.

Millington, I. (2006), *Artificial Intelligence for Games*, San Francisco, CA: Morgan Kauffman.

Mishra, S., T. Welch, P. Torrens, C. Fu, H. Zhu and E. Knaap (2015), A tool for measuring and visualizing connectivity of transit stop, route and transfer center in a multimodal transportation network, *Public Transport*, **7** (1), 77–99.

Mitchell, W.J. (1995), *City of Bits: Space, Place, and the Infobahn*, Cambridge, MA: The MIT Press.

Nareyek, A. (2004), AI in computer games, *Queue*, **1** (10), 58–65.

Nechyba, M.C. and Y. Xu (1997), Human control strategy: Abstraction, verification, and replication, *IEEE Control Systems*, **17** (5), 48–61.

Newell, A. and H.A. Simon (1972), *Human Problem Solving*, Englewood Cliffs, NJ: Prentice-Hall.

Nguyen, N.T., D.Q. Phung, S. Venkatesh and H. Bui (2005), Learning and detecting activities from movement trajectories using the hierarchical hidden markov models, in M. Hebert and D. Kriegman (eds), *2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05)*, San Diego, CA, June 20–25, 2005, San Diego, CA: IEEE Computer Society, pp. 955–960.

Nieuwenhuisen, D., A. Kamphuis and M.H. Overmars (2007), High quality navigation in computer games, *Science of Computer Programming*, **67** (1), 91–104.

Nystuen, J.D. (1984), Comment on “Artificial intelligence and its applicability to geographical problem solving”, *The Professional Geographer*, **36** (3), 358–359.

O’Keefe, J., N. Burgess, J.G. Donnett, K.J. Jeffery and E.A. Maguire (1998), Place cells, navigational accuracy, and the human hippocampus, *Philosophical Transactions of the Royal Society B: Biological Science*, **353** (1373), 1333–1340.

Openshaw, S., M.E. Charlton, C. Wymer and A. Craft (1987), A Mark 1 Geographical Analysis Machine for the automated analysis of point data sets, *International Journal of Geographic Information Systems*, **1** (4), 335–358.

Pedersen, C., J. Togelius and G.N. Yannakakis (2010), Modeling player experience for content creation, *IEEE Transactions on Computational Intelligence and AI in Games*, **2** (1), 54–67.

Ran, B., P.J. Jin, D. Boyce, T.Z. Qiu and Y. Cheng (2012), Perspectives on future transportation research: Impact of intelligent transportation system technologies on next-generation transportation modeling, *Journal of Intelligent Transportation Systems*, **16** (4), 226–242.

Rand, W. and R.T. Rust (2011), Agent-based modeling in marketing: Guidelines for rigor, *International Journal of Research in Marketing*, **28** (3), 181–193.

Raney, B., N. Cetin, A. Völlmy, M. Vrtic, K. Axhausen and K. Nagel (2003), An agent-based microsimulation model of Swiss travel: First results, *Networks and Spatial Economics*, **3** (1), 23–41.

Reynolds, C.W. (1993), An evolved, vision-based behavioral model of coordinated group motion, in J.-A. Meyer, H.L. Roitblat and S.W. Wilson (eds), *From Animals to Animats 2*, Cambridge, MA: The MIT Press, pp. 384–392.

Rheingold, H. (1993), *The Virtual Community: Homesteading on the Electronic Frontier*, Cambridge, MA: The MIT Press.

Richardson, A.E., D.R. Montello and M. Hegarty (1999), Spatial knowledge acquisition from maps and from navigation in real and virtual environments, *Memory & Cognition*, **27** (4), 741–750.

Salomon, B., M. Garber, M.C. Lin and D. Manocha (2003), Interactive navigation in complex environments using path planning, in *Proceedings of the 2003 Symposium on Interactive 3D Graphics, SI3D 2003*, April 28–30, 2003, Monterey, CA, Washington, DC: Association of Computing Machinery, pp. 41–50.

Samet, H., J. Sankaranarayanan, M.D. Lieberman, M.D. Adelfio, B.C. Fruin, J.M. Lotkowski, . . . B.E. Teitler (2014), Reading news with maps by exploiting spatial synonyms, *Communications of the ACM*, **57** (10), 64–77.

Shiode, N. (2001), 3D urban models: Recent developments in the digital modeling of urban environments in three-dimensions, *GeoJournal*, **52** (3), 263–269.

Shiode, N. and P.M. Torrens (2008), Comparing the growth dynamics of real and virtual cities, in K. Hornsby and M. Yuan (eds), *Understanding Dynamics of Geographic Domains*, Boca Raton, FL: CRC Press, pp. 187–203.

Simon, H.A. (1977), Artificial intelligence systems that understand, in the *Proceedings of the Fifth International Joint Conference on Artificial Intelligence*, Vol. 2, Cambridge, MA: Morgan Kaufmann, pp. 1059–1073.

Skog, I. and P. Händel (2009), In-car positioning and navigation technologies—A survey, *IEEE Transactions on Intelligent Transportation Systems*, **10** (1), 4–21.

Smith, T.R. (1984), Artificial intelligence and its applicability to geographical problem solving, *The Professional Geographer*, **36** (2), 147–158.

Snavely, N., S.M. Seitz and R. Szeliski (2008), Skeletal graphs for efficient structure from motion, in N. Ahuja and L. Shapiro (eds), *Proceedings of the 2008 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, Anchorage, AK, June 23–28, 2008, Anchorage, AK: IEEE, pp. 1–8.

Spiers, H.J. and E.A. Maguire (2006), Thoughts, behaviour, and brain dynamics during navigation in the real world, *Neuroimage*, **31** (4), 1826–1840.

Stephenson, N. (1993), *Snow Crash*, New York: Bantam Books.

Sud, A., E. Andersen, S. Curtis, M.C. Lin and D. Manocha (2008), Real-time path planning in dynamic virtual environments using multiagent navigation graphs, *IEEE Transactions on Visualization and Computer Graphics*, **14** (3), 526–538.

Sun, L., D.-H. Lee, A. Erath and X. Huang (2012), Using smart card data to extract passenger's spatio-temporal density and train's trajectory of MRT system, in O.E. Wolfson (ed.), *Proceedings of the ACM SIGKDD International Workshop on Urban Computing*, Beijing, August 12, 2012, New York: ACM, pp. 142–148.

Szeliski, R. (2010), *Computer Vision: Algorithms and Applications*, New York: Springer Science & Business Media.

Thawonmas, R. and K. Iizuka (2008), Visualization of online-game players based on their action behaviors, *International Journal of Computer Games Technology*, **5**, 1–9.

The Economist (Sep 8, 2006), Special Report: Virtual online worlds—Living a second life, *The Economist*, **380**, 98.

Thompson, W.B., P. Willemse, A.A. Gooch, S.H. Creem-Regehr, J.M. Loomis and A.C. Beall (2004), Does the quality of the computer graphics matter when judging distances in visually immersive environments? *Presence: Teleoperators and Virtual Environments*, **13** (5), 560–571.

Thrift, N. and S. French (2002), The automatic production of space, *Transactions of the Institute of British Geographers*, **27** (3), 309–335.

Thrun, S., M. Montemerlo, H. Dahlkamp, D. Stavens, A. Aron, J. Diebel, . . . P. Mahoney (2006), Stanley: The robot that won the DARPA Grand Challenge, *Journal of Field Robotics*, **23** (9), 661–692.

Torrens, P.M. (2007), Behavioral intelligence for geospatial agents in urban environments, in T.Y. Lin, J.M. Bradshaw, M. Klusch and C. Zhang (eds), *IEEE Intelligent Agent Technology (IAT 2007)*, Los Alamitos, CA: IEEE, pp. 63–66.

Torrens, P.M. (2010), Geography and computational social science, *GeoJournal*, **75** (2), 133–148.

Torrens, P.M. (2014), High-fidelity behaviours for model people on model streetscapes, *Annals of GIS*, **20** (3), 139–157.

Torrens, P.M. (2015a), Exploring behavioral regions in agents' mental maps, *The Annals of Regional Science*, **57** (2–3), 1–26.

Torrens, P.M. (2015b), Geographical agents in three dimensions, in A. Singleton and C. Brunsdon (eds), *Geocomputation: A Practical Primer*, London: Sage, pp. 40–62.

Torrens, P.M. and W.A. Griffin (2013), Exploring the micro-social geography of children's interactions in preschool: A long-term observational study and analysis using geographic information technologies, *Environment and Behavior*, **45** (5), 584–614.

Torrens, P.M., X. Li and W.A. Griffin (2011), Building agent-based walking models by machine-learning on diverse databases of space-time trajectory samples, *Transactions in Geographic Information Science*, **15** (suppl. 1), 67–94.

Torrens, P.M., A. Nara, X. Li, H. Zhu, W.A. Griffin and S.B. Brown (2012), An extensible simulation environment and movement metrics for testing walking behavior in agent-based models, *Computers, Environment and Urban Systems*, **36** (1), 1–17.

Turing, A.M. (1936), On computable numbers, with an application to the Entscheidungsproblem, *Proceedings of the London Mathematical Society*, **2** (1), 230–265.

Turing, A.M. (1938), On computable numbers, with an application to the Entscheidungsproblem: A correction, *Proceedings of the London Mathematical Society*, **2** (1), 544–546.

Turing, A.M. (1950), Computing machinery and intelligence, *Mind*, **59** (236), 433–460.

Ulam, S. (1958), Tribute to John von Neumann, *Bulletin of the American Mathematical Society*, **64** (3), 1–49.

Vinge, V. (1993), The coming technological singularity: How to survive in the post-human era, in *VISION-21 Symposium*, March 30–31, 1993, Cleveland, OH: NASA Lewis Research Center/Ohio Aerospace Institute.

Vishhton, P.M. and J.E. Cutting (1995), Wayfinding, displacements, and mental maps: Velocity fields are not typically used to determine one's aimpoint, *Journal of Experimental Psychology*, **21** (5), 978–995.

von Ahn, L. (2006), Games with a purpose, *Computer*, **39** (6), 92–94.

von Neumann, J. (1951), The general and logical theory of automata, in L.A. Jeffress (ed.), *Cerebral Mechanisms in Behavior*, New York: Wiley, pp. 1–41.

Wallner, G. and S. Kruglstein (2015), Comparative visualization of player behavior for serious game analytics, in S.C. Loh, Y. Sheng and D. Ifenthaler (eds), *Serious Games Analytics: Methodologies for Performance Measurement, Assessment, and Improvement*, New York: Springer International, pp. 159–179.

Weiser, M. (1991), The computer for the 21st century, *Scientific American*, **265** (3), 94–104.

Weiser, M. (1993), Some computer science problems in ubiquitous computing, *Communications of the ACM*, **36** (7), 75–84.

Zhang, T. and M.-H. Tsou (2009), Developing a grid-enabled spatial Web portal for Internet GIServices and geospatial cyberinfrastructure, *International Journal of Geographic Information Science*, **23** (5), 605–630.

Zhang, W. and J. Gelerner (2014), Geocoding location expressions in Twitter messages: A preference learning method, *Journal of Spatial Information Science*, **2014** (9), 37–70.

Zhang, Z. (2012), Microsoft Kinect sensor and its effect, *IEEE MultiMedia*, **19** (2), 4–10.

Zheng, Y., L. Capra, O. Wolfson and H. Yang (2014), Urban computing: Concepts, methodologies, and applications, *ACM Transactions on Intelligent Systems and Technology (TIST)*, **5** (3), 38.

Zyda, M. (2005), From visual simulation to virtual reality to games, *Computer*, **38** (9), 25–33.