

A Virtual-Reality-Based Training and Assessment System for Bridge Inspectors With an Assistant Drone

Yu Li , Muhammad Monjurul Karim , and Ruwen Qin , *Member, IEEE*

Abstract—Over 600 000 bridges in the U.S. must be inspected every two years to identify flaws, defects, or potential problems that may need follow-up maintenance. Bridge inspection has adopted unmanned aerial vehicles (or drones) for improving safety, efficiency, and cost-effectiveness. Although drones can operate in an autonomous mode, keeping inspectors in the loop is critical for complex tasks in bridge inspection. Therefore, inspectors need to develop the skill and confidence to operate drones in their jobs. This article presents the design and development of a virtual-reality-based training and assessment system for inspectors assisted by a drone in bridge inspection. The system is composed of four integrated modules: a simulated bridge inspection developed in Unity, an interface that allows a trainee to operate the drone in simulation using a remote controller, data monitoring and analysis to provide real-time in-task feedback to trainees to assist their learning, and a post-study assessment supporting personalized training. This article also conducts a proof-of-concept pilot study to illustrate the functionality of this system. The study demonstrated that the training and assessment system for bridge inspection with an assistant drone, as a tool for the early-stage training, can objectively identify the training needs of individuals in detail and, further, help them develop the skill and confidence in collaborating with a drone in bridge inspection. The system has built a modeling and analysis platform for exploring advanced solutions to the human–drone cooperative inspection of civil infrastructure.

Index Terms—Human in the loop, infrastructure inspection, performance assessment, sensing, training, unmanned aerial vehicle, virtual reality (VR).

I. INTRODUCTION

THE U.S. Highway Bridge Inventory has approximately 617 000 bridges. 42% of them are over 50 years old, and 7.5% are structurally deficient [1]. To avoid catastrophic incidents, all bridges are required to be inspected every two years for identifying flaws, defects, or potential problems that may need follow-up maintenance. Traditional bridge inspection may

require closing the traffic and the use of heavy equipment such as a snooper truck. Inspecting a bridge needs a crew of inspectors working at the site for many hours. Some field operations are dangerous, such as climbing up to high bridge columns.

To make bridge inspection safer, faster, cheaper, and less interruptive to the traffic, unmanned aerial vehicles or drones have been adopted for use. A drone can conveniently access various locations of a bridge to capture a large amount of inspection data efficiently using sensors that it carries, such as RGB cameras and infrared cameras. Bridge inspectors can collect bridge inspection data using a drone if they have a license issued by the Federal Aviation Administration (FAA) and a waiver of the regulation “keeping the drone within visual line of sight” in FAA’s Small UAS (Part 107) Regulations. Then, inspectors will bring the data back to their offices and analyze the data with the assistance of machine learning algorithms [2]. The use of drones for data collection also minimizes the traffic closure and the use of heavy expensive equipment. A survey conducted by the American Association of State Highway and Transportation Officials shows that using drones for bridge inspection can reduce the cost by 74% [3]. Besides bridges, other low-accessible infrastructures have also been adopting drones for inspection, such as dams and penstocks [4], transmission lines [5], and railways [6].

Current studies on the bridge inspection with an assistant drone mainly focus on the drone technology (see, e.g., [7]) and data analysis using image processing and computer vision (see, e.g., [2]). The human factors aspect is largely ignored. The use of drones for bridge inspection is not to eliminate bridge inspectors but to augment their ability [8]. Although a drone can fly in the autonomous mode by following a pre-planned path, keeping human in the loop will enhance the safety, efficiency, and effectiveness of bridge inspection. There are various situations that the inspector needs to disengage the autonomous mode and take control of the drone. For example, if the inspector identifies a severe concern with a certain spot of the bridge during the inspection, the inspector can temporarily pause the autonomous mode to collect desired data around that spot. After that, the autonomous mode can be resumed to continue the planned inspection. In response to an alarming situation or a suddenly emerging need anticipated by the inspector or an artificial intelligence model, the inspector may also have to take control of the drone [9].

Training is essential to help inspectors gain and retain the skill and confidence in inspecting bridges with an assistant drone. Training inspectors to collect data using an assistant drone should take place progressively in multiple stages. Like

Manuscript received June 29, 2021; revised November 12, 2021 and February 4, 2022; accepted February 20, 2022. Date of publication March 25, 2022; date of current version July 14, 2022. This work was supported by the National Science Foundation under Grant ECCS-2026357 and Grant CMMI-1646162. This article was recommended by Associate Editor Matthew L. Bolton. (Corresponding author: Ruwen Qin.)

The authors are with the Department of Civil Engineering, Stony Brook University, Stony Brook, NY 11794 USA (e-mail: yu.li.5@stonybrook.edu; muhammadmonjur.karim@stonybrook.edu; ruwen.qin@stonybrook.edu).

This work involved human subjects or animals in its research. Approval of all ethical and experimental procedures and protocols was granted by Stony Brook University IRB under Application No. IRB2021-0019.

Color versions of one or more figures in this article are available at <https://doi.org/10.1109/THMS.2022.3155373>.

Digital Object Identifier 10.1109/THMS.2022.3155373

aviation training systems or driving simulators, a virtual reality (VR)-based training and assessment system is a cost-effective tool for the early-stage training. After that, inspectors can move to the augmented-reality-based training that uses either a virtual drone at a real inspection site or a real drone in a virtual inspection scene. Ultimately, the training will be at a real bridge site with a real drone. VR-based training systems have been developed for civil engineers in pipe maintenance [10], bridge construction process [11], and bridge crane operation [12]. Some commercial drone flight simulators have been developed as well. For example, AeroSim Drone Simulator [13] offers training scenarios of inspecting wind turbines, power lines, towers, and solar panels. Moud *et al.* [14] also developed a first-ever drone flight simulator for construction sites. To our best knowledge, no simulator has been developed for inspector–drone cooperative bridge inspection, nor a data-driven framework for assessing the training performance of bridge inspectors.

A dedicated simulator is required for training bridge inspectors to operate a drone in their jobs. Commercial drone simulators are not tailored toward the need for training bridge inspectors, according to our discussions with researchers in human factors and a center for training inspectors. Some unique features of bridge inspection differentiate it from other types of inspection, such as the traffic passing the bridge, complex and diverse structures, and narrow irregular spaces between structural elements, such as diaphragms and interlayers. Moreover, factors that may impact the drone-assisted bridge inspection are broad, including job-site-related, drone-related, task-related, and human-related factors. However, commercial drone simulators only considered some of those, such as the wind speed and direction, battery level, and task difficulty level (see, e.g., [13]–[16]). The skill and confidence developed using simulators for inspecting other types of infrastructure are not transferred to the bridge inspection effectively.

A dedicated assessment method for training bridge inspectors is also desired. The assessment utilizes the data captured from the simulation training to measure inspectors' performance using specially designed metrics. The stakeholder of the training system usually would like to set a baseline for rating inspectors' overall performance in utilizing an assistant drone as excellent, good, acceptable, and others, for example. Without well-defined performance metrics, the baseline is difficult to determine objectively. Feedback to inspectors, both in-training and post-training, helps accelerate their learning processes. Effective feedback to an inspector should be built on measurements of the inspector's tasks performance and human states (e.g., cognitive load, physical load, emotion, and other psychological states). The measurements are from multiple dimensions, including time, quality, productivity, safety, cost, and others. Commercial drone simulators do not include a module that provides desired measures and metrics for monitoring and assessing bridge inspectors in training. While task performance measurements have been studied widely in operations management [17], many metrics are output-based, such as the completion time and productivity, not applicable to providing in-task feedback. The evaluation of task performance and human states can be performed by subjects themselves, peers, or evaluators. However, subjective

judgment lacks reliability, timeliness, and accuracy. Despite these limitations, subjective evaluation is still often used due to the low cost and the ease of implementation. The NASA Task Load Index [18] is a questionnaire commonly used by pilots for reporting their physical demand, time pressure, effort, performance, mental demand, and frustration level [15], [19].

Filling gaps in the literature, contributions of this article are twofold:

- 1) the design and development of a VR-based training and assessment system for bridge inspection with an assistant drone (TASBID);
- 2) a data-driven method with unique measures and metrics for analyzing and understanding inspectors' needs for training and assistance.

The source code of TASBID is publicly available for download at Github [20]. The rest of this article is organized as follows. Section II presents the proposed system. Section III exhibits the functionality of the system using a small-scale pilot study. Finally, Section IV concludes this article.

II. TRAINING AND ASSESSMENT SYSTEM

The architecture of the TASBID is illustrated in Fig. 1. The system is designed to consist of four modules: 1) the bridge inspection simulation; 2) an interface that allows the bridge inspector (the trainee) to operate the drone in the simulated inspection; 3) monitoring and data analysis; and 4) the post-study assessment. The trainee, who could be equipped with biometric sensors, operates the drone in the simulated inspection using a remote controller. Streaming data of the inspector and the drone are monitored to provide real-time in-task feedback to the inspector. The data on job specifications, the bridge, and the site are references for monitoring and analysis. Upon completing a training, a comprehensive assessment based on the collected data is performed to provide both the required information for designing an individualized training plan and the post-study feedback to the trainee. The four modules are discussed in detail in the following.

A. Simulated Bridge Inspection

The inspection simulation created in Unity is illustrated in Fig. 1. The simulation provides the trainee with the visual stimulus of drone-assisted bridge inspection. To assure that it is close to the real-world work context, the simulation is designed to include five major elements of bridge inspection: the ground team, the drone, bridges, the job site, and example tasks.

1) *Ground Team*: The ground team in the simulation comprises an inspector (the virtual counterpart of the trainee) and a truck. The simulation defines the location of the ground team where the drone takes off and returns to. The simulation provides two views side by side on the screen to the trainee. The left is the inspector's view at the site, and the right is the camera's view from the drone. During the simulation training, the trainee can switch her/his gazes between the two views to focus on the most useful one. For example, the inspector's view can be useful during taking-off and landing. The camera's view is what




Fig. 1. Architecture of the TASBID.

the trainee would concentrate on during the inspection and for the visual navigation.

2) *Drone*: The simulation adopts a drone simulation model from a Unity drone controller asset [21] and revises it for the bridge inspection. Parameters for modeling the drone include the drone model, mass and load, movement force, maximum forward speed, maximum sideward speed, rotation speed, slow-down time, movement sound, propellers' rotation, battery capacity, and movement types. In this simulation, eight types of movement are sufficient for the bridge inspection. They are forward and backward, right-sideward and left-sideward, up and down, and right-rotation and left-rotation. The trainee controls the movement, rotation, and speed of the drone using the remote controller. The battery level is a dynamic constraint for the drone operation, which drops gradually during the inspection. This simulation does not include the return-to-home function that can bring the drone to the home point when the battery level drops to a prespecified level. Instead, the battery level is displayed for examining the trainee's time stress. The drone has a snapshot function that the inspector can straightforwardly use to label an event on the timeline of the inspection video. Later, the inspector can retrieve and review the labeled frames. The snapshot function is also a simple way of confirming the inspector's visual attention to an area of concern.

3) *Bridges*: The simulation uses a Unity asset named Road Architect [22] to create the bridge models, wherein multiple types of bridges are available for choice and redesign. The simulation includes an arch bridge and a suspension bridge to provide trainees with different experiences in training. For example, the arch bridge in the simulation has cramped spaces, where controlling the drone is challenging to the trainee. Road

Architect defines the structural elements of the bridges. Accordingly, the spatial-temporal relationship between the drone and specific bridge elements during the simulated inspection can be determined. Defects, such as cracks, are added to the surface of some bridge elements to assess the trainee's situational awareness during the inspection.

4) *Job Site*: Simulation of the bridge inspection site focuses on creating the geographic context, the environmental condition, and the traffic condition at the bridges. Bridges to be inspected sit on a lake in a mountain area. Bridge inspection needs to be conducted in the daytime with clear weather although a sudden change in the weather may occur in rare cases. Therefore, only wind under level 5 of the Beaufort Wind Scale has been considered as a possible weather impact in the system. The wind factor is simulated by adding the force value and direction in Unity. Since most commercial drones can be flown in the wind between 10 and 30 mi/h, TASBID considers three levels of wind: light, gentle, and medium. They correspond to the wind speed around 2, 11, and 22 mi/h and cause the force of 0.12, 3, and 12 N, respectively. A 3-D vector can set up the wind direction. Lighting condition is another common factor impacting the inspection. To create a more realistic lighting condition, the simulation turns on the Global Illumination in Unity to simulate the light reflected from the water surface. Some dark areas of bridges, such as the bridge bottom, are still present although the natural lighting is good. TASBID is designed to include tasks that inspect dark areas of bridges. The drone in the simulation is equipped with a light. Trainees can turn it ON or OFF according to their needs by pressing "B" on the keyboard. Traffic volume is modeled as well because inspectors may feel pressure when flying the drone near the traffic. Vehicles moving on the bridges are included

in TASBID using a free traffic simulation asset [23]. The total number of vehicles can be increased or decreased as desired.

5) *Inspection Tasks*: Tasks selected for the simulation training must capture representative scenarios of the real-world inspection. TASBID includes four tasks that have various shapes of inspection paths (e.g., a long straight line versus multiple short lines, and a large curve versus a small circle), types of accessible space (spacious and narrow), lighting conditions (bright versus dark), and various levels of complexity in controlling the drone (gross versus fine control, and movement versus rotation control).

- 1) Task 1 is to inspect the slab of the arch bridge from one side. The accessible space is spacious, and the lighting condition usually is not a concern. The recommended inspection path for this task is a straight line along one side of the bridge. The trainee controls the drone and moves it along the slab from one end to another end of the bridge.
- 2) Task 2 is to inspect the bridge bottom. The accessible space is spacious, but the lighting condition might not be ideal. The trainee needs to adjust the drone's position frequently when moving it along the arch-shaped bridge bottom.
- 3) Task 3 is to inspect the interlayer of the arch bridge in a narrow space, and the lighting condition might not be ideal. The trainee needs to delicately control the movement and rotation of the drone to capture both the upper side and the down side of the interlayer area safely.
- 4) Task 4 is to inspect the corrosion situation of the suspension bridge at a pier. The path for the drone is a circle with a small radius near the water surface. The trainee needs to rotate the drone when moving around the pier frequently.

The task sequence presented above is just a recommendation. The trainee can plan and decide the sequence of tasks.

B. Interface Between the Trainee and the Drone

The trainee operates the drone in the simulated inspection using a remote controller. Currently, TASBID uses a Phantom 2 DJI controller for this purpose. The controller is connected to Unity using the vJoy device driver [24] and the method in mDjiController [25]. The trainee adjusts the joysticks of the controller to control the movement, rotation, and speed of the drone. The trainee's operations of the drone are recorded as time series data.

C. Monitoring and Data Analysis

TASBID can collect six types of data from the study, as illustrated in Fig. 1. The work site characteristics, the bridge models, the drone model, and job specifications are prespecified data that do not change during a study. The flight data of the drone and the trainee's operation data are the frame-level streaming data that vary in each time of the study.

1) *Streaming Data*: A simulated inspection is captured by a sequence of N frames, indexed by i . Given the fixed frame rate, f , the total duration of an inspection is N/f . The starting frame is defined as the time when the drone is taking off. The ending frame corresponds to the time when the drone lands near the ground team or it cannot continue to finish the inspection

(e.g., the battery drains or the drone crashes into the traffic), whichever occurs the first. Let O_i and D_i denote the trainee's operation data and the drone flight data, respectively, collected at any frame i .

The trainee operates the remote controller that has four-axis inputs for controlling the movement, rotation, and speed of the drone. Besides, the trainee can press "B" on the keyboard to turn ON/OFF the light and "P" to take "snapshots" during the inspection. Therefore, the trainee's operation data are time-series data in six dimensions:

$$O_i = [o_{fb,i}, o_{rl,i}, o_{ud,i}, o_{rt,i}, o_{b,i}, o_{p,i}] \quad (1)$$

where

$o_{fb,i}$ forward (+) and backward (-);
 $o_{rl,i}$ right (+) and left (-) sideward;
 $o_{ud,i}$ up (+) and down (-);
 $o_{rt,i}$ right (+) and left (-) rotation;
 $o_{b,i}$ turning ON (1) and OFF (0) the light;
 $o_{p,i}$ taking a snapshot (1) and not (0).

The drone flight data include the position, velocity, and the remaining battery level of the drone

$$D_i = [\mathcal{L}_i, v_i, b_i] = [l_{x,i}, l_{y,i}, l_{z,i}, v_i, b_i] \quad (2)$$

where $\mathcal{L}_i = (l_{x,i}, l_{y,i}, l_{z,i})$ are the 3-D coordinates of the drone's location in the earth reference system, v_i is the linear speed of drone, and b_i is the remaining battery level in percentage.

2) *On-Path Analysis*: Although the drone has the gimbal and zoom functions to make the data collection more flexible, the flexibility is bounded. Therefore, the inspector's ability to send the assistant drone to suitable locations is still critical to obtaining desired inspection data in desired quality. For the training purpose, TASBID recommends reference paths appropriate for performing individual tasks, but not for the entire job, to the trainee. Let t be the index of tasks and n be the index of reference points. $\{t, n | n = 1, \dots, N_t\}$ defines the reference flying path for the drone in task t .

Denote $X_{t,i}$ as the binary variable indicating if the drone in frame i is on the reference path of task t , for any t and i . $\sum_{t=1}^T X_{t,i} \leq 1$ for any i , indicating that the drone cannot be on more than one task simultaneously. Using Algorithm 1, the analysis module evaluates if the drone is on the reference path for task t . Specifically, the algorithm uses the reference path of task t and the location of the drone as inputs to determine the value of the binary variable $X_{t,i}$.

Using the outputs of Algorithm 1, the starting frame of task t , $I_{t,s}$, and the ending frame, $I_{t,e}$, are determined accordingly. The analysis module treats the first frame when $X_{t,i}$ is one as the starting frame for task t and the last frame when $X_{t,i}$ is one as the ending frame:

$$I_{t,s} = \min_i \{i | X_{t,i} = 1\}$$

$$I_{t,e} = \max_i \{i | X_{t,i} = 1\} \quad (3)$$

3) *On-Speed Analysis*: A speed limit $\bar{v}$ is also specified for the inspection tasks. Setting a speed limit for the drone would

Algorithm 1: On-Path Analysis for Task t in Any Frame i

```

//  $\{p_{t,n} | n = 1, \dots, N_t\}$ : reference points that define the
// reference path for the drone in task  $t$ ,
//  $E_i$ : position of the drone in frame  $i$ ,
//  $l(E_i, p_{t,n})$ : the distance between the drone and the
// reference point  $p_{t,n}$ ,
//  $n^*$ : the index of the reference point with the shortest
// distance to the drone,
//  $v_{t,n}$ : the segment of the reference path, defined by  $p_{t,n}$ 
// and its adjacent point(s),
//  $l(E_i, v_{t,n})$ : the distance from the drone to any location
// on the segment  $v_{t,n}$ ,
//  $l_{t,i}^*$ : the minimum distance from the drone to the
// reference path,
//  $\bar{l}_t$ : the threshold distance for identifying if the drone is
// on the reference path for task  $t$ ,
//  $X_{t,i}$ : binary variable indicating whether the drone in
// frame  $i$  is on the reference path of task  $t$ .
Step 1: find the reference point with the shortest distance
to the drone,  $p_{t,n^*}$ , where
 $n^* := \arg \min_n \{l(E_i, p_{t,n}) | n = 1, \dots, N_t\}$ .
Step 2: The shortest distance from the drone to the
reference path is computed as:
 $l_{t,i}^* = \min \{l(E_i, v_{t,n^*})\}$ 
Step 3: Determine if the drone in frame  $i$  is on path:
 $X_{t,i} = \mathbf{1}\{l_{t,i}^* \leq \bar{l}_t\}$ 
Return ( $X_{t,i}, l_{t,i}^*$ )

```

help lower the chance of motion blur in the inspection video data. The value of $\bar{v}$ is 10 mi/h in TASBID. Similarly, a binary variable $X_{s,i}$ is defined to indicate if the drone in frame i is speeding when performing inspection tasks

$$X_{s,i} = \mathbf{1}\{v_i > \bar{v}, i \in \cup_{t=1}^T [I_{t,s}, I_{t,e}]\}. \quad (4)$$

4) *Crash Analysis*: A crash in the simulation is defined as an event that the drone touches traffic agents, the bridges, the terrain, or the water body. The simulation can sense the type of an object the drone crashes into and track timings of crash events. $X_{h,i}$ is a binary variable indicating if the drone in frame i touches a human in the traffic. $X_{v,i}$ is another binary variable indicating if the drone crashes into a vehicle in the traffic. $X_{o,i}$ is a categorical variable indicating if the drone touches any other objects. A crash event may last for multiple frames. Therefore, whenever $X_{h,i}$ turns from 0 to 1, the simulation identifies the occurrence of a crash into a human, indicated by a binary variable X_h

$$X_h = \mathbf{1}\{\exists X_{h,i} = 1\} \quad (5)$$

and another binary variable X_v indicates if a crash into a vehicle happened

$$X_v = \mathbf{1}\{\exists X_{v,i} = 1\}. \quad (6)$$

Crashing into other objects will not terminate the study. At the end, the total number of crashes into other objects will be

$$X_o = \sum_{i=1}^N \mathbf{1}\{X_{o,i} \neq 0 \text{ \& } X_{o,i-1} = 0\}. \quad (7)$$

5) *Visual Attention Analysis*: The study randomly places X_d surface defects on the bridges. The trainee can take a snapshot if she/he believes an area of concern is found. The total number of snapshot events is

$$X_{pd} = \sum_{i=1}^N o_{p,i}. \quad (8)$$

The snapshots may include false detection. The number of true detection is X_{td} .

6) *Real-Time In-Task Feedback*: Using the monitoring data and measurements calculated from the data, real-time in-task feedback is provided to the trainee. To raise the trainee's attention to job safety and task specifications, TASBID provides five types of information, illustrated in Fig. 2.

The remaining battery level is updated in real time and displayed at the upper right corner of the camera view, as illustrated in Fig. 2. The battery icon is in green color when the remaining power is 70% or higher, yellow if between 30% and 70%, and in red otherwise. The battery icon starts to flush once the remaining power drops below 30%. The displayed battery level set a time constraint to encourage the trainee to finish the inspection before the drone runs out of power. The drone's speed is always displayed at the upper left corner of the camera view. Three types of messages may appear at the bottom left when certain conditions occur.

- 1) A message about speeding will show up at the bottom left corner if $X_{s,i}$ in (4) is 1.
- 2) A message to remind the recommended distance from the bridge elements will appear if the drone is off-path, far away from the bridge element to inspect (i.e., Algorithm 1 returns $X_{t,i} = 0$ and $l_{t,i}^* \leq 8$ m for the inspection task t).
- 3) A message appears if the drone senses any object within 2.5 m to the center of the drone or crashes into anything (i.e., whenever $X_{h,i}$, $X_{v,i}$, or $X_{o,i}$ turns from zero to a positive value).

D. Post-Study Assessment

After a simulation training ends, data collected from the training are further used to perform a comprehensive post-study assessment. The assessment covers the trainee's task performance and self-assessment using a questionnaire.

1) *Task Performance*: It is desired to make the bridge inspection faster, cheaper, safer, more objective, and less interruptive to the traffic. Therefore, TASBID evaluates trainees' job/tasks performance from multiple dimensions: conformity, efficiency, safety, and accuracy, which are important to the bridge inspection.




Fig. 2. (a)–(d) Illustration of real-time in-task feedback.

The trainee's ability to conform with task specifications is term *conformity*. Conformity captures inspectors' essential ability to operate the drone along desired paths, move it to desired locations, and maintain the recommended speed, during the inspection. Conformity positively contributes to the quality of data collection. The ability to be on-path in performing task t is measured by the percentage of task time when the drone is on the reference paths of the tasks

$$P_{p,t} = \frac{\sum_{i=I_{t,s}}^{I_{t,e}} X_{t,i}}{I_{t,e} - I_{t,s} + 1}. \quad (9)$$

To measure the trainee's on-speed ability in performing task t , a weighted sum of times when the drone is speeding is calculated, and the weights are the ratios of speed to speed limit

$$P_{s,t} = \frac{\sum_{i=I_{t,s}}^{I_{t,e}} (v_i/v^-) X_{s,i}}{I_{t,e} - I_{t,s} + 1}. \quad (10)$$

Then, the conformity is an aggregation of $P_{p,t}$ and $P_{s,t}$ for all tasks

$$P_C = \omega_p \sum_{t=1}^T P_{p,t} + \omega_s \sum_{t=1}^T P_{s,t} \quad (11)$$

where ω_p is the gain coefficient for on-path and ω_s is the loss coefficient for speeding. The range of P_C in TASBID is $[-100, 100]$. The maximum score occurs if the drone is always on-path and never speeding in all tasks. The minimum score occurs when the drone is never on-path and always flying at its

maximum speed. The maximum speed of the drone in TASBID is 30 mi/h and the speed limit for inspection is 10 mi/h. Therefore, ω_p and ω_s are set to be 25 and $-25/3$, respectively.

The trainee's ability to finish the inspection with fewer resources and less waste is termed time *efficiency*. It is selected as a training performance metric for encouraging inspectors to keep the inspection cost-effective. Multiple critical values are defined with respect to the time efficiency of trainees. $\underline{\tau}$ defines

the cutoff point of the inspection time for receiving the highest score and τ^- is the maximum allowable flight time for the drone. The battery drains if the inspection would go beyond τ^- . Let X_b be a binary variable indicating if the drone fails to return to the ground team due to running out of power. X_b equals 1 if $N/f > \tau^-$ and 0 otherwise. Accordingly, the score of time efficiency, P_E , is calculated as

$$P_E = [\omega_{e0} + \omega_{e1}(N/f - \underline{\tau})^+](1 - X_b) + \omega_b X_b. \quad (12)$$

The range of P_E score is $[-100, 100]$. ω_{e0} in (12) is set to be 100, representing the highest efficiency score a trainee receives if the inspection is done by $\underline{\tau}$. ω_b is set to be -100 , indicating that the trainee fails to complete the inspection within the maximum allowable time τ and, thus, loses 100 points. P_E score will be 0 if the inspection is completed at the defined maximum allowable time τ . $\omega_{e1} = -\omega_{e0}/(\tau - \underline{\tau})$, representing the score deduction for every additional unit of time exceeding $\underline{\tau}$. In TASBID, τ^- is assumed to be 25 min, estimated based on the maximum flight time of representative commercial lithium-battery-based drones [26]. $\underline{\tau}$ is set to be 15 min.

Job *safety* is the trainee's ability to keep the drone and other traffic agents safe during the inspection. The lack of ability to keep safe in inspection is measured by the total lost score due to crashes

$$P_S = \max[\omega_h X_h + \omega_v X_v + \omega_o X_o, P_S'] \quad (13)$$

where ω_h , ω_v , and ω_o are losses from each crash into a human, a vehicle, and any other object, respectively. In TASBID, ω_h and ω_v are set to be -100 , indicating that a crash into a traffic agent usually has severe consequences such as a fatality or a hospitalized incident. ω_o is set to be -3 , indicating that the consequence of crash into other objects is more related to the drone damage. P_S' is set to be -100 in TASBID, meaning that no more points will be further deducted if the cumulative loss has reached P_S' . Therefore, the range of P_S score is $[-100, 0]$. Limiting the loss by P_S' can avoid the scenario that safety dominates other performance metrics.

Accuracy is the trainee's ability to keep alert during the inspection and, thus, develop the visual perception of the bridge condition. With situational awareness, inspectors can efficiently utilize the assistant drone in data collection and, later, effectively collaborate with machine learning algorithms in analyzing the inspection video data. The assessment module calculates the recall (the portion of the surface defects that the trainee detected correctly)

$$Rc = X_{td}/X_d \quad (14)$$

and the precision (the portion of snapshots with a surface defect)

$$Pr = X_{td}/X_{pd} \quad (15)$$

to measure the accuracy. F_β further integrates the recall and the precision as a single metric

$$F_\beta = \frac{(1 + \beta^2)PrRc}{\beta^2 Pr + Rc} \quad (16)$$

where β is a nonnegative coefficient indicating the relative importance of recall with respect to precision. Setting β as zero

TABLE I
SELF-ASSESSMENT QUESTIONNAIRE

QUESTIONS	
Overall	Time Pressure: I finished the inspection without stress in regard of the required time.
	Frustration: I never felt insecure, irritated, stressed, or discomforted during this task.
	In-task Feedback: The in-task feedback (e.g. battery level, speed, messages) were helpful for me.
By tasks	Performance: I finished the task with a good performance.
	Mental Demand: It's easy to finish the task.
	Physical Demand: There was no physical activity (including pressing, pulling, turning, controlling, and holding) required in the task.

indicates that precision is dominantly important, and setting it as ∞ means that recall is dominantly important. β is equal to 1 if precision and recall are equally important. F_β is within $[0, 100\%]$. Accordingly, the score of accuracy is measured as

$$P_A = \omega_f F_\beta. \quad (17)$$

ω_f in (17) is set to be 100 and so the range of P_A is $[0, 100]$.

The trainee's scores on conformity, efficiency, safety, and accuracy are further standardized to be within the range from 0% to 100%. Then, the standardized scores are presented as a Kiviat diagram to show the trainee's task performance on the four dimensions.

2) *Questionnaire-Based Workload Assessment:* After a simulation training is completed, the trainee is invited to fill out a questionnaire adopted from [15] and revised for TASBID. The questionnaire complements the objective assessment of TASBID. Table I lists the six aspects that the questionnaire asks. "Time pressure," "Frustration," and "In-task feedback" are three aspects asked regarding the overall simulated inspection. "Performance," "Mental demand," and "Physical demand" are asked with respect to each phase or task of the inspection, including calibration, taking-off, individual tasks 1–4, and landing. Responses to questions are on a five-point Likert scale: strongly agree (1), agree (2), neutral (3), disagree (4), and strongly disagree (5). "Strongly agree" stands for the most positive response, and "strongly disagree" stands for the most negative response.

Heavy physical or mental demand may cause frustration and time pressure, and these psychological states may further influence the task performance. In-task feedback may mitigate the negative effect of the physical and mental loads posed on inspectors. The questionnaire can assist in causation analysis of the aforementioned relationship among causal factors (physical and mental demands), psychological states (time pressure and frustration), task performance, and the moderator (in-task feedback).

3) *Repetitive Training for Improvement:* Practice using TASBID would help improve a trainee's task performance and the tolerance to physical and mental demands. The improvement is manifested by progressive changes in both the performance measurements and subjective evaluation results. A hypothesis is that the post-study feedback would accelerate the learning of the trainee.




Fig. 3. Participant in the simulated inspection.

III. CAPABILITY DEMONSTRATION

A small-scale pilot study was conducted to demonstrate the functionality of TASBID. This study obtained the Institutional Review Board approval, which requires that participants are at least 18 years old and their participation is fully voluntary. Twenty-two participants voluntarily contributed to the study. Among them, four are female, and 18 are male. Their ages are from 18 to 45, and their education backgrounds are civil engineering, aerospace engineering, earth and space science, physics, computer science and engineering, and others. All participants have no prior experience with operating drones or serious games, but ten out of 22 have the experience of playing video games for entertainment.

A. Experiment Protocol

The experiment protocol for the simulation training is the following. In the beginning, an introduction to TASBID will be presented to the participant using a few PowerPoint slides. Then, a short tutorial [27] on the simulation training is presented as images and video clips with annotations. After that, the participant is offered an opportunity to practice the drone operation using the provided remote controller. The practice scene has some random variations from the scene for the simulation training. The simulated inspection starts after the participant feels she/he has enough practice and is ready for the study. After the training, the participant will fill out the questionnaire and then exit the study. The duration of the entire study can last 20–60 min, depending on the participant's prior experience with TASBID. Fig. 3 illustrates a participant operating the drone in the simulated inspection. Vivid videos of the inspection simulation can be found at the project website [27].

B. Performance in the Placement Training

The task performance of a participant in the simulated inspection is calculated according to the assessment method presented in Section II-D1. The maximum overall score is 400, with 100 points allocated to each of the four performance metrics: conformity, efficiency, safety, and accuracy. The left chart in Fig. 4 is the distribution of the 22 participants' overall scores in their first training. The chart indicates the heterogeneity in task




Fig. 4. Overall score distribution and marginal distributions on the four performance metrics.




Fig. 5. Individuals' conformity scores by tasks.

performance. The participants' overall score ranges from 220 to 370. The mean value is 316.59 and the distribution is skewed to the low end. The distribution of the overall score indicates a room for improvement. The four charts on the right of Fig. 4 further show the score distributions on the four performance metrics, respectively. Efficiency has the largest mean (91.68) and the second smallest distribution range (38), indicating that it is the best achieved performance metric compared to others. Safety has the largest distribution range (97) but the smallest mean value (68.86), making it the most critical dimension for improvement. The mean scores of conformity (78.32) and accuracy (77.73) are well below the maximum 100, suggesting the need for improvement.

Fig. 5 further visualizes the conformity score of individual participants, broken down by their on-path and on-speed abilities in each of the four tasks. The figure shows that every participant has a unique conformity score profile in the first training; therefore, personalized feedback to individuals would be more helpful. For example, participant 9 needs more practice for task 4 because of the low on-path score and the large loss due to speeding in that task. However, this is not true for participant 7 who needs to improve the on-path ability on task 1.

During the first training, the 22 participants had 203 crashes in total. Fig. 6 counts the number of crashes by participants and tasks. The figure shows that participants' ability to avoid crashes varies largely. Participants 3 and 7 each had only one crash, whereas participant 8 had 24 crashes. The figure also indicates that the distribution of crashes on tasks varies largely




Fig. 6. Individuals' safety scores split by tasks.




Fig. 7. 22 participants' responses to the post-study questionnaire in the first training.

from one participant to another. For example, participants 4, 17, and 19 all had 13 crashes, but their safety concerns are different. Cumulatively, the proportion of crashes when inspecting the bridge bottom (63) is the largest, and the proportion when inspecting the pier (15) is the smallest.

C. Self-Assessment of the Placement Training

Fig. 7 summarizes the distributions of the 22 participants' responses to the questionnaire after they completed the first training. Only 45.5% (10) participants agreed or strongly agreed that they were not frustrated by the job, and 68.2% (15) participants agreed or strongly agreed that they did not feel time pressure in the job. However, 90.1% (20) participants agreed or strongly agreed that the in-task feedback is helpful. Operating a drone in a narrow space is likely to increase the mental demand. For example, the task of inspecting the bridge interlayer received the most negative answers compared to other tasks. Only 40.9% (9) participants agreed or strongly agreed this task is low in mental demand, and only 50% (11) participants agreed or strongly agreed that they performed well in this task. Operating a drone along the curved path with frequent position adjustments, like in task 2, seems to require more physical demand. Only 59.1% (13) participants agreed or strongly agreed that task 2 is low in physical demand.




Fig. 8. Performance measurements from three times of training.

TABLE II
PAIRED t TESTS OF THE LEARNING EFFECT

	Conformity			Efficiency		
	1 vs. 2	1 vs. 3	2 vs. 3	1 vs. 2	1 vs. 3	2 vs. 3
t value	2.609	2.969	1.090	-0.175	-0.938	-0.661
p value	0.018 ^u	0.010 ^u	0.312 ^t	0.866 ^t	0.380 ^t	0.530 ^t
	Safety			Accuracy		
	1 vs. 2	1 vs. 3	2 vs. 3	1 vs. 2	1 vs. 3	2 vs. 3
t value	3.340	3.498	0.475	1.930	-0.662	-7.638
p value	0.006 ^u	0.005 ^u	0.649 ^t	0.048 ^u	0.529 ^t	0.000 ^t

Note: "b" versus "a": the increment tested is the score in "a" minus the score in "b." The superscripts "u," "l," and "t" indicate the upper-tail test, lower-tail test, and two-tail test, respectively.

D. Performance Improvement From the Repetitive Training

Trainees can improve their skill of operating the assistant drone gradually through the repetitive training on TASBID. The post-study assessment result provided to participants may positively influence their learning outcome. For the illustration purpose, a focused group of eight participants repeated the training for three times. The group was randomly drawn from the 22 participants, without referring to their placement training performance or other information. Chi-squared homogeneity tests at the level of significance 0.05 confirm that the focused group can represent the 22 participants. The interval between two successive training sessions is at least two days. The overall inspection scene does not change over the repetitive training, but locations and size of surface defects are changed from one training to another. Fig. 8 uses box plots to visualize the group's performance achieved from the repetitive training. It is clear that, in the second or the third training, the group's average performance is improved on multiple performance metrics and the within-group variation was reduced.

Table II further performed paired t tests on the mean increments of performance scores. Compared to the first training, the group improved the mean conformity score in the second training (p value of the upper tail test = 0.018) and maintained the achieved improvement in the third training (p value of the two-tail test = 0.312). The group's mean improvement of the safety score after completing the second training was significant (p value of the upper tail test = 0.006), and the improvement was maintained in the third training (p value of the two-tail




Fig. 9. Participants' responses to the post-study questionnaires in the repetitive training.

test = 0.649). The improvements of conformity and safety in the second and third training did not worsen the time efficiency. The group maintained the efficiency throughout the three times of training (p values of two-tail tests ≥ 0.380). The group improved the mean accuracy after completing the second training (p value of the upper tail test = 0.048). However, the mean accuracy was reduced after finishing the third training (p value of the lower tail test = 0.000), mainly due to the increased difficulty to visually detect surface defects.

E. Self-Assessment of the Repetitive Training

The repetitive training helps trainees improve not only their task performance, but also confidence and comfort in operating an assist drone for bridge inspection. Fig. 9 summarizes the self-assessment of the eight participants after finishing each training. The figure implies that participants struggle more when inspecting the bridge from a narrow space (task 2) or on curved paths (tasks 3 and 4). However, overall, the response to the questionnaire turns to be more positive after they practiced the inspection using the TASBID.

F. Performance Analysis for Individual Trainees

TASBID can determine the specific strengths and weaknesses for any trainee, identify causes of the weaknesses, and track the training progress. Fig. 10 presents participant 18's performance in the three times of training as an illustrative example. The participant improved the accuracy score from 40 to 70 in the second training. Although the accuracy score dropped to 60 in the third training, that change was mainly caused by the increased challenge in recognizing the cracks visually in that experiment. The




Fig. 10. Performance of participant 18.

efficiency score of participant 18 did not change much, ranging from 22.5 to 24 min in the repetitive training. The participant improved the conformity score in the third training, from 72 to 80. The upper-right figure further shows the on-path scores of the participant in performing each of the four tasks. In the second training, the participant improved the on-path scores on tasks 1 and 2, but she/he did not perform task 3 due to insufficient time. In the third training, the participant significantly improved the on-path score for task 3. Overall, the participant needs more practice to improve the ability to fly the drone along reference paths. The participant clearly improved her/his safety score in the second training and maintained the safety performance in the third training. The plot at the bottom-right indicates that the participants crashed into the bridge 12 times in the first training, but not at all in the second and third training. The number of crashes to the terrain or the water body has a decreasing trend over the three times of training.

G. Subjective Versus Objective Evaluations

Overall, this pilot study shows a consistency between the subjective evaluation result and the objective assessment result. However, self-assessment is subject to a certain degree of bias, which may lead to inconsistent results [28], [29]. The self-ratings of task performance by a few trainees seem to contradict their actual performance. For example, participant 8 made 28 out of 100 points on safety from the first training due to many crashes. Although the participant should know that (because a warning message is shown on the screen if a crash happened), the participant strongly agreed that she/he performed well in the tasks. Participant 13 made 100 out of 100 on safety and 97 out of 100 on conformity, but the participant did not strongly agree that she performed well. Biases are present in their responses to another question "I finished the inspection without stress regarding the required time." Two striking contrasts are the answers from participants 10 and 18. Participant 10 spent 13.75 min to finish all four tasks, but her/his response to this statement is a disagree. Participant 18 spent 24 min completing three tasks only, but the answer is neutral. Another example of the contradictory response is from participant 2. This participant kept on the reference path for inspecting the bridge interlayer for about 30% of the task

time, but the participant believes she/he performed well in this task. The relatively good performances on some dimensions (i.e., quick completion and few crashes) probably made the participant underestimate the consequence of the insufficient data collection. From the aforementioned contradictory examples, the pilot study supports the use of objective assessment. The post-study analysis can tell what happened by analyzing the captured training data to provide objective feedback to the trainee.

IV. CONCLUSION

This article designed and developed a VR-based training and assessment system named TASBID for bridge inspectors collaborating with an assistant drone to collect data at inspection sites. The pilot study, although is in a small scale, demonstrated that TASBID can objectively identify the training needs of individuals in detail and further help them develop the skill and confidence in collaborating with a drone in bridge inspection. This study shares the source code with the public. Prospective users can easily revise it to adapt to their own specific studies or needs [20].

The training and assessment introduced in this article have built a foundation for adding the semi-autonomous mode to TASBID. With the semi-autonomous mode, the drone will fly automatically, but the inspector can disengage the autonomous mode of the drone and take control of it when needed. Besides, a gap is present between the simulation created in Unity and the real-world inspection scene. A generative adversarial network can convert the simulation to a more realistic scene, thus providing improved visual stimuli to inspectors. Furthermore, this article focuses on the system design and development, thus only conducting a small-size pilot study to demonstrate the system functionality. Factorial experiments at a larger scale would be necessary for comprehensive system testing and improvement. TASBID can integrate a multimodal biometric sensor system comprised of an eye tracker, electromyography, and inertial measurement units. Deep neural networks need to be developed for analyzing the biometric sensor data to reliably detect and classify human states and for creating other methods of human-drone interactions. This article has built a foundation for exploring the above-discussed opportunities.

REFERENCES

- [1] American Society of Civil Engineers, "2021 report card for America's infrastructure," Amer. Soc. Civil Eng., Reston, VA, USA. Accessed: Mar. 2021. [Online]. Available: https://infrastructurereportcard.org/wp-content/uploads/2020/12/National_IRC_2021-report-2.pdf
- [2] M. M. Karim, R. Qin, G. Chen, and Z. Yin, "A semi-supervised self-training method to develop assistive intelligence for segmenting multiclass bridge elements from inspection videos," *Struct. Health Monit.*, May 2021, doi: [10.1177/14759217211010422](https://doi.org/10.1177/14759217211010422).
- [3] American Association of State Highway and Transportation Officials, "2019 AASHTO UAS/drone survey of all 50 state DOTs," Amer. Assoc. State Highway Transp. Officials, Washington, DC, USA. Accessed: Mar. 2021. [Online]. Available: https://www.transportation.org/wp-content/uploads/2019/05/MissionControl_Drones3.pdf
- [4] T. Öztaşlan, S. Shen, Y. Mulgaonkar, N. Michael, and V. Kumar, "Inspection of penstocks and featureless tunnel-like environments using micro UAVs," in *Field and Service Robotics*. Berlin, Germany: Springer, 2015, pp. 123–136.
- [5] Y. Li, Z. Sun, K. Xu, and R. Qin, "A two-layer routing algorithm for unmanned aerial vehicle in transmission line inspection," in *Proc. Int. Annu. Conf. Amer. Soc. Eng. Manage.*, 2020, pp. 1–9.
- [6] M. Banic, A. Miltenovic, M. Pavlovic, and I. C. Iric, "Intelligent machine vision based railway infrastructure inspection and monitoring using UAV," *Facta Univ., Ser.: Mech. Eng.*, vol. 17, no. 3, pp. 357–364, 2019.
- [7] N. Metni and T. Hamel, "A UAV for bridge inspection: Visual servoing control law with orientation limits," *Autom. Construction*, vol. 17, no. 1, pp. 3–10, 2007.
- [8] R. Hopcroft, E. Burchat, and J. Vince, "Unmanned aerial vehicles for maritime patrol: Human factors issues," Defence Sci. Technol. Org., Edinburgh, Australia, Tech. Rep. DSTO-GD-0463, 2006.
- [9] M. P. Kontitsis, N. C. Tsourveloudis, and K. P. Valavanis, "A UAV based automated airborne surveillance system," in *Proc. 11th Mediterranean Conf. Control Autom.*, Rhodes, Greece, Jun. 2003.
- [10] Y. Shi, J. Du, and D. A. Worthy, "The impact of engineering information formats on learning and execution of construction operations: A virtual reality pipe maintenance experiment," *Autom. Construction*, vol. 119, 2020, Art. no. 103367.
- [11] A. Z. Sampaio and L. Viana, "Virtual reality used as a learning technology: Visual simulation of the construction of a bridge deck," in *Proc. 8th Iberian Conf. Inf. Syst. Technol.*, 2013, pp. 1–5.
- [12] H. Dong, S. Zou, D. Chen, and H. Xu, "Research and development of distributed bridge crane training system based on virtual reality," in *Proc. 2nd Int. Conf. Intell. Comput. Technol. Autom.*, 2009, vol. 1, pp. 670–673.
- [13] *Aerosim Drone Simulator*, AeroSim, Hong Kong. Accessed: Mar. 2021. [Online]. Available: <https://www.aerosimrc.com/en/pro.htm>
- [14] H. I. Moud, M. A. Razkenari, I. Flood, and C. Kibert, "A flight simulator for unmanned aerial vehicle flights over construction job sites," in *Advances in Informatics and Computing in Civil and Construction Engineering*. Berlin, Germany: Springer, 2019, pp. 609–616.
- [15] G. Gabriel, M. A. Ramallo, and E. Cervantes, "Workload perception in drone flight training simulators," *Comput. Hum. Behav.*, vol. 64, pp. 449–454, 2016.
- [16] P. Rauffet, A. Botzer, A. Kostenko, C. Chauvin, and G. Coppin, "Eye activity measures as indicators of drone operators' workload and task completion strategies," in *Proc. Hum. Factors Ergonom. Soc. Eur. Ch.*, 2016, pp. 211–227.
- [17] A. Neely, M. Gregory, and K. Platts, "Performance measurement system design: A literature review and research agenda," *Int. J. Oper. Prod. Manage.*, vol. 15, no. 4, pp. 80–116, 1995.
- [18] S. G. Hart and L. E. Staveland, "Development of NASA-TLX (Task Load Index): Results of empirical and theoretical research," in *Advances in Psychology*, vol. 52. Amsterdam, The Netherlands: Elsevier, 1988, pp. 139–183.
- [19] C. M. Fidopiastis et al., "Impact of automation and task load on unmanned system operator's eye movement patterns," in *Proc. Int. Conf. Found. Augmented Cogn.*, 2009, pp. 229–238.
- [20] Y. Li, "Bridge inspection with a drone." Accessed: May 2021. [Online]. Available: <https://github.com/yuli1102/Bridge-Inspection-with-a-Drone>
- [21] M. Haberle, "Drone controller full (pc/joystick/mobile)." Accessed: Mar. 2021. [Online]. Available: <https://assetstore.unity.com/packages/tools/physics/drone-controller-full-pc-joystick-mobile-111163>
- [22] Djohns451, "Road architect for unity." Accessed: Mar. 2021. [Online]. Available: <https://github.com/MicroGSD/RoadArchitect>
- [23] Mchrbn, "Unity-traffic-simulation." Accessed: Mar. 2021. [Online]. Available: <https://github.com/mchrbn/unity-traffic-simulation>
- [24] Shauleiz, "Vjoy device driver." Accessed: Sep. 2021. [Online]. Available: <https://github.com/shauleiz/vJoy>
- [25] M. K. Svensson, "mDjiController." Accessed: May 2021. [Online]. Available: <https://github.com/Matsemann/mDjiController>
- [26] Y. Li, Z. Sun, and R. Qin, "Routing algorithm and cost analysis for using hydrogen fuel cell powered unmanned aerial vehicle in high voltage transmission line inspection," in *Proc. Int. Annu. Conf. Amer. Soc. Eng. Manage.*, 2018, pp. 1–11.
- [27] Y. Li, "TASBID experiment." Accessed: May 2021. [Online]. Available: <https://sites.google.com/view/yuli1102/projects/bridge-inspection-flight-simulation>
- [28] S. I. Donaldson and E. J. Grant-Vallone, "Understanding self-report bias in organizational behavior research," *J. Bus. Psychol.*, vol. 17, no. 2, pp. 245–260, 2002.
- [29] Z. Dienes, "Assumptions of subjective measures of unconscious mental states: Higher order thoughts and bias," *J. Consciousness Stud.*, vol. 11, no. 9, pp. 25–45, 2004.