Polarization Transport in Ferroelectrics

```
G.E.W. Bauer, <sup>1,2,3</sup> P. Tang, <sup>1</sup> R. Iguchi, <sup>4</sup> J. Xiao, <sup>5</sup> K. Shen, <sup>6</sup> Z. Zhong, <sup>7,8</sup>
                     T. Yu. S.M. Rezende, 10 J.P. Heremans, 11, 12, 13 and K. Uchida 4, 14
                           <sup>1</sup>WPI Advanced Institute for Materials Research and CSRN,
                           Tohoku University, 2-1-1, Katahira, Sendai 980-8577, Japan
         <sup>2</sup>Institute for Materials Research, Tohoku University, 2-1-1 Katahira, Sendai 980-8577, Japan
 <sup>3</sup>Kavli Institute for Theoretical Sciences, University of the Chinese Academy of Sciences, Beijing 10090, China
                        <sup>4</sup>National Institute for Materials Science, Tsukuba 305-0047, Japan
<sup>5</sup>Department of Physics and State Key Laboratory of Surface Physics, Fudan University, Shanghai 200433, China
                       <sup>6</sup>Center for Advanced Quantum Studies and Department of Physics.
                                 Beijing Normal University, Beijing 100875, China
                            <sup>7</sup>Ningbo Institute of Materials Technology and Engineering,
                                Chinese Academy of Sciences, Ningbo 315201, China
                       <sup>8</sup>China Center of Materials Science and Optoelectronics Engineering,
                      University of the Chinese Academy of Sciences, Beijing 100049, China
           <sup>9</sup>School of Physics, Huazhong University of Science and Technology, Wuhan 430074, China
    <sup>10</sup>Departamento de Física, Universidade Federal de Pernambuco, 50670-901, Recife, Pernambuco, Brazil
                                <sup>11</sup>Department of Materials Science and Engineering,
                             The Ohio State University, Columbus, Ohio 43210, USA
                              <sup>12</sup>Department of Mechanical and Aerospace Engineering,
                             The Ohio State University, Columbus, Ohio 43210, USA
               <sup>13</sup>Department of Physics, The Ohio State University, Columbus, Ohio 43210, USA
         <sup>14</sup>Institute for Materials Research, Tohoku University, 2-1-1 Katahira, 980-8577 Sendai, Japan
                                              (Dated: November 3, 2023)
```

The duality between electric and magnetic dipoles in electromagnetism only partly applies to condensed matter. In particular, the elementary excitations of the magnetic and ferroelectric orders, namely magnons and ferrons, respectively, have received asymmetric attention from the condensed matter community in the past. In this perspective, we introduce and summarize the current state of the budding field of "ferronics". We argue that the introduction of dipole-carrying elementary excitations allows the modeling of many observables and potentially leads to applications in thermal, information, and communication technologies.

I. FERROELECTRICITY AND MAGNETISM

Ferroelectrics are materials that exhibit permanent and switchable electric polarization resulting from the ordering of electric dipoles below possibly high critical temperatures. Comparing and contrasting the behavior of ferroelectrics with that of magnets, in which magnetic dipoles order, can enhance our understanding of both material classes [1, 2]. Due to their high dielectric constant, ferroelectrics are commonly used in (power) capacitors. Their polarization can be manipulated by external electric fields and temperature, leading to applications such as electrocaloric cooling via thermodynamic cycles similar to those used in magnetocalorics [3]. Pyro- and piezoelectricity can be utilized for sensor and energy harvesting applications [4]. The finite coercivity of the switchable order makes ferroelectrics useful materials for nonvolatile memories that complement (and compete with) magnetism-based devices [5].

The polarization of a polar material is affected by the details of its surface, but the distinction between a ferroelectric and an unpolarized dielectric is a well-defined bulk property that can be computed from first principles [6]. While the analogies between ferroelectricity and magnetism are well-understood for equilibrium thermal properties in terms of the entropy of the dipolar order.

Surprisingly, the excited states of ferroelectrics or "ferrons" [9] and their non-equilibrium transport properties, attract much less attention than the equivalent states in magnets, known as magnons [7, 8]. In this Perspective, we summarize the state-of-the-art of "ferronics", with a particular focus on its potential applications.

II. FERROELECTRIC MATERIALS

The exchange interaction drives magnetism by favoring parallel spins over antiparallel ones. The magneto-dipolar interaction is relatively weak and causes secondary effects, such as the formation of domains. In ferroelectrics, there is no exchange interaction but the dipolar interaction is stronger by a factor of $1/(\alpha^2\epsilon_r)\approx 10^3$, where $\alpha=1/137$ is the fine-structure constant and ϵ_r is a high-frequency relative dielectric constant [10]. The electric dipolar energy drives ferroelectricity in some but not all cases. "Improper" ferroelectricity [12] accompanies a structural or magnetic phase transition in which electrostatics does not play a leading role. Since there is no unifying physical origin, many types of ferroelectrics exist. In the following, we discuss a few selected examples.

- Order-disorder ferroelectrics: In materials with

bistable protons or loosely locked molecular dipoles, the entropy increases with temperature drives a second-order phase transition that destroys a ferroelectric state at a critical temperature. This phenomenology is similar to magnetic systems and can be modeled by Ising pseudospin Hamiltonians [13, 14].

- Displacive ferroelectrics: Most ferroelectric phase transitions, including that of the iconic perovskite BaTiO₃, are associated with an inversion symmetry-breaking structural phase transition triggered by a soft transverse optical phonon. The Landau-Devonshire theory, based on a parameterized Landau free energy, is an appropriate description of the ferroelectric phase transitions in these materials [10].
- Hyperferroelectrics: Hyperferroelectrics are a class of semiconducting ferroelectrics with a polarization that remains stable under an unscreened depolarization field [11].
- Shift-induced ferroelectricity was discovered only recently in atomically thin bilayers of two-dimensional materials with hexagonal non-centrosymmetric unit cells such as WTe₂ [15] and BN [16–18]. Here a small slide or twist between the two monolayers reverses an electric dipole by mutual electric polarization and charge transfer. Landau theory [19] and first-principles calculations [20] explain the observed high critical temperatures and low switching fields.
- Electronic ferroelectrics: Ionic displacements cause permanent polarization in the above material classes. The inertia of the atomic masses slows down the switching dynamics. Ferroelectricity caused by charge ordering without rearrangement of the lattice [21–23] promises a much faster response. Even though the microscopic physics is very different, the phenomenology of polarization accumulation and transport should be the same as for phonon-based ferroelectrics [24].
- Ferroelectric conductors: According to conventional wisdom electric conduction and ferroelectricity are incompatible because of the efficient screening of bulk charges by mobile electrons. Nevertheless, ferroelectric conductors and metal do exist in special materials with incomplete screening [25]. The perpendicular polarization in WTe₂ [15] or bilayer graphene [23] can exist because two-dimensional conduction electrons cannot screen a permanent dipole oriented perpendicularly to the planes. A two-dimensional metal such as graphene also does not screen a homogeneous polarization normal to a close-by ferroelectric [19].
- Antiferroelectrics: The condensation of a Brillouin zone center (edge) phonon precedes the ferroelectric (antiferroelectric) order. Ferrielectricity and more complex textures [26] may emerge at phase transitions that do not need to be displacive.
- (Anti)ferroelectric topological insulators have been predicted to allow control of band topology by applied electric fields [27, 28].
- *Multiferroics*: In multiferroic materials, the order in the electric and magnetic polarizations coexist [29].

- "Electromagnons" are the excitations in multiferroic materials in the presence of ac electric fields that may carry electric dipoles [30, 32]. Electric and magnetic dynamics are coupled by the Moriya-Dzyaloshinskii interaction [31, 32].
- *Electrets* are materials with a metastable macroscopic electric polarization that cannot be switched [33], in contrast to conventional ferroelectrics with spontaneously formed bistable ground states.
- *Polar materials* with broken inversion symmetry but without spontaneous electric polarization may still be piezo- and pyroelectric, i.e. develop transient polarizations under stress and heat. Such materials also may support the ferron excitations discussed in more detail below. Here we concentrate on ferroelectrics because their switchability allows control of larger polarization currents and the phase transition to the inversion-symmetric paraelectric phase quenches the polarity.

III. FERRONICS

Ferronics is the study of the elementary excitations of the ferroelectric order or "ferrons" [19, 34–38], analogous with the subfield of magnonics in magnetism [7, 8]. In contrast to spin waves that look the same in most ferromagnets, the excitations of ferroelectrics reflect the richness of their ground states. Figure 1 is a schematic of the symmetry-restoring ferron excitations in selected materials.

- Ferrons: A ferron in state i is a bosonic excitation that carries electric polarization in the form of a finite dipole \mathbf{p}_i . By a direct derivation [36] or the Hellmann-Feynman theorem, the latter follows from the dependence of its frequency $\omega_i = \epsilon_i/\hbar$ on an applied electric field \mathbf{E}

$$\mathbf{p}_i = -\frac{\partial \omega_i}{\partial \mathbf{E}},\tag{1}$$

For comparison, the magnetic moment of a magnon j in simple ferromagnets with frequency ω_j reads $\mathbf{m}_j = -\partial \omega_j/(\partial \mathbf{B})$, where \mathbf{B} is the magnetic field. Its value is $m_j \approx -2\mu_B$, where μ_B is the Bohr magneton. A similar simple relation does not exist for the ferron polarization, however.

The temperature dependence of the equilibrium polarization

$$\Delta \mathbf{p}_0 = \mathbf{p}_0(T) - \mathbf{p}_0(0) = \sum_i \mathbf{p}_i f_P(\epsilon_i, T), \qquad (2)$$

in terms of the sum over the eigenstates of the system, where $f_P(\epsilon_i,T) = \exp[\epsilon_i/(k_BT)-1]^{-1}$ is the Planck distribution and k_B Boltzmann's constant. The excitations of ferroelectrics (and ferromagnets) suppress the order, hence $p_0(T) \leq p_0(0)$.

The ferrons of most ferroelectrics are also phonons, but not all phonons are ferrons. The optical phonons in dielectrics with inversion symmetry including the paraelectric phase of ferroelectrics above the phase transition




Figure 1. The green arrows indicate symmetry-restoring ferron excitations in selected ferroelectric materials. (a) sketches the soft-phonon excitation in the free energy landscape of a displacive ferroelectric with a temperature-dependent barrier (blue arrow). (b) In typical order-disorder ferroelectrics, the symmetry is restored by the hopping of protons in hydrogen bonds. (c) Thermally activated rotations destroy the order of permanent molecular dipoles. (d) The rigid relative shift of the bilayers reverses the electric polarization in a double well potential. (e) In electronic ferroelectrics, the symmetry is restored by the motion of electrons, not the ions.

temperature scale like $\delta\omega_{\rm op}\sim -E^2$ and therefore cannot harbor ferrons. do not harbor ferrons. Ferron excitations exist only as anharmonic oscillators in crystals with intrinsic or induced broken inversion symmetry. Ferron modes can be both transverse (Goldstone-like) or longitudinal (Higgs-like) as illustrated in Figure 2, as well as acoustic or optical. In complex displacive ferroelectrics, we expect that the soft polar phonons dominate the polarization dynamics while other phonons form an inert background.

In the following, we focus on ferroelectrics because their switchability implies "larger" ferrons and associated functionalities for technological applications.

- Models: In most materials, ferroelectricity is associated with the movement of charge ions. The ferrons are a subset of the phonon spectrum and accessible to lattice dynamical calculations that include the non-harmonic corrections that endow the excitations with an electric dipole. A very simple model system are one-dimensional chains with two atoms in the unit cell [34, 35]. \mathbf{p}_i depends strongly on band index and crystal momentum. It is mainly carried by optical modes, but in transport phenomena, the much larger group velocity of the sound waves can compensate for their smaller dipoles.

In order-disorder ferroelectrics, the ferron dipole is caused by the hopping of protons or the rotation of molecular dipoles. These are two-level systems that can be




Figure 2. Sketch of an (a) "Goldstone" transverse and (b) "Higgs" longitudinal ferron mode. In (a) the modulus of the electric dipole P_0 is conserved during transverse oscillations, as in stable molecular dipoles. The projection on the equilibrium polarization $|\overline{P}| < |P_0|$. In (b) the length of the dipole fluctuates in an anharmonic potential V(z) that also reduces the average value $|\overline{P}| < |P_0|$.

modeled by Ising pseudo-spins in which the tunneling between the two spin states and dipolar coupling between the dipoles govern the ferron dispersion [13, 14].

In displacive and shift-induced ferroelectrics the lattice vibrations in a double-well potential reduce the modulus of the average dipole. Landau theory [10] governs the ferron dispersion and mode amplitudes of displacive ferroelectrics in the long wavelength limit [19, 36].

In electronic ferroelectrics, ferrons emerge in the Falikov-Kimball model as excitations of an excitonic insulator phase [24].

Equation (1) is a simple recipe to compute the ferron dipole by model or first-principles calculations. Many observables can be computed from the ferron energy dispersion $\epsilon_{\nu \mathbf{k}}$ for a ferron band ν and wave vector \mathbf{k} and its polarization $\mathbf{p}_{\nu \mathbf{k}} = -\partial \epsilon_{\nu \mathbf{k}}/(\hbar \partial \mathbf{E})$.

- Non-equilibrium: The equilibrium polarization \mathbf{p}_0 density of a ferroelectric depends on temperature and the applied electric field. When the equilibrium of an isotropic medium is perturbed by gradients of temperature $(\partial_x T)$ and/or effective electric field $(\partial_x E_{\text{eff}})$ parallel to the polarization in the x-direction, the energy (j_q) and polarization (j_p) current densities flow to restore the equilibrium. When the perturbations are sufficiently small and slow in time and space, local linear response relations (Ohm's Law) apply.

$$\begin{pmatrix} -j_p \\ j_q \end{pmatrix} = \sigma_p \begin{pmatrix} 1 & S_p \\ \Pi_p & \kappa/\sigma_p \end{pmatrix} \begin{pmatrix} \partial_x E_{\text{eff}} \\ -\partial_x T \end{pmatrix}, \quad (3)$$

where σ_p (κ) is the polarization (thermal) conductivity with units m/ Ω (WK⁻¹m⁻¹), while S_p ($\Pi_p = S_p T$) is the ferroelectric Seebeck (Peltier) coefficient with units VK⁻¹m⁻¹ (V/m).

- Coherent ferrons: Similar to magnons, we can study ferrons in two different limits. Propagating magnons that are coherently excited by microwaves at GHz frequencies propagate over centimeters in high-quality magnets such as yttrium iron garnet (YIG). The ferrons in displacive ferroelectrics resonate at THz frequencies [39]. Moreover, resonance line broadenings are governed by viscous

dissipation that scales like $\sim \omega$, whence the lifetimes of optical phonons and their group velocities may turn out to be relatively small. On the other hand, while their dipole and thus the coupling to ac and dc electric fields are weak, acoustic ferrons are attractive for experiments on propagating ferrons in crystals with low acoustic attenuation and high group (sound) velocities.

The interaction with ac electric fields leads to substantial and anisotropic anticrossings between photon and ferron branches, i.e. ferron polaritons [14]. At ferroelectric surfaces, the dipolar interaction guides the ferrons excited by localized sources into focused beams [40].

- Transport: In order to improve upon the simple diffusion theory sketched above, the transport coefficients in Eq. (1) can be computed from the ferron spectrum and dipoles.

In constrictions such as point contacts, mean free paths may exceed the length of the current-limiting geometrical features. In that "ballistic" limit Landauer-Büttiker scattering theory is appropriate [35].

In the opposite "diffuse" regime, a semiclassical linearized Boltzmann equation leads to microscopic expressions for the parameters of the diffusion theory. When a non-equilibrium polarization or polarization accumulation (or ferron chemical potential) $\delta p = p(x,t) - p_0$ relaxes over a time τ_p , the conservation relation for the polarization $\partial_x j_p = -(\partial_t - 1/\tau_p) \delta p$ leads to a diffusion equation for δp that can be solved with appropriate boundary conditions [34, 36]. τ_p is the polarization relaxation time that can be very long as long as the ferron and normal phonon band density of states do not overlap [14]. The effective field E_{eff} is the sum of applied and internal fields including a diffusion term proportional to $\partial_x \delta p$. Its gradient is necessarily transient on a time scale τ_p , as is the field-driven thermal current or "polarization Peltier effect". The polarization Seebeck effect is observable in terms of dc thermovoltages induced by a temperature gradient [34, 35]. While both the Peltier effect and thermovoltage vanish with τ_p , the polarization current induced by a temperature gradient persists and can be detected, e.g., by its stray magnetic fields [35].

IV. EXPERIMENTS

Wooten et al. [41] reported the first experimental evidence of ferron excitations in terms of an electric-field dependence of the thermal (or heat) conductivity κ (Fig. 2) and velocity v of pressure waves in a lead zirconium titanate (PZT)-based ferroelectric device. The observed field dependence is consistent with the relation $\kappa = (1/3)Cv^2\tau$, where the volumetric heat capacity at constant pressure C is constant above the Debye temperature. Assuming that the scattering time τ does not depend on field $d \ln \kappa/dE = 2d \ln v/dE$ as observed. These results indicate that the effect is intrinsic, i.e. caused by the field modulation of acoustic phonons that carry an electric dipole.

The original theories [34, 36] are not appropriate to model these results since (i) PZT is a displacive ferroelectric and (ii) in the Landau model the dipoles are carried exclusively by a single band of longitudinal soft optical phonons at high frequencies and small group velocities. The piezoelectric strain, i.e. the linear contraction of the lattice by an applied electric field in ferroelectrics, modulates the sound velocities in particular via the mode and frequency-dependent Grüneisen coefficients and thereby the thermal conductivity. The model predicts that $d \ln v/dE = -(d_{33} + 2d_{31})\gamma$, where the piezoelectric coefficient d_{33} (d_{31}) measures the strain along (normal to) **E** and $\gamma = d \ln \omega / d \ln V$ is the GrÂuneisen constant, i.e. the derivative of the phonon frequency ω with respect to the volume V. For the known material parameters for PZT the model explains the observations remarkably well. Below the Debye temperature $C \propto v^{-3}$ and $d \ln \kappa / dE = 2d \ln v / dE$ changes sign. Moreover, while $d_{33} + 2d_{31} > 0$ in PZT, it is negative in Pb(Mg_{1/3}Nb_{2/3})O₃-PbTiO₃ (PMN-PT), potentially enabling the design of complementary heat switches.

Preliminary data on non-ferroelectric materials with large piezoelectricity/electrostriction and high dielectric constants such as $SrTiO_3$ do not show any field dependence, which confirms the role of ferrons.

Analogously, the modulation of the sound velocity in ferromagnetic materials by magnetostriction [42] may affect the thermal transport under an applied magnetic field.




Figure 3. Electric field dependence of the thermal conductivity of the ferroelectric PZT (adapted from [41])

V. POTENTIAL APPLICATIONS

- Thermal management: In the footsteps of spin caloritronics, the science and technology of coupled spin, heat, and charge currents [44, 45], ferrons offer new strategies for thermal control and power generation.

Ferroelectric capacitors under temperature gradients generate stable surface charges, in contrast to the transient polarization offered by the pyroelectric effect. A transient polarization Peltier effect may contribute to electrocaloric cooling [34, 35].

The polarization drag effect in heterostructures between ferroelectrics and metals frees device designers from the yoke of the Wiedemann-Franz Law. In such structures, heat and charge currents flow in parallel but are spatially separated in different materials. Choosing a ferroelectric with a low thermal and a metal with a high electric conductivity leads to respectable thermoelectric figures of merit in van der Waals stacks [38]. In the spin Seebeck effect, the heat current in the magnet is also spatially separated from the induced transverse charge current in heavy-metal contacts, but the thermoelectric figure of merit is limited by small spin Hall angles [46].

The electric field-dependence of the thermal conductivity [41] could lead to electrically controlled all-solid-state heat switches between high- and low-conducting states with important potential applications [47] in energy-saving technologies, particularly in engines with transient heating cycles such as solar-thermal power plants. Their development would enable all-solid-state power generators and refrigeration technologies, improving the efficiency of electrocaloric and magnetocaloric engines. Particularly interesting would be a set of complementary devices in a high- and low-conducting state that switches their role by an applied electric field that also powers the active electrocaloric material, which is an option offered by the experiments [41].

- Logics and interconnects: The weak dissipation of magnons makes them suitable conduits to exchange spin information and carry out logic operations [48]. Coherently excited ferrons can in principle carry out the same functions. The first theory of surface ferrons predicts new functionalities, such as tunable routing of focused ferron beams without the need for micro/nanostructuring the surface into wave guides [40]. Since spin currents are the bread and butter of spin-torque magnetic memories [49], polarization currents might be useful in the writing and read-out of ferroelectric memories [5].
- THz source: When injected into a metal, the polarization current decays on a femtosecond scale. However, when injected into an undoped semiconductor with a fundamental band gap below thermal energies, the generated electron and holes may recombine to emit photons. When the non-radiative recombination times are sufficiently long, such a structure could operate as a THz radiation source driven by waste heat.

VI. CONCLUSIONS AND CHALLENGES

The present Perspective only scratches the surface of a full understanding of the basic physics and the applications of electric-dipole carrying excitations in ferroelectrics and ferroelectric devices. Fundamental issues such as the formulation and observation of the polarization relaxation length must be still addressed. Some lowhanging fruits may be picked by applying the advanced insights of magnonics and mechanics to ferroelectric materials as in the examples below.

- Charge-spin-polarization coupling: The spin-charge coupling is essential spintronics, but a polarization-charge coupling such as in the ferron drag effect [38] is much less established.

Ferroelectricity in or close to a conducting channel strongly affects the spin-orbit interaction. A switch of polarization then reverses the direction of spin Hall currents [50]. The reciprocal effect is the excitation of a ferron current by spin currents. Natural or composite multiferroic materials have been the focus of many studies in the past decades, but such a coupling between polarization and spin currents has to the best of our knowledge been overlooked. A systematic study of transport phenomena in the presence of polarization and magnetic order coupled with the Moriya-Dzyaloshinskii interaction [31, 32] could lead, for instance, to polarization-current detectors.

- Ferroelectric textures: In unpoled ferroelectrics, the external electric fields are quenched by domain with opposite polarizations that are separated by domain walls. Moving domain walls facilitate ferroelectric switching by strongly suppressing critical fields. The interaction of ferrons with domain walls [20] and topological textures such as skyrmions [51], appears interesting and important. Ferroelectric domain walls may also provide waveguides for ferron excitations [52]. In analogy with magnonics, we envisage manipulation of ferroelectric textures by polarization currents, or in polar metals, even by charge currents.
- Quantum effects: Extending the techniques of optomechanical systems [53] to ferroelectric materials would allow the quantum control of macroscopic electric polarization.

In order to progress, more experiments are sorely needed. We hope that we have been able to inspire our colleagues and stimulate new collaborative efforts between experts in the fields of ferroelectrics and magnetism.

ACKNOWLEDGMENTS

P.T. and G.B. acknowledge the financial support by JSPS KAKENHI Grants No. 19H00645 and No. 22H04965. S.R. was financially supported by Conselho Nacional de Desenvolvimento Científico e Tecnológico (CNPq), Coordenacão de Aperfeicoamento de Pessoal de Nível Superior (CAPES), Financiadora de Estudos e Projetos (FINEP), and Fundacão de Amparo á Ciência e Tecnologia do Estado de Pernambuco (FACEPE). T.Y. acknowledges support by the National Natural Science Foundation of China under Grant No. 0214012051, and the startup grant of Huazhong University of Science and Technology (Grants No. 3004012185 and No. 3004012198). J.H. is sup-

ported by the U.S. National Science Foundation grant CBET-2133718 "Polarization Caloritronics: a pathway to electrically-controlled heat switches". R.I and K.U. are supported by JSPS KAKENHI Grants No. 20H02609

and 22H04965 as well as JST CREST "Creation of Innovative Core Technologies for Nano-enabled Thermal Management" Grant No. JPMJCR17I1.

- N.A. Spaldin, Analogies and Differences between Ferroelectrics and Ferromagnets, in: *Physics of Ferroelectrics* K. M. Rabe, C.H. Ahn, J.-M. Triscone (Eds.) (Springer-Verlag, Berlin, 2007), pp. 175.
- [2] Duality (electricity and magnetism), en.wikipedia.org/ wiki/Duality_(electricity_and_magnetism).
- [3] S. Crossley, N. D. Mathur, and X. Moya, New developments in caloric materials for cooling applications, AIP Advances 5, 067153 (2015).
- [4] M. Kang and E. M. Yeatman, Thermal Energy Harvesting Using Pyroelectric and Piezoelectric Effects, J. Phys.: Conf. Ser. 773, 012073 (2016).
- [5] M. Si, H. Cheng, T. Ando, G. Hu, and P D. Ye, Overview and outlook of emerging non-volatile memories, MRS Bulletin 46, 1 (2021) .
- [6] D. Vanderbilt, Berry Phases in Electronic Structure Theory: Electric Polarization, Orbital Magnetization and Topological Insulators, (Cambridge University Press, Cambridge, 2018).
- [7] S.M. Rezende, Fundamentals of Magnonics (Springer, Cham, 2020).
- [8] A. Barman *et al.*, The 2021 Magnonics Roadmap, J. Phys.: Condens. Matter **33**, 413001 (2021).
- [9] G.E.W. Bauer, P. Tang, R. Iguchi, and K. Uchida, Magnonics vs. Ferronics, J. Magn. Magn. Mater. 541, 168468 (2022).
- [10] P. Chandra and P. B. Littlewood, A Landau Primer for Ferroelectrics, in *Physics of Ferroelectrics*, (Springer Verlag, Berlin, 2007), pp. 69.
- [11] K.F. Garrity, K.M. Rabe, and D. Vanderbilt, Hyperferroelectrics: Proper Ferroelectrics with Persistent Polarization, Phys. Rev. Lett. 112, 127601 (2014).
- [12] V. Dvořák, Improper Ferroelectrics, Ferroelectrics 7, 1 (1974).
- [13] R. Blinc and B. Žekš, Dynamics of order-disorder-type ferroelectrics and anti-ferroelectrics, Advances in Physics 21, 693 (1972).
- [14] P. Tang and G.E.W. Bauer, Electric Analog of Magnons in Order-Disorder Ferroelectrics, arXiv:2309.03691.
- [15] Z. Fei, W. Zhao, T.A. Palomaki, B. Sun, M.K. Miller, Z. Zhao, J. Yan, Xi. Xu, and D.H. Cobden, Ferroelectric switching of a two-dimensional metal, Nature 560, 336 (2018).
- [16] C. R. Woods et al., Charge-polarized interfacial superlattices in marginally twisted hexagonal boron nitride, Nat. Commun. 12, 347 (2021).
- [17] K. Yasuda, X. Wang, K. Watanabe, T. Taniguchi, and P. Jarillo-Herrero, Stacking-engineered ferroelectricity in bilayer boron nitride, Science 372, 1458 (2021).
- [18] M. Vizner Stern et al., Interfacial ferroelectricity by van der Waals sliding. Science 372, 1462–1466 (2021).
- [19] P. Tang and G.E.W. Bauer, The sliding phase transition in ferroelectric van der Waals bilayers, Phys. Rev. Lett. 130, 176801 (2023).

- [20] R. He, B. Zhang, H. Wang, L. Li, T. Ping, G.E.W. Bauer, Z. Zhong, Ultrafast switching dynamics of the ferroelectric order in stacking-engineered ferroelectrics, Acta Materialia 262 119416 (2024),
- [21] N. Ikeda et al., Ferroelectricity from iron valence ordering in the charge-frustrated system LuFe2O4, Nature 436, 1136 (2005).
- [22] K. Yamauchi and P. Barone, Electronic ferroelectricity induced by charge and orbital orderings, J. Phys.: Condens. Matter 26, 103201 (2014).
- [23] Z. Zheng et al., Unconventional ferroelectricity in moiré heterostructures, Nature 588, 71 (2020).
- [24] H. Adachi, N. Ikeda, and E. Saitoh, Ginzburg-Landau action and polarization current in an excitonic insulator model of electronic ferroelectricity, Phys. Rev. B 107, 155142 (2023).
- [25] W. X. Zhou and A. Ariando, Review on ferroelectric/polar metals, Jpn. J. Appl. Phys. 59, SI0802 (2020).
- [26] C.A. Randall, Z. Fan, I. Reaney, L. Chen, S. Trolier-McKinstry, Antiferroelectrics: History, fundamentals, crystal chemistry, crystal structures, size effects, and applications, Am. Ceram. Soc. 104, 3775 (2021).
- [27] B. Monserrat, J.W. Bennett, K. M. Rabe, and D. Vanderbilt, Antiferroelectric Topological Insulators in Orthorhombic AMgBi Compounds (A=Li,Na, K), Phys. Rev. Lett. 119, 036802 (2017).
- [28] Y. Liang, N. Mao, Y. Dai, L. Kou, B. Huang, and Y. Ma, Intertwined ferroelectricity and topological state in twodimensional multilayer, npj Computational Materials 7, 172 (2021).
- [29] T. Lottermoser and D. Meier, A short history of multiferroics, Physical Sciences Reviews (2020) https://doi.org/10.1515/psr-2020-0032.
- [30] Y. Takahashi, R. Shimano, Y. Kaneko, H. Murakawa, and Y. Tokura, Magnetoelectric resonance with electromagnons in a perovskite helimagnet, Nat. Phys. 8, 121 (2012).
- [31] K. Shen, Electrical and magnetic control of spin-lattice configuration and magnon-ferron hybridization in a twodimensional multiferroic model, Phys. Rev. B 108, 094413 (2023).
- [32] K. Shen, Magnon-ferron coupling mediated by dynamical Dzyaloshinskii-Moriya interaction in a two-dimensional multiferroic model, Phys. Rev. B 106, 104411 (2022).
- [33] *Electrets*, Edited by G.M. Sessler, Topics in Applied Physics (Springer Berlin, Heidelberg, 1987).
- [34] G.E.W. Bauer, R. Iguchi, and K. Uchida, Theory of Transport in Ferroelectric Capacitors, Phys. Rev. Lett. 126, 187603 (2021).
- [35] P. Tang, R. Iguchi, K.-i. Uchida, and G.E.W. Bauer, Thermoelectric Polarization Transport in Ferroelectric Ballistic Point Contacts, Phys. Rev. Lett. 128, 047601 (2022).
- [36] P. Tang, R. Iguchi, K. Uchida, and G. E. W. Bauer, Thermoelectric Polarization Transport in Ferroelectric Ballis-

- tic Point Contacts, Phys. Rev. B 106, L081105 (2022).
- [37] P. Tang, R. Iguchi, K. Uchida, and G. E. W. Bauer, Excitations of the ferroelectric order, Phys. Rev. B 106, L081105 (2022).
- [38] P. Tang, K. Uchida, and G. E. W. Bauer, Nonlocal Drag Thermoelectricity Generated by Ferroelectric Heterostructures, Phys. Rev. B 107, L121406 (2023).
- [39] S. H. Zhuang and J.-M. Hu, Role of polarization-photon coupling in ultrafast terahertz excitation of ferroelectrics, Phys. Rev. B 106, L140302 (2022).
- [40] X. Zhou, P. Tang, R. L. Rodríguez-Suárez, S. M. Rezende, G.E.W. Bauer, T. Yu, Surface Ferron Excitations in Ferroelectrics and Their Directional Routing, Chinese Physics Letters 40, 087103 (2023).
- [41] B.L. Wooten, R. Iguchi, P. Tang, J. Kang, K. Uchida, G.E.W. Bauer, and J. P. Heremans, Electric fielddependent phonon spectrum and heat conduction in ferroelectrics, Sci. Adv. 9, eadd7194 (1-9) (2023).
- [42] J. De Klerk, Effect of a Magnetic Field on the Propagation of Sound Waves in a Ferromagnetic Material, Nature 168, 963 (1951).
- [43] S.R. Boona and J.P. Heremans, Magnon thermal mean free path in yttrium iron garnet, Phys. Rev. B 90, 064421 (2014).

- [44] G.E.W. Bauer, E. Saitoh, and B.J. van Wees, Spin Caloritronics, Nat. Mat. 11, 391 (2012).
- [45] K. Uchida and R. Iguchi, Spintronic Thermal Management, J. Phys. Soc. Jpn. 90, 122001 (2021).
- [46] A.B. Cahaya, O.A. Tretiakov, and G.E.W. Bauer, Spin Seebeck Power Conversion, IEEE Trans. Magn. 51, 0800414 (2015),
- [47] G. Wehmeyer, T. Yabuki, C. Monachon, J. Wu, and C. Dames, Thermal diodes, regulators, and switches: Physical mechanisms and potential applications, Appl. Phys. Rev. 4, 041304 (2017).
- [48] A. V. Chumak et al., Roadmap on Spin-Wave Computing, IEEE Trans. Magn. 58, 0800172 (2022).
- [49] S. Bhatti, R. Sbiaa, A. Hirohata, H. Ohno, S. Fukami, S.N. Piramanayagam, Spintronics based random access memory: A review, Materials Today 20, 530. (2017).
- [50] C. Rinaldi et al., Ferroelectric Control of the Spin Texture in GeTe, Nano Lett. 18, 2751 (2018).
- [51] J. Hlinka and P. Ondrejkovic, Skyrmions in ferroelectric materials, Solid State Physics 70, 143 (2019).
- [52] G. Chen, J. Lan, T. Min, and J. Xiao, Narrow Waveguide Based on Ferroelectric Domain Wall, Chinese Phys. Lett. 38, 087701 (2021).
- [53] S. Barzanjeh, A. Xuereb, S. Gröblacher, M. Paternostro, C. A. Regal, and E.M. Weig, Optomechanics for quantum technologies, Nature Phys. 18, 15 (2022).