





# **Design by Contract for Deep Learning APIs**

## Shibbir Ahmed

shibbir@iastate.edu Iowa State University USA

## Sayem Mohammad Imtiaz

sayem@iastate.edu Iowa State University USA

# Samantha Syeda Khairunnesa

skhairunnesa@fsmail.bradley.edu Bradley University USA

## Breno Dantas Cruz

bdantasc@iastate.edu Iowa State University USA

#### Hridesh Rajan

hridesh@iastate.edu Iowa State University USA

## **ABSTRACT**

Deep Learning (DL) techniques are increasingly being incorporated in critical software systems today. DL software is buggy too. Recent work in SE has characterized these bugs, studied fix patterns, and proposed detection and localization strategies. In this work, we introduce a preventative measure. We propose design by contract for DL libraries, DL Contract for short, to document the properties of DL libraries and provide developers with a mechanism to identify bugs during development. While DL Contract builds on the traditional design by contract techniques, we need to address unique challenges. In particular, we need to document properties of the training process that are not visible at the functional interface of the DL libraries. To solve these problems, we have introduced mechanisms that allow developers to specify properties of the model architecture, data, and training process. We have designed and implemented DL Contract for Python-based DL libraries and used it to document the properties of Keras, a well-known DL library. We evaluate DL Contract in terms of effectiveness, runtime overhead, and usability. To evaluate the utility of DL Contract, we have developed 15 sample contracts specifically for training problems and structural bugs. We have adopted four well-vetted benchmarks from prior works on DL bug detection and repair. For the effectiveness, DL Contract correctly detects 259 bugs in 272 real-world buggy programs, from well-vetted benchmarks provided in prior work on DL bug detection and repair. We found that the DL Contract overhead is fairly minimal for the used benchmarks. Lastly, to evaluate the usability, we conducted a survey of twenty participants who have used DL Contract to find and fix bugs. The results reveal that DL Contract can be very helpful to DL application developers when debugging their code.

## **CCS CONCEPTS**

• Software and its engineering  $\rightarrow$  Specification languages; • Computing methodologies  $\rightarrow$  Machine learning.



This work is licensed under a Creative Commons Attribution 4.0 International License.

ESEC/FSE '23, December 3–9, 2023, San Francisco, CA, USA © 2023 Copyright held by the owner/author(s). ACM ISBN 979-8-4007-0327-0/23/12. https://doi.org/10.1145/3611643.3616247

## **KEYWORDS**

Deep learning, API contracts, specification language

#### **ACM Reference Format:**

Shibbir Ahmed, Sayem Mohammad Imtiaz, Samantha Syeda Khairunnesa, Breno Dantas Cruz, and Hridesh Rajan. 2023. Design by Contract for Deep Learning APIs. In *Proceedings of the 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering (ESEC/FSE '23), December 3–9, 2023, San Francisco, CA, USA.* ACM, New York, NY, USA, 13 pages. https://doi.org/10.1145/3611643.3616247

#### 1 INTRODUCTION

Deep learning is a popular tool for solving complex software development problems such as NLP and vision, but research has shown that deep learning models also have unique bugs [33, 36, 37, 66]. To address this, SE researchers have focused on detecting and localizing these bugs [46, 57, 62]. In this work, we explore an alternative approach to improve the reliability of deep learning software, design by contract (DbC). Traditional DbC [19, 41, 43, 48] provides support for writing preconditions and postconditions at APIs. However, prior work does not provide mechanisms for documenting properties of the model architecture, data, and training process, which are crucial for applying DbC to deep learning APIs. Recent research has proposed techniques for inferring these properties, but DbC aims to provide specification mechanisms for programmers.

We propose a DbC methodology for deep learning libraries, called *DL Contract*. It exposes meta-level properties of the DL training process and model structure as variables, called *ML variable*, for use in writing contracts. Unlike grey-box contracts [23] that expose part of the program, *ML variable* provides a higher-level abstraction of the training process and model structure. They are similar to specification-only fields [27] in object-oriented programs [42, 49], but abstract away from the details of the DL model.

We have developed *DL Contract* for Python and a runtime assertion checking framework for *DL Contract*. We have applied contracts to key API methods of the *Keras* library and evaluated them using four benchmarks for deep learning bug detection from prior works [52, 57, 62, 65], comprising 272 *Keras* codes. Our results show that the *Keras* library with contracts can identify 95% of such bugs during runtime checking. Additionally, we have evaluated the annotation overhead of *DL Contract* and found it to be zero for users of DL libraries. This means that users do not need to add any contract annotations to their code in order to benefit from our approach. We have also added 15 contracts to the model compilation and training




Figure 1: Buggy code [2, 3, 6, 7, 9] achieves 9.78% training accuracy. Similar correct code [10] achieves ~ 99% training accuracy.

methods of the *Keras* API and evaluated 257 correct programs, finding 18 false positives due to the randomness effect during training. To evaluate the usability of the contract-enabled *Keras* library, we conducted a user study with 20 participants with varying levels of expertise in DL application development. We found that *DL Contract* enabled *Keras* is very helpful to developers in debugging DL software. Also, writing *DL Contract* and integrating *DL Contract* with *Keras* is an easier process for the API designers. Our evaluation also shows that the runtime overhead of checking contracts is fairly minimal. We obtained that the runtime overhead increases by around 15% compared to the baseline. *DL Contract* can be disabled during production to result in zero overhead.

Our contributions are as follows:

- A novel methodology for writing and checking contracts for deep learning libraries by specifying DL APIs with preconditions and postconditions.
- A framework [15] that is extensible and generalized to different classes of DL bugs and maps contract violation as a bug, symptoms as the constraint to check, and contract violation messages as suggestions to fix bugs.
- The notion of specifying DL-specific contracts by abstracting the DL model architecture, its data properties, and training behavior.
- A collection of 15 contracts that prevents prevalent training problems and structural bugs in DL programs.
- An annotated version of *Keras* with the *DL Contract* as a virtual environment (*@Keras*) [11]. Developers can use this *@Keras* environment for debugging without any annotation overhead and minimal runtime overhead (≈15%).

#### 2 MOTIVATION

To highlight the difficulty in specifying deep learning APIs and the need for *DL Contract*, consider a simple Convolutional Neural Network (CNN) code shown in Fig. 1. This code is intended for digit classification when implemented correctly, as outlined in the *Keras* documentation [10], it achieves 99% training accuracy on the MNIST dataset. In the correct version, images are normalized to the range [0,1] before being processed by a Sequential model with a specific layer architecture. The model is configured using the Compile API and trained using the Fit API, and the evaluate API is used to calculate the loss and accuracy.

However, as shown in Fig. 1, the code snippet contains three bugs (on lines 19, 20, and 22) which result in low accuracy and high training time. These bugs are specific to DL programs [62] and may not cause crashes. For example, on line 19, the incorrect activation function, 'relu' is used in the last layer of the Dense API [2, 5, 6]. Additionally, on line 20, the incorrect loss function of 'binary\_crossentropy' is applied in the Compile API [2, 3, 9]. Lastly, on lines 5 and 6, the data is not normalized before being fed into the Fit API [6, 7].

This example also illustrates another challenge for specifying DL APIs. All DL APIs work on a shared DL model, where early APIs construct the model and later APIs, such as fit, compile, and evaluate, make use of it. To write pre/postconditions for DL APIs, having access to only the formal parameters and return values of the APIs is not sufficient. Correct usage depends on the model state at the point of the API call. *DL Contract* addresses these challenges and can help prevent such bugs by providing a clear specification of the intended behavior of deep learning APIs.

#### 3 DEEP LEARNING CONTRACTS

In the *DL Contract* approach, we abstract the data properties, expected output, model architecture, and training behavior of a DNN model and specify the properties of DL APIs connected via a computation graph. We gather and inspect necessary conditions from three sources (details in §4.1). We filter out the obligations from the DL app developer as *preconditions* and expectations from DL software in as *postconditions*. Here, we use a novel runtime assertion check in DL computation. In the contract checker modules first parse those contracts and translate them into templates. Those templates are validated to handle the exception if it occurs. If a contract is violated, the user receives a contract violation message Otherwise, the API returns the normal execution output. Thus, our proposed solution generalizes to other bugs and model categories in this way. It would be easy for library developers to specify the contracts for other types of bugs following these procedures of *DL Contract*.

Next, we present the design and usage of *DL Contract*, including examples and our approach for abstracting DL related properties.

# 3.1 Writing Deep Learning Contract

*DL Contract* uses an annotation-based approach [18, 28] to add contracts to DL APIs, which allows library developers to add contracts without modifying compilers and build tools. This means that software using DL APIs does not need to be modified. DL library developers can add *preconditions* that must be satisfied before the API is called and *postconditions* that the API guarantees to be true upon completion.

3.1.1 Syntax. To use contracts in a deep learning library, it is necessary to annotate the API with @contract and @new\_contract. This allows library developers to create expressions for checking specified contracts. *DL Contract* can check types such as tensors and model objects, as well as simple data types like strings, floats, numbers, arrays, and booleans. It utilizes logical operators like AND(,) and OR(|) and allows for arithmetic and comparison expressions. Additionally, *DL Contract* can be used to check constraints of various model properties during training and abstraction.

3.1.2 Illustrative Example. To create a contract, a library developer annotates a DL API using @contract and @new\_contract. Inside @contract, the developer defines types and functions for checking contracts. Using @new\_contract, the developer writes functions for performing computations necessary for a contract and for checking preconditions and postconditions. For instance, in Example 3.1, a contract is imposed as a precondition on the *Keras* training function Fit to ensure that data is within a specified range before training. To prevent this type of bug, a function data\_normalization is declared as a contract definition using the @contract annotation (line 8) using the parameter x. Inside the @contract annotation, in the data\_normalization function (line 2), the developer further computes to get the range of training data, declared as normalization\_interval as a ML variable (line 3). The developer can specify the appropriate range of the ML variable within the contract checker function. The condition is checked on line 4 and if the contract is violated, a suggestion to fix the issue is raised on line 7.

```
1 | @new_contract
2 | def data_normalization(x):
3 | normalization_interval = np.max(x) - np.min(x)
4 | if(normalization_interval>2.0):
5 | msg = "Data should be normalized before training,train and test data should be divided by value " + str(np.max(x))
7 | raise ContractException(msg)
8 | @contract(x='data_normalization')
9 | def fit(self, x=None, y=None,...):
```

Example 3.1: A contract on Fit API inside Keras library

When a buggy DL program makes use of this annotated API, *DL Contract* will throw the following error.

| ContractViolated: Data should be normalized before training, train and test data should be divided by value 255.0.

Example 3.2 illustrates the use of *DL Contract* to prevent overfitting bugs [46], in which a model has high training accuracy but low test accuracy. A contract is specified on the validation loss and training loss to check for increasing differences in validation loss and decreasing differences in training loss [57], which is a common cause of overfitting. This expectation is encoded as a postcondition.

```
2
    def overfitting(history):
       while i <= (len(history.epoch)-2):
5
           enochNo = i + 2
           diff_loss = history['loss'][i + 1] - history['loss'][i]
 6
           diff_val_loss = history['val_loss'][i + 1]
8
           history['val_loss'][i]
10
           if(diff_val_loss > 0.0):
                if(diff_loss <= 0.0):
                   msg = "After Epoch"+str(epochNo)+",diff_val_loss='
12
                   +str('%.4f' % diff_val_loss)+"and diff_loss="
+str('%.4f' % diff_loss) + "causes overfitting"
13
15
                   raise ContractException(msg)
16
   @contract(returns='overfitting')
17 | def fit(self, x=None, y=None,...): return self.history
```

**Example 3.2: Overfitting Contract on Fit API** 

To prevent overfitting, a contract can be added to the output of the Fit method in *Keras* using @contract and a postcondition can be checked using the overfitting function specified with returns (line 16). In this function, the contract writer uses the obtained history object to compute diff\_loss and diff\_val\_loss (line 6-7) and checks if the difference between validation loss of consecutive epochs tends to increase while the difference between training loss continues to decrease. If this condition is not met, a contract violation message is thrown and when a buggy DL program uses this annotated API, *DL Contract* will throw an error.

```
| ContractViolated: After Epoch: 11, diff_val_loss = 0.34 and diff_loss = -0.12 causes overfitting.
```

#### 3.2 DL Contract Approach

Next, we present our approach and describe the technical challenges in DL contract checking, such as the need for context-aware *ML variable* (§3.2.1), assertion techniques (§3.2.2), and support for contracts across multiple APIs in the ML pipeline (§3.2.3). Also, we discuss our technique's support for post-training contract checking (§3.2.4).

3.2.1 Abstraction of DL-specific Properties to Contracts. To enforce DbC technique for deep learning APIs, a mechanism is needed to capture model abstraction, data properties, and training behavior beyond just the formal parameters and return values of the DL APIs. Standard contracts only enforce constraints on the values of formal

parameters and return values of an API method or attributes of an API class. Additionally, machine learning APIs are not isolated, but connected through a computational graph [16]. Therefore, specifying contracts on one API with its formal parameters alone is not sufficient in the DL-specific settings.

Fig. 2 describes a scenario in which the developer wants to add a contract to the method dense to ensure that the activation function for the last layer is not relu [8]. Additionally, the developer wants to check the appropriate loss function parameter for the Compile API Fig. 2. The problem with this scenario is that the conventional Design by Contract (DbC) technique cannot specify this contract on a model's API without causing false alarms in correct codes because it only allows for checking contracts on each API of a model.

To solve such problem, we design a way to write *DL Contract* using functions that allows to compute subset of meta-information with *ML variable* abstracting model architecture, data properties, training behavior. Fig. 2 shows one way to solve this challenge using *DL Contract*. In this solution, activation, and loss\_func are computed in specified @new\_contract contract\_checker functions where activation is the parameter of last layer Dense API and loss\_func is the parameter of Compile API. This is how *DL Contract* mechanism enables specifying and checking contract with abstracted model properties which works on any stage of computation graph pipeline.

3.2.2 DL Contract Runtime Assertion Technique. A model is more than what the configuration script defines. Many properties of the model only become tractable during training. As a result, a DL Contract must enable a runtime assertion technique that allows enforcing contracts beyond formal parameters, unlike traditional contract checkers. Furthermore, it must be possible to impose contracts on different pipeline stages of the modeling, i.e., data preprocessing, during model building, and training, etc. To that end, we propose a DL Contract checker with such capabilities by enabling library developers to annotate APIs. Eventually, DL Contract annotations benefit end-users to check their model, data properties, and training behavior at different stages in the DL pipeline.

Our method outlined in Algorithm 1 shows the steps involved in parsing and checking contracts in a library. It consists of two steps: registering new contracts defined by the library developer and parsing and validating newly defined contracts applied to the functions defined by the library developer. The framework inspects the library code base to find custom user-defined contracts defined as functions with the @new\_contract annotation. The usage of @new\_contract on a function invokes the register\_new\_contract method, which stores a reference to the function in a dictionary. This way of annotating contracts allows writing contracts using abstracted DL properties as discussed in section 3.2.1. For instance, if a library developer writes a contract with any of the properties of model object and checks as a precondition before model compilation or before model training, our technique allows doing that in this way (more details in Example 3.3) which is different than the traditional way of writing contract. The contract\_checker method is used to intercept and validate such contracts applied to user-defined functions with the @contract annotation before the function is executed. The method parses the annotation reference, obtains a

#### Algorithm 1 DL Contract Checker

```
1: procedure contract checker (userFRef, annoteRef)
       fArgs \leftarrow formal\ arguments(userFRef)
 3:
       \operatorname{argContrDict} \leftarrow parse\_contract(annotateRef)
 4:
       for each (fArg, cond) in argContrDict do
           aArg \leftarrow actual\_arguments(fArg, userFRef)
 5:
 6:
           template \leftarrow parse\_template(cond)
 7:
           template.check\_contract(aArg)
       returnCondition \leftarrow parse\_contract(annoteRef)
       aArgs \leftarrow actual\_arguments(userFRef)
       result \leftarrow userFRef(aArgs)
10:
11:
       returnTemplate \leftarrow parse\_template(returnCondition)
       returnTemplate.check_contract(result)
13:
       return result
14: procedure register New Contract (funcRef)
                                                                   ▶ @new contract
       identifier \leftarrow getFuncName(funcRef)
15:
       newContRegister[identifier] \leftarrow funcRef
16:
17: procedure parse_template (cond)
        if len(cond) > 1 then

    multiple conditions

           subclauses ←[]
20:
           for c \in cond do
21:
               subclauses \leftarrow parse\_template(c)
22:
           return And(subclauses)
23:
       if istype(cond) then
                                                                   ▶ if it is cond type
24:
           return CheckType(cond)
25:
       if cond \epsilon newContRegister then
                                                                     ▶ if it is callable
           return CheckCallable(newContRegister[cond])
```

dictionary of conditions applied to the function's arguments, and validates the conditions using the visitor design pattern.

Consider a contract, @contract(loss='str,contract\_func'). It validates the loss function and the validation takes place inside a user-defined contract, contract\_func. The contract body is stored in argContrDict as <loss, (str, contract\_func)>. Then, it obtains the value for the argument loss. The method parse\_template is used to obtain a validation tree for the conditions by composing validation classes (in Algorithm 2). In the example of loss contract, an And class is obtained, with each condition as a subclause. If the first condition, str, is satisfied, a CheckType validation class is returned. If the second condition is a user-defined function, a CheckCallable validation class is returned. The composed validation tree is returned in a template variable. Each validation class implements the method check\_contract. To validate the template, check\_contract is invoked on the root validation class, which is And. If validation fails for any subclause, And raises an exception. The argument on which a contract is imposed is validated. If preconditions are satisfied, the postconditions are validated. The returned result of the user function is validated as per written contracts.

3.2.3 Contextualized Inter-API Call Contracts. The next challenge is to ensure that *DL Contract* can be written involving multiple APIs at different stages of the DL pipeline. To solve this problem, *DL Contract* is designed to write multiple functions using @new\_contract annotations that take formal parameters across multiple DL APIs. For example, when the number of the target class is 2 (i.e., binary classification), the activation function of the last layer should not be softmax or relu [3, 5, 9] (which is a type of contract within the same Dense API) and loss function should be 'binary\_crossentropy' [2, 3] (which is an inter-argument contract with different APIs, i.e., between last layer and Compile API). Although the best activation function for hidden layers is ReLu [30], if ReLu is used on the last layer, it will set all the negative output to zero, thus




Figure 2: DL Contract approach using activation and loss functions involving multiple APIs in DL computation graph

```
Algorithm 2 Check Contract
 1: class CHECKCONTRACT
 2:
       procedure Abstract Check_Contract (Value)
 3: end class
 4: class CheckCallable(CheckContract)
       procedure INIT (FUNCREF)
 5:
           callable \leftarrow funcRef
 6:
       procedure CHECK_CONTRACT (VALUE)
 7:
           if callable(value) raised exception then
 8:
 9.
              raise contractException()
10: end class
11: class And(CheckContract)
       procedure INIT (SUBCLAUSES)
13:
           subclauses ← subclauses
14:
       procedure CHECK_CONTRACT (VALUE)
15:
           \mathbf{for} \ \mathsf{sc} \in \mathsf{subclauses} \ \mathbf{do}
16:
              if sc.check_contract(value) raised exception then
                  raise contractException()
17:
18: end class
19: class CheckType(CheckContract)
20:
       procedure INIT (TYPE)
21:
           expected\_type \leftarrow type
22:
       procedure CHECK_CONTRACT (VALUE)
           \texttt{actual\_type} \leftarrow \textit{getActualType}(\texttt{value})
23:
24:
           if actual type ∉ expected type then
25:
              raise\ contractException()
26: end class
```

leading to an accuracy problem. To prevent such kinds of problems in model architecture, library developers can write *DL Contract* using the activation and loss function for the binary and multi-class classification according to the experts' suggestion [2, 3]. Our insight is that such types of contracts can be added to deep learning model-compilation API, i.e., *Keras* Compile, exposing objects capturing the entire model properties.

```
1 | @new_contract
2 | def contract_checkerfunc1(model):
3 | last_layer_output = int(str((model.layers[len(model.layers) + 1]).output_shape).split(',').pop(-1).strip(')'))
5 | activation_func = str(model.layers[len(model.layers) - 1].
```

```
getattribute__('activation')).split()[1]
          if (last_layer_output >= 3):
              if (activation_func not in 'softmax'):
    msg1= 'For multiclass classification activation_func
 8
 9
10
                    should be softmax'
11
                    raise ContractException(msg1)
12
    @new_contract
         contract_checkerfunc2(loss):
      if (loss not in 'categorical_crossentropy'):
    msg2 = 'loss should be categorical crossentropy'
14
15
            raise ContractException(msg2)
16
17
    @contract(self='model, contract_checkerfunc1')
    @contract(loss='str, contract_checkerfunc2')
19 | def compile(self.optimizer='rmsprop'.loss=None.metrics=None....):
```

Example 3.3: Last layer activation and loss function contract on *Keras* Compile API

Example 3.3 shows last layer activation and loss function contract applied to Keras Compile API, which asserts before Compile API execution. Here, contract\_checker1 has been annotated with model object type on line 17 and contract\_checker2 has been annotated using loss parameter with string type on line 18. Here, last\_layer\_output and activation\_func are computed on line 3 and line 5 from model object. The loss function has been a formal parameter of Compile API, and contract\_checkerfunc2 checks the condition on line 14 and shows a message with suggestions to fix if a contract violation occurs for both Dense and Compile APIs. As those specified contacts are ANDed one after another for one contract (last layer activation and loss function), 'contract checkerfunc2' is only executed if 'contract checkerfunc1' is executed. Since 'contract checkerfunc1' checks whether the number of classes ≥ 3, then 'checkerfunc2' would also know if the program runs a multiclass classification. In Example 3.3, on lines 17-18, 'contract\_checkerfunc1' and 'contract\_checkerfunc2' have been enforced together. A case of that contract violation is shown below.

```
| ContractViolated: For multiclass classification activation_func should be softmax, loss should be categorical crossentropy.
```

3.2.4 Post-training Contracts. The challenge of capturing DNN training behavior at different stages of the DL pipeline can be addressed with our proposed DL Contract. Library developers can specify desired training behavior for their DL software by adding training-related contracts on properties such as, gradients rate, gradients percentage etc. Training behavior-related properties indicate the expected output from the DL model, so this is a postcondition. The root cause behind a training problem could be client obligation in hidden layers APIs such as activation function, which is a parameter of Dense API (this is a precondition) We might encounter such types of preconditions and postconditions in DL-specific settings, and contracts can be specified using @new\_contract and @contract annotations in our proposed approach. To handle such cases, DL Contract advocates specifying contracts as postconditions on DL training APIs, e.g., Keras Fit API, which provides detailed training history. Based on the supplied contract checking function in @new\_contract, we compute relevant training properties from the history object such as validation accuracy, loss value, gradient rate etc. Algorithm 1 (lines 8-13) describes how we check and validate postconditions in our framework. Example 3.2 demonstrates this type of postcondition contract.

## 4 EVALUATION

In this section, we aim to answer the following research questions:

- **RQ1** (Effectiveness): How effective is *DL Contract* in real world programs?
- **RQ2** (Applicability): Is *DL Contract* enabled *Keras* applicable to find performance (i.e., low accuracy, high training time) bugs?
- **RQ3** (Efficiency): How efficient is *DL Contract* for detecting DL performance bugs in terms of precision and recall?
- **RQ4** (Overhead): What is the overhead of the *DL Contract* compared to related works in terms of runtime?
- **RQ5** (**Usability**): How useful is the *DL Contract* enabled *Keras* in developing DL Apps?

First, in order to evaluate our approach, we collect contracts by following the procedure described in  $\S4.1$ . We implemented *DL Contract* (in  $\S4.2$ ) using our proposed approach (in  $\S3.2$ ). Then we conducted experiments using the setups (in  $\S4.3$ ). Finally, we report results and analysis (in  $\S4.4$ ).

## 4.1 Deep Learning Contracts Collection

In this section, we describe the process of contract collection used in the evaluation. We have identified contracts related to the model, data, and training properties. These contracts prevent structure and training bugs, which lead to performance issues (i.e., low accuracy, high training time). DL libraries like *Keras* does not provide error messages for such types of bugs yet. Fig. 3 shows how we collected the conditions of *DL Contract*. In 1, we abstract the data properties, expected output, model architecture, training behavior of a DNN model. In 2, we gather and inspect necessary conditions from three sources. We used the official *Keras* library documentation [4]. In particular, we followed the selection criterion from DL bugs from prior works [34, 36, 37] while focusing on the APIs used for model compilation and training. Again, we collected a list of state-of-the-art research articles and their benchmarks of buggy and

Table 1: Collected contracts targeting DNN structural and logical bugs, improper data, and training problems

	Class of bugs	DL Contract							
Data bugs	Data a second limiting workland	Decoration consultation interest?							
1	Data normalization problem	Precondition: normalization_interval≤2, Postcondition: True							
	Incorrect activation and loss	Precondition: activation='linear tanh', loss_func='mse',							
gi	function: regression	Postcondition: True							
<u>ة</u>	Incorrect activation and loss	Precondition: activation='sigmoid', loss_func='binary_crossentropy',							
g;	function: binary classification	Postcondition: True							
≗	Incorrect activation and loss	Precondition: activation='softmax',							
1 1	function: multiclass classifica-	loss_func='categorical_crossentropy',							
=	tion	Postcondition: True							
🖺	Incorrect activation and loss	Precondition: activation='sigmoid', loss_func='binary_crossentropy',							
l t	function: multilabel multiclass	Postcondition: True							
Structural and logic bugs	classification								
,	Incorrect activation in hidden	Precondition: activation !=linear,							
	layers	Postcondition: True							
	Incorrect hyperparameter	Precondition: learn_rate >0.0000007,<0.01, Postcondition: True							
	Overfitting	Precondition: True, Postcondition: diff_val_loss<0, diff_loss≤0							
ا ہا	High validation accuracy	Precondition: True,							
Training problem		Postcondition: val_acc_threshold<0.95, diff_val_acc_train_acc<0.05							
<u>ا جو</u>	High dropout rate	Precondition: dropout_rate>0.5							
ᆲ	Dying relu	Precondition: activation!='tanh exponential relu sigmoid'							
180		Postcondition: zero_gradients_percentage $\leq \lambda$							
I 🖫	Vanishing gradient	Precondition: activation!='tanh exponential relu sigmoid'							
Ţā.		Postcondition: gradients_rate $> \beta_1$ , norm_kernel $> \zeta$							
F	Exploding gradient	Precondition: activation!='tanh exponential relu sigmoid'							
		Postcondition: gradients_rate_EG<\(\beta_2\), gradient_value!=nan							
	Oscillating loss	Precondition: True,							
		Postcondition: accuracy_fluctuation_rate $\leq \eta$ , val_acc_diff >= $\delta$							
	Slow convergence	Precondition: True, Postcondition: acc_diff $\geq = \delta$							




Figure 3: Methodology to collect deep learning contracts

correct DL programs [34, 36, 37]. The selection criterion for these articles is that if the work in question solves DL performance bugs and renders the conditions that lead to these bugs. We filter out the obligations from DL app developer as *preconditions* (in 3) and expectation from DL software as *postconditions* (in 4). This process resulted in the collection of 15 contracts. A detailed table( Table 1) with collected contracts with corresponding bugs are shared in the supplementary material [12].

### 4.2 Implementation

To implement *DL Contract*, we extended the open-source package *PyContracts* [32]. *PyContracts* allows developers to declare constraints on method parameters and return values. We have extended *PyContracts* to support tensor, model types, as existing DL APIs require additional preconditions and postconditions [39]. We have addressed all the technical challenges described in §3.2.

## 4.3 Experimental Setup

To evaluate *DL Contract* on *Keras*, we modify the library by importing the extended *PyContracts* package in library codes. We also decorate respective *Keras* APIs with relevant implemented contracts that prevent performance bugs (in §4.1). We have conducted all the experiments on a machine with a 2 GHz Quad-Core Intel Core i7 and 32 GB 1867 MHz DDR3 RAM running the macOS 11.14.

Table 2: Effectiveness of DL Contract in real world programs targeting different class of bugs using collected benchmarks

DI Contro eta torrest	ing along of bugs	Deep	Localize	UM	LAUT		AUTO	TRAINER		NeuraLint		#Contract
DL Contracts targeting class of bugs			GH	CIF-10	FMNIST	Blob	Circle	MNIST	CIF-10	so	GH	Violation
Improper Data	Data normalization problem	5	2	1	1	-	-	-	-	1	1	11
	Incorrect activation & loss function	17	5	1	1	-	-	-	-	6	5	35
Structural bugs	Incorrect activation in hidden layers	3	1	1	1	-	-	-	-	-	-	6
	Incorrect learning rate	1	1	1	1	-	-	-	-	-	-	4
	Overfitting		-	-	-	-	-	-	-	-	-	1
	High validation accuracy	2	1	1	1	-	-	-	-	-	-	5
	High dropout rate	1	1	1	1	-	-	-	-	1	-	5
Training problem	Dying relu	1	-	-	-	4	9	23	36	-	-	73
Training problem	Vanishing gradient	-	-	-	-	16	36	34	35	-	-	121
	Exploding gradient	-	-	-	-	11	18	21	20	-	-	70
	Oscillating loss	1	-	-	-	1	3	1	-	-	-	6
	Slow convergence	5	2	-	-	28	41	19	42	-	-	137

<sup>\*</sup> Numbers represented total contract violations in real world buggy programs from DeepLocalize, UMLAUT, AUTOTRAINER, NeuraLint benchmarks; SO, GH, CIF-10 indicates benchmark from Stack Overflow, GitHub, CIFAR-10 respectively, "-" indicates contracts are satisfied and did not trigger a violation in buggy programs.

Table 3: Applicability of *DL Contract* comparing against *Keras* Callbacks, Deeplocalize [62] and *DL Contract* (full table [14])

DeepLocalize	DeepLocalize						I	Buggy Cod	le						Correct Code			
Benchmark		Original	TOnNaN E		ES('1	('loss') ES('accuracy')		Union (TOnNaN, ES)		DeepLocalize		DL Contract		Original	DL Contract	RT		
Source	#	RT	RT	Bug#	RT	Bug#	RT	Bug#	RT	Bug #	RT	Bug#	RT	Bug#	RT	RT	Overhead	
StackOverflow	30	42.20	30.15	2	24.92	19	24.76	23	18.53	27	447.05	27	6.41	29	34.60	37.93	0.22	
GitHub	11	352.90	439.88	0	299.18	6	269.70	7	160.77	7	2772.77	7	9.23	10	345.04	27.37	0.23	

<sup>\*</sup> Total detected bugs in buggy and correct codes (#), Keras debugging TerminateOnNan (TOnNan), EarlyStopping(monitor='loss') (ES(loss), EarlyStopping(monitor='accuracy') (ES(accuracy))

Table 4: Applicability of DL Contract, Runtime comparison between UMLAUT callback [57] and DL Contract

			Buggy Code			Correct Code								
	Original	Original UMLAUT			Contract	Original	UMLAUT	DL Contract	UMLAUT	DL Contract				
Benchmark	Runtime	Bug	Runtime	Bug	Runtime	Runtime	Runtime	Runtime	Runtime Overhead	Runtime Overhead				
A1 (CIFAR-10)	1318.99	Y	8.85	Y	28.52	1376.04	1455.99	1353.81	1.06	0.02				
A2 (CIFAR-10)	1483.26	Y	8.93	Y	24.80	1459.21	1384.75	1478.52	0.95	0.01				
A3 (CIFAR-10)	1455.93	Y	140.98	Y	23.56	1483.29	1251.69	1497.94	0.84	0.01				
B1 CIFAR-10	1493.12	Y	152.57	Y	16.28	1420.40	1049.76	1438.59	0.74	0.01				
B2 (CIFAR-10)	1319.18	Y	8.85	Y	26.58	1448.27	792.97	1440.55	0.55	0.01				
B3 (CIFAR-10)	1692.83	Y	664.60	Y	669.83	1463.87	795.15	1499.39	0.54	0.02				
A1 (F-MNIST)	17.09	Y	7.02	Y	23.25	16.84	15.55	22.76	0.92	0.35				
A2 (F-MNIST)	17.04	Y	9.61	Y	18.62	16.36	15.59	24.57	0.95	0.50				
A3 (F-MNIST)	15.69	Y	9.61	Y	18.30	16.36	14.34	23.52	0.88	0.44				
B1 (F-MNIST)	17.90	Y	9.87	Y	21.06	15.93	14.96	22.92	0.94	0.44				
B2 (F-MNIST)	15.96	Y	7.16	Y	18.94	16.96	14.48	23.93	0.85	0.41				
B3 (F-MNIST)	17.62	Y	12.31	Y	31.85	15.39	14.85	24.06	0.96	0.56				

Benchmark selection: To answer the RQs, we compare and contrast *DL Contract* against four recently-published DL performance bug localization benchmarks [52, 57, 62, 65]. The *DeepLocalize*'s benchmark proposed by Wardat *et al.* [62] consists of 41 executable *Keras* codes with buggy and correct versions of DL programs from *Stack Overflow* (30) and GitHub (11). For the *UMLAUT* benchmark [57], we followed their procedure. AUTOTRAINER [65] reported their tool's results on 495 DL programs where 262 have training problems Here, we have utilized 4 out of 6 datasets which are comprised of sequential models. NeuraLint [52] utilized a total of 63 buggy programs of crash and performance bugs. We have used 16 buggy programs from the benchmark which does not yield crash bugs. We have considered all 4 of these benchmarks as "unseen" because we have not seen their buggy and correct programs before writing and implementing contracts.

**Metrics:** We recorded the total execution time utilization for all techniques when analyzing buggy and correct programs from the benchmarks and computed overhead. Also, we recorded how many bugs were detected by each approach. For computing the efficiency

of *DL Contract*, we utilize performance metrics as precision, recall following prior work [46, 65].

We consider the benchmarks as ground truth for buggy and correct programs. Here, a false positive indicates that a bug was detected in the correct program. True positive represents if a bug is detected in a buggy program. A false negative indicates that there is no bug detected in a buggy program. Lastly, if there is no bug detected in a correct program, we consider that as a true negative.

We collected the real-world time elapsed between the program entry and program exit using the python time module. We collected this information for both correct and buggy programs five times to reduce randomness, following [61, 65]. To isolate the other process and void interference in this experiment, we executed only one program under analysis in a standalone environment inside the IDE. We start recording the time from the beginning of a DL program until the first contract violation has been thrown, and the rest of the execution is halted in the buggy program. For the correct program and if there is no contract violation, we obtained the elapsed time until the complete execution of the program.

## 4.4 Results and Analysis

4.4.1 RQ1 (Effectiveness). To demonstrate the effectiveness of DL Contract in real-world programs, we have utilized 4 benchmarks of DL performance bugs. Table 2 shows the results of DL Contract targeting different class of bugs. We have developed a total of 15 contracts and annotated on model compilation and training Keras APIs using DL Contract approach targeting different classes of bugs related to improper data, structural bugs, and training problems. In particular, each row represents the number of contract violations in buggy programs where DL Contract successfully detected bugs and terminated the program execution. We observe that in the last 'Contract Violation' column, those 15 contracts trigger a total of 474 contract violation messages in 272 buggy programs. In Table 2, "-" indicates contracts were used but did not trigger a violation for that class of bugs. For example, AUTOTRAINER mainly focuses on training problems, which is why there is no contract violation involving structural and improper data-related bugs. Those contracts (postcondition) violations have been triggered by DL Contract using abstracted training properties. DeepLocalize, UMLAUT, NeuraLint benchmarks consist of structural and data bugs, that precondition violation triggers using ML variable related to model abstraction.  $DL\ Contract\ {\rm did}\ {\rm not}\ {\rm detect}\ {\rm bugs}\ {\rm in}\ 13\ {\rm out}\ {\rm of}\ 272\ {\rm programs}.$  We have investigated these undetected bugs and discussed in §4.4.2. We also evaluated that the same 15 contracts were used in 257 correct programs in benchmarks. We found 18 contract violations as false positives, mainly due to randomness factor [55, 67] during training. In summary, DL Contract is efficient in real-world DL programs.

4.4.2 RQ2 (Applicability). Table 3, 4, 5, and 6 show the applicability of *DL Contract* on real-world benchmarks comprising of performance bugs in DL software. Each table highlights and summarizes the results of Buggy and Correct programs.

Table 3 shows the summary of the results [14] of deploying the *DeepLocalize* benchmark. Please refer to supplementary material [15] for more details. Table 3 shows that *DL Contract* can detect **39 out of 41 buggy programs** with precise contract violation messages. Out of these results, 29 are from *Stack Overflow* and 9 out from GitHub. Also, when compared with *Keras* and *DeepLocalize* callbacks. *Keras* debugging techniques *TerminateOnNan*, *EarlyStopping(monitor='loss')*, *EarlyStopping(monitor='accuracy')* and *DeepLocalize* can detect 2, 24, 28, 32, and 34 respectively [62]. Again, 2 out of 41 were not detected from DeepLocalize [62] benchmark. SO52800582 and GH[2] were missed because generalized contracts cannot be applied on weight initialization and optimizer. Finally, regarding bug detection speed, *DL Contract* is 200 times faster than *DeepLocalize* and 11 times faster than *Keras* callbacks.

Table 4 shows that *DL Contract* applies to all **12 buggy programs** from the *UMLAUT* benchmark. In terms of computation overhead, we observed *DL Contract* has lower runtime than *UMLAUT* (in §4.4.4). Lastly, we have manually verified the contract breaches reported by *DL Contract* and found no false alarms for buggy programs.

Table 5 shows that *DL Contract* has detected **195 bugs in 203 buggy programs** in the AUTOTRAINER benchmark. While *AUTOTRAINER* reports the symptoms of 5 training problems, *DL Contract* detects bugs as postcondition violations. We observed that both approaches detect the Slow Change in accuracy (SC) more often than

the other four symptoms. 8 out of 203 buggy programs in AUTO-TRAINER [65] benchmark were not detected due to the randomness in DNN training. In terms of runtime, *DL Contract* is slightly faster than *AUTOTRAINER*. In particular, *DL Contract* takes on average 241.19 seconds, while *AUTOTRAINER* 248.43 seconds. Lastly, **out of 188 correct programs**, *DL Contract* misdetected 3 programs. Further investigation revealed that those misdetections were due to data normalization issues, unsupported by *AUTOTRAINER*.

Table 6 shows how DL Contract performs on 16 bugs compared to the NeuraLint tool. DL Contract detected 13 out of 16 bugs in the NeuraLint benchmark. 3 out of 16 from the NeuraLint benchmark [52] were missed because we investigated that we had no layer properties related contracts written. NeuraLint detects 14 out of 16 bugs but *DL Contract* requires less time than *NeuraLint*. In particular *DL Contract* on average required 5.10 seconds while NeuraLint 9.80 seconds. These buggy programs use common API methods such as Compile and Fit, which were annotated with 15 DL Contracts. These 272 buggy programs have common root causes and symptoms. For instance, AUTOTRAINER [65] benchmark consists of 203 buggy programs, with 5 different training problems. By writing 5 contracts on the fit method targeting those problems, DL Contract detects 195 out of 203 bugs. In summary, DL Contract is applicable to detect performance bugs in real-world buggy programs with good accuracy.

4.4.3 RQ3 (Efficiency). We have measured the efficiency of DL Contract using 4 benchmarks DeepLocalize [62], UMLAUT [57], AUTOTRAINER [65], NeuraLint [52] (in Table 7). We have evaluated 257 correct (clean) real-world programs and found 18 false positives. We have found 10 FPs in DeepLocalize, 0 in UMLAUT, 3 in AUTOTRAINER, and 5 in NeuraLint benchmark. In terms of efficiency, our evaluation results show that DL Contract has similar accuracy to UMLAUT (12 TPs and no FPs) but has lower time consumption (in Fig. 4). Regarding the AUTOTRAINER benchmark, DL Contract could not detect bugs due to the accuracy threshold [65] (0.6) due to randomness factor during training. Regarding the NeuraLint benchmark, we observed 3 FN. As DL Contract does not have contracts on layer properties yet. Compared to other tools using DeepLocalize benchmark, we found DeepLocalize, AUTOTRAINER, UMLAUT, NeuraLint, DeepDiagnosis [61] resulted in 19, 14, 14, 35 TP and 22, 27, 23, 6 FN respectively [13]. DeepDiagnosis reported 70 FP and 67 FN in correct codes from AUTOTRAINER benchmark. In summary, DL Contract efficiently detects performance bugs in real-world buggy programs.

Superiority of DL Contract: Prior work specifically DeepLocalize [62], UMLAUT [57], AUTOTRAINER [65], DeepDiagnosis [61] and NeuraLint [52] are not comprehensive enough to detect different classes of structural and training bugs. Furthermore, these approaches depend on specific implementations such as model format (.h5), semantic change in model architecture, and rely upon additional debugging or verification facilities, e.g., Keras callbacks (DeepLocalize, UMLAUT, AUTOTRAINER), and Groove model checker (NeuraLint). Also, DeepLocalize, UMLAUT, NeuraLint did not compute FP and FN. AUTOTRAINER computed FP, FN only with AUTOTRAINER benchmark. All 4 baseline techniques did not compare against any other benchmarks except their own benchmarks. DeepLocalize [55] invokes callbacks after each epoch and computes

Table 5: Applicability of DL Contract, Runtime (RT) comparison with AUTOTRAINER [65] (AT) and DL Contract (DLC)

	Buggy											Correct									
Benchmark					AT			DLC												Overhead	Overhead
			D	etected	Sympto	ms#			Postcondition Violation #						Original		AT		DLC	AT	DLC
Dataset	#	VG	EG	DR	SC	OL	RT	VG	EG	DR	SC	OL	RT	#	RT	Sym #	RT	Viol #	RT	Runtime	Runtime
Blob	48	12	10	8	29	4	13.83	6	5	4	30	1	11.95	39	8.62	0	9.22	0	11.79	0.070	0.368
Circle	71	10	10	9	43	7	16.50	10	8	9	41	3	11.54	36	16.06	0	12.28	2	16.27	0.235	0.013
CIFAR-10	46	5	8	3	28	2	1302.06	5	16	37	43	0	487.43	35	1186.50	0	1898.54	0	1528.16	0.600	0.288
MNIST	38	8	3	4	21	8	688.02	8	13	23	19	1	423.55	78	466.22	0	535.90	2	535.51	0.149	0.149
Total/ Avg	203	35	31	24	121	21	505.10	29	42	73	133	5	233.62	188	419.35	0	613.99	4	522.93	0.464	0.247

\* Count (#), Vanishing Gradient (VG), Explode Gradient (EG), Dying Relu (DR), Slow Change in Accuracy (SC), Oscillating Loss (OL), Symptom (Sym), Contract Violation(Viol)

Table 6: Applicability of *DL Contract*, Runtime overhead comparison with NeuraLint [52] and *DL Contract* 

			Buggy Code			Correct Code									
	Original	Ne	uraLint	DL	Contract	Original	NeuraLint	DL Contract	Runtime Overhead	Runtime Overhead					
Benchmark	Runtime	Bug	Runtime	Bug	Runtime	Runtime	Runtime	Runtime	NeuraLint	DL Contract					
50555434	2.73	Y	18.72	Y	4.77	2.66	6.29	4.78	1.37	0.80					
34311586	3.17	Y	9.62	Y	4.81	3.09	3.18	5.12	0.03	0.66					
50079585_1	2.88	Y	18.02	Y	5.11	2.75	6.52	4.92	1.37	0.79					
51749207	2.80	Y	17.89	Y	4.87	2.68	5.89	4.84	1.20	0.81					
58844149	3.03	Y	8.46	Y	5.06	2.89	6.28	5.01	1.17	0.73					
33969059	5.20	Y	5.20	Y	6.53	2.62	2.64	4.63	0.01	0.77					
44322611	2.93	Y	8.80	N	4.94	2.62	2.69	4.62	0.02	0.76					
55776436	3.11	Y	10.78	Y	5.27	3.04	3.06	5.15	0.01	0.69					
60566498	2.87	Y	16.57	Y	4.74	2.74	7.38	4.86	1.69	0.77					
GH 1	2.90	Y	5.13	Y	5.04	2.96	7.71	4.97	1.60	0.68					
GH 2	2.83	Y	5.52	N	4.91	2.80	6.94	4.86	1.48	0.74					
GH 3	3.05	Y	5.51	Y	4.96	3.00	6.70	4.89	1.23	0.63					
GH 4	4.43	Y	8.50	N	6.44	4.04	137.13	5.99	32.94	0.48					
GH 5	2.78	Y	7.42	Y	4.88	2.78	6.38	4.82	1.30	0.74					
GH 6	2.74	N	5.20	Y	4.69	2.68	6.14	4.66	1.29	0.74					
GH 7	2.72	N	5.39	Y	4.59	2.71	5.97	4.61	1.20	0.70					
Total/Average	3.14	14	9.80	13	5.10	2.88	13.81	4.92	2.99	0.72					

Table 7: DL Contract efficiency on different buggy and correct benchmarks

	DL Contract											
Benchmark	FP	TP	FN	TN	Precision	Recall						
DeepLocalize	10	39	2	31	0.80	0.95						
UMLAUT	0	12	0	12	1.00	1.00						
AUTOTRAINER	3	195	8	185	0.98	0.96						
NeuraLint	5	13	3	11	0.72	0.81						

metrics to detect numeric bugs which take lots of time. *AUTOTRAINER* [58] requires the model in a specific format and needs to finish the training to detect bugs and then provide solutions as fixes. In the case of UMLAUT [50], without a semantic change of model, the tool will report a false alarm. *NeuraLint* [48] requires graph computation from the model and performs static checking with some specified rules which yield a longer runtime.

4.4.4 RQ4 (Overhead). We have computed the runtime overhead of DL Contract using UMLAUT, DeepLocalize, NeuraLint, and AUTOTRAINER benchmark. Figure 4 shows the runtime overhead of DL Contract. DL Contract (DLC) runtime overhead is lower than the one of all approaches. In particular, DL Contract is 4.31, 3.69, 1.85, and 4.15 times more efficient in terms of runtime overhead than DeepLocalize, UMLAUT, AUTOTRAINER, and NeuraLint. The runtime overhead of DL Contract is minimal because the technique only checks model structure-related preconditions before model compilation API and training-related postconditions before training. Unlike techniques DeepLocalize, UMLAUT, AUTOTRAINER, that rely on Keras callbacks, DL Contract does not invoke model




Figure 4: Comparison of runtime overhead

compilation or training APIs multiple times to monitor metrics periodically during or after training. Specifically, *NeuraLint* requires graph computation from model and performs static checking with some specified rules, yielding longer runtime. Also, We measured that the runtime overhead increases by around 15% compared to the baseline *Keras. In summary, DL Contract incurs less runtime overhead compared to existing deep learning debugging tools.* 

4.4.5 RQ5 (Usability). We have evaluated the usability of DL Contract annotated Keras in terms of its usefulness to find and fix bugs while developing DL programs. Also, we evaluate separately the efforts of API designers to write and integrate DL Contract. To that end, we perform a user study following IRB guidelines and collected feedback on using DL Contract annotated Keras.

**RQ5.1** (Usefulness): How useful is the *DL Contract* enabled *Keras* in developing DL Apps?

**RQ5.2 (Easiness)**: How easy is to write *DL Contract* and integrate it with DL library APIs?

**Participants:** After following similar procedure [24, 57] from prior work we recruited 20 participants from university mailing lists for our study (17 Ph.D., 2 MS students, and a Post-doc). Participants were asked to self classify their level of expertise from 1 - beginner to 5 - expert and we obtained their expertise level: programming ( $\mu = 3.3$ ,  $\sigma = 1.0$ ), debugging ( $\mu = 2.9$ ,  $\sigma = 1.4$ ), using existing neural networks ( $\mu = 2.9$ ,  $\sigma = 1.1$ ), and developing new DNNs ( $\mu = 2.5$ ,  $\sigma = 1.2$ ), and developing other ML algorithms ( $\mu = 2.7$ ,  $\sigma = 1.3$ ). So, the average/mean ( $\mu$ ) of the expertise levels is more than 2.5 in all of the 20 selected participants.

Study Design, Procedure and Tasks: Participants completed an hour-long online study on their machines. Each participant completed two sessions with corresponding tasks. After each session, participants completed survey questions online via Qualtrics. For RQ5, in session 1, we provided the necessary environment to execute buggy programs in regular Keras (baseline condition) and DL Contract enabled Keras. We provided 3 buggy versions of randomly chosen real-world programs with 3 different performance bugs related to model architecture, data properties, and training behavior. The buggy programs have low accuracy and high training time issues. We asked the participants to execute the buggy programs using both regular Keras and DL Contract enabled Keras. Then, we asked participants to detect and fix the buggy programs by using the outputs from both regular Keras and DL Contractenabled *Keras*. Finally, we asked participants the survey questions regarding their experience using DL Contract. For RQ5, in session 2, we first provide tutorial to participants on how to write contracts on Keras API. Then, we asked them to write 3 similar contracts with instructions. After completing the sessions, participants filled up a survey indicating their experience while using DL Contract enabled Keras to detect and fix bugs as a DL application developer. In that survey, participants also shared their experience about the writing process of *DL Contract* as a library developer. The details of the survey questions for session 1 and session 2 are provided in the supplementary material [15].

Results and Discussion: RQ5.1 (Usefulness): For all 3 buggy programs in session 1, none of the participants was able to find any of the bugs in the baseline condition (regular *Keras*). That is because Keras does not inform users about such types of performance bugs. However, participants were able to detect and fix the bugs by following DL Contract enabled Keras's contract violation messages. Furthermore, survey responses indicate that DL Contract enabled Keras helps participants to detect and fix bugs efficiently. In particular, on a 5-point Likert scale questions (1 = Not helpful to 5 = Very Helpful), participants rated their experience on questions. Participants indicated that, DL Contract enabled Keras was very helpful to 65% ( $\mu = 4.55$ ,  $\sigma = 0.67$ ) in detecting bugs in deep learning programs that yield unexpected performance (low accuracy, high training time). 25% rated helpful (rating 4), and 10% of participants rated reasonably helpful (rating 3). Therefore, 90% of the participants responded positively (rating > 3) regarding this criteria. Likewise, 95% of participants rated positively (rating > 3) about the message from DL Contract fixing those bugs ( $\mu = 4.75$ ,  $\sigma = 0.54$ ).




Figure 5: Survey results with participants ratings on how useful is *DL Contract* enabled *Keras* in developing DL Apps

Again, 90% of the participants rated positively (rating > 3) specifically, 55% of the participants indicates that it would be very useful to develop DL applications ( $\mu$  = 4.45,  $\sigma$  = 0.67). If participants are involved in doing a class or research project that requires DNNs, 80% rated positively especially, 55% of the participants rated *DL Contract* enabled *Keras* as very helpful ( $\mu$  = 4.30,  $\sigma$  = 0.90).

*RQ5.2 (Easiness):* Regarding how easy is to write *DL Contract* on top of *Keras* APIs, we have obtained that 65% of the participants rates the writing process of a contract to *Keras* positively (Rating > 3). Regarding the rating of the writing process of a contract to *Keras*, the participants' rating ( $\mu = 3.8$ ,  $\sigma = 0.67$ ) is moderate (35%), easy (50%), very easy(15%) as illustrated in Fig. 6. About the integration of the written contract with *Keras* library, 60% of the participants rated positively ( $\mu = 3.75$ ,  $\sigma = 0.69$ ). The detailed breakdown rating of integration of the written contract with *Keras* library, the participants' ratings is moderate 40%), easy (45%), very easy(15%) as shown in Fig. 6. *In summary, we have evaluated that DL Contract enabled Keras is very helpful to developers in debugging DL software, and writing and integrating DL Contract is very easy to <i>API designers*.




Figure 6: Survey results with participants ratings on how easy is to write *DL Contract* on DL library APIs

#### 4.5 Limitations

Our proposed *DL Contract* approach has been evaluated primarily on problems related to multilabel, multiclass, binary classification, and regression with various structural and logical bugs in the sequential DNN model architecture and common training issues. Further research is needed to apply and evaluate our approach for other types of bugs and model categories. Despite this, the concept of using contracts in deep learning is not limited to *Keras* and can

be extended to other DL libraries. While our paper illustrates the idea of deep learning contracts for *Keras*, our contribution can be generalized to other DL libraries like TensorFlow, PyTorch. We focused on *Keras* to keep the implementation effort manageable and leverage this library's large body of benchmarks.

# 4.6 Threats to Validity

Our proposed approach may be affected by external threats, such as imprecise precondition and postcondition definitions obtained from library documentation, *Stack Overflow* posts, and GitHub commits. However, we have adopted definitions from recent research studies [37, 46, 66] to mitigate this. Threshold parameters may also cause false positives in some new real-world programs. Additionally, implementation using *PyContracts* may have unforeseen internal threats, but our general open-source framework can be extended using reproducible package [15] with detailed results.

#### 5 RELATED WORK

Specification of Deep Neural Networks: The closest related ideas in the specification of DNNs include [31, 58, 59]. While [58] provides an overview of the opportunities and challenges of formalizing and reasoning about DNN properties, it does not propose any methodology for writing and checking specifications for deep learning libraries. In contrast, [31] presents a technique for computing input and layer properties from a feed-forward network using input-output characterizations as formal contracts. Additionally, [59] introduces a method for repairing neural network classifiers by inferring the correct specifications. Both [31] and [59] propose inference techniques, while our technique proposes a specification and checking technique that enables the specification of DL libraries and checks those contracts in client code using those libraries, thus preventing bugs and providing fix suggestions. Recently, an empirical study [38] reports categories of required ML contracts, which may help designers of contract languages.

**Deep Learning Testing, Debugging, and Repairing:** Prior work on DL testing, debugging, and repairing includes DeepLocalize [62], MODE [46], *AUTOTRAINER* [65], *DeepDiagnosis*[61], *DeepFD*[25], Ariadne [29], Lagouvardos [40], Nikanjam *et al.* [52], SHAPETRACER [44], and Tensfa [63]. These approaches focus on detecting and localizing bugs, but *DL Contract* supports documentation of expected behavior. While *DL Contract* checker can also double as a bug detection tool, in the long term, developers would also benefit from the documentation and write more correct DL programs. Empirical studies [26, 34, 36, 37, 56, 64, 66] have motivated the need for DL bug repair, but none propose a DbC methodology like *DL Contract*.

Existing DbC Methodology: Existing DbC frameworks for Python, such as PyContracts [32], Pylint [1], and PyTA [45], do not have the capability to check contracts for properties of models and data, or monitor training behavior of DL models. These frameworks do not address the technical challenges of checking contracts beyond API parameters, contracts involving multiple APIs at different stages of the ML pipeline, and contracts on intermediate properties to specify desired training behavior. Additionally, DL Contract's use of runtime assertions is distinct from checking runtime properties, such as interpreting statecharts [47]. To the best of our knowledge,

the concept of applying DbC over the DL computational graph and specifying DL-specific contracts is novel.

API Misuse Detection: There have been some API misuse detection techniques such as, [60], which examines the usage of machine learning (ML) cloud APIs in open-source applications. This work finds that many of these applications contain API misuses that degrade their functionality and performance, leading to the development of automated checkers for identifying such misuses. [52] tackles API Misuse (APIM) bugs statically by some rules that occur when practitioners misunderstand the usage of deep learning APIs. Such misusage leads to inconsistencies between the designed DL program and the API's usage conditions, potentially resulting in reduced effectiveness or runtime exceptions. Existing API misuse detection methods may not be suitable for checking contracts written by library API designers that capture properties of models, data, and training behavior at various program points during runtime. To address this limitation, our approach overcomes technical challenges associated with checking contracts beyond formal API parameters, handling contracts involving multiple APIs at different stages of the ML pipeline, and specifying intermediate properties for desired training behavior.

#### 6 CONCLUSIONS AND FUTURE WORK

In this work, we proposed a novel method for checking contracts for deep learning libraries by specifying DL APIs with preconditions and postconditions. Our approach is extensible and generalizable, allowing for the abstraction of model architecture, data properties, and training behavior. We developed 15 sample DL contracts targeting common bugs and found they effectively prevented structural bugs and training problems. Additionally, our user study showed the usability of *DL Contract* when applied to the Keras library. We have submitted an API design proposal for its incorporation in future releases of Keras. Possible future work includes static validation, unit testing, and inferring contracts for additional libraries. With ongoing research on decomposing DNN into modules [35, 53, 54], we intend to write contracts for the expected behavior of a DNN module effectively. We want to explore writing contracts to prevent nonfunctional bugs such as fairness bugs [20, 21]. We would also like to extend our approach to prevent additional types of bugs in different stages of the ML pipeline [22]. We can adapt techniques [50, 51] for collecting contracts from mined models with improved performance in terms of accuracy and training time.

## 7 DATA AVAILABILITY

The replication packages and results are available in this repository [17] that can be leveraged by further research.

#### **ACKNOWLEDGMENTS**

We acknowledge the reviewers for their insightful comments. We also thank the user study participants. This material is based upon work supported by the National Science Foundation under Grant CCF-15-18897, CNS-15-13263, CNS-21-20448, CCF-19-34884, and CCF-22-23812. All opinions are of the authors and do not reflect the view of sponsors.

#### REFERENCES

- [1] 2016. Pylint. https://pylint.pycqa.org/en/latest/
- [2] 2021. CNN with keras, accuracy not improving. https://stackoverflow.com/questions/50079585/. [Online; accessed Feb-2023].
- [3] 2021. How to train and tune an artificial multilayer perceptron neural network using Keras? https://stackoverflow.com/questions/34673164/. [Online; accessed Feb-2023].
- [4] 2021. Keras API reference. https://keras.io/api/. [Online; accessed Feb-2023].
- [5] 2021. Keras unreasonnably slower than TensorFlow. https://stackoverflow.com/ questions/47352366/. [Online; accessed Feb-2023].
- [6] 2021. Loss becomes NaN. https://stackoverflow.com/questions/55328966/. [Online; accessed Feb-2023].
- [7] 2021. Low accuracy after training a CNN. https://stackoverflow.com/questions/ 59325381/. [Online; accessed Feb-2023].
- [8] 2021. Multilabel Text Classification using TensorFlow. https://stackoverflow.com/questions/35400065/multilabel-text-classification-using-tensorflow. [Online; accessed Feb-2023].
- [9] 2021. Sigmoid layer in Keras. https://stackoverflow.com/questions/45442843/.[Online; accessed Feb-2023].
- [10] 2021. Simple MNIST convnet example from Keras documentation. https://keras. io/examples/vision/mnist\_convnet/. [Online; accessed Feb-2023].
- [11] 2023. An annotated version of Keras with the DL Contract (@Keras). https://github.com/shibbirtanvin/DLContract/tree/main/ReproducibilityPackage/% 40Keras. [Online; accessed Aug-2023].
- [12] 2023. Collected Contracts Table in the Repo. https://github.com/shibbirtanv in/DLContract/blob/main/Appendix/ListofContracts.pdf. [Online; accessed Aug-2023].
- [13] 2023. Comparison of DeepDiagnosis with DL Contract in Anonymous Repo. https://github.com/shibbirtanvin/DLContract/tree/main/Results/Experimental Evaluation. [Online; accessed Aug-2023].
- [14] 2023. DeepLocalize Full Results in the Reposioty. https://github.com/shibbirtanv in/DLContract/tree/main/Results/ExperimentalEvaluation/DeepLocalize\_Resu lts.pdf. [Online; accessed Aug-2023].
- [15] 2023. Reposioty of DL Contract. https://github.com/shibbirtanvin/DLContract. [Online; accessed Aug-2023].
- [16] Martín Abadi, Paul Barham, Jianmin Chen, Zhifeng Chen, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Geoffrey Irving, Michael Isard, Manjunath Kudlur, Josh Levenberg, Rajat Monga, Sherry Moore, Derek G. Murray, Benoit Steiner, Paul Tucker, Vijay Vasudevan, Pete Warden, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. 2016. TensorFlow: A System for Large-Scale Machine Learning. In Proceedings of the 12th USENIX Conference on Operating Systems Design and Implementation (Savannah, GA, USA) (OSDI'16). USENIX Association, USA 265-283
- [17] Shibbir Ahmed, Sayem Mohammad Imtiaz, Samantha Syeda Khairunnesa, Breno Dantas Cruz, and Hridesh Rajan. 2023. Replication Package of the ES-EC/FSE 2023 Paper Entitled "Design by Contract for Deep Learning APIs". https://doi.org/10.5281/zenodo.8271853 The replication packages and results are available in this GitHub repository [https://github.com/shibbirtanvin/DLContract] that can be leveraged by further research.
- [18] Mike Barnett, Robert DeLine, Manuel Fähndrich, Bart Jacobs, K. Rustan M. Leino, Wolfram Schulte, and Herman Venter. 2008. The Spec# Programming System: Challenges and Directions. Springer Berlin Heidelberg, Berlin, Heidelberg, 144– 152. https://doi.org/10.1007/978-3-540-69149-5\_16
- [19] Mike Barnett, Manuel Fähndrich, K Rustan M Leino, Peter Müller, Wolfram Schulte, and Herman Venter. 2011. Specification and verification: the Spec# experience. Commun. ACM 54, 6 (2011), 81–91. https://doi.org/10.1145/1953122. 1953145
- [20] Sumon Biswas and Hridesh Rajan. 2020. Do the Machine Learning Models on a Crowd Sourced Platform Exhibit Bias? An Empirical Study on Model Fairness. In Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Virtual Event, USA) (ESEC/FSE 2020). Association for Computing Machinery, New York, NY, USA, 642–653. https://doi.org/10.1145/3368089.3409704
- [21] Sumon Biswas and Hridesh Rajan. 2021. Fair Preprocessing: Towards Understanding Compositional Fairness of Data Transformers in Machine Learning Pipeline. In Proceedings of the 29th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Athens, Greece) (ESEC/FSE 2021). Association for Computing Machinery, New York, NY, USA, 981–993. https://doi.org/10.1145/3468264.3468536
- [22] Sumon Biswas, Mohammad Wardat, and Hridesh Rajan. 2022. The Art and Practice of Data Science Pipelines: A Comprehensive Study of Data Science Pipelines in Theory, in-the-Small, and in-the-Large. In Proceedings of the 44th International Conference on Software Engineering (Pittsburgh, Pennsylvania) (ICSE '22). Association for Computing Machinery, New York, NY, USA, 2091–2103. https://doi.org/10.1145/3510003.3510057
- [23] Martin Büchi and Wolfgang Weck. 1999. The Greybox Approach: When Blackbox Specifications Hide Too Much. Technical Report 297. Turku Center for Computer Science. http://tinyurl.com/ywmuzy.

- [24] Margaret Burnett, Robin Counts, Ronette Lawrence, and Hannah Hanson. 2017. Gender HCl and microsoft: Highlights from a longitudinal study. In 2017 IEEE Symposium on Visual Languages and Human-Centric Computing (VL/HCC). 139– 143. https://doi.org/10.1109/VLHCC.2017.8103461
- [25] Jialun Cao, Meiziniu Li, Xiao Chen, Ming Wen, Yongqiang Tian, Bo Wu, and Shing-Chi Cheung. 2022. DeepFD: Automated Fault Diagnosis and Localization for Deep Learning Programs. In Proceedings of the 44th International Conference on Software Engineering (Pittsburgh, Pennsylvania) (ICSE '22). Association for Computing Machinery, New York, NY, USA, 573–585. https://doi.org/10.1145/35 10003.3510099
- [26] Zhenpeng Chen, Yanbin Cao, Yuanqiang Liu, Haoyu Wang, Tao Xie, and Xuanzhe Liu. 2020. A Comprehensive Study on Challenges in Deploying Deep Learning Based Software. In Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Virtual Event, USA) (ESEC/FSE 2020). Association for Computing Machinery, New York, NY, USA, 750–762. https://doi.org/10.1145/3368089.3409759
- [27] Yoonsik Cheon, Gary Leavens, Murali Sitaraman, and Stephen Edwards. 2005. Model Variables: Cleanly Supporting Abstraction in Design by Contract: Research Articles. Softw. Pract. Exper. 35, 6 (may 2005), 583–599.
- [28] Pascal Cuoq, Florent Kirchner, Nikolai Kosmatov, Virgile Prevosto, Julien Signoles, and Boris Yakobowski. 2012. Frama-C. In Software Engineering and Formal Methods, George Eleftherakis, Mike Hinchey, and Mike Holcombe (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 233–247.
- [29] Julian Dolby, Avraham Shinnar, Allison Allain, and Jenna Reinen. 2018. Ariadne: Analysis for Machine Learning Programs. In Proceedings of the 2nd ACM SIG-PLAN International Workshop on Machine Learning and Programming Languages (Philadelphia, PA, USA) (MAPL 2018). Association for Computing Machinery, New York, NY, USA, 1–10. https://doi.org/10.1145/3211346.3211346
- [30] Konstantin Eckle and Johannes Schmidt-Hieber. 2019. A comparison of deep networks with ReLU activation function and linear spline-type methods. *Neural Networks* 110 (2019), 232–242.
- [31] Divya Gopinath, Hayes Converse, Corina Pasareanu, and Ankur Taly. 2019. Property Inference for Deep Neural Networks. In 2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE). 797–809. https://doi.org/10.1109/ASE.2019.00079
- [32] Brett Graham, William Furr, Karol Kuczmarski, Bernhard Biskup, and Adam Palay. 2010. PyContracts. https://andreacensi.github.io/contracts//
- [33] Nargiz Humbatova, Gunel Jahangirova, Gabriele Bavota, Vincenzo Riccio, Andrea Stocco, and Paolo Tonella. 2020. Taxonomy of Real Faults in Deep Learning Systems. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (Seoul, South Korea) (ICSE '20). Association for Computing Machinery, New York, NY, USA, 1110–1121. https://doi.org/10.1145/3377811.3380395
- [34] Nargiz Humbatova, Gunel Jahangirova, Gabriele Bavota, Vincenzo Riccio, Andrea Stocco, and Paolo Tonella. 2020. Taxonomy of Real Faults in Deep Learning Systems. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (Seoul, South Korea) (ICSE '20). Association for Computing Machinery, New York, NY, USA, 1110–1121. https://doi.org/10.1145/3377811.3380395
- [35] Sayem Mohammad Imtiaz, Fraol Batole, Astha Singh, Rangeet Pan, Breno Dantas Cruz, and Hridesh Rajan. 2023. Decomposing a Recurrent Neural Network into Modules for Enabling Reusability and Replacement. In 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). 1020–1032. https://doi.org/10.1109/ICSE48619.2023.00093
- [36] Md Johirul Islam, Giang Nguyen, Rangeet Pan, and Hridesh Rajan. 2019. A Comprehensive Study on Deep Learning Bug Characteristics. In Proceedings of the 2019 27th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Tallinn, Estonia) (ESEC/FSE 2019). Association for Computing Machinery, New York, NY, USA, 510–520. https://doi.org/10.1145/3338906.3338955
- [37] Md Johirul Islam, Rangeet Pan, Giang Nguyen, and Hridesh Rajan. 2020. Repairing Deep Neural Networks: Fix Patterns and Challenges. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (Seoul, South Korea) (ICSE '20). Association for Computing Machinery, New York, NY, USA, 1135–1146. https://doi.org/10.1145/3377811.3380378
- [38] Samantha Syeda Khairunnesa, Shibbir Ahmed, Sayem Mohammad Imtiaz, Hridesh Rajan, and Gary T. Leavens. 2023. What Kinds of Contracts Do ML APIs Need? Empirical Software Engineering 1, 1 (March 2023).
- [39] Sifis Lagouvardos, Julian Dolby, Neville Grech, Anastasios Antoniadis, and Yannis Smaragdakis. 2020. Static Analysis of Shape in TensorFlow Programs. In 34th European Conference on Object-Oriented Programming (ECOOP 2020) (Leibniz International Proceedings in Informatics (LIPIcs), Vol. 166), Robert Hirschfeld and Tobias Pape (Eds.). Schloss Dagstuhl-Leibniz-Zentrum für Informatik, Dagstuhl, Germany, 15:1–15:29. https://doi.org/10.4230/LIPIcs.ECOOP.2020.15
- [40] Sifis Lagouvardos, Julian Dolby, Neville Grech, Anastasios Antoniadis, and Yannis Smaragdakis. 2020. Static Analysis of Shape in TensorFlow Programs. In 34th European Conference on Object-Oriented Programming, ECOOP 2020, November 15-17, 2020, Berlin, Germany (Virtual Conference) (LIPIcs, Vol. 166), Robert Hirschfeld and Tobias Pape (Eds.). Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 15:1– 15:29. https://doi.org/10.4230/LIPIcs.ECOOP.2020.15

- [41] Gary T. Leavens, Albert L. Baker, and Clyde Ruby. 2006. Preliminary Design of JML: A Behavioral Interface Specification Language for Java. SIGSOFT Softw. Eng. Notes 31, 3 (May 2006), 1–38. https://doi.org/10.1145/1127878.1127884
- [42] K. Rustan M. Leino. 1995. Toward Reliable Modular Programs. Ph. D. Dissertation. California Institute of Technology. Available as Technical Report Caltech-CS-TR-95-03.
- [43] K. Rustan M. Leino. 2010. Dafny: An Automatic Program Verifier for Functional Correctness. In Logic for Programming, Artificial Intelligence, and Reasoning, Edmund M. Clarke and Andrei Voronkov (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 348–370. https://doi.org/10.1007/978-3-642-17511-4\_20
- [44] Chen Liu, Jie Lu, Guangwei Li, Ting Yuan, Lian Li, Feng Tan, Jun Yang, Liang You, and Jingling Xue. 2021. Detecting TensorFlow Program Bugs in Real-World Industrial Environment. In 2021 36th IEEE/ACM International Conference on Automated Software Engineering (ASE). 55–66. https://doi.org/10.1109/ASE51524.202 1.9678891
- [45] Nigel Fong Lorena Buciu, Simon Chen and et al. 2016. PyTA. https://www.cs.tor onto.edu/~david/pyta/index.html/
- [46] Shiqing Ma, Yingqi Liu, Wen-Chuan Lee, Xiangyu Zhang, and Ananth Grama. 2018. MODE: Automated Neural Network Model Debugging via State Differential Analysis and Input Selection. In Proceedings of the 2018 26th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Lake Buena Vista, FL, USA) (ESEC/FSE 2018). Association for Computing Machinery, New York, NY, USA, 175–186. https://doi.org/10.114 5/3236024.3236082
- [47] Tom Mens, Alexandre Decan, and Nikolaos I Spanoudakis. 2019. A method for testing and validating executable statechart models. Software & Systems Modeling 18, 2 (2019), 837–863. https://doi.org/10.1007/s10270-018-0676-3
- [48] B. Meyer. 1992. Applying 'design by contract'. Computer 25, 10 (1992), 40-51. https://doi.org/10.1109/2.161279
- [49] Peter Müller. 2001. Modular Specification and Verification of Object-Oriented programs. Ph. D. Dissertation. FernUniversität Hagen, Germany. http://tinyurl. com/itwot
- [50] Giang Nguyen, Sumon Biswas, and Hridesh Rajan. 2023. Fix Fairness, Don't Ruin Accuracy: Performance Aware Fairness Repair using AutoML. In ESEC/FSE'2023: The 31st ACM Joint European Software Engineering Conference and Symposium on the Foundations of Software Engineering (San Francisco, California).
- [51] Giang Nguyen, Md Johirul Islam, Rangeet Pan, and Hridesh Rajan. 2022. Manas: Mining Software Repositories to Assist AutoML. In Proceedings of the 44th International Conference on Software Engineering (Pittsburgh, Pennsylvania) (ICSE '22). Association for Computing Machinery, New York, NY, USA, 1368–1380. https://doi.org/10.1145/3510003.3510052
- [52] Amin Nikanjam, Houssem Ben Braiek, Mohammad Mehdi Morovati, and Foutse Khomh. 2021. Automatic Fault Detection for Deep Learning Programs Using Graph Transformations. ACM Trans. Softw. Eng. Methodol. 31, 1, Article 14 (sep 2021), 27 pages. https://doi.org/10.1145/3470006
- [53] Rangeet Pan and Hridesh Rajan. 2020. On Decomposing a Deep Neural Network into Modules. In Proceedings of the 28th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering (Virtual Event, USA) (ESEC/FSE 2020). Association for Computing Machinery, New York, NY, USA, 889–900. https://doi.org/10.1145/3368089.3409668
- [54] Rangeet Pan and Hridesh Rajan. 2022. Decomposing Convolutional Neural Networks into Reusable and Replaceable Modules. In Proceedings of the 44th International Conference on Software Engineering (Pittsburgh, Pennsylvania) (ICSE '22). Association for Computing Machinery, New York, NY, USA, 524–535. https: //doi.org/10.1145/3510003.3510051
- [55] Hung Viet Pham, Shangshu Qian, Jiannan Wang, Thibaud Lutellier, Jonathan Rosenthal, Lin Tan, Yaoliang Yu, and Nachiappan Nagappan. 2021. Problems and Opportunities in Training Deep Learning Software Systems: An Analysis of Variance. In Proceedings of the 35th IEEE/ACM International Conference on

- Automated Software Engineering (Virtual Event, Australia) (ASE '20). Association for Computing Machinery, New York, NY, USA, 771–783. https://doi.org/10.1145/3324884.3416545
- [56] Vincenzo Riccio, Gunel Jahangirova, Andrea Stocco, Nargiz Humbatova, Michael Weiss, and Paolo Tonella. 2020. Testing machine learning based systems: a systematic mapping. Empirical Software Engineering 25, 6 (2020), 5193–5254. https://doi.org/10.1007/s10664-020-09881-0
- [57] Eldon Schoop, Forrest Huang, and Bjoern Hartmann. 2021. UMLAUT: Debugging Deep Learning Programs Using Program Structure and Model Behavior. In Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems (Yokohama, Japan) (CHI '21). Association for Computing Machinery, New York, NY, USA, Article 310, 16 pages. https://doi.org/10.1145/3411764.3445538
- [58] Sanjit A. Seshia, Ankush Desai, Tommaso Dreossi, Daniel J. Fremont, Shromona Ghosh, Edward Kim, Sumukh Shivakumar, Marcell Vazquez-Chanlatte, and Xiangyu Yue. 2018. Formal Specification for Deep Neural Networks. In Automated Technology for Verification and Analysis. Springer International Publishing, Cham, 20–34. https://doi.org/10.1007/978-3-030-01090-4\_2
- [59] Muhammad Usman, Divya Gopinath, Youcheng Sun, Yannic Noller, and Corina S. Päsäreanu. 2021. NNrepair: Constraint-based Repair of Neural Network Classifiers. In Computer Aided Verification: 33rd International Conference, CAV 2021, Virtual Event, July 20–23, 2021, Proceedings, Part I. Springer-Verlag, Berlin, Heidelberg, 3–25. https://doi.org/10.1007/978-3-030-81685-8\_1
- [60] Chengcheng Wan, Shicheng Liu, Henry Hoffmann, Michael Maire, and Shan Lu. 2021. Are Machine Learning Cloud APIs Used Correctly?. In Proceedings of the 43rd International Conference on Software Engineering (Madrid, Spain) (ICSE '21). IEEE Press, 125–137. https://doi.org/10.1109/ICSE43902.2021.00024
- [61] Mohammad Wardat, Breno Dantas Cruz, Wei Le, and Hridesh Rajan. 2022. DeepDiagnosis: Automatically Diagnosing Faults and Recommending Actionable Fixes in Deep Learning Programs. In Proceedings of the 44th International Conference on Software Engineering (Pittsburgh, Pennsylvania) (ICSE '22). Association for Computing Machinery, New York, NY, USA, 561–572. https://doi.org/10.1145/3510003.3510071
- [62] Mohammad Wardat, Wei Le, and Hridesh Rajan. 2021. DeepLocalize: Fault Localization for Deep Neural Networks. In Proceedings of the 43rd International Conference on Software Engineering (Madrid, Spain) (ICSE '21). IEEE Press, 251–262. https://doi.org/10.1109/ICSE43902.2021.00034
- [63] Dangwei Wu, Beijun Shen, Yuting Chen, He Jiang, and Lei Qiao. 2021. Tensfa: Detecting and Repairing Tensor Shape Faults in Deep Learning Systems. In 2021 IEEE 32nd International Symposium on Software Reliability Engineering (ISSRE). 11–21. https://doi.org/10.1109/ISSRE52982.2021.00014
- [64] Ru Zhang, Wencong Xiao, Hongyu Zhang, Yu Liu, Haoxiang Lin, and Mao Yang. 2020. An Empirical Study on Program Failures of Deep Learning Jobs. In Proceedings of the ACM/IEEE 42nd International Conference on Software Engineering (Seoul, South Korea) (ICSE '20). Association for Computing Machinery, New York, NY, USA, 1159–1170. https://doi.org/10.1145/3377811.3380362
- [65] Xiaoyu Zhang, Juan Zhai, Shiqing Ma, and Chao Shen. 2021. AutoTrainer: An Automatic DNN Training Problem Detection and Repair System. In Proceedings of the 43rd International Conference on Software Engineering (Madrid, Spain) (ICSE '21). IEEE Press, 359–371. https://doi.org/10.1109/ICSE43902.2021.00043
- [66] Yuhao Zhang, Yifan Chen, Shing-Chi Cheung, Yingfei Xiong, and Lu Zhang. 2018. An Empirical Study on TensorFlow Program Bugs. In Proceedings of the 27th ACM SIGSOFT International Symposium on Software Testing and Analysis (Amsterdam, Netherlands) (ISSTA 2018). Association for Computing Machinery, New York, NY, USA, 129–140. https://doi.org/10.1145/3213846.3213866
- [67] Donglin Zhuang, Xingyao Zhang, Shuaiwen Song, and Sara Hooker. 2022. Randomness in Neural Network Training: Characterizing the Impact of Tooling. In Proceedings of Machine Learning and Systems, D. Marculescu, Y. Chi, and C. Wu (Eds.), Vol. 4. 316–336. https://proceedings.mlsys.org/paper\_files/paper/2022/file/427e0e886ebf87538afdf0badb805b7f-Paper.pdf